



Lymphhe

Gres porcellanato - Porcelain stoneware - Feinsteinzeug - Grès cérame fin vitrifié

 **City**
c e r a m i c h e

by

 **REFIN**
C E R A M I C H E




Lymphe - Chic 25x150 - 10"x60" R



Lymphe - Chic 25x150 - 10"x60" R

Lymphe

Gres porcellanato - Porcelain stoneware - Grès cérame fin vitrifié - Feinsteinzeug

 9 mm



25x150 - 10"x60" R



JEUNE 25x150 - 10"x60" R

OL85



CHIC 25x150 - 10"x60" R

OL87



NATUREL 25x150 - 10"x60" R

OL86



FONCÉ 25x150 - 10"x60" R

OL88



Lymphe - Jeune 25x150 - 10"x60" R



CITY
Boutique Hotel
San Francisco

Reception

16

Lymphe - Naturel 25x150 - 10"x60" R



Lympe - Naturel 25x150 - 10°x60° R



Lymphe - Foncé 25x150 - 10"x60" R



Lymphe - Jeune 25x150 - 10"x60" R

CARATTERISTICHE TECNICHE - TECHNICAL FEATURES - CARACTERISTIQUES TECHNIQUES - TECHNISCHE EINGESCHAFTEN

GRES FINE PORCELLANATO - EN 14411 ISO 13006 Gruppo Bla Annex G

	NORMA REGULATION NORME NORM	VALORE PRESCRITTO DELLA NORMA EN 14411 ISO 13006 REQUIRED STANDARDS VALEUR PRESCRIPTE PAR LES NORMES NORMVORGABE	VALORE CITY CITY VALUES VALEUR CITY CITY PRODUKTION	
			Lymphe	
Dimensioni/Sizes/Dimensions/Abmessungen/ Afmetingen/Dimensiones	UNI EN ISO 10545/2	→Lunghezza e larghezza/Length and width/Longueur et largeur/Länge und Breite/Lengte en breedte/ Longitud y anchura →Spessore/Thickness/Epaisseur/Stärke/Dikte/Grosor →Rettilineità spigoli/Linearity/Rectitude des arêtes/Kantengeradheit/ Rechttheit kanten/Rectitud de los lados →Ortogonalità/Wedging/Orthogonalité/Rechtwinkligkeit/Haaksheid hoeken/Ortogonalidad →Planarità/Warpage/Planéité/Ebenflächigkeit/Vlakheid/Planitud	± 0,6 % max 2mm ± 5 % max 0,5mm ± 0,5 % max 1,5mm ± 0,5 % max 2mm ± 0,5 % max 2mm	Conforme Compliant
Assorbimento acqua/Water absorption/ Absorption d'eau/Wasseraufnahme/ Waterabsorptie/Absorción de agua	UNI EN ISO 10545/3	≤ 0,5 %	0,2%	
Resistenza alla flessione/Flexual Strenght/ Résistance à la flexion/Biegezugfestigkeit/ Buigvastheid/Resistencia a la flexión	UNI EN ISO 10545/4	≥ 35 N/mm ²		Conforme Compliant
		S ≥ 1300 N (thickness ≥ 7,5 mm)		Conforme Compliant
Coefficiente di restituzione (COR)/ Coefficient of restitution (COR)/ Coefficient de restitution (COR)/ Restitutionskoeffizienten (COR) / Restitutiecoëfficiënt (COR)/ Coeficiente de restitución (COR)	UNI EN ISO 10545/5	Valore consigliato ≥ 0,55/ Recommended value ≥ 0,55/ Valeur recommandée ≥ 0,55/ Empfohlener Wert ≥ 0,55/ Aanbevolen waarde ≥ 0,55/ Rvalor recomendado ≥ 0,55		Conforme Compliant
Resistenza all'abrasione profonda/Deep abrasion resistance/Résistance à l'abrasion/Bestimmung des Widerstandes gegen Tiefenverschleiß/ Weerstand tegen afschuren/Resistencia a la abrasión profunda	UNI EN ISO 10545/6	≤ 175 mm ³		Conforme Compliant
Coefficiente di dilatazione termica lineare/ Coefficient of thermal linear expansion/ Coefficient de dilatation thermique linear/ Wärmeausdehnungskoeffizient/ Lineaire thermische uitzetting /Coeficiente de dilatación termica linear	UNI EN ISO 10545/8	Metodo di prova disponibile/Tests method available/ Methode d'essai disponible/Verfügbares/Prüfverfahren/ Testmethode beschikbaar/Método de prueba disponible		≤ 7 10 ⁻⁶ ·C ⁻¹
Resistenza al gelo/Frost resistance/Résistance au gel/Frostwiderständigkeit/Vorstbestandheid/ Resistencia a la helada	UNI EN ISO 10545/12	Resistenti/Resistant/Resistants/Widerstandsfähig/ Weerbarstig/Resistentes		Conforme Compliant
Resistenza all'attacco chimico/Chemical resistance/Résistance à l'attaque chimique/Beständigkeit gegen Chemikalien/Chemische bestandheid/Resistencia al ataque químico	UNI EN ISO 10545/13	Metodo di prova disponibile/Tests method available/ Methode d'essai disponible/Verfügbares/Prüfverfahren/ Testmethode beschikbaar/Método de prueba disponible		A – LA – HA
Resistenza alle macchie/Stain resistance/ Insensibilité aux taches/Widerstandsfähigkeit gegen fl eckenbildende/Substanzen/Weerstand tegen vlekken/Resistencia a las manchas	UNI EN ISO 10545/14	UGL Dichiarare un valore / UGL Declare a value		Classe 5 / Class 5
Indicazione di resistenza allo scivolamento/ Assessment of slip resistance/Indication de la résistance au glissement/ Bestimmung der Trittsicherheit/Indicatie voor de slipvastheid/Indicación de resistencia al deslizamiento	DIN 51130	Dichiarare un valore (A+B+C) / Declare a value (A+B+C)		R10
	DIN 51097	Dichiarare un valore (A+B+C) / Declare a value (A+B+C)		
	BS 7976- 2:2002 (CEN/ TS 16165, Annex C) Pendulum Friction Test	Dichiarare un valore / Declare a value		
Coefficiente di attrito dinamico/Measurement of dynamic friction coefficient/Mesure du coefficient de frottement dynamique/Messung des Dynamischen Reibungskoeffizienten/Meting van de dynamische wrijvingscoëfficiënt/Coeficiente de rozamiento dinámico	B.C.R.A. Rep. CEC/81	Asciutto > 0,40 / Bagnato > 0,40		Asciutto > 0,40 / Bagnato > 0,40
	ANSI A137.1-2012 (BOT3000)	> 0,42 Wet		> 0,42 Wet



Imballi - Packaging - Emballage - Verpackungseinheiten

size	pcs x box	m ² / m x box	kg x box	box x pallet	m ² / m x pallet	kg x pallet
25x150 - 10"x60" 8mm	3	1,1250	23,58	30	33,75	707,40

Lymphe - Jeune 25x150 - 10"x60" R

 **City**
c e r a m i c h e

by

 **REFIN**
C E R A M I C H E

Via I Maggio, 22 - Salvaterra
42013 Casalgrande (RE) Italy
Tel. +39.0522.990.499
Fax Ita +39.0522.849.270
Fax Exp +39.0522.990.578



I prodotti City Ceramiche sono studiati e realizzati interamente in Italia.
The products of City Ceramics are entirely designed and made in Italy.
Die Produkte City Ceramiche werden komplett in Italien entworfen und hergestellt.
Les produits City Ceramiche sont entièrement conçus et produits en Italie.