



2023



SMALL CATALOGUE 2023



EVOLUTION
AND DEVELOPMENT
NEVER ENDS

SMALL CATALOGUE 2023



Headquarter

Progress Profiles SpA
Via Le Marze 7
31011 ASOLO (TV) Italy
Tel. +39 0423 950398
Fax +39 0423 950979
Certified Company
UNI EN ISO 9001:2015
www.progressprofiles.com
info@progressprofiles.com

Branch Office & Warehouse

Progress Profiles America Inc.
4 Middlebury Boulevard (Unit 14)
Randolph, New Jersey 07869
U.S.A.
Tel. 001 973 584 2650
Fax 001 973 584 2657
usa@progressprofiles.com

Branch Office & Warehouse



Progress Profiles Middle East LLC
AL QUOZ INDUSTRIAL FOURTH
26th Street, Showroom No. 1
Dubai, U.A.E.
Tel. 00971-04 325 1499
Fax 00971-04 325 1466
P.O. BOX: 29101
uae@progressprofiles.com

Branch Office & Warehouse

Progress Profiles España S.L.
Elche Parque Industrial
Calle German Bernacer Nº 15
03203 Elche Alicante
España / Spain
Tel. +34 965 057 279
Fax +34 966 054 073
ppe@progressprofiles.com



PROGRESS®
P R O F I L E S



All previous price lists lose their validity on the publication of this price list. Errors, changes, and printing mistakes as well as changes necessary in the interest of product innovation or shipping reserved. For reasons of printing, colours shown in this price list may differ from actual product colours.

ARTICLE	PAGE	ARTICLE	PAGE	ARTICLE	PAGE	ARTICLE	PAGE		
AG...	276	PCF...	312	PFXACPR...	140	PLVOL 358...	81	PSS...	54
AGAC...	276	PCR...	89,110	PFXAL...	141	PLVOL 4413	81	PST...	306
AGE...25	237	PCR...1045	86	PFXALN...	142	PMF...	100	PST...	292
AGOL...	276	PCR...14PT	91	PFXOT...	141	PMG...	101	PSTRAN	296
AGP...	277	PCRA...	89	PGAO...	71	PMPFX...	245	PSTSL...	298
AL...	277	PCRA...261	238,270	PGAW...15	205	PMQ...	100	PSWC...	264
ALP...	277	PCRA...110	205	PGBORD	205	PNPLS	330	PSYA...	127
BR...	331	PCRAC...	88	PGR...	117,137	PNPLWS	330	PSYAC...	126
BTA... 40	225	PCRO...	88	PHTST...	206	PNPSR	330	PSYACS 2610	114
BTA... 60	227	PCT...	60	PI...	279	PNSP...	261	PSYGRACS 6020	118
BTA... 80	229	PCT...T	60	PI...	32,33	PNVA.. 713	82	PSYKLA 1045	161
BTA...100	231	PDA...	75	PIAC...	30	PP...	313	PSYO...	126
BTAC...	230	PDAACV...	111	PIF...	283	PPD...	305	PSYW...	129
BTAC... 40	224	PDAC...	74	PIKL...	32,160	PPN...	312	PT...	37
BTAC... 60	226	PDD...	164	PIKLAC...	30	PPT...	304	PT...	66
BTAC... 80	228	PDDR...	174,177	PIKLAC...	160	PPU...	310	PT...	39
BTEPR...4010	235,269	PDES...	185	PIN...	271,272	PPV...	310	PTAC...	16
BTEPR...7011	235	PDESEC...	183	PINS...	260	PPY...	311	PTAC...	36
BTEPR...7011	269	PDESH...	181	PINT...	110	PQE...	71	PTACV...	104
BTEPR...7016	234	PDESHG...	179	PINTPC...	252,258	PRB...	188	PTANCV...	105
BTEPR...7016	268	PDESHK...	182	PINYC...	254	PRBBU...	186	PTEDP...	167
BTEPR..R	233,267	PDESHST...	183	PINYLC...	255	PRBFX...	186	PTI...	35
BTEPR..S	232,266	PDKLA...	86	PINZ...	260,262	PRKLA...	186	PTO...	37
BTFP...	236	PDLRA...	75	PINZC...	250,258	PRKLAB...	186	PTO...	65
BTPR...	237	PDO...	74	PISPC...	249,258	PRBTE...	185	PTONCV...	105
BTVP...	236	PDONCV...	111	PITA...	72	PRBT	186	PTP...	120
C 550...	319	PDRI 10	188	PITO...	72	PRBT	196	PTPW...	129
C51...	146,147	PDORP	171	PJ...	18	PRCLEAN	300	PTR...	120
CAT...	331	PDSND...	187	PJ...	23	PRCP...	239	PTR50...	119
CLPS	307	PDSNDTP...	187	PJ...	22	PRCPS...	239	PTRACS...	114
COF...	328	PDWR...	76	PJAACV...	109	PRDAC	54	PTRB...	121
COFMIE	329	PDZ...	308	PRFA...	15	PRFA...	71	PTRGRACS...	117
COL...	328	PED 4528...	135	PJE...	25	PRFAACV...	108	PTRKLA 2045	161
CPGC...	321	PED...7537	135	PJE...	24	PRFA...	70	PTRELEAA...	124
CT...	282	PEDBD...	45	PJO...	17	PRFO...	70	PTRW...	128
CU...	278	PEF...	187	PJONCV...	109	PRFONCV...	108	PTRWZ...	128
CURAS	326	PEG...	48	PJP...	23	PRLISH	300	PTS.. 613	82
CW...	278	PEGA...	48	PJQ...	9	PRLW...	290	PTSA...	127
DMP...	309	PEGO...	46	PJQS...	6	PRMKL	186	PTSAA...	253
DSVT	311	PEGR...	46	PJQSAC...	2	PRS...	289	PTSPA...	122
DVO...	311	PEGR.. 5230	137	PJQSOS...	5	PRS...712...	84	PTSPAC...	59
ESHAN 250	325	PEGR.. 7032	136	PJQT...	11,14	PRSHLF...	205	PTSPAC...	122
ESPB...	331	PEGRAA 50	136	PJQAC...	10	PRSPD 10	301	PTUE...	170
ESPCLSH...	331	PEGRAA 50	136	PJTR...	28	PRTA...	78	PTV...	320
ESPD	330	PEGRA...	47	PJTR135...	29	PRTAC...	77	PWK...	133
ESPFDPP	330	PEGRO...	47	PJTRAC...	26	PRTO...	77	PWK...25...	134
ESPGLED...	328	PEL...	68	PJTRO...	27	PS...	53	PWKAC...	136
ESPGSM 18	326	PELAACV...	107	PKAA...	220	PSA...	56	R...	302
ESPGSMBT	327	PELONCV...	107	PKCHAA...	211	PSA...	55	R...	291
ESPPDHT...	329	PEM	337	PKFLAA...	211	PSAW...20	238	R...	304
ESPPS	330	PEN...	150	PKGLEDAA...	219	PSAW...20	270	RT11...	304
ESPST	330	PENF...	149	PKINSAA 60	212	PSB...	57	SC...	131
ESPQC...	324	PEP...	337	PKISPAA...	213	PSBF...	57	SO...	131
ESPSHW 70	329	PESP...	326	PKL...	156	PSD...	306	SQ...	299
FLY...	331	PETAA...	91	PKLEDAA...	217	PSDWK...	167	T...	282
FTPP	300	PETAC...	90	PKLIAA	212	PSDWK...	123	T...	282
G...	146	PETFX...	153	PKLL...	58	PSF...	56	TCT...	131
GCAC...	143	PETFXPAA...	153	PKLL...	157	PSHA...	52	TDA...	304
GCAN...	143	PETO...	90	PKLT...	214	PSHAC...	50	TET...	131
GCT...	305	PFC..40	45	PKSHAA 70	221	PSHD...	159	TGS...	131
GDA ...	150	PFD...	166	PKSHAA...	221	PSHLDK	201	TP...	280
GDA 55...	151	PFDPP...	165	PLF...	309	PSHPAN	190	TQP...	280
GDSP...	147	PFL...	188	PLF...R...	309	PSHPANCEK	200	TQV...	281
GNS...	152	PFLP...	189	PLFE...	309	PSHPANNEK	190	TR...	281
GP...	148	PFLPAN...	203	PLG...	67,68	PSHR...	159	TRAG18	326
GPL...	73	PFLPANICH	44	PLS...	97	PSHW...	193	TV...	280
GRP...	306	PFLT...	44	PLSAC...	93	PSHWBB...	191	UG...	281
KBPSHWAC...	195	PFSAL...	295	PLSO...	95	PSHWCP	201	VIN...	273
KMD	300	PFR...1216	84	PLT...	43	PSHWDL...	191	WP...	307
M...	314	PFR...24...	85	PLTAC...	40	PSHWDL...	192		
MCAT...	331	PFR...712	83	PLTCH...	34,198	PSHW...	194		
MSP...	291	PFRAC...712	83	PLTLED	43	PSHW...	194		
PBP...	121	PFRO...712	83	PLTP...	42	PSHW...	194		
PBPLS...	331	PFTT...	301	PLTPO...	41	PSHW...	196		
PC...	169	PFX...	148	PLU...16	85	PSHW...	197		
PCG...	168	PFX...	144	PLV...	99	PSHW...	197		
PCLA...	73	PFXS...	144	PLV...29	79	PSHW...	193		
PCLO...	73	PFXSPR...	145	PLV...30...	80	PSHW...	193		
PCM 08	111	PFXAC...	140	PLV...32	80	PSM	301		
		PFXACN...	142	PLVOL 33	79	PSRPT...	295		



Look into our eyes and we will tell you who we are

A story a human character and perseverance.

Bold decisions. Ours is a story of accomplishments that started in Canada in 1965 and blossomed in Italy. The extensive know-how acquired over 55 years of prior experience in the field of plastic extrusion and metal profiles brought to the company's turning point occurred during the 90s. This was a period rich in investments in additional qualified personnel, state-of-the-art machinery, and cutting edge innovations that opened the doors to internationalization and the development of innovative solutions for ceramic tiles, marble, wood/parquet, laminate and vinyl flooring, fitted carpets, resin or concrete flooring, mosaic and low thicknesses flooring and innovative fixing/ Laying Heating, Uncoupling and waterproofing membrane systems. All this took PROGRESS PROFILES® in a new trajectory, as demonstrated by the quick growth of the company which became increasingly larger and articulate, recognized as a true reference point in the market. This great success is mainly due to the team play spirit within our company. Highly dedicated, trained and skilled professionals in every single department, technical, training, design, manufacturing, sales, logistic, marketing allow us to bring constantly innovative solution to the international marketplace. In particular investments in marketing and marketing support has been clearly visible in and a wide range of technical catalogues, leaflets and marketing material, which have led the company, already having a leading position in the international market and being the undisputed leader in the Italian market, to achieve the goal of over 10000 active and satisfied clients.






The eyes are the mirror of the soul and of the company



Explore new ideas to constantly improve, by testing and challenging existing practices.

An example of cutting-edge entrepreneurship with determined goals and a forward-looking action plan aiming at capturing the latest trends in the sector. All this is proved by over 38 years of success in the International market, a steadily increasing turnover, and a solid business context, which, as of today, boasts over 130 employees and a network of over 120 high-profile national and international agents, and three headquarters located abroad, in America, Dubai and Spain, to promote Italian high quality through a bold internationalization policy. A dynamic policy that is expressed in the participation in the most important International trade fairs, as well as in a cooperative International dialog with several of the main characters in the design and architectural spaces of today trend development. This dialog is critical and challenging but the company faces it with great enthusiasm and desire to grow through idea exchanging and learning.






A glance at the future




Following the entire product life cycle from idea to project and finally to finished product

The wide range of PROGRESS PROFILES® products is the result of over 38 years of research and development applied to the most advanced technologies and materials available on the market to create exclusive, functional and state-of-the-art solutions for improving the quality of the finished project, while reducing the installers efforts. These objectives have guided the company policy of important investments in enhancing the Planning Office, acquiring state-of-the-art equipment and a team of professionals that are able to seize the soul of a product and develop its full potential and performances, according to all the customer requirements and trends of the sector. A policy that has led the company to invent, design, and deposit patents and trademarks aiming at promoting and overturning established application concepts.





Eyes wide open on innovation




Learning and Technical Training is the most important investment for any enterprise.

PROGRESS PROFILES® feather in the cap is the depth of training offers reserved to employees and clients, in which the company has, since the beginning, invested a large amount of energy and resources. To confirm such focus in the recently inaugurated (2015) Headquarters in Asolo the company has set up a 200 sqm showroom and 500 sqm training facility and training center equipped with latest technologies to allow operators of the trade – Italian and foreign representatives, architects, engineers, planners, designers, building and Tile laying fixers companies to view and to acquire the technical knowledge needed to use the latest product in their trade. This is achieved through practical demonstrations, video tutorials on laying methods, technical seminars and workshops, all held by accomplished, skilled and accredited professionals. All this transfer of knowledge and information to our internal and external partners is accompanied by certifications and standards documents that further strengthens and enrich the quality of their overall training, allowing them to be always up-to-date on the latest systems and products in their field.



A company that sees clearly



First of all, Made in Italy.

The new headquarters in Asolo, with an indoor area of over 16000 sqm and equipped with a photovoltaic roof system, generating 800 kWh, can boast state-of-the-art technology equipment: latest generation machinery for processing stainless steel, aluminium, brass, PVC and real wood, as well as packaging, labelling and assembling machines. The result of all this are the over 30 million linear metres of its profiles that are laid every year. High-quality and great aesthetic impact characterise the wide range of PROGRESS PROFILES® products, which includes over 15000 technical and design solutions and system, most of which are

patented ,for interior finishes, laying ceramic and wood, as well as for residential and commercial buildings. A wide range of products that has grown over the years through advanced technological processes that have led to the development of products, materials, and innovative modern finishes, such as anodized, polished and brushed titanium, copper, chrome and Gold, Tiltex, Black line , Tuscany line, Stone line and the latest heating and uncoupling membranes and shower systems. The entire production is strictly Italian made and ISO 9001:2015 certified. The excellence of the results is the proof.




We keep an eye on everything!



Everything at its place to guarantee efficiency and punctuality.

The logistics system devised by PROGRESS PROFILES® for the operative management of the complex warehouse is emergency proof. Studied in the slightest detail according to the most advanced methods and logics of the system, it ensures a systematic organization of the goods in a total space of 8000 sqm, which allows an efficient and punctual service and prompt delivery any time of the year. Moreover, a state of the art software management service is actively keeping direct and constant control over the entire order procedure, leaving nothing to chance and ensuring maximum reliability and accuracy.





An eye for detail that make the difference



The quality can be seen, touched and is 100% guaranteed.

Every PROGRESS PROFILES® product is made and tested according to the strictest standards that allow us to guarantee their excellence from every point of view. At the forefront in the quality, the company operates with a management system certified according to UNI EN ISO 9001 since 1999, among the first in the world in its field, and it is today ISO 9001:2015 certified. An absolute certainty of reliability that is ensured also by important company choices: 100% made in Italy,

the exclusive use of non-toxic materials and top quality stainless steel, aluminium and brass alloys, conforming to Italian and International standards, the choice of high quality raw materials and their use in compliance with the REACH requirements, implementing the LEED products mapping system for gaining GREENTOP credits, and more in general, by the ability to offer a service designed in the slightest detail to meet all requirements and make a difference in the market.






A forward-looking company



A courageous international growth campaign.

PROGRESS PROFILES® sales network in Italy and abroad creates a capillary knowledge and support delivery system. Even though as today 60% our turnover is made within the Italian national territory, there are over 80 countries accounted for worldwide where the company exports and sells its products. Apart from the main markets such as France, Austria, Greece, Portugal, Germany, Switzerland, Scandinavia, England, Ireland, Belgium, India, Australia, New Zealand – the company is also present in the countries of former Yugoslavia and Eastern Europe, in particular Russia, Croatia

, Hungary, Slovenia, Czech Rep. Slovakia, Poland in all the countries of the Middle East, Africa, and Central and South America. As a demonstration of the importance of the internationalization process, the company takes part in all the most important trade fairs of the sector and has recently created headquarters in 3 major contemporary business capitals: U.S.A.: Progress Profiles America Inc., U.A.E.: Progress Profiles Middle East LLC., and SPAIN: Progress Profile España S.L







CATALOGUE SECTIONS INDEX	PG
● PROFILES FOR WALLS	1 - 61
● PROFILES FOR FLOORS	62 - 101
● BENDABLE & CURVE PROFILES	102 - 111
● STAIR NOSING PROFILES	112 - 137
● EXPANSION JOINTS	138 - 153
● LOW THICKNESS PROFILES	154 - 161
● PROFILES FOR TERRACES	162 - 171
● MEMBRANES & PANELS	172 - 189
● SHOWER SYSTEMS	190 - 207
● SKIRTING BOARDS	208 - 239
● PROFILES FOR LAMINATES & LVT FLOORS	240 - 273
● DO IT YOUR SELF	274 - 283
● PRODUCTS FOR LAYING	284 - 301
● BUILDING SYSTEMS	302 - 321
● MARKETING	322 - 339
News	

A	● ADHESIVE-LAID JOINTS	146
	● ANCHORING CLIPS FOR WATERSTOP	307
B	● BROCHURE	331
C	● CANAL DOUBLE U-FORM ALU.	278
	● CANAL U-FORM.	278
	● CATALOGUES	331
	● CONTRAINBALANCE ALU.	282
	● CORNER EQUAL SIDES ALU.	276
	● CORNER EQUAL SIDES BRASS	276
	● CORNER EQUAL SIDES PVC	277
	● CORNER EQUAL SIDES STEEL	276
	● CORNER L-FORM ALU.	277
	● CORNER L-FORM PVC	277
	● CORNER PVC	237
	● COUNTER DISPLAY FOR BROCHURES	331
	● COUNTER DISPLAY FOR FLYER	331
	● CURVE PROFILE ALU.	281
D	● DISPLAYS FOR PROFILES	337
	● DOPPY	311
	● DRAIN REDUCTION	193
	● DRIP PVC	305
E	● EMPTY RECTANGULAR TUBE ALU.	281
	● EMPTY ROUND TUBE ALU.	280
	● EMPTY SQUARE TUBE ALU.	281
	● END CAPS / TUBE PLUGS	131
	● END CAPS FOR DISTANCE TUBE	304
	● EXHIBITION BOARD	330
	● EXPOSURE DISPLAY PEM	337
	● EXPOSURE WALL	325
F	● FINNED DISTANCE TUBE PVC	304
	● FIREPROOF CORD	151
	● FISHBONE RIBBED JOINT PVC	306
	● FLAT ALU.	279
	● FLAT BRASS	279
	● FLAT SPACER	312
	● FLYER	331
	● FULL ROUND TUBE ALU.	280
	● FULL SQUARE TUBE ALU.	280
G	● GADGETS	338
	● GAP-COVERING BALLOON SHEATH	319
	● GASKETS FOR PRECAST FORMS	314
	● GDA 25, GDA 35, GDA 55 ALU.	150
	● GNS 20, GNS 50, GNS 75 ALU.	152
	● HINGE SUPPORT	131
I	● IRON	283
L	● LVT PROFILES	271
M	● MAGNET KIT	300
	● MEMBRANE CASE	329
	● MINICATALOGUE / BROCHURE	331
	● MODULAR ASSEMBLY KIT	193
	● MODULAR DISPLAY SYSTEM	332
	● MORTAR LAYING FULL JOINT	148
	● MORTAR-LAID DOUBLE JOINT	147
	● MORTAR-LAID JOINTS PVC	147

	● MORTAR-LAID JOINTS STEEL, BRASS, ALU.	146
	● MULTIPIEDE	309
	● MULTISPACER	291
P	● PAU	310
	● PAV	310
	● PAVIJOINT PVC	320
	● PIPE COLLAR PROFOIL	186,196
	● PREFORMED CORNERS AND PIPE COLLAR	188
	● PRO GOBOARD PANEL	205
	● PROANGLE BRASS	71
	● PROANGLE WOOD PVC	238
	● PROANGLE WOOD PVC	270
	● PROBAND 150/250	185
	● PROBAND BU	186
	● PROBAND FIX	186
	● PROBAND KOLL	186
	● PROBAND KOLL AB	186
	● PROBATH FLEX PVC	57
	● PROBATH PVC	57
	● PROBORD STEEL	45
	● PROBRASPTEP ALU.	121
	● PROCANAL ALU.	73
	● PROCANAL BRASS	73
	● PROCAP SYL	239
	● PROCARE CLEAN	300
	● PROCARPET ACC STEEL	77
	● PROCARPET ALL ALU.	78
	● PROCARPET OTT BRASS	77
	● PROCOVER 1045 ALL ALU.	86
	● PROCOVER 14PT ALU.	91
	● PROCOVER ALU.	89
	● PROCOVER ALU.	110
	● PROCOVER BRASS	88
	● PROCOVER STEEL	88
	● PROCOVER WOOD	89,110
	● PROCOVER WOOD	261
	● PROCURVE MACHINE	111
	● PRODESO DRAIN 5	174
	● PRODESO DRAIN 8	177
	● PRODESO ECO/ECO STICK	183
	● PRODESO HEAT / PRODESO / PROTERRACE DISPLAY	329
	● PRODESO HEAT GRIP SYSTEM	179
	● PRODESO HEAT KIT	182
	● PRODESO HEAT STICK	183
	● PRODESO HEAT SYSTEM	181
	● PRODESO MEMBRANE	185
	● PRODESO SOUND	187
	● PRODESO SOUND TAPE	187
	● PRODESO/PRODESO HEAT DISPLAY	329
	● PRODILAT ALU.	143
	● PRODILAT STEEL	143
	● PRODISTANZ	308
	● PRODRAIN 10	188
	● PRODRIP	171
	● PROECOFON	187
	● PROEDGE AC STEEL	46
	● PROEDGE AL ALU.	48
	● PROEDGE FLEX PVC	45
	● PROEDGE OT BRASS	46
	● PROEDGE PVC	48
	● PROEDGE R AC STEEL	47
	● PROEDGE R OT BRASS	47
	● PROELEGANT ALU.	68
	● PROELEGANT BRASS	68
	● PROELEGANT CURVE ALU.	107
	● PROELEGANT CURVE BRASS	107
	● PROEND 5050 ALU.	136
	● PROEND ALU.	132
	● PROEND GRIP 70 ALU.	136
	● PROEND GRIP ALU.	137
	● PROEND INS 75 ALU.	135
	● PROEND INS ALU.	135

	● PROEXPAN 115-130-190-210 ALU.	149
	● PROEXPAN H20-H40 ALU.	150
	● PROFILE T-FORM ALU.	282
	● PROFILE TRIANGULAR CHAMFER	306
	● PROFILE WITH DOUBLE CHAMFER	306
	● PROFILES COLOUR RANGE	328
	● PROFINAL ALU.	71
	● PROFINAL BRASS	70
	● PROFINAL CURVE ALU.	108
	● PROFINAL CURVE BRASS	108
	● PROFINAL STEEL	70
	● PROFINLIST 20 ALU.	44
	● PROFIXER LINE SYSTEM ALU.	262
	● PROFLAT STEEL-BRASS	73
	● PROFLEX 25 PVC	148
	● PROFLEX 5 PR PVC	145
	● PROFLEX 5 PVC	144
	● PROFLEX ACC PR STEEL	140
	● PROFLEX ACC STEEL	140
	● PROFLEX ACN STEEL	142
	● PROFLEX AL ALU.	141
	● PROFLEX ALN ALU.	142
	● PROFLEX OT BRASS	141
	● PROFLEX PVC	144
	● PROFLOOR 1216 STEEL-BRASS	84
	● PROFLOOR 24 STEEL-BRASS	85
	● PROFLOOR 712 ALU.	83
	● PROFLOOR 712 BRASS	83
	● PROFLOOR 712 STEEL	83
	● PROFOIL PANEL	189
	● PROFOIL PANEL NICHE	203
	● PROFOIL PASTE	188
	● PROFOIL/PROFOIL PRO	188
	● PROGRIP	117
	● PROGRIP	137
	● PROHEATER	206
	● PROINSERT (optional)	273
	● PROINSERT (top)	272
	● PROINTER AC STEEL	30
	● PROINTER AL ALU.	32
	● PROINTER KL	160
	● PROINTER KL ACC STEEL	30,160
	● PROINTER KL ALL BRASS-ALU.	32,160
	● PROINTER PVC	33
	● PROJOLLY ALU.	72
	● PROJOLLY BRASS	72
	● PROJOLLY ALU.	18
	● PROJOLLY ANGLE 135 STEEL	29
	● PROJOLLY BRASS	17
	● PROJOLLY CURVE ALU.	109
	● PROJOLLY CURVE BRASS	109
	● PROJOLLY ECO MARBLE PVC	25
	● PROJOLLY ECO PVC	24
	● PROJOLLY MARBLE PVC	23
	● PROJOLLY OPEN PVC	23
	● PROJOLLY PVC	22
	● PROJOLLY QUART ALU.	11
	● PROJOLLY QUART PVC	14
	● PROJOLLY QUART STEEL	10
	● PROJOLLY SQUARE ALU.	6
	● PROJOLLY SQUARE BRASS	5
	● PROJOLLY SQUARE PVC	9
	● PROJOLLY SQUARE STEEL	2
	● PROJOLLY STEEL	15
	● PROJOLLY TRIANGLE ALU.	28
	● PROJOLLY TRIANGLE BRASS	27
	● PROJOLLY TRIANGLE STEEL	26
	● PROKERLAM JOLLY / SQUARE ALL.	156
	● PROKERLAM LINE	58,157
	● PROKERLAM LINE ALL.	157
	● PROLEVALL 25-35-38 ALU.	99
	● PROLEVALL 29 ALU.	79

●	PROLEVAL 305 STEEL-BRASS	80
●	PROLEVAL 32 ALU.	80
●	PROLEVAL 33 BRASS	79
●	PROLEVAL 358 BRASS	81
●	PROLEVAL 4413 BRASS-ALU.	81
●	PROLEVELING SYSTEM	289
●	PROLEVELING SYSTEM BOARD	330
●	PROLEVELING SYSTEM DISPLAY	330
●	PROLEVELING WEDGE SYSTEM	290
●	PROLEVELING WEDGE SYSTEM BOARD	330
●	PROLEVIGAL ALU.	67
◊	PROLEVIGAL BRASS	67
●	PROLINOLEUM ALU.	85
●	PROLISTEL ACC STEEL	40
●	PROLISTEL ALL ALU.	43
●	PROLISTEL AND SKIRTING DISPLAY	326
●	PROLISTEL CHANNEL ALL.	34,198
●	PROLISTEL CHANNEL STEEL	34,198
●	PROLISTEL LED ALU.	43
●	PROLISTEL P ALL ALU.	42
●	PROLISTEL P BRASS	41
◊	PROMEMBRANE KOLL	186
●	PROMOQUETTE ALU.	100
●	PROMOQUETTE FIX ALU.	100
●	PROMOQUETTE GIN ALU.	101
●	PROMULTIFIX SYSTEM	245
◊	PROMULTISKIRT ROUND pvc	233,267
◊	PROMULTISKIRT SQUARE pvc	232,266
●	PRONIVO ALU.	82
●	PROPLATE 80 ALZ ALU.	91
●	PROPLATE BRASS	90
●	PROPLATE FIX ALU.	153
●	PROPLATE FIX PVC	153
●	PROPLATE STEEL	90
●	PROPOLISH	300
●	PROPRESS 712 STEEL-BRASS	84
●	PRORAIL SYSTEM	296
●	PROROUND STEEL	54
●	PROSANI STRIP PVC	54
●	PROSCREW ALU. BASE + TOP	264
●	PROSCREW ALU. TOP	264
●	PROSCREW BASE ALU.	264
●	PROSEAL 25 PVC	56
●	PROSEAL 50 PVC	55
●	PROSEAL FLEX PVC	56
●	PROSEAL WOOD PVC	238,270
●	PROSGUSCIO DA PVC	53
◊	PROSHELF	205
●	PROSHELL ALL ALU.	52
●	PROSHELL D ALL ALU.	159
●	PROSHELL R ALL ALU.	159
◊	PROSHELL STEEL	50
●	PROSHOWER BASE BASIC PVC	191
◊	PROSHOWER BASE L PRO	194
●	PROSHOWER BASE L STEEL	191
●	PROSHOWER CENTRAL PANEL	200
◊	PROSHOWER DRAIN CENTRAL PRO	201
●	PROSHOWER DRAIN LATERAL KIT	201
●	PROSHOWER LINEAR KIT SYSTEM	190
●	PROSHOWER PANEL	190
●	PROSHOWER PROFILE	196
●	PROSHOWER PROFILE FRONT	197
●	PROSHOWER PROFILE GLASS	196
●	PROSHOWER PROFILE WALL	197
●	PROSHOWER SYSTEM DISPLAY	329
●	PROSHOWER TOP PRO	194
◊	PROSHOWER TOP STEEL	192
●	PROSIDE WALK	167
●	PROSIDE WALK ALU.	123
●	PROSKID BRASS-ALU.	78
●	PROSKIRTING 40 ALU.	221
●	PROSKIRTING ALU.	220
●	PROSKIRTING CHANNEL ALU.	211
●	PROSKIRTING FLAT ALU.	211
●	PROSKIRTING GILED ALU.	219
●	PROSKIRTING INS ALU.	212
●	PROSKIRTING ISP ALU.	213
●	PROSKIRTING LED / GILED DISPLAY	328
●	PROSKIRTING LED ALU.	217
●	PROSKIRTING LINE ALU.	212
●	PROSKIRTING LIST	214
●	PROSKIRTING SHELL ALU.	221
●	PROSLIDER ALU.	75
●	PROSLIDER BRASS	74
●	PROSLIDER CURVE ALU.	111
●	PROSLIDER CURVE BRASS	111
●	PROSLIDER KL ALL ALU.	86
●	PROSLIDER LR ALU.	75
●	PROSLIDER STEEL	74
●	PROSLIDER WOOD	76
●	PROSOL 18-30-35-40 BRASS	95
●	PROSOL 18-30-35-40 STEEL	93
●	PROSOL 30-35-40 ALU.	97
●	PROSQUARE BRASS	71
●	PROSTAIR 50 ALU.	119
●	PROSTAIR ACC STEEL	114
●	PROSTAIR ALU.	120
●	PROSTAIR BBRASSON / STRIP STEEL	121
●	PROSTAIR GRIP ACC STEEL	117
●	PROSTAIR KL 20 ALU.	161
●	PROSTAIR LED ALU.	124
●	PROSTAIR WOOD	128
●	PROSTAIR WOOD Z	128
●	PROSTEP INS ALU.	127
●	PROSTEP PVC	120
●	PROSTEP WOOD	129
●	PROSTYLE 2610 STEEL	114
●	PROSTYLE ALU.	127
●	PROSTYLE BRASS	126
●	PROSTYLE GRIP ACC STEEL	118
●	PROSTYLE KL 10 ALU.	161
●	PROSTYLE STEEL	126
●	PROSTYLE WOOD	129
●	PROSUPPORT PROFILE A & B	295
●	PROSUPPORT PROFILE T & N	295
●	PROSUPPORT SLIM SYSTEM	298
●	PROSUPPORT TUBE DISPLAY	330
●	PROSUPPORT TUBE SYSTEM	292
●	PROTECTIVE CAPS	312
●	PROTERMINAL ALU.	37
●	PROTERMINAL ALU.	66
●	PROTERMINAL BRASS	37
●	PROTERMINAL BRASS	65
●	PROTERMINAL CURVE ALU.	105
●	PROTERMINAL CURVE BRASS	105
●	PROTERMINAL CURVE STEEL	104
●	PROTERMINAL INT ALU.	35
●	PROTERMINAL PVC	39
●	PROTERMINAL STEEL	16
●	PROTERMINAL STEEL	36
●	PROTERMSTEP ACC STEEL	122
●	PROTERMSTEP ACC STEEL	59
●	PROTERMSTEP ACC STEEL	122
●	PROTERMSTEP ALL ALU.	122
●	PROTERRACE DISPLAY	330
◊	PROTERRACE DOUBLE DRIP ALU.	164
●	PROTERRACE DRAIN DRIP ALU.	165
●	PROTERRACE DRAIN FDP ALU.	166
●	PROTERRACE ECO DRIP ALU.	167
●	PROTERRACE PC ALU.	169
●	PROTERRACE PC STEEL	169
●	PROTERRACE PCG ALU.	168
●	PROTERRACE PCG STEEL	168
◊	PROTERRACE UNDER EDGE L/C	170
●	PROTOP ALU.	60
●	PROTOP T ALU.	60
●	PROTRANS ALU.	82
●	PROWALK 2510 & 2520 ALU.	134
●	PROWALK ACC STEEL	132
●	PROWALK BRASS-ALU.	133
●	RAPY 100	309
●	RAPY 100 ECO	309
●	RAPY 200	309
●	RIBBED DISTANCE TUBE PVC	305
●	ROLLER	301
●	ROTATING DISPLAY	326
●	ROUNDED TRIANGULAR CHAMFER FILLET	306
●	SAMPLE BOARD	326
●	SAMPLE CASES	328
●	SCISSORS FOR PVC PROFILES	300
●	SHEATH LAYING TROLLEY	321
●	SHOWROOM SET-UP EXAMPLES	334
●	SKIRTING 100 ALU.	231
●	SKIRTING 100-150 STEEL	230
●	SKIRTING 40 ALU.	225
●	SKIRTING 40 PVC	235
●	SKIRTING 40 PVC	269
●	SKIRTING 40 STEEL	224
●	SKIRTING 60 ALU.	227
●	SKIRTING 60 STEEL	226
●	SKIRTING 60/120 PVC	236
●	SKIRTING 62F PVC	236
◊	SKIRTING 7011 PVC	235,269
◊	SKIRTING 7016 PVC	234,268
●	SKIRTING 80 ALU.	229
●	SKIRTING 80 STEEL	228
●	SKIRTING COVECAP PVC	239
●	SKIRTING PVC	237
◊	SKIRTING ROTATING DISPLAY	327
●	SMALL EXPOSURE STAND	326
●	SNAP-ON STRAND SHEATH PVC	304
●	SNAP-ON STRAND TUBE PVC	304
●	SOL 30 AUTOADESIVI ALU.	260
●	SOL 30P LVT	258
●	SOL 40 P ALU. (proinsert)	249
●	SOL 40P ALU.	261
●	SPACER FOR GLASS BRICK	311
●	SPACER FOR VERTICAL / HORIZONTAL MESH	311
●	SPACERS DISPLAY	330
●	SPACERS LEVELING WEDGES	291
●	SPACERS PAX-PAL-PAS	313
●	SQUARE SHOW CASE	324
●	STYLE STAIR ALU.	254
●	STYLE STAIR L ALU.	255
●	SUPPORT / EYELET	131
●	SUPPORT AND LEVELLER	299
●	TERMINAL ALU.	253
●	TERMINAL CURVE ALU.	110
●	TERMINAL PIN ALU. (proinsert)	252
●	TERMINAL PIN LVT	258
●	TROLLEY	326
●	TROWEL	301
●	TROWEL PVC	301
●	TUBE FOR RUNNERS	131
●	TUBES AND ACCESSORIES	131
◊	WALL DRAIN BOX	195
●	WATERSTOP	307
●	ZERO CURVE ALU. (proinsert)	250
●	ZERO CURVE AUTOADESIVI ALU.	260
●	ZERO CURVE LVT	258

● PROFILES FOR WALLS

ARTICLE	CODE	PAGE
PROJOLLY SQUARE STEEL	PJQSAC...	2
◊ PROJOLLY SQUARE BRASS	PJQSOS...	5
PROJOLLY SQUARE ALU.	PJQS...	6
PROJOLLY SQUARE PVC	PJQ...	9
PROJOLLY QUART STEEL	PJQTAC...	10
PROJOLLY QUART ALU.	PJQT...	11
PROJOLLY QUART PVC	PJQT...	14
PROJOLLY STEEL	PJAC...	15
PROTERMINAL STEEL	PTAC...	16
PROJOLLY BRASS	PJO...	17
PROJOLLY ALU.	PJ...	18
PROJOLLY PVC	PJ...	22
PROJOLLY MARBLE PVC	PJ...	23
PROJOLLY OPEN PVC	PJP	23
PROJOLLY ECO PVC	PJE...	24
PROJOLLY ECO MARBLE PVC	PJE...	25
PROJOLLY TRIANGLE STEEL	PJTRAC...	26
PROJOLLY TRIANGLE BRASS	PJTRO...	27
PROJOLLY TRIANGLE ALU.	PJTR...	28
PROJOLLY ANGLE 135 STEEL	PJTR135...	29
PROINTER AC STEEL	PIAC...	30
PROINTER KL ACC STEEL	PIKLAC...	30
PROINTER AL ALU.	PI...	32
PROINTER KL ALL BRASS-ALU.	PIKL...	32
PROINTER PVC	PI...	33
PROLISTEL CHANNEL ALU.	PLTCH...	34
PROLISTEL CHANNEL STEEL	PLTCH...	34
PROTERMINAL INT ALU.	PTI...	35
PROTERMINAL STEEL	PTAC...	36
PROTERMINAL ALU.	PT...	37
◊ PROTERMINAL BRASS	PTO...	37
PROTERMINAL PVC	PT...	39
PROLISTEL ACC STEEL	PLTAC...	40
PROLISTEL P BRASS	PLTPO...	41
PROLISTEL P ALL ALU.	PLTP...	42
PROLISTEL ALL ALU.	PLT...	43
PROLISTEL LED ALU.	PLTLED	43
PROFINLIST 20 ALU.	PFLT...	44
PROBORD STEEL	PEBD...	45
PROEDGE FLEX PVC	PFC...40	45
PROEDGE AC STEEL	PEGAC...	46
PROEDGE OT BRASS	PEGO...	46
PROEDGE R AC STEEL	PEGRAC...	47
PROEDGE R OT BRASS	PEGRO...	47
PROEDGE AL ALU.	PEG...	48
PROEDGE PVC	PEGA...	48
PROSHELL STEEL	PSHAC...	50
PROSHELL ALL ALU.	PSHA...	52
PROSGUSCIO DA PVC	PS...	53
PROROUND STEEL	PRDAC	54
PROSANI STRIP PVC	PSS...	54
PROSEAL 50 PVC	PSA...	55
PROSEAL 25 PVC	PSA...	56
PROSEAL FLEX PVC	PSF...	56
PROBATH FLEX PVC	PSBF...	57
PROBATH PVC	PSB...	57
PROKERLAM LINE	PKLL...	58
PROTERMSTEP ACC STEEL	PTSPAC...	59
PROTOP ALU.	PCT...	60
PROTOP T ALU.	PCT...T	60




● PROFILES FOR FLOORS

ARTICLE	CODE	PAGE
PROTERMINAL BRASS	PTO...	65
PROTERMINAL ALU.	PT...	66
PROLEVIGAL ALU.	PLG...	67
PROLEVIGAL BRASS	PLG...	67
PROLEGANT ALU.	PLG...	68
PROLEGANT BRASS	PEL...	68
PROFINAL BRASS	PRFO...	70
PROFINAL STEEL	PRFAC...	70
PROANGLE BRASS	PGA...	71
PROFINAL ALU.	PQE...	71
PROSQUARE BRASS	PRFA...	71
PROJOINT ALU.	PITA...	72
PROJOINT BRASS	PITO...	72
PROCANAL ALU.	PCLA...	73
◊ PROCANAL BRASS	PCLO...	73
PROFLAT STEEL-BRASS	GPL...	73
PROSLIDER BRASS	PDO...	74
PROSLIDER STEEL	PDAC...	74
PROSLIDER ALU.	PDA...	75
PROSLIDER LR ALU.	PDLRA...	75
PROSLIDER WOOD	PDWR...	76
PROCARPET ACC STEEL	PRTAC...	77
PROCARPET OTT BRASS	PRTO...	77
PROCARPET ALL ALU.	PRTA...	78
PROSKID BRASS-ALU.	PSLD...	78
PROLEVALL 29 ALU.	PLV...29	79
PROLEVALL 33 BRASS	PLVOL 33	79
PROLEVALL 305 STEEL-BRASS	PLV...30...	80
PROLEVALL 32 ALU.	PLV...32	80
PROLEVALL 358 BRASS	PLVOL 358...	81
PROLEVALL 4413 BRASS-ALU.	PLVOL 4413	81
PRONIVO ALU.	PNVA... 713	82
PROTRANS ALU.	PTS.. 613	82
PROFLOOR 712 ALU.	PFRAC...712	83
PROFLOOR 712 BRASS	PFRAC...712	83
PROFLOOR 712 STEEL	PFRA... 712	83
PROFLOOR 1216 STEEL-BRASS	PFR...1216	84
PROPRESS 712 STEEL-BRASS	PRS...712...	84
PROFLOOR 24 STEEL-BRASS	PFR...24...	85
PROLINOLEUM ALU.	PLU...16	85
PROCOVER 1045 ALL ALU.	PCR...1045	86
PROSLIDER KL ALL ALU.	PDKLA...	86
◊ PROCOVER BRASS	PCRO...	88
PROCOVER STEEL	PCRAC...	88
PROCOVER ALU.	PCR...	89
PROCOVER WOOD	PCRA...	89
PROPLATE BRASS	PETO...	90
PROPLATE STEEL	PETAC...	90
PROCOVER 14PT ALU.	PCR...14PT	91
PROPLATE 80 ALZ ALU.	PETAA...	91
PROSOL 18-30-35-40 STEEL	PLSAC...	93
PROSOL 18-30-35-40 BRASS	PLSO...	95
PROSOL 30-35-40 ALU.	PLS...	97
PROLEVALL 25-35-38 ALU.	PLV...	99
PROMOQUETTE ALU.	PMF...	100
PROMOQUETTE FIX ALU.	PMQ...	100
PROMOQUETTE GIN ALU.	PMG...	101




● CURVE PROFILES

ARTICLE	CODE	PAGE
PROTERMINAL CURVE STEEL	PTACV...	104
PROTERMINAL CURVE ALU.	PTANCV...	105
PROTERMINAL CURVE BRASS	PTONCV...	105
PROELEGANT CURVE ALU.	PELAACV...	107
PROELEGANT CURVE BRASS	PELONCV...	107
PROFINAL CURVE ALU.	PRFAACV...	108
PROFINAL CURVE BRASS	PRFONCV...	108
PROJOLLY CURVE ALU.	PJAACV...	109
PROJOLLY CURVE BRASS	PJONCV...	109
PROCOVER ALU.	PCR...	110
PROCOVER WOOD	PCRA...	110
TERMINAL CURVE ALU.	PINT...	110
PROCURVE MACHINE	PCM 08	111
PROSLIDER CURVE ALU.	PDAACV...	111
PROSLIDER CURVE BRASS	PDONCV...	111




● STAIR NOSINGS PROFILES

ARTICLE	CODE	PAGE
PROSTAIR ACC STEEL	PSYACS 2610	114
PROSTYLE 2610 STEEL	PTRACS...	114
PROGRIP	PGR...	117
PROSTAIR GRIP ACC STEEL	PTRGRACS...	117
PROSTYLE GRIP ACC STEEL	PSYGRACS 6020	118
PROSTAIR 50 ALU.	PTR50...	119
PROSTAIR ALU.	PTP...	120
PROSTEP PVC	PTR...	120
PROBRASSTEP ALU.	PBP...	121
PROSTAIR BRASSON / STRIP STEEL	PTRB...	121
PROTERMSTEP ACC STEEL	PTSPA...	122
PROTERMSTEP ACC STEEL	ptspac...	122
PROTERMSTEP ALL ALU.	PTSPAC...	122
PROSIDE WALK ALU.	PSDWK...	123
PROSTAIR LED ALU.	PTRLEDAA...	124
PROSTYLE BRASS	PSYO...	126
PROSTYLE STEEL	PSYAC...	126
PROSTEP INS ALU.	PTSAA...	127
PROSTYLE ALU.	PSYA...	127
PROSTAIR WOOD	PTRW...	128
PROSTAIR WOOD Z	PTRWZ...	128
PROSTEP WOOD	PSYW...	129
PROSTYLE WOOD	PTPW...	129
END CAPS / TUBE PLUGS	TET...	131
HINGE SUPPORT	SC...	131
SUPPORT / EYELET	SO...	131
TUBE FOR RUNNERS	TGS...	131
TUBES AND ACCESSORIES	TCT...	131
PROEND ALU.	PED...	132
PROWALK ACC STEEL	PWKAC...	132
PROWALK BRASS-ALU.	PWK...	133
PROWALK 2510 & 2520 ALU.	PWK...25...	134
PROEND INS 75 ALU.	PED 4528...	135
PROEND INS ALU.	PED...7537	135
PROEND 5050 ALU.	PEGR...7032	136
PROEND GRIP 70 ALU.	PEGRAA 50	136
PROEND GRIP ALU.	PEGR... 5230	137
PROGRIP	PGR...	137




● EXPANSION JOINTS

ARTICLE	CODE	PAGE
PROFLEX ACC PR STEEL	PFXACPR...	140
PROFLEX ACC STEEL	PFXAC...	140
PROFLEX AL ALU.	PFXAL...	141
PROFLEX OT BRASS	PFXOT...	141
PROFLEX ACN STEEL	PFXACN...	142
PROFLEX ALN ALU.	PFXALN...	142
PRODILAT ALU.	GCAN...	143
PRODILAT STEEL	GCAC...	143
PROFLEX 5 PVC	PFX...	144
PROFLEX PVC	PFX5...	144
PROFLEX 5 PR PVC	PFX5PR...	145
ADHESIVE-LAID JOINTS	C51...	146
MORTAR-LAID JOINTS STEEL, BRASS, ALU.	G...	146
MORTAR-LAID DOUBLE JOINT	GDSP...	147
MORTAR-LAID JOINTS PVC	C51...	147
MORTAR LAYING FULL JOINT	GP...	148
PROFLEX 25 PVC	PFX...	148
PROEXPAN 115-130-190-210 ALU.	PENF...	149
GDA 25, GDA 35, GDA 55 ALU.	GDA ...	150
PROEXPAN H20-H40 ALU.	PEN...	150
FIREPROOF CORD	GDA 55...	151
GNS 20, GNS 50, GNS 75 ALU.	GNS...	152
PROPLATE FIX ALU.	PETFX...	153
PROPLATE FIX PVC	PETFXPAA...	153



● LOW THICKNESS PROFILES

ARTICLE	CODE	PAGE
PROKERLAM JOLLY / SQUARE ALL.	PKL...	156
PROKERLAM LINE	PKLL...	157
PROKERLAM LINE ALL.	PKLL...	157
PROSHELL D ALL ALU.	PSHD...	159
PROSHELL R ALL ALU.	PSHR...	159
PROINTER KL	PIKL...	160
PROINTER KL ACC STEEL	PIKLAC...	160
PROINTER KL ALL BRASS-ALU.	PIKL...	160
PROSTAIR KL 20 ALU.	PSYKLA 1045	161
PROSTYLE KL 10 ALU.	PTRKLA 2045	161




● PROFILES FOR TERRACES

ARTICLE	CODE	PAGE
PROTERRACE DOUBLE DRIP ALU.	PDD...	164
PROTERRACE DRAIN DRIP ALU.	PFDDP...	165
PROTERRACE DRAIN FDP ALU.	PFDP...	166
PROSIDE WALK	PSDWK...	167
PROTERRACE ECO DRIP ALU.	PTEDP...	167
PROTERRACE PCG ALU.	PCG...	168
PROTERRACE PCG STEEL	PCG...	168
PROTERRACE PC ALU.	PC...	169
PROTERRACE PC STEEL	PC...	169
PROTERRACE UNDER EDGE L/C	PTUE...	170
PRODRIIP	PDRP	171

MEMBRANES & PANELS

ARTICLE	CODE	PAGE
PRODESO DRAIN 5	PDDR...	174
PRODESO DRAIN 8	PDDR...	177
PRODESO HEAT GRIP SYSTEM	PDESHG...	179
PRODESO HEAT SYSTEM	PDESH...	181
PRODESO HEAT KIT	PDESHK...	182
PRODESO ECO/ECO STICK	PDESEC...	183
PRODESO HEAT STICK	PDESHST...	183
PROBAND 150/250	PRBPE...	185
PRODESO MEMBRANE	PDES...	185
PIPE COLLAR PROFOIL	PRBT	186
PROBAND BU	PRBBU...	186
PROBAND FIX	PRBFX...	186
PROBAND KOLL	PRBKL...	186
PROBAND KOLL AB	PRBKLAB...	186
PROMEMBRANE KOLL	PRMKL	186
PRODESO SOUND	PDSND...	187
PRODESO SOUND TAPE	PDSNDTP...	187
PROECOFON	PEF...	187
PREFORMED CORNERS AND PIPE COLLAR	PRB...	188
PRORAIN 10	PDR1 10	188
PROFOIL PASTE	PFLOPST...	188
PROFOIL/PROFOIL PRO	PFLO...	188
PROFOIL PANEL	PFLPAN...	189



SHOWER SYSTEMS

ARTICLE	CODE	PAGE
PROSHOWER LINEAR KIT SYSTEM	PSHPANEK	190
PROSHOWER PANEL	PSHPAN	190
PROSHOWER BASE BASIC PVC	PSHWBB...	191
PROSHOWER BASE L STEEL	PSHWDL...	191
PROSHOWER TOP STEEL	PSHWDL...	192
DRAIN REDUCTION	PSHWDR...	193
MODULAR ASSEMBLY KIT	PSHW...	193
PROSHOWER BASE L PRO	PSHWP...	194
PROSHOWER TOP PRO	PSHWPLT...	194
WALL DRAIN BOX	KBPSHWAC...	195
PIPE COLLAR PROFOIL	PRBT	196
PROSHOWER PROFILE	PSHWPCS...	196
PROSHOWER PROFILE GLASS	PSHWPGACS...	196
PROSHOWER PROFILE FRONT	PSHWPFACS...	197
PROSHOWER PROFILE WALL	PSHWPLACS...	197
PROLISTEL CHANNEL ALL.	PLTCH...	198
PROLISTEL CHANNEL STEEL	PLTCH...	198
PROSHOWER CENTRAL PANEL	PSHPANCEK	200
PROSHOWER DRAIN CENTRAL PRO	PSHWCP	201
PROSHOWER DRAIN LATERAL KIT	PSHLDK	201
PROFOIL PANEL NICHE	PFLPANICH	203
PRO GOBOARD PANEL	PGBORD	205
PROSHELF	PRSHLF...	205
PROHEATER	PHTST...	206




SKIRTING

ARTICLE	CODE	PAGE
PROSKIRTING CHANNEL ALU.	PKCHAA...	211
PROSKIRTING FLAT ALU.	PKFLAA...	211
PROSKIRTING INS ALU.	PKINSAA 60	212
PROSKIRTING LINE ALU.	PKLIAA	212
PROSKIRTING ISP ALU.	PKISPAA...	213
PROSKIRTING LIST	PKLT...	214
PROSKIRTING LED ALU.	PKLEDA...	217
PROSKIRTING GILED ALU.	PKGLEDA...	219
PROSKIRTING ALU.	PKAA...	220
PROSKIRTING 40 ALU.	PKSHAA 70	221
PROSKIRTING SHELL ALU.	PKSHAA...	221
SKIRTING 40 STEEL	BTAC... 40	224
SKIRTING 40 ALU.	BTA... 40	225
SKIRTING 60 STEEL	BTAC... 60	226
SKIRTING 60 ALU.	BTA... 60	227
SKIRTING 80 STEEL	BTAC... 80	228
SKIRTING 80 ALU.	BTA... 80	229
SKIRTING 100-150 STEEL	BTAC...	230
SKIRTING 100 ALU.	BTA...100	231
PROMULTISKIRT SQUARE pvc	BTEPR...S	232
PROMULTISKIRT ROUND pvc	BTEPR...R	233
SKIRTING 7016 PVC	BTEPR...7016	234
SKIRTING 40 PVC	BTEPR...4010	235
SKIRTING 7011 PVC	BTEPR...7011	235
SKIRTING 60/120 PVC	BTPV...	236
SKIRTING 62F PVC	BTPF...	236
CORNER PVC	AGE...25	237
SKIRTING PVC	BTPR...	237
PROANGLE WOOD PVC	PGAW...15	238
PROSEAL WOOD PVC	PSAW...20	238
PROCAP S/L	PRCPS...	239
SKIRTING COVECAP PVC	PRCP...	239

PROFILES FOR WOOD

ARTICLE	CODE	PAGE
PROMULTIFIX SYSTEM	PMPFX...	245
SOL 40 P ALU. (proinsert)	PISPC...	249
ZERO CURVE ALU. (proinsert)	PINZC...	250
TERMINAL PIN ALU. (proinsert)	PINTPC...	252
TERMINAL ALU.	PTSAA...	253
STYLE STAIR ALU.	PINYC...	254
STYLE STAIR L ALU.	PINYLC...	255
SOL 30P LVT	PISPC...	258
TERMINAL PIN LVT	PINTPC...	258
ZERO CURVE LVT	PINZC...	258
SOL 30 AUTOADESIVI ALU.	PINS...	260
ZERO CURVE AUTOADESIVI ALU.	PINZ...	260
PROCOVER WOOD	PCRA...	261
SOL 40P ALU.	PNSP...	261
PROFIXER LINE SYSTEM ALU.	PINZ...	262
PROSCREW ALU. BASE + TOP	PSWC...	264
PROSCREW ALU. TOP	PSWC...	264
PROSCREW BASE ALU.	PSWC...	264
PROMULTISKIRT SQUARE pvc	BTEPR...S	266
PROMULTISKIRT ROUND pvc	BTEPR...R	267
SKIRTING 7016 PVC	BTEPR...7016	268
SKIRTING 40 PVC	BTEPR...4010	269
SKIRTING 7011 PVC	BTEPR...7011	269
PROANGLE WOOD PVC	PGAW...15	270
PROSEAL WOOD PVC	PSAW...20	270
LVT PROFILES	PIN...	271
PROINSERT (top)	PIN...	272
PROINSERT (optional)	VIN...	273



● DO IT YOURSELF

ARTICLE	CODE	PAGE
CORNER EQUAL SIDES ALU.	AG...	276
CORNER EQUAL SIDES BRASS	AGOL...	276
CORNER EQUAL SIDES STEEL	AGAC...	276
CORNER EQUAL SIDES PVC	AGP...	277
CORNER L-FORM ALU.	AL...	277
CORNER L-FORM PVC	ALP...	277
CANAL DOUBLE U-FORM ALU.	CW...	278
CANAL U-FORM.	CU...	278
FLAT ALU.	PI...	279
FLAT BRASS	PI...	279
EMPTY ROUND TUBE ALU.	TV...	280
FULL ROUND TUBE ALU.	TP...	280
FULL SQUARE TUBE ALU.	TQP...	280
CURVE PROFILE ALU.	UG...	281
EMPTY RECTANGULAR TUBE ALU.	TR...	281
EMPTY SQUARE TUBE ALU.	TQV...	281
CONTRAINBALANCE ALU.	CT...	282
PROFILE T-FORM ALU.	T...	282
IRON	PIF...	283



● PRODUCTS FOR LAYING

ARTICLE	CODE	PAGE
PROLEVELING SYSTEM	PRS...	289
PROLEVELING WEDGE SYSTEM	PRLW...	290
MULTISPACER	MSP...	291
SPACERS LEVELING WEDGES	R...	291
PROSUPPORT TUBE SYSTEM	PST...	292
PROSUPPORT PROFILE A & B	PFPSAL...	295
PROSUPPORT PROFILE T & N	PSPRPT...	295
PRORAIL SYSTEM	PSTRAN	296
PROSUPPORT SLIM SYSTEM	PSTSL...	298
SUPPORT AND LEVELLER	SQG...	299
MAGNET KIT	KMD	300
PROCARE CLEAN	PRCLEAN	300
PROPOLISH	PRLISH	300
SCISSORS FOR PVC PROFILES	FTPP	300
ROLLER	PRSPD 10	301
TROWEL	PFTT...	301
TROWEL PVC	PSM	301



● BUILDINGS SYSTEM

ARTICLE	CODE	PAGE
END CAPS FOR DISTANCE TUBE	PPT...	304
FINNED DISTANCE TUBE PVC	TDA...	304
SNAP-ON STRAND SHEATH PVC	R11...	304
SNAP-ON STRAND TUBE PVC	R11...	304
DRIP PVC	GCT...	305
RIBBED DISTANCE TUBE PVC	PPD...	305
FISHBONE RIBBED JOINT PVC	GRP...	306
PROFILE TRIANGULAR CHAMFER	PST...	306
PROFILE WITH DOUBLE CHAMFER	R...	306
ROUNDED TRIANGULAR CHAMFER FILLET	PSD...	306



ANCHORING CLIPS FOR WATERSTOP	CLPS	307
WATERSTOP	WP...	307
PRODISTANZ	PDZ...	308
MULTIPIEDE	DMP...	309
RAPY 100	PLF...	309
RAPY 100 ECO	PLF...R...	309
RAPY 200	PLFE...	309
PAU	PPU...	310
PAV	PPV...	310
DOPPY	PPY...	311
SPACER FOR GLASS BRICK	DSVT	311
SPACER FOR VERTICAL / HORIZONTAL MESH	DVO...	311
FLAT SPACER	PPN...	312
PROTECTIVE CAPS	PCPF...	312
SPACERS PAX-PAL-PAS	PP...	313
GASKETS FOR PRECAST FORMS	M...	314
GAP-COVERING BALLOON SHEATH	C 550...	319
PAVJOINT PVC	PVJ...	320
SHEATH LAYING TROLLEY	CPGC...	321



● MARKETING


ARTICLE	CODE	PAGE
SQUARE SHOW CASE	ESPQC...	324
EXPOSURE WALL	ESHSPAN 250	325
PROLISTEL AND SKIRTING DISPLAY	ESPCLSH...	326
ROTATING DISPLAY	ESPGSM 18	326
SAMPLE BOARD	PESP...	326
SMALL EXPOSURE STAND	CURAS	326
TROLLEY	TRAG18	326
SKIRTING ROTATING DISPLAY	ESPGSMBT	327
PROFILES COLOUR RANGE	COL...	328
PROSKIRTING LED / GILED DISPLAY	ESPGLED...	328
SAMPLE CASES	COF...	328
MEMBRANE CASE	COFMIE	329
PRODESO HEAT / PRODESO / PROTERRACE DISPLAY	ESPPDHT...	329
PRODESO/PRODESO HEAT DISPLAY	SPCPDES...	329
PROSHOWER SYSTEM DISPLAY	ESPSHW 70	329
EXIBITION BOARD	PNPSR	330
PROLEVELING SYSTEM BOARD	PNPLS	330
PROLEVELING SYSTEM DISPLAY	ESPPLS	330
PROLEVELING WEDGE SYSTEM BOARD	PNPLWS	330
PROSUPPORT TUBE DISPLAY	ESPPST	330
PROTERRACE DISPLAY	ESPFDP	330
SPACERS DISPLAY	ESPD	330
BROCHURE	BR...	331
CATALOGUES	CAT...	331
COUNTER DISPLAY FOR BROCHURES	ESPB...	331
COUNTER DISPLAY FOR FLYER	PBPLS...	331
FLYER	FLY...	331
MINICATALOGUE / BROCHURE	MCAT...	331
MODULAR DISPLAY SYSTEM	-	332
SHOWROOM SET-UP EXAMPLES	-	334
DISPLAYS FOR PROFILES	PEP...	337
EXPOSURE DISPLAY PEM	PEM	337
GADGETS	-	338





An interpretation of:
**Unicredit Tower, César Pelli &
Vertical Forest, Stefano Boeri Architetti, MILAN (Italy), 2014**


PROFILES FOR WALLS



PROJOLLY SQUARE


POLISHED, SUPER POLISHED, SANDED AND BRUSHED STAINLESS STEEL AISI 304/1.4301-V2A

PROJOLLY SQUARE is a square corner bead profile in polished, super polished, sanded, brushed stainless steel AISI 304/1.4301-V2A that can be applied on external corners of coverings. It can be used to close the perimeter of coverings, like a connection profile between step tread and riser of stairs coated with ceramic and natural stone tiles, and also as separation profile for floor and wall coverings. Its particular section, the availability in three different finishes and special pieces such as internal and external corners, end caps and joints make **PROJOLLY SQUARE** a much sought-after profile that allows a workmanlike application even in environments subject to high mechanical stresses.



PJQSAC/S 11 & PJQSACML 11 AVAILABLE H 11 MM
PJQSAC/S 15 & PJQSACML 15 AVAILABLE H 15 MM

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROJOLLY SQUARE" according to the tile thickness and desired finish.
2. Cut "PROJOLLY SQUARE" to the desired length and apply the adhesive on the support where the profile will be laid.
3. Press the anchoring flange of "PROJOLLY SQUARE" into the adhesive.
4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile.
5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.



POLISHED STAINLESS STEEL AISI 304/1.4301-V2A with protective film
bar length 2,7 lm - Pack 20 Pcs - 54 lm (H 4,5 - 108 lm) - 8/10 mm

Article	H mm		
PJQSAC 045	4,5		
PJQSAC 06	6		
PJQSAC 07	7		
PJQSAC 08	8		
PJQSAC 09	9		
PJQSAC 10	10		
PJQSAC 11	11		
PJQSAC 125	12,5		
PJQSAC 15	15		

SUPER POLISHED STAINLESS STEEL AISI 304/1.4301-V2A thermo Packed
bar length 2,7 lm - Pack 20 Pcs - 54 lm - 8/10 mm

Article	H mm		
PJQSACML 045	4,5		
PJQSACML 06	6		
PJQSACML 07	7		
PJQSACML 08	8		
PJQSACML 09	9		
PJQSACML 10	10		
PJQSACML 11	11		
PJQSACML 125	12,5		
PJQSACML 15	15		

SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS.



Brushed STAINLESS ST. AISI 304/1.4301-V2A with protective film
bar length 2,7 lm - Pack 20 Pcs - 54 lm (H 4,5 - 108 lm) - 8/10 mm

Article	H mm		
PJQSACS 045	4,5		
PJQSACS 06	6		
PJQSACS 07	7		
PJQSACS 08	8		
PJQSACS 09	9		
PJQSACS 10	10		
PJQSACS 11	11		
PJQSACS 125	12,5		
PJQSACS 15	15		

SANDED STAINLESS STEEL AISI 304/1.4301-V2A with protective film
bar length 2,7 lm - Pack 20 Pcs - 54 lm - 8/10 mm

Article	H mm		
PJQSACSB 07	7		
PJQSACSB 08	8		
PJQSACSB 09	9		
PJQSACSB 10	10		
PJQSACSB 125	12,5		

COLOURS



ACSB - SPECIAL FINISH, REQUEST AVAILABILITY

CAPSULES, END CAPS and THREE-WAYS JOINTS

POLISHED, SUPER POLISHED, SATIN AND SANDED FINISH ST. STEEL AISI 304/1.4301-V2A / PLASTIC

* Capsules & end caps of the on demand profiles are also on demand

CAPSULES and END CAPS - POLISHED STAINLESS STEEL AISI 304/1.4301-V2A

Article	H mm	Pack 10 Pcs	Pack 2 Pcs
CPJQSAC .../...	045/06/07/08/09/10/11/125/15		
TPJQSAC .../...	045/06/07/08/09/10/11/125/15		

Choose the desired pack. & height
Ex.: 4,5 mm capsule in 10 Pcs Pack - CPJQSAC 045/10

CAPSULES and END CAPS - SANDED STAINLESS STEEL AISI 304/1.4301-V2A

Article	H mm	Pack 10 Pcs	Pack 2 Pcs
CPJQSACSB .../...	07/08/09/10/125		
TPJQSACSB .../...	07/08/09/10/125		

Choose the desired pack. & height
Ex.: 8 mm capsule in 10 Pcs Pack - CPJQSACSB 08/10

CAPSULES AND END CAPS - BRUSHED STAINLESS ST. AISI 304/1.4301-V2A

Article	H mm	Pack 10 Pcs	Pack 2 Pcs
CPJQSACS .../...	045/06/07/08/09/10/11/125/15		
TPJQSACS .../...	045/06/07/08/09/10/11/125/15		

Choose the desired pack. & height
Ex.: 4,5 mm capsule in 10 Pcs Pack - CPJQSACS 045/10

JOINTS - PLASTIC


Article	H mm	Pack 10 Pcs	Pack 2 Pcs
GIJQ .../...	045/06/07/08/09/10/11/125/15		

Choose the desired pack. & height
Ex.: 4,5 mm joint in 10 Pcs Pack - GIJQ 045/10

CAPSULES - SUPER POLISHED STAINLESS STEEL AISI 304/1.4301-V2A

Article	H mm	Pack 10 Pcs	Pack 2 Pcs
CPJQSACML .../...	045/06/07/08/09/10/11/125/15		
TPJQSACML .../...	045/06/07/08/09/10/11/125/15		

Choose the desired pack. & height
Ex.: 4,5 mm capsule in 10 Pcs Pack - CPJQSACML 045/10



News 2023

* = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed

PROJOLLY SQUARE is a square corner bead profile in polished stainless steel AISI 304/1.4301-V2A that can be applied on external corners of coverings. It can be used to close the perimeter of coverings, like a connection profile between step tread and riser of stairs coated with ceramic and natural stone tiles, and also as separation profile for floor and wall coverings. Its particular section and the availability of special pieces such as internal and external corners, end caps and joints make **PROJOLLY SQUARE** a much sought-after profile that allows a workmanlike application even in environments subject to high mechanical stresses.

PROJOLLY SQUARE

POLISHED, BRUSHED STAINLESS STEEL
AISI 316LL/1.4404-V4A



POLISHED STAINLESS STEEL AISI 316LL/1.4404-V4A
with protective film
bar length 2,7 LM - Pack 20 Pcs - 54 lm - 8/10 mm



Article	H mm		
PJQSACM 08	8		*
PJQSACM 10	10		
PJQSACM 11	11		
PJQSACM 125	12,5		

COLOURS





BRUSHED STAINLESS STEEL AISI 316LL/1.4404-V4A
with protective film
bar length 2,7 LM - Pack 20 Pcs - 54 lm - 8/10 mm



Article	H mm		
PJQSACMS 10	10		*
PJQSACMS 11	11		*
PJQSACMS 125	12,5		*

COLOURS



INSTRUCTIONS FOR LAYING METHODS

1. Choose "PROJOLLY SQUARE" according to the tile thickness and desired finish.
2. Cut "PROJOLLY SQUARE" to the desired length and apply the adhesive on the support where the profile will be laid.
3. Press the anchoring flange of "PROJOLLY SQUARE" into the adhesive.
4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile.
5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.

SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS.

CAPSULES, END CAPS and THREE-WAYS JOINTS

STAINLESS STEEL AISI 316LL

Capsules & end caps of the on demand profiles are also on demand *

CAPSULES and END CAPS - POLISHED STAINLESS STEEL AISI 316LL/1.4404

Article	H mm	Pack 10 Pcs	Pack 2 Pcs
CPJQSACM .../...	08/10/11/12,5		
TPJQSACM .../...	08/10/11/12,5		

Choose the desired pack. & height
Ex.: 10 mm capsule in 10 Pcs PACMk - CPJQSACM 10/10

CAPSULES and END CAPS - BRUSHED STAINLESS STEEL AISI 316LL/1.4404


Article	H mm	Pack 10 Pcs	Pack 2 Pcs
CPJQSACMS .../...	10/11/125		
TPJQSACMS .../...	10/11/125		

Choose the desired pack. & height
Ex.: 10 mm capsule in 10 Pcs PACMk - CPJQSACMS 10/10

JOINTS - PLASTIC

Article	H mm	Pack 10 Pcs	Pack 2 Pcs
GJJQ .../...	08/10/11/125		

Choose the desired pack. & height
Ex.: 8 mm joint in 10 Pcs Pack - GJJQ 08/10



* = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed



PROJOLLY SQUARE is a square corner bead profile in chromed brass or antique brass that can be applied on external corners of coverings. It can be used to close the perimeter of coverings, like a connection profile between step tread and riser of stairs coated with ceramic and natural stone tiles, and also as separation profile for floor and wall coverings. Its particular section and elegance and the availability of special pieces such as internal and external corners, end caps and joints make **PROJOLLY SQUARE** a much sought-after profile that allows an elegant workmanlike application.

PROJOLLY SQUARE

CHROMED BRASS, BRUSHED AND ANTIQUE BRASS




CHROMED BRASS thermo Packed
bar length 2,7 lm - Pack 20 Pcs - 54 lm

Article	H mm		
PJQSOC 045	4,5		
PJQSOC 06	6		
PJQSOC 08	8		
PJQSOC 10	10		
PJQSOC 125	12,5		



BRUSHED BRASS thermo Packed
bar length 2,7 lm - Pack 20 Pcs - 54 lm


Article	H mm		
* PJQSOS 045	4,5		*
* PJQSOS 06	6		*
* PJQSOS 08	8		*
* PJQSOS 10	10		*
* PJQSOS 125	12,5		*



ANTIQUÉ BRASS thermo Packed bar length 2,7 lm
Pack 20 Pcs - 54 lm (PJQSOB 125 - Pack 10 Pcs)

Article	H mm		
PJQSOB 08	8		
PJQSOB 10	10		
PJQSOB 125	12,5		


COLOURS



INSTRUCTIONS FOR LAYING

1. Choose "PROJOLLY SQUARE" according to the tile thickness.
2. Cut "PROJOLLY SQUARE" to the desired length and apply the adhesive on the support where the profile will be laid.
3. Press the anchoring flange of "PROJOLLY SQUARE" into the adhesive.
4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile.
5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.

EXAMPLES OF LAYING



CAPSULES, END CAPS and THREE-WAYS JOINTS

CHROMED BRASS - PLASTIC

Capsules & end caps of the on demand profiles are also on demand *

CAPSULES and END CAPS - CHROMED BRASS

Article	H mm	Pack 10 Pcs	Pack 2 Pcs
CPJQSOC .../...	045/06/08/10/125		
TPJQSOC .../...	045/06/08/10/125		

Choose the desired pack. & height
Ex: 10 mm capsule in 10 Pcs Pack - CPJQSOS 10/10

CAPSULES and END CAPS - ANTIQUE BRASS

Article	H mm	Pack 10 Pcs	Pack 2 Pcs
CPJQSOB .../...	08/10/125		
TPJQSOB .../...	08/10/125		

Choose the desired pack. & height
Ex: 10 mm capsule in 10 Pcs Pack - CPJQSOB 10/10

CAPSULES and END CAPS - BRUSHED BRASS

Article	H mm	Pack 10 Pcs	Pack 2 Pcs
* CPJQSOS .../...	045/06/08/10/125		
* TPJQSOS .../...	045/06/08/10/125		

Choose the desired pack. & height
Ex: 10 mm capsule in 10 Pcs Pack - CPJQSOS 10/10

JOINTS - PLASTIC

Article	H mm	Pack 10 Pcs	Pack 2 Pcs
GIJQ .../...	045/06/08/10/125		


Choose the desired pack. & height
Ex: 8 mm joint in 10 Pcs Pack - GIJQ 08/10




PROJOLLY SQUARE

ANODIZED AND POLISHED ALUMINIUM

PROJOLLY SQUARE is a square corner bead profile in anodized and polished aluminium that can be applied on external corners of coverings. It can be used to close the perimeter of coverings, like a connection profile between step tread and riser of stairs coated with ceramic and natural stone tiles and also as separation profile for floor and wall coverings. Its particular section and elegance, the availability in eight finishes and special pieces such as internal and external corners, end caps and joints make **PROJOLLY SQUARE** a much sought-after profile that allows an elegant workmanlike application.



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROJOLLY SQUARE" according to the tile thickness and desired finish. 2. Cut "PROJOLLY SQUARE" to the desired length and apply the adhesive on the support where the profile will be laid. 3. Press the anchoring flange of "PROJOLLY SQUARE" into the adhesive. 4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile. 5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.



ANODIZED ALUMINIUM thermo Packed (silver-gold-copper-titanium-black)
bar length 2,7 lm - Pack 40 Pcs - 108 lm (H 12,5 mm - Pack 20 Pcs - 54 lm)

Article	H mm			
PJQSAA 045	4,5			*
PJQSAA 06	6			
PJQSAA 08	8			
PJQSAA 10	10			
PJQSAA 11	11			
PJQSAA 125	12,5			
PJQSAO 08	8			*
PJQSAO 10	10			*
PJQSAO 125	12,5			*
PJQSAR 045	4,5			*
PJQSAR 06	6			
PJQSAR 08	8			
PJQSAR 10	10			
PJQSAR 125	12,5			
PJQSAT 045	4,5			*
PJQSAT 06	6			
PJQSAT 08	8			
PJQSAT 10	10			
PJQSAT 11	11			
PJQSAT 125	12,5			
PJQSNE 08	8			
PJQSNE 10	10			
PJQSNE 11	11			
PJQSNE 125	12,5			



POLISHED ALUMINIUM thermo Packed (chrome- gold- titanium-copper-black)
bar length 2,7 lm - Pack 40 Pcs - 108 lm (H 12,5 mm - Pack 20 Pcs - 54 lm)

Article	H mm			
PJQSBC 045	4,5			*
PJQSBC 06	6			
PJQSBC 08	8			
PJQSBC 10	10			
PJQSBC 11	11			
PJQSBC 125	12,5			
PJQSBO 08	8			*
PJQSBO 10	10			
PJQSBO 125	12,5			
PJQSBR 045	4,5			*
PJQSBR 06	6			
PJQSBR 08	8			*
PJQSBR 10	10			
PJQSBR 125	12,5			
PJQSBT 045	4,5			*
PJQSBT 06	6			
PJQSBT 08	8			
PJQSBT 10	10			
PJQSBT 11	11			
PJQSBT 125	12,5			
PJQSBN 08	8			
PJQSBN 10	10			
PJQSBN 11	11			
PJQSBN 125	12,5			

COLOURS

ANODIZED				
AA - Anod. silver alum.	AO - Anod. gold alum.	AR - Anod. copper alum.	AT - Anod. titanium alum.	NE - Anod. black alum.
POLISHED				
BC - Pol. chrome alum.	BO - Pol. gold alum.	BR - Pol. copper alum.	BT - Pol. titanium alum.	BN - Pol. black alum.

CAPSULES, END CAPS and THREE-WAYS JOINTS

* Capsules & end caps of the on demand profiles are also on demand

ANODIZED AND POLISHED ALUMINIUM / PLASTIC

CAPSULES and END CAPS - ANODIZED ALUMINIUM

Article	H mm	Pack 10 Pcs	Pack 2 Pcs
CPJQSAA .../...	045/06/08/10/11/125		
TPJQSAA .../...	045/06/08/10/11/125		
CPJQSAO .../...	8/10/125		
TPJQSAO .../...	8/10/125		
CPJQSAR .../...	045/06/08/10/125		
TPJQSAR .../...	045/06/08/10/125		
CPJQSAT .../...	045/06/08/10/11/125		
TPJQSAT .../...	045/06/08/10/11/125		
CPJQSNE .../...	08/10/11/125		
TPJQSNE .../...	08/10/11/125		

Choose the desired pack. & height
Ex.: 10 mm capsule in 10 Pcs Pack - CPJQSAA 10/10

CAPSULES and END CAPS - POLISHED ALUMINIUM

Article	H mm	Pack 10 Pcs	Pack 2 Pcs
CPJQSBC .../...	045/06/08/10/11/125		
TPJQSBC .../...	045/06/08/10/11/125		
CPJQSBO .../...	8/10/125		
TPJQSBO .../...	8/10/125		
CPJQSBR .../...	045/06/08/10/125		
TPJQSBR .../...	045/06/08/10/125		
CPJQSBT .../...	045/06/08/10/11/125		
TPJQSBT .../...	045/06/08/10/11/125		
CPJQSBN .../...	08/10/11/125		
TPJQSBN .../...	08/10/11/125		

Choose the desired pack. & height
Ex.: 10 mm capsule in 10 Pcs Pack - CPJQSBC 10/10

JOINTS - PLASTIC

Article	H mm	Pack 10 Pcs	Pack 2 Pcs
GIJQ .../...	045/06/08/10/11/125		

Choose the desired pack. & height
Ex.: 8 mm joint in 10 Pcs Pack - GIJQ 08/10



* = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed

PROJOLLY SQUARE is a square corner bead profile in brushed and tiltex aluminium that can be applied on external corners of coverings. It can be used to close the perimeter of coverings, like a connection profile between step tread and riser of stairs coated with ceramic and natural stone tiles and also as separation profile for floor and wall coverings. Its particular section and elegance, the availability in eight finishes and special pieces such as internal and external corners, end caps and joints make **PROJOLLY SQUARE** a much sought-after profile that allows an elegant workmanlike application.

PROJOLLY SQUARE

BRUSHED POLISHED AND ANODIZED BRUSHED TILTEX ALUMINIUM



BRUSHED POLISHED ALUM. thermo Packed (silver-gold-copper titanium-black)
bar length 2,7 lm - Pack 40 Pcs - 108 lm (H 12,5 mm - Pack 20 Pcs - 54 lm)


Article	H mm		
PJQSBS 045	4,5		*
PJQSBS 06	6		
PJQSBS 08	8		
PJQSBS 10	10		
PJQSBS 11	11		
PJQSBS 125	12,5		
PJQSRS 045	4,5		*
PJQSRS 06	6		
PJQSRS 08	8		
PJQSRS 10	10		
PJQSRS 125	12,5		
PJQSTS 045	4,5		*
PJQSTS 06	6		
PJQSTS 08	8		
PJQSTS 10	10		
PJQSTS 11	11		
PJQSTS 125	12,5		
PJQSBS 08	8		
PJQSBS 10	10		
PJQSBS 125	12,5		
PJQSBRS 10	10		*
PJQSBRS 125	12,5		*
PJQSNS 08	8		
PJQSNS 10	10		
PJQSNS 11	11		
PJQSNS 125	12,5		

ANOD. BRUSHED TILTEX ALUM. thermo Packed (silver-copper-titanium)
- bar length 2,7 lm - Pack 40 Pcs - 108 lm (H 12,5 mm - Pack 20 Pcs - 54 lm)


Article	H mm		
PJQSBX 06	6		
PJQSBX 08	8		
PJQSBX 10	10		
PJQSBX 11	11		
PJQSBX 125	12,5		
PJQSRX 06	6		
PJQSRX 08	8		
PJQSRX 10	10		
PJQSRX 125	12,5		
PJQSTX 06	6		
PJQSTX 08	8		
PJQSTX 10	10		
PJQSTX 11	11		
PJQSTX 125	12,5		

COLOURS

BRUSHED POLISHED		
ANOD. BRUSHED TILTEX		



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROJOLLY SQUARE" according to the tile thickness and desired finish. 2. Cut "PROJOLLY SQUARE" to the desired length and apply the adhesive on the support where the profile will be laid. 3. Press the anchoring flange of "PROJOLLY SQUARE" into the adhesive. 4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile. 5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.

CAPSULES, END CAPS and THREE-WAYS JOINTS

ANODIZED BRUSHED POLISHED ALUMINIUM, TILTEX / PLASTIC

Capsules & end caps of the on demand profiles are also on demand *

CAPSULES and END CAPS - BRUSHED POLISHED ALUMINIUM

Article	H mm	Pack 10 Pcs	Pack 2 Pcs
CPJQSBS .../...	045/06/08/10/11/125		
TPJQSBS .../...	045/06/08/10/11/125		
CPJQSRS .../...	045/06/08/10/125		
TPJQSRS .../...	045/06/08/10/125		
CPJQSTS .../...	045/06/08/10/11/125		
TPJQSTS .../...	045/06/08/10/11/125		
CPJQSBS 08 .../...	08/10/125		
TPJQSBS 08 .../...	08/10/125		
CPJQSBRS .../...	10/125		
TPJQSBRS .../...	10/125		
CPJQSNS .../...	08/10/11/125		
TPJQSNS .../...	08/10/11/125		

Choose the desired pack. & height
Ex.: 10 mm capsule in 10 Pcs Pack - CPJQSBS 10/10

CAPSULES and END CAPS - ANODIZED BRUSHED TILTEX ALUMINIUM

Article	H mm	Pack 10 Pcs	Pack 2 Pcs
CPJQSBX .../...	06/08/10/11/125		
TPJQSBX .../...	06/08/10/11/125		
CPJQSRX .../...	06/08/10/125		
TPJQSRX .../...	06/08/10/125		
CPJQSTX .../...	06/08/10/11/125		
TPJQSTX .../...	06/08/10/11/125		

Choose the desired pack. & height
Ex.: 10 mm capsule in 10 Pcs Pack - CPJQSBX 10/10

JOINTS - PLASTIC

Article	H mm	Pack 10 Pcs	Pack 2 Pcs
GIJQ .../...	045/06/08/10/11/125		

Choose the desired pack. & height
Ex.: 8 mm joint in 10 Pcs Pack - GIJQ 08/10




* = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed

PROJOLLY SQUARE

ALUMINIUM STONE LINE, VARNISHED ALUMINIUM AND TUSCANY LINE

PROJOLLY SQUARE is a corner bead profile in powder coated aluminum that can be applied on external corners of coverings. It can be used to close the perimeter of coverings. Its particular section and the availability of several finishes and special pieces such as internal and external corners, junctions and end caps make **PROJOLLY SQUARE** an elegant and much-sought after profile. workmanlike application.



STONE LINE thermo Packed
bar length 2,7 lm - Pack 20 Pcs-54 lm

Article	H mm		
PJQSA 06-SL...	6		
PJQSA 08-SL...	8		
PJQSA 10-SL...	10		
PJQSA 11-SL...	11		
PJQSA 125-SL...	12,5		

Available in the colours: SL01 - SL02 - SL03 - SL04 - SL05 - SL06 - SL07 - SL08 - SL09 - SL10 - SL11 - SL12 - SL13.



WHITE VARNISHED ALUMINIUM thermo Packed
bar length 2,7 lm - Pack 20 Pcs - 54 lm (white colour 40 Pcs-108 lm)

Article	H mm		
PJQSA 045-01	4,5		*
PJQSA 08-01	8		
PJQSA 10-...	10		
PJQSA 11-01	11		*
PJQSA 125-01	12,5		

Available in the colours: 01 - 0106 - 02 - 11. Available on demand 010 - 03 - 0211 - 0311 - 06 - 10 - 17 with a minimum quantity order of 100 pcs.

TUSCANY LINE thermo Packed
bar length 2,7 lm - Pack 40 Pcs- 108 lm (H 12,5 mm - Pack 20 Pcs)

Article	H mm		
PJQSA 08-...	8		*
PJQSA 10-...	10		
PJQSA 125-...	12,5		

Available in the colours: 03TU - 05TU - 20TU.
The code of the selected colour must be added to the article code.
Eg.: PJQA 08-... (chosen colour tuscanly grey) PJQA 08-03TU.

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROJOLLY SQUARE" according to the tile thickness and desired finish. 2. Cut "PROJOLLY SQUARE" to the desired length and apply the adhesive on the support where the profile will be laid. 3. Press the anchoring flange of "PROJOLLY SQUARE" into the adhesive. 4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile. 5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.

COLOURS

STONE LINE						
SL01 - Stone white	SL02 - Stone cream	SL03 - Stone greyvory	SL04 - Stone sand	SL05 - Stone gray	SL06 - Stone cristal gray	SL07 - Stone antragraj
SL08 - Stone antradark	SL09 - Stone bronze	SL10 - Stone corten	SL11 - Stone brown	SL12 - Stone black	SL13 - Stone oyster grey	
VARNISHED				TUSCANY LINE		
01 - White varnished aluminium (9016)	010 - White Matt varnished aluminium (9016)	0106 - White ivory varnished aluminium (9001)	02 - Light grey varnished aluminium (7035)	11 - Black varnished aluminium (9005)	03TU - Tuscanly grey	05TU - Tuscanly beige
					20TU - Tuscanly bronze	

AVAILABLE MINIMUM QUANTITY 100 PCS by colour and height (Price to be agreed. Production delay 4/5 weeks)

03 - Stone grey varnished alum. (7030)	0211 - Varnished quartz grey alum. (7039)	0311 - Varnished asphalt grey alum. (7043)	06 - Varnished ivory alum. (1015)	10 - Klinker red varnished alum. (8004)	17 - Varnished bahama beige alum.
--	---	--	-----------------------------------	---	-----------------------------------

CAPSULES, END CAPS and THREE-WAYS JOINTS

ALUMINIUM STONE LINE, TUSCANY LINE AND VARNISHED ALUMINIUM / PLASTIC

* Capsules & end caps of the on demand profiles are also on demand

CAPSULES and END CAPS - STONE LINE

Article	H mm	Pack 10 Pcs	Pack 2 Pcs
CPJQSA ...-SL.../...	06/08/10/11/12,5		
TPJQSA ...-SL.../...	06/08/10/11/12,5		

Choose the desired pack. & height
Ex.: 10 mm capsule in 10 Pcs Pack - CPJQSA 10-SL01/10

CAPSULES and END CAPS - VARNISHED


Article	H mm	Pack 10 Pcs	Pack 2 Pcs
CPJQSA ...-.../...	045/08/10/11/125		
TPJQSA ...-.../...	045/08/10/11/125		

Choose the desired pack. & height
Ex.: 10 mm capsule in 10 Pcs Pack - CPJQSA 10-03/10

CAPSULES and END CAPS - TUSCANY LINE

Article	H mm	Pack 10 Pcs	Pack 2 Pcs
CPJQSA ...-...TU/...	08/10/125		

Choose the desired pack. & height
Ex.: 10 mm capsule in 10 Pcs Pack - CPJQSA 10-03/10



JOINTS - PLASTIC


Article	H mm	Pack 10 Pcs	Pack 2 Pcs
GIJQ .../...	045/06/08/10/11/125		

Choose the desired pack. & height
Ex.: 8 mm joint in 10 Pcs Pack - GIJQ 08/10

PROJOLLY SQUARE is a square corner bead profile in shockproof non - toxic colored vinyl resin that can be applied on external corners of coverings. It can be used to close the perimeter of coverings. Its particular section, the availability in different colours also on demand and special pieces such as internal and external corners make **PROJOLLY SQUARE** a much sought-after profile. It can be easily matched with the wall covering and that allows an elegant workmanlike application.

PROJOLLY SQUARE

SHOCKPROOF NON - TOXIC COLORED VINYL RESIN




NON-TOXIC SHOCKPROOF VINYL RESIN
bar length **2,7 lm** - Pack **20 Pcs** - **54 lm** (white colour **40 Pcs-108 lm**)

Article	H mm		
PJQ 06...	6		
PJQ 08...	8		
PJQ 10...	10		
PJQ 125...	12,5		

H 6 mm available the colours 01, other colours on demand.
Available in the colours: 00-01-0106-03-06-12-17. On demand 02-04-05-07-08-09-10-11-13-14-15-16-18-19-20-21-22-23-24-25-26-27-28-29 with a minimum quantity order of 800 pcs.
The code of the selected colour must be added to the article code.
E.g.: PJQ 08... (chosen colour white) PJQ 08-01.


WHITE NOT FOR SALE SINGLY

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROJOLLY SQUARE" according to the tile thickness and desired colour. 2. Cut "PROJOLLY SQUARE" to the desired length and apply the adhesive on the support where the profile will be laid. 3. Press the anchoring flange of "PROJOLLY SQUARE" into the adhesive. 4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. 5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.

COLOURS




AVAILABLE MINIMUM QUANTITY 800 PCS by colour and height (Price to be agreed. Production delay 4/5 weeks)



CAPSULES and THREE-WAYS JOINTS

POLYPROPYLENE / POLYETYLENE UV RESISTANT



EXTERNAL CAPSULES POLYPROPYLENE/POLYETYLENE

Article	H mm	Pack 20 Pcs	Pack 5 Pcs
CPJQ 06-.../...	6		
CPJQ 08-.../...	8		
CPJQ 10-.../...	10		
CPJQ 125-.../...	12,5		

INTERNAL CAPSULES EXTERNAL CAPSULES



IPJQ ...-.../...



CPJQ ...-.../...

INTERNAL CAPSULES POLYPROPYLENE/POLYETYLENE


Article	H mm	Pack 20 Pcs	Pack 5 Pcs
IPJQ 06-.../...	6		
IPJQ 08-.../...	8		
IPJQ 10-.../...	10		
IPJQ 125-.../...	12,5		

H 6 mm available the colours 01, other colours on demand.
Available in the colours: 00-01-0106-03-06-12-17. On demand 02-04-05-07-08-09-10-11-13-14-15-16-18-19-20-21-22-23-24-25-26-27-28-29
The code of the selected colour must be added to the article code.
E.g.: CPJQ 08-.../... (chosen colour white) CPJQ 08-01/20.
IPJQ 08-.../... (chosen colour white) IPJQ 08-01/20.

PROJOLLY QUART

POLISHED, SUPER POLISHED AND BRUSHED STAINLESS STEEL AISI 304/1.4301-V2A

PROJOLLY QUART is a quarter-circle rounded bead profile in polished, super polished and brushed stainless steel AISI 304/1.4301-V2A that can be applied on external corners of coverings. It can be used to close the perimeter of coverings and like a connection profile between step tread and riser of stairs coated with ceramic or natural stone tiles. Its particular section, the availability in three different finishes and special pieces such as internal and external corners, end caps and joints make **PROJOLLY QUART** a much sought-after profile that allows a workmanlike application even in environments subject to high mechanical stresses.



EXAMPLES FOR LAYING METHODS



POLISHED STAINLESS STEEL AISI 304/1.4301-V2A with protective film
bar length 2,7 lm - pack. 20 Pcs - 54 lm (H 4,5 mm - 108 lm) - 10/10 mm

Article	H mm		
PJQTAC 045	4,5		
PJQTAC 06	6		
☉ PJQTAC 07	7		
PJQTAC 08	8		
☉ PJQTAC 09	9		
PJQTAC 10	10		
PJQTAC 11	11		
PJQTAC 125	12,5		

SUPER POLISHED STAINLESS STEEL AISI 304/1.4301-V2A thermo packed
bar length 2,7 lm - pack. 20 Pcs 54 lm (H 4,5 mm - 108 ml) - 10/10 mm

Article	H mm		
PJQTACML 045	4,5		
PJQTACML 06	6		
☉ PJQTACML 07	7		
PJQTACML 08	8		
☉ PJQTACML 09	9		
PJQTACML 10	10		
PJQTACML 11	11		
PJQTACML 125	12,5		



Brushed STAINLESS ST. AISI 304/1.4301-V2A with protective film
bar length 2,7 lm - pack. 20 Pcs - 54 lm (H 4,5 mm - 108 lm) - 10/10 mm

Article	H mm		
PJQTACS 045	4,5		
PJQTACS 06	6		
☉ PJQTACS 07	7		
PJQTACS 08	8		
☉ PJQTACS 09	9		
PJQTACS 10	10		
PJQTACS 11	11		
PJQTACS 125	12,5		

COLOURS



SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS.

INSTRUCTIONS FOR LAYING METHODS

1. Choose "PROJOLLY QUART" according to the tile thickness and desired finish.
2. Cut "PROJOLLY QUART" to the desired length and apply the adhesive on the support where the profile will be laid.
3. Press the anchoring flange of "PROJOLLY QUART" into the adhesive.
4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile.
5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.

CAPSULES, END CAPS and THREE-WAYS JOINTS

* Capsules & end caps of the on demand profiles are also on demand

POLISHED, SUPER POLISHED AND BRUSHED STAINLESS ST. AISI 304/1.4301-V2A / PLASTIC

CAPSULES and END CAPS - POLISHED STAINLESS ST. AISI 304/1.4301-V2A

Article	H mm	Pack 10 Pcs	Pack 2 Pcs
CPJQTAC 045/...	4,5		
IPJQTAC 045/...	4,5		
CPJQTAC 06/...	6		
IPJQTAC 06/...	6		
☉ CPJQTAC 07/...	7		
☉ IPJQTAC 07/...	7		
CPJQTAC 08/...	8		
IPJQTAC 08/...	8		
☉ CPJQTAC 09/...	9		
☉ IPJQTAC 09/...	9		
CPJQTAC 10/...	10		
IPJQTAC 10/...	10		
CPJQTAC 11/...	11		
IPJQTAC 11/...	11		
CPJQTAC 125/...	12,5		
IPJQTAC 125/...	12,5		
TPJQTAC 045-06-08-10-11-125-.../...			

Choose the desired packaging: E.g.: CPJQTAC .../10 (Pack. 10 Pcs)
CPJQTAC .../2 (Pack. 2 Pcs)

CAPSULES and END CAPS - BRUSHED STAINLESS ST. AISI 304/1.4301-V2A

Article	H mm	Pack 10 Pcs	Pack 2 Pcs
CPJQTACS 045/...	4,5		
IPJQTACS 045/...	4,5		
CPJQTACS 06/...	6		
IPJQTACS 06/...	6		
☉ CPJQTACS 07/...	7		
☉ IPJQTACS 07/...	7		
CPJQTACS 08/...	8		
IPJQTACS 08/...	8		
☉ CPJQTACS 09/...	9		
☉ IPJQTACS 09/...	9		
CPJQTACS 10/...	10		
IPJQTACS 10/...	10		
CPJQTACS 11/...	11		
IPJQTACS 11/...	11		
CPJQTACS 125/...	12,5		
IPJQTACS 125/...	12,5		
TPJQTACS 045-06-08-10-11-125-.../...			

Choose the desired packaging: E.g.: CPJQTACS .../10 (Pack. 10 Pcs)
CPJQTACS .../2 (Pack. 2 Pcs)

CAPSULES - SUPER POLISHED STAINLESS ST. AISI 304/1.4301-V2A


Article	H mm	Pack 10 Pcs	Pack 2 Pcs
CPJQTACML 045/...	4,5		
IPJQTACML 045/...	4,5		
CPJQTACML 06/...	6		
IPJQTACML 06/...	6		
☉ CPJQTACML 07/...	7		
☉ IPJQTACML 07/...	7		
CPJQTACML 08/...	8		
IPJQTACML 08/...	8		
☉ CPJQTACML 09/...	9		
☉ IPJQTACML 09/...	9		
CPJQTACML 10/...	10		
IPJQTACML 10/...	10		
CPJQTACML 11/...	11		
IPJQTACML 11/...	11		
CPJQTACML 125/...	12,5		
IPJQTACML 125/...	12,5		

Choose the desired packaging: E.g.: CPJQTACML .../10 (Pack. 10 Pcs)
CPJQTACML .../2 (Pack. 2 Pcs)

JOINTS - PLASTIC

Article	H mm	Pack 10 Pcs	Pack 2 Pcs
GJQT 045/...	4,5		
GJQT 06/...	6		
☉ GJQT 07/...	7		
GJQT 08/...	8		
☉ GJQT 09/...	9		
GJQT 10/...	10		
GJQT 11/...	11		
GJQT 125/...	12,5		

Choose the desired packaging: E.g.: GJQT .../10 (Pack. 10 Pcs)
GJQT .../2 (Pack. 2 Pcs)



☉ = News 2023

* = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed

PROJOLLY QUART is a quarter-circle rounded bead profile in anodized and polished aluminium that can be applied on external corners of coverings. It can be used to close the perimeter of coverings and like a connection profile between step tread and riser of stairs coated with ceramic and natural stone tiles. Its particular section and elegance, the availability in four finishes and special pieces such as internal and external corners, end caps and joints make **PROJOLLY QUART** a much sought-after profile that allows an elegant workmanlike application.

PROJOLLY QUART

ANODIZED AND POLISHED ALUMINIUM




ANODIZED ALUMINIUM (silver-titanium-gold-antique bronze) thermo packed - bar length 2,7 lm - pack. 40 Pcs - 108 lm (H 12,5 mm, 15 mm - pack. 20 Pcs)

Article	H mm		
PJQTAA 06	6		
PJQTAA 08	8		
PJQTAA 10	10		
PJQTAA 11	11		
PJQTAA 125	12,5		
PJQTAA 15	15		
PJQTAO 06	6		
PJQTAO 08	8		
PJQTAO 10	10		
PJQTAO 11	11		
PJQTAO 125	12,5		
PJQTAT 08	8		
PJQTAT 10	10		
PJQTAT 11	11		
PJQTAT 125	12,5		
PJQTBRA 10	10		
PJQTBRA 125	12,5		




POLISHED ALUMINIUM (chrome-titanium-gold) thermo packed - bar length 2,7 lm - pack. 40 Pcs - 108 lm (H 15 mm - 54 lm) - (H 12,5 mm, 15 mm - pack. 20 Pcs)

Article	H mm		
PJQTBC 06	6		
PJQTBC 08	8		
PJQTBC 10	10		
PJQTBC 11	11		
PJQTBC 125	12,5		
PJQTBC 15	15		
PJQTBO 06	6		
PJQTBO 08	8		
PJQTBO 10	10		
PJQTBO 11	11		
PJQTBO 125	12,5		
PJQBT 08	8		
PJQBT 10	10		
PJQBT 11	11		
PJQBT 125	12,5		




EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROJOLLY QUART" according to the tile thickness and desired finish.
2. Cut "PROJOLLY QUART" to the desired length and apply the adhesive on the support where the profile will be laid.
3. Press the anchoring flange of "PROJOLLY QUART" into the adhesive.
4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile.
5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.

COLOURS



ON DEMAND MAY BE REALISED IN OTHER FINISHES OF THE COLOUR CHART.
CONTACT OUR CUSTOMER SERVICE FOR MINIMUM QUANTITY, TIMING AND PRICE.

CAPSULES, END CAPS and THREE-WAYS JOINTS

ANODIZED, POLISHED ALUMINIUM / PLASTIC

Capsules & end caps of the on demand profiles are also on demand *

CAPSULES and END CAPS - ANODIZED ALUMINIUM

Article	H mm	Pack 10 Pcs	Pack 2 Pcs
CPJQTAA .../...	06/08/10/ 11/125/15		
IPJQTAA .../...	06/08/10/ 11/125/15		
TPJQTAA .../...	06/08/10/ 11/125/15		
CPJQTAO .../...	06/08/10/ 11/125		
IPJQTAO .../...	06/08/10/ 11/125		
TPJQTAO .../...	06/08/10/ 11/125		
CPJQTAT .../...	08/10/11/125		
IPJQTAT .../...	08/10/11/125		
TPJQTAT .../...	08/10/11/125		
CPJQTBRA .../...	10/125		
IPJQTBRA .../...	10/125		
TPJQTBRA .../...	10/125		

Choose the desired pack. & height
Ex.: 4,5 mm capsule in 10 Pcs Pack - CPJQTAA 10/10

CAPSULES and END CAPS - POLISHED ALUMINIUM


Article	H mm	Pack 10 Pcs	Pack 2 Pcs
CPJQTBC .../...	06/08/10/ 11/125/15		
IPJQTBC .../...	06/08/10/ 11/125/15		
TPJQTBC .../...	06/08/10/ 11/125/15		
CPJQTBO .../...	06/08/10/ 11/125		
IPJQTBO .../...	06/08/10/ 11/125		
TPJQTBO .../...	06/08/10/ 11/125		
CPJQBT .../...	08/10/11/125		
IPJQBT .../...	08/10/11/125		
TPJQBT .../...	08/10/11/125		

Choose the desired pack. & height
Ex.: 4,5 mm capsule in 10 Pcs Pack - CPJQTBC 10/10

JOINTS - PLASTIC

Article	H mm	Pack 10 Pcs	Pack 2 Pcs
GIJQT .../...	06/08/10/ 11/125/15		

Choose the desired pack. & height
Ex.: 10 mm joint in 10 Pcs Pack - GIJQT 10/10



EXTERNAL CAPSULES
CPJQT.../.../...

INTERNAL CAPSULES
IPJQT.../.../...



END CAP
TPJQT.../.../...




JOINT
GIJQT.../.../...

* = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed


PROJOLLY QUART

BRUSHED POLISHED, BRUSHED AND VARNISHED ALUMINIUM

PROJOLLY QUART is a quarter-circle rounded bead profile in brushed and varnished aluminium that can be applied on external corners of coverings. It can be used to close the perimeter of coverings and (only brushed version) like a connection profile between step tread and riser of stairs coated with ceramic and natural stone tiles. Its particular section and elegance, the availability in three finishes and special pieces such as internal and external corners, end caps and joints make **PROJOLLY QUART** a much sought-after profile that allows an elegant workmanlike application.



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROJOLLY QUART" according to the tile thickness and desired finish.
2. Cut "PROJOLLY QUART" to the desired length and apply the adhesive on the support where the profile will be laid.
3. Press the anchoring flange of "PROJOLLY QUART" into the adhesive.
4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile.
5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.




BRUSHED POLISHED ALUMINIUM thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm (H 12,5 mm, 15 mm - pack. 20 Pcs)

Article	H mm		
PJQTBS 08	8		
PJQTBS 10	10		
PJQTBS 11	11		
PJQTBS 125	12,5		
PJQTBS 08	8		
PJQTBS 10	10		
PJQTBS 11	11		
PJQTBS 125	12,5		


BRUSHED ANTIQUE BRONZE ALUMINIUM thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm (H 12,5 mm, 15 mm - pack. 20 Pcs)

Article	H mm		
PJQTBAS 10	10		
PJQTBAS 125	12,5		

COLOURS



ON DEMAND MINIMUM QUANTITY 100 PCS



(Price to be agreed. Production delay 4/5 weeks)

ON DEMAND MAY BE REALISED IN OTHER FINISHES OF THE COLOUR CHART. CONTACT OUR CUSTOMER SERVICE FOR MINIMUM QUANTITY, TIMING AND PRICE.




VARNISHED ALUMINIUM thermo packed - bar length 2,7 M
pack. 20 Pcs - 54 lm (white colour 40 Pcs - 108 lm)

Article	H mm		
PJQTA 06-01	6		
PJQTA 08-01	8		
PJQTA 08-...	8		
PJQTA 10-01	10		
PJQTA 10-...	10		
PJQTA 11-01	11		
PJQTA 125-01	12,5		


Available in the colours: 01. Available on demand 010 - 0106 - 02 - 03 - 11 - 17. The code of the selected colour must be added to the article code. E.g.: PJQTA 08... (chosen colour White) PJQTA 08-01.

COLOURS



For other colors than white in sizes 06, 11, 125, contact the sales office for quantities and prices

ON DEMAND MINIMUM QUANTITY 100 PCS



(Price to be agreed. Production delay 4/5 weeks)

CAPSULES, END CAPS and THREE-WAYS JOINTS

* Capsules & end caps of the on demand profiles are also on demand

POLISHED BRUSHED, VARNISHED ALUMINIUM/ PLASTIC

CAPSULES & CAPS - POLISHED BRUSHED ALUMINIUM

Article	H mm	Pack 10 Pcs	Pack 2 Pcs
CPJQTBS .../...	08/10/11/125		
IPJQTBS .../...	08/10/11/125		
TPJQTBS .../...	08/10/11/125		
CPJQTBS 08.../...	08/10/11/125		
IPJQTBS 08.../...	08/10/11/125		
TPJQTBS 08.../...	08/10/11/125		
CPJQTBAS .../...	10/125		
IPJQTBAS .../...	10/125		
TPJQTBAS .../...	10/125		

Choose the desired pack. & height
Ex.: 4,5 mm capsule in 10 Pcs Pack - CPJQTBS 10/10

CAPSULES & CAP - VARNISHED ALUMINIUM

Article	H mm	Pack 10 Pcs	Pack 2 Pcs
CPJQTA ...-.../...	06/08/10/11/125		
IPJQTA ...-.../...	06/08/10/11/125		
TPJQTA ...-.../...	06/08/10/11/125		


Choose the desired pack. & height
Ex.: 4,5 mm capsule in 10 Pcs Pack - CPJQTA 02-10/10



JOINTS - PLASTIC

Article	H mm	Pack 10 Pcs	Pack 2 Pcs
GIJQT .../...	06/08/10/11/125		

Choose the desired pack. & height
Ex.: 10 mm joint in 10 Pcs Pack - GIJQT 10/10



PROJOLLY QUART is a quarter-circle rounded bead profile in powder coated aluminum that can be applied on external corners of coverings. It can be used to close the perimeter of coverings. Its particular section and the availability of thirteen finishes and special pieces such as internal and external corners, junctions and end caps make **PROJOLLY QUART** an elegant and much-sought after profile.

PROJOLLY QUART

STONE LINE ALUMINIUM




STONE LINE ALUMINIUM thermo packed
bar length 2,7 M - pack. 20 Pcs - 54 lm

Article	H mm
PJQTA 06-SL...	6
PJQTA 08-SL...	8
PJQTA 10-SL...	10
PJQTA 11-SL...	11
PJQTA 125-SL...	12,5


Available in the colours: SL01 - SL02 - SL03 - SL04 - SL05 - SL06 - SL07 - SL08 - SL09 - SL10 - SL11 - SL12 - SL13.
The code of the selected colour must be added to the article code.
E.g.: PJQTA 08... (chosen colour stone white) PJQTA 08-SL01.

COLOURS

STONE LINE						
SL01 - Stone white	SL02 - Stone cream	SL03 - Stone greywory	SL04 - Stone sand	SL05 - Stone gray	SL06 - Stone cristal gray	SL07 - Stone antragray
SL08 - Stone antradark	SL09 - Stone bronze	SL10 - Stone corten	SL11 - Stone brown	SL12 - Stone black	SL13 - Stone oyster gray	



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROJOLLY QUART" according to the tile thickness and desired finish.
2. Cut "PROJOLLY QUART" to the desired length and apply the adhesive on the support where the profile will be laid.
3. Press the anchoring flange of "PROJOLLY QUART" into the adhesive.
4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile.
5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.



CAPSULES, END CAPS and THREE-WAYS JOINTS

STONE LINE ALUMINIUM / PLASTIC

Capsules & end caps of the on demand profiles are also on demand *

JOINTS - PLASTIC

Article	H mm	Pack 10 Pcs	Pack 2 Pcs
GIJQT .../...	06/08/10/ 11/125		

Choose the desired pack. & height
Ex.: 10 mm joint in 10 Pcs Pack - GIJQT 10/10

END CAP
GIJQT .../...



CAPSULES & CAP - STONE LINE ALUMINIUM

Article	H mm	Pack 10 Pcs	Pack 2 Pcs
CPJQTA ...-SL.../...	06/08/10/ 11/125		
IPJQTA ...-SL.../...	06/08/10/ 11/125		
TPJQTA ...-SL.../...	06/08/10/ 11/125		

Choose the desired pack. & height
Ex.: 4,5 mm capsule in 10 Pcs Pack - CPJQTA 10-SL06/10



EXTERNAL CAPSULES

INTERNAL CAPSULES



CPJQTA .../...



IPJQTA .../...

JOINT
TPJQT.../...




* = Production on demand with minimum quantity of 80 pcs. Production delay 4/5 weeks. Price to be agreed


PROJOLLY QUART

SHOCKPROOF NON - TOXIC COLORED VINYL RESIN

PROJOLLY QUART is a quarter-circle rounded bead profile in shockproof non - toxic colored vinyl resin that can be applied on external corners of coverings. It can be used to close the perimeter of coverings. Its particular section, the availability in different colours also on demand and special pieces such as internal and external corners make **PROJOLLY QUART** a much sought-after profile. It can be easily matched with the wall covering and allows an elegant workmanlike application.



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROJOLLY QUART" according to the tile thickness and desired colour.
2. Cut "PROJOLLY QUART" to the desired length and apply the adhesive on the support where the profile will be laid.
3. Press the anchoring flange of "PROJOLLY QUART" into the adhesive.
4. Lay the tiles, aligning them with the profile leaving a 2 mm joint.
5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation.

NON-TOXIC SHOCKPROOF VINYL RESIN
bar length **2,7 lm** - pack. **54 lm** (white colour pack. **108 lm**)

Article	H mm		
PJQT 08-...	8		
PJQT 10-...	10		
PJQT 125-...	12,5		

Available in the colours: 00-01-02-03-05-06-11-17-18.
Available on demand 0106 - 04 - 07 - 08 - 09 -10-12-13-14-15-16-19-20-21-22-23-24-25-26-27-28-29 with a minimum quantity order of 800 pcs. The code of the selected colour must be added to the article code. E.g.: PJQT 08-... (chosen colour white) PJQT 08-01.

WHITE NOT FOR SALE SINGLY

COLOURS

00 - White ice	01 - White	02 - Light grey	03 - Cement gray	05 - Dark beige	06 - Ivory
11 - Black	17 - Bahama beige	18 - Grey			

ON DEMAND - MINIMUM QUANTITY 800 PCS by colour and height (Price to be agreed. Production delay 4/5 weeks)

0106 - White ivory	04 - Light beige	07 - Pink	08 - Sky blue	09 - Yellow	10 - Red
12 - Silver	13 - Gold	14 - Green	15 - Brown	16 - Blue	19 - Beige
20 - Dark ivory	21 - Light pink	22 - Dark pink	23 - Dark antique pink	24 - Dark sky blue	25 - Brick red
26 - Turquoise green	27 - Dark green	28 - Hazel brown	29 - Dark brown		

CAPSULES and THREE-WAYS JOINTS

POLYPROPYLENE/POLYETYLENE UV RESISTANT



POLYPROPYLENE/POLYETYLENE UV RESISTANT

Article	H mm	Pack. 20 Pcs	Pack. 5 Pcs
CPJQT 08-.../...	8		
IPJQT 08-.../...	8		
CPJQT 10-.../...	10		
IPJQT 10-.../...	10		
CPJQT 125-.../...	12,5		
IPJQT 125-.../...	12,5		

Available in the colours: 01-02-03-05-06-11-17-18 (available on demand 0106-04-07-08-09-10-12-13-14-15-16-19-20-21-22-23-24-25-26-27-28-29). The code of the selected colour must be added to the article code. E.g.: CPJQT 08-.../... (chosen colour white) CPJQT 08-01/20.

EXTERNAL CAPSULES



CPJQT .../.../...

INTERNAL CAPSULES



IPJQT .../.../...



PROJOLLY is a rounded bead profile in polished, super polished, sanded and brushed stainless steel AISI 304/1.4301-V2A that can be applied on external corners of coverings. It can be used to close the perimeter of coverings and like a connection profile between step tread and riser of stairs coated with ceramic or natural stone tiles. Its particular section, the availability in three different finishes and special pieces such as internal and external corners, end caps and joints make **PROJOLLY** a much sought-after profile that allows a workmanlike application even in environments subject to high mechanical stresses.

PROJOLLY

POLISHED, SUPER POLISHED, SANDED AND BRUSHED STAINLESS STEEL AISI 304/1.4301-V2A



POLISHED STAINLESS STEEL AISI 304/1.4301-V2A with protective film
bar length 2,7 lm - pack. 20 Pcs - 54 lm - 10/10 mm

Article	H mm		
PJAC 06	6		
PJAC 08	8		
PJAC 10	10		
PJAC 11	11		
PJAC 125	12,5		
PJAC 15	15		

SUPER POLISHED STAINLESS ST. AISI 304/1.4301-V2A
thermo packed - bar length 2,7 lm - pack. 20 Pcs
54 lm - 10/10 mm



Article	H mm		
PJACML 06	6		
PJACML 08	8		
PJACML 10	10		
PJACML 11	11		
PJACML 125	12,5		
PJACML 15	15		



BRUSHED STAINLESS ST. AISI 304/1.4301-V2A with protective film
bar length 2,7 lm - pack. 20 Pcs - 54 lm - 10/10 mm

Article	H mm		
PJACS 06	6		
PJACS 08	8		
PJACS 10	10		
PJACS 11	11		
PJACS 125	12,5		
PJACS 15	15		


SANDED STAINLESS INOX AISI 304/1.4301-V2A with protective film
bar length 2,7 ml - pack. 20 Pcs 54 lm - 10/10 mm

Article	H mm		
PJACSB 08	8		
PJACSB 10	10		
PJACSB 125	12,5		


COLOURS



ACSB - SPECIAL FINISH, REQUEST AVAILABILITY



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROJOLLY" according to the tile thickness and desired finish.
2. Cut "PROJOLLY" to the desired length and apply the adhesive on the support where the profile will be laid.
3. Press the anchoring flange of "PROJOLLY" into the adhesive.
4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile.
5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.

SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS.

CAPSULES, END CAPS and THREE-WAYS JOINTS

POLISHED, SUPER POLISHED AND BRUSHED STAINLESS ST. AISI 304/1.4301-V2A / PLASTIC

Capsules & end caps of the on demand profiles are also on demand *

CAPSULES and END CAPS - POLISHED STAINLESS ST. AISI 304/1.4301-V2A

Article	H mm	Pack 10 Pcs	Pack 2 Pcs
CPJAC 06/...	6		
IPJAC 06/...	6		
CPJAC 08/...	8		
IPJAC 08/...	8		
CPJAC 10/...	10		
IPJAC 10/...	10		
CPJAC 11/...	11		
IPJAC 11/...	11		
CPJAC 125/...	12,5		
IPJAC 125/...	12,5		
CPJAC 15/...	15		
IPJAC 15/...	15		
TPJAC 06-08-10-11-125-15-.../...			

Choose the desired packaging: E.g.: CPJAC .../10 (Pack 10 Pcs)
CPJAC .../2 (Pack 2 Pcs)

CAPSULES and END CAPS - BRUSHED STAINLESS ST. AISI 304/1.4301-V2A

Article	H mm	Pack 10 Pcs	Pack 2 Pcs
CPJACS 06/...	6		
IPJACS 06/...	6		
CPJACS 08/...	8		
IPJACS 08/...	8		
CPJACS 10/...	10		
IPJACS 10/...	10		
CPJACS 11/...	11		
IPJACS 11/...	11		
CPJACS 125/...	12,5		
IPJACS 125/...	12,5		
CPJACS 15/...	15		
IPJACS 15/...	15		
TPJACS 06-08-10-11-125-15-.../...			

Choose the desired packaging: E.g.: CPJACS .../10 (Pack 10 Pcs)
CPJACS .../2 (Pack 2 Pcs)

CAPSULES - SUPER POLISHED STAINLESS ST. AISI 304/1.4301-V2A

Article	H mm	Pack 10 Pcs	Pack 2 Pcs
CPJACML 06/...	6		
IPJACML 06/...	6		
CPJACML 08/...	8		
IPJACML 08/...	8		
CPJACML 10/...	10		
IPJACML 10/...	10		
CPJACML 11/...	11		
IPJACML 11/...	11		
CPJACML 125/...	12,5		
IPJACML 125/...	12,5		
CPJACML 15/...	15		
IPJACML 15/...	15		

Choose the desired packaging: E.g.: CPJACML .../10 (Pack 10 Pcs)
CPJACML .../2 (Pack 2 Pcs)

JOINTS - PLASTIC

Article	H mm	Pack 10 Pcs	Pack 2 Pcs
GJAC 06/...	6		
GJAC 08/...	8		
GJAC 10/...	10		
GJAC 11/...	11		
GJAC 125/...	12,5		
GJAC 15/...	15		

Choose the desired packaging: E.g.: GJAC .../10 (Pack 10 Pcs)
GJAC .../2 (Pack 2 Pcs)

CAPSULES - SANDED STAINLESS INOX AISI 304/1.4301-V2A

Article	H mm	Pack 10 Pcs	Pack 2 Pcs
CPJACSB 08/...	8		
IPJACSB 08/...	8		
CPJACSB 10/...	10		
IPJACSB 10/...	10		
CPJACSB 125/...	12,5		
IPJACSB 125/...	12,5		



END CAP TPJ... .../... EXTERNAL CAPSULES CPJ... .../... INTERNAL CAPSULES IPJ... .../... JOINT GJAC .../...




* = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed


PROJOLLY

POLISHED STAINLESS STEEL INOX AISI 316LL/1.4404-V4A

PROJOLLY is a rounded bead profile in polished stainless steel INOX AISI 316LL/1.4404-V4A that can be applied on external corners of coverings. It can be used to close the perimeter of coverings and like a connection profile between step tread and riser of stairs coated with ceramic or natural stone tiles. Its particular section, the availability in three different finishes and special pieces such as internal and external corners, end caps and joints make **PROJOLLY** a much sought-after profile that allows a workmanlike application even in environments subject to high mechanical and chemical stresses.



EXAMPLES OF LAYING



POLISHED STAINLESS STEEL AISI 316LL/1.4404-V4A with protective film
- bar length 2,7 lm - pack. 20 Pcs - 54 lm - 10/10 mm



Article	H mm		
PJACM 06	6		
PJACM 08	8		
PJACM 10	10		
PJACM 11	11		
PJACM 125	12,5		

SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS.



COLOURS



ACM - Polished stainless st.
AISI 316LL

1. Choose "PROJOLLY" according to the tile thickness. 2. Cut "PROJOLLY" to the desired length and apply the adhesive on the support where the profile will be laid. 3. Press the anchoring flange of "PROJOLLY" into the adhesive. 4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile. 5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.

CAPSULES and THREE-WAYS JOINTS

POLISHED STAINLESS STEEL AISI 316LL/1.4404-V4A



POLISHED STAINLESS STEEL AISI 316LL/1.4404-V4A

Article	H mm	Pack 10 Pcs	Pack 2 Pcs
CPJACM 06/...	6		
IPJACM 06/...	6		
CPJACM 08/...	8		
IPJACM 08/...	8		
CPJACM 10/...	10		
IPJACM 10/...	10		
CPJACM 11/...	11		
IPJACM 11/...	11		
CPJACM 125/...	12,5		
IPJACM 125/...	12,5		

Choose the desired packaging: E.g.:
CPJACM .../10 (Pack. 10 Pcs)
CPJACM .../2 (Pack. 2 Pcs)

EXTERNAL CAPSULES



CPJACM .../...

INTERNAL CAPSULES




IPJACM .../...

PROTERMINAL

POLISHED STAINLESS STEEL INOX AISI 316LL/1.4404-V4A


PROTERMINAL is a "L-shaped" profile in polished stainless steel INOX AISI 316LL/1.4404-V4A that can be applied on external corners of coverings. It can be used to close the perimeter of coverings, like a connection profile between step tread and riser of stairs coated with ceramic and natural stone tiles, and also as separation profile for floor coverings. Its particular section and the availability in three different heights make **PROTERMINAL** a much sought-after profile that allows a workmanlike application even in environments subject to high mechanical and chemical stresses.



EXAMPLES OF LAYING



COLOURS



ACM - Polished stainless st.
AISI 316LL

1. Choose "PROTERMINAL" according to the tile thickness. 2. Cut "PROTERMINAL" to the desired length and apply the adhesive on the support where the profile will be laid. 3. Press the anchoring flange of "PROTERMINAL" into the adhesive. 4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile. 5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.



POLISHED STAINLESS STEEL AISI 316LL/1.4404-V4A
bar length 2,7 lm - pack. 40 Pcs - 108 lm - 10/10 mm




Article	H mm		
PTACM 06	6		
PTACM 08	8		
PTACM 10	10		
PTACM 125	12,5		

SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS.

PROJOLLY is a rounded bead profile in natural, antique brass, polished varnished and chromed brass that can be applied on external corners of coverings. It can be used to close the perimeter of coverings and like (only natural and chromed version) a connection profile between step tread and riser of stairs coated with ceramic or natural stone tiles. Its particular section, the availability in three different finishes and special pieces such as internal and external corners, end caps and joints make **PROJOLLY** a much sought-after and elegant profile that allows a workmanlike application.

PROJOLLY

NATURAL, POLISHED VARNISHED,
CHROMED AND ANTIQUE BRASS



NATURAL BRASS thermo packed
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H mm		
PJON 08	8		
PJON 10	10		
PJON 125	12,5		

SUPER POLISHED VARNISHED CHROMED BRASS thermo packed bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H mm		
PJOC 06	6		
PJOC 08	8		
PJOC 10	10		
PJOC 125	12,5		

MIRROR LINE

POLISHED VARNISHED BRASS thermo packed
bar length 2,7 lm - pack. 20 Pcs - 54 lm


Article	H mm		
PJOL 06	6		
PJOL 08	8		
PJOL 10	10		
PJOL 125	12,5		

Polished varnished brass is not suitable for frequent pedestrian traffic places and/or scratching.

ANTIQUÉ BRASS thermo packed
bar length 2,7 lm - pack. 20 Pcs - 54 lm


Article	H mm		
PJOB 08	8		
PJOB 10	10		
PJOB 125	12,5		

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROJOLLY" according to the tile thickness and desired finish.
2. Cut "PROJOLLY" to the desired length and apply the adhesive on the support where the profile will be laid.
3. Press the anchoring flange of "PROJOLLY" into the adhesive.
4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile.
5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.

COLOURS



CAPSULES, END CAPS and THREE-WAYS JOINTS

VARNISHED POLISHED BRASS AND CHROMED BRASS EFFECT / PLASTIC

Capsules & end caps of the on demand profiles are also on demand *

CAPS and JOINTS - CHROMED BRASS / PLASTIC

Article	H mm	Pack 10 Pcs	Pack 2 Pcs
TPJOC 06-08-10-125/...	6-8-10-12,5		
GJJA 06-08-10-125/...	6-8-10-12,5		

Choose the desired packaging: E.g.: GJJA.../10 (Pack. 10 Pcs)
GJJA.../2 (Pack. 2 Pcs)

END CAP



TPJOC .../...

JOINT



GJJA .../...

EXTERNAL CAPSULES



CPJ... .../...

CPJD... .../...

INTERNAL CAPSULES



IPJD... .../...

IPJ... .../...

LEFT CAPSULES - POLISHED VARNISHED/CHROMED BRASS

Article	H mm	Pack 10 Pcs	Pack 2 Pcs
CPJOL/OC 06/...	6		
IPJOL/OC 06/...	6		
CPJOL/OC 08/...	8		
IPJOL/OC 08/...	8		
CPJOL/OC 10/...	10		
IPJOL/OC 10/...	10		
CPJOL/OL 125/...	12,5		
IPJOL/OC 125/...	12,5		

Choose the desired packaging: E.g.: CPJOL.../10 (Pack. 10 Pcs)
CPJOL.../2 (Pack. 2 Pcs)

The right capsules are available on demand and must be used only in the following cases:

A) when you are laying the cut base of the profile perpendicularly on the floor;

B) as an alternative to end-caps (right side).



Add "D" to the article code.
For example: CPJDOL 06.



Add "D" to the article code.
For example: IPJDOL 06.

LEFT CAPSULES - ANTIQUE BRASS

Article	H mm	Pack 10 Pcs	Pack 2 Pcs
CPJOB 08/...	8		
IPJOB 08/...	8		
CPJOB 10/...	10		
IPJOB 10/...	10		
CPJOB 125/...	12,5		
IPJOB 125/...	12,5		

Choose the desired packaging: E.g.: CPJOB.../10 (Pack. 10 Pcs)
CPJOB.../2 (Pack. 2 Pcs)



LEFT CAPSULES

RIGHT CAPSULES

Add "D" to the article code. For example: CPJDOC 06.


News 2023

* = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed


PROJOLLY

ANODIZED ALUMINIUM
SILVER, COPPER, TITANIUM, GOLD AND BLACK

PROJOLLY is a rounded bead profile in anodized aluminium that can be applied on external corners of coverings. It can be used to close the perimeter of coverings and like a connection profile between step tread and riser of stairs coated with ceramic or natural stone tiles. Its particular section and elegance, the availability in five different finishes and special pieces such as internal and external corners, end caps and joints make **PROJOLLY** a much sought-after and elegant profile that allows a workmanlike application.



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROJOLLY" according to the tile thickness and desired finish. 2. Cut "PROJOLLY" to the desired length and apply the adhesive on the support where the profile will be laid. 3. Press the anchoring flange of "PROJOLLY" into the adhesive. 4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile. 5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.



ANODIZED ALUM. (silver-copper-gold-titanium-black) thermo packed
bar length **2,7 lm** - pack. **40 Pcs - 108 lm**
(for H 15 anodized silver alum. pack. **20 Pcs - 54 lm**)

Article	H mm		
PJAA 03	3		
PJAA 045	4,5		
PJAA 06	6		
PJAA 08	8		
PJAA 10	10		
PJAA 125	12,5		
PJAA 15	15		
PJAO 03	3		
PJAO 045	4,5		
PJAO 06	6		
PJAO 08	8		
PJAO 10	10		
PJAO 125	12,5		
PJAO 15	15		
PJAR 08	8		
PJAR 10	10		
PJAR 125	12,5		*
PJAT 08	8		
PJAT 10	10		
PJAT 125	12,5		
PJNE 08	8		
PJNE 10	10		
PJNE 125	12,5		

COLOURS



CAPSULES, END CAPS and THREE-WAYS JOINTS

* Capsules & end caps of the on demand profiles are also on demand

Anodized ALUMINIUM (silver, copper, titanium, gold and black) / PLASTIC

LEFT CAPSULES ANODIZED ALUMINIUM

(silver, copper, titanium and gold)

Article	H mm	Pack 10 Pcs	Pack 2 Pcs
CPJAA .../...	06/08/10/125		
CPJAA 15/...	15		
IPJAA .../...	06/08/10/125		
IPJAA 15/...	15		
TPJAA .../...	06/08/10/125/15		
CPJAO .../...	06/08/10		
CPJAO 15/...	15		
IPJAO .../...	06/08/10		
IPJAO 15/...	15		
TPJAO .../...	06/08/10/15		
CPJAR .../...	08/10/125		
IPJAR .../...	08/10/125		
TPJAR .../...	08/10/125		
CPJAT .../...	08/10/125		
IPJAT .../...	08/10/125		
TPJAT .../...	08/10/125		
CPJNE .../...	08/10/125		
IPJNE .../...	08/10/125		
TPJNE .../...	08/10/125		

Choose the desired pack & height
Ex.: 4,5 mm capsule in 10 Pcs Pack - CPJAA 10/10

JOINTS - PLASTIC

Article	H mm	Pack 10 Pcs	Pack 2 Pcs
GIJA .../...	06/08/10/125/15		

Choose the desired pack & height
Ex: 10 mm joint in 10 Pcs Pack - GIJA 10/10

EXTERNAL CAPSULES



INTERNAL CAPSULES



CAPS




JOINTS



The right capsules are available on demand and must be used only in the following cases:


A) when you are laying the cut base of the profile perpendicularly on the floor;



Add "D" to the article code. For example: CPJDAA 06.

Add "D" to the article code. For example: IPJDAA 06.

B) as an alternative to end-caps (right side).



LEFT CAPSULES
RIGHT CAPSULES
Add "D" to the article code. For example: CPJDAA 06.

PROJOLLY is a rounded bead profile in polished aluminium that can be applied on external corners of coverings. It can be used to close the perimeter of coverings and like a connection profile between step tread and riser of stairs coated with ceramic or natural stone tiles. Its particular section and elegance, the availability in five different finishes and special pieces such as internal and external corners, end caps and joints make **PROJOLLY** a much sought-after and elegant profile that allows a workmanlike application.

PROJOLLY


POLISHED ALUMINIUM
CHROME, COPPER, TITANIUM, GOLD AND BLACK




POLISHED ALUMINIUM (chrome-copper-titanium-gold-black)
thermo packed - bar length 2,7 lm - pack. 40 Pcs - 108 lm (H 15 mm - 54 lm)

Article	H mm		
PJBC 03	3		
PJBC 045	4,5		
PJBC 06	6		
PJBC 08	8		
PJBC 10	10		
PJBC 125	12,5		
PJBC 15	15		
PJBO 03	3		
PJBO 045	4,5		
PJBO 06	6		
PJBO 08	8		
PJBO 10	10		
PJBO 125	12,5		
PJBR 08	8		
PJBR 10	10		
PJBR 125	12,5		
PJBT 08	8		
PJBT 10	10		
PJBT 125	12,5		
PJBN 08	8		
PJBN 10	10		
PJBN 125	12,5		

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROJOLLY" according to the tile thickness and desired finish.
2. Cut "PROJOLLY" to the desired length and apply the adhesive on the support where the profile will be laid.
3. Press the anchoring flange of "PROJOLLY" into the adhesive.
4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile.
5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.



COLOURS



CAPSULES, END CAPS and THREE-WAYS JOINTS

POLISHED ALUMINIUM (chrome, copper, titanium, gold, black) / PLASTIC

Capsules & end caps of the on demand profiles are also on demand *

JOINTS - PLASTIC

Article	H mm	Pack 10 Pcs	Pack 2 Pcs
GIJA .../...	06/08/10/ 125/15		


Choose the desired pack & height
Ex.: 10 mm joint in 10 Pcs Pack - GIJA 10/10



EXTERNAL CAPSULES



INTERNAL CAPSULES




LEFT CAPSULES POLISHED ALUMINIUM chrome, copper, titanium and gold

Article	H mm	Pack 10 Pcs	Pack 2 Pcs
CPJBC .../...	06/08/10/125		
CPJBC 15/...	15		
IPJBC .../...	06/08/10/125		
IPJBC 15/...	15		
TPJBC .../...	06/08/10/125/15		
CPJBO .../...	06/08/10/125		
IPJBO .../...	06/08/10/125		
TPJBO .../...	06/08/10/15		
CPJBR .../...	08/10/125		
IPJBR .../...	08/10/125		
TPJBR .../...	08/10/125		
CPJBT .../...	08/10/125		
IPJBT .../...	08/10/125		
TPJBT .../...	08/10/125		
CPJBN .../...	08/10/125		
IPJBN .../...	08/10/125		
TPJBN .../...	08/10/125		

Choose the desired pack & height
Ex.: 4,5 mm capsule in 10 Pcs Pack - CPJBC 10/10


(*) 12,5/15 mm NOT SUITABLE FOR THREE-WAYS CORNER

The right capsules are available on demand and must be used only in the following cases:
A) when you are laying the cut base of the profile perpendicularly on the floor;



Add "D" to the article code. For example: CPJDBC 06.
Add "D" to the article code. For example: IPJDBC 06.

B) as an alternative to end-caps (right side).




LEFT CAPSULES
RIGHT CAPSULES
Add "D" to the article code. For example: CPJDBC 06.


PROJOLLY

BRUSHED ALUMINIUM

PROJOLLY is a rounded bead profile in brushed aluminium that can be applied on external corners of coverings. It can be used to close the perimeter of coverings and like a connection profile between step tread and riser of stairs coated with ceramic or natural stone tiles. Its particular section and elegance, the availability in four different finishes and special pieces such as internal and external corners, end caps and joints make **PROJOLLY** a much sought-after and elegant profile that allows a workmanlike application.



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROJOLLY" according to the tile thickness and desired finish.
2. Cut "PROJOLLY" to the desired length and apply the adhesive on the support where the profile will be laid.
3. Press the anchoring flange of "PROJOLLY" into the adhesive.
4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile.
5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.



BRUSHED POLISHED ALUMINIUM (silver-gold-copper-titanium-black)
thermo packed - bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm		
PJBS 03	3		
PJBS 045	4,5		
PJBS 08	8		
PJBS 10	10		
PJBS 125	12,5		
PJRS 03	3		
PJRS 045	4,5		
PJRS 08	8		
PJRS 10	10		
PJRS 125	12,5		
PJBOS 03	3		
PJBOS 045	4,5		
PJBOS 08	8		
PJBOS 10	10		
PJBOS 125	12,5		
PJTS 03	3		
PJTS 045	4,5		
PJTS 08	8		
PJTS 10	10		
PJTS 125	12,5		
PJNS 08	8		
PJNS 10	10		
PJNS 125	12,5		



COLOURS



AVAILABLE MINIMUM QUANTITY 100 PCS by colour and height



(Price to be agreed. Production delay 4/5 weeks)

CAPSULES, END CAPS and THREE-WAYS JOINTS

* Capsules & end caps of the on demand profiles are also on demand

BRUSHED POLISHED ALUMINIUM (silver, copper, titanium, black) / PLASTIC

LEFT CAPSULES - BRUSHED POLISHED ALUMINIUM

silver-gold-copper-titanium-black

Article	H mm	Pack 10 Pcs	Pack 2 Pcs
CPJBS .../...	08/10/125		
IPJBS .../...	08/10/125		
TPJBS .../...	08/10/125		
CPJBOS .../...	08/10/125		
IPJBOS .../...	08/10/125		
TPJBOS .../...	08/10/125		
CPJRS .../...	08/10/125		
IPJRS .../...	08/10/125		
TPJRS .../...	08/10/125		
CPJTS .../...	08/10/125		
IPJTS .../...	08/10/125		
TPJTS .../...	08/10/125		
CPJNS .../...	08/10/125		
IPJNS .../...	08/10/125		
TPJNS .../...	08/10/125		

Choose the desired pack & height
Ex.: 4,5 mm capsule in 10 Pcs Pack - CPJBS 10/10

JOINTS - PLASTIC

Article	H mm	Pack 10 Pcs	Pack 2 Pcs
GIIA .../...	08/10/125		

Choose the desired pack & height
Ex.: 10 mm joint in 10 Pcs Pack - GIIA 10/10

EXTERNAL CAPSULES




INTERNAL CAPSULES



The right capsules are available on demand and must be used only in the following cases:

A) when you are laying the cut base of the profile perpendicularly on the floor;



Add "D" to the article code. For example: CPJDBS 08.

Add "D" to the article code. For example: IPJDBS 08.

B) as an alternative to end-caps (right side).



LEFT CAPSULES **RIGHT CAPSULES**
Add "D" to the article code. For example: CPJDBS 08.

END CAP




JOINT



PROJOLLY is a rounded bead profile in varnished aluminium that can be applied on external corners of coverings. It can be used to close the perimeter of coverings. Its particular section and elegance, the availability in five different colours and special pieces such as internal and external corners, end caps and joints make **PROJOLLY** a much sought-after and elegant profile that allows a workmanlike application.

PROJOLLY

VARNISHED ALUMINIUM



VARNISHED ALUMINIUM (HOT-WORKED 200°) thermo packed bar length 2,7 lm - pack. 20 Pcs-54 lm (colour white 40 Pcs - 108 lm)

Article	H mm
PJA 06-01	6
PJA 08-...	8
PJA 10-...	10
PJA 125-01	12,5

With H 8 and 10 mm available in the colours: 01 - 0106 - 0311 - 06 - 11
Available on demand: 010 - 02-03-0211-10-17.
The code of the selected colour must be added to the article code.
E.g.: PJA 08... (chosen colour white) PJA 08-01.

On demand may be realised in other finishes of the colour chart. Contact our customer service for minimal quantity, timing and price.

COLOURS

01 - Varnished white alum. (9016)	0106 - Varnished white ivory alum. (9001)	0311 - Varnished asphalt grey alum. (7043)
06 - Varnished ivory alum. (1015)	11 - Varnished black alum. (9005)	

AVAILABLE MINIMUM QUANTITY 100 PCS by colour and height
(Price to be agreed. Production delay 4/5 weeks)

010 - Varnished white matt alum. (9016)	02 - Varnished light grey alum. (7035)	03 - Varnished stone grey alum. (7030)
0211 - Varnished quartz grey alum. (7039)	10 - Varnished klinker red alum. (8004)	17 - Varnished bahama beige alum.

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROJOLLY" according to the tile thickness and desired colour.
2. Cut "PROJOLLY" to the desired length and apply the adhesive on the support where the profile will be laid.
3. Press the anchoring flange of "PROJOLLY" into the adhesive.
4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile.
5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.

CAPSULES, END CAPS and THREE-WAYS JOINTS

VARNISHED ALUMINIUM / PLASTIC

Capsules & end caps of the on demand profiles are also on demand

LEFT CAPSULES VARNISHED ALUMINIUM (HOT-WORKED 200°)

Article	H mm	Pack 10 Pcs	Pack 2 Pcs
CPJA .../.../...	08/10/125		
IPJA .../.../...	08/10/125		
TPJA .../.../...	08/10/125		

Choose the desired pack. & height
Ex.: 4,5 mm capsule in 10 Pcs Pack - CPJA 10-06/10 10/10

EXTERNAL CAPSULES



CPJA... /.../...



CPJDA... /.../...

INTERNAL CAPSULES



IPJA... /.../...



IPJDA... /.../...

JOINTS - PLASTIC

Article	H mm	Pack 10 Pcs	Pack 2 Pcs
GIJA .../...	08/10/125		

Choose the desired pack. & height
Ex.: 10 mm joint in 10 Pcs Pack - GIJA 10/10

END CAP



TPJA... /.../...

JOINT



GIJA .../...

The right capsules are available on demand and must be used only in the following cases:

A) when you are laying the cut base of the profile perpendicularly on the floor;



Add "D" to the article code. For example: CPJDA 06-01.



Add "D" to the article code. For example: IPJDA 06-01.

B) as an alternative to end-caps (right side).



LEFT CAPSULES


RIGHT CAPSULES

Add "D" to the article code. For example: CPJDA 06-01.


PROJOLLY

SHOCKPROOF NON - TOXIC
COLORED VINYL RESIN

PROJOLLY is a rounded bead profile in shockproof non - toxic colored vinyl resin that can be applied on external corners of coverings. It can be used to close the perimeter of coverings. Its particular section, the availability in different colours also on demand and special pieces such as internal and external corners make **PROJOLLY** a much sought-after profile. It can be easily matched with the wall covering and allows an elegant workmanlike application.



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROJOLLY" according to the tile thickness and desired colour. 2. Cut "PROJOLLY" to the desired length and apply the adhesive on the support where the profile will be laid. 3. Press the anchoring flange of "PROJOLLY" into the adhesive. 4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. 5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation.

NON-TOXIC SHOCKPROOF VINYL RESIN

bar length **2,7 lm** - pack. **54 lm** (colour white pack. **108 lm**)

Article	H mm		
PJ 06-...	6		
PJ 08-...	8		
PJ 10-...	10		
PJ 125-...	12,5		

Available in the colours: 00 - 01 - 02 - 03 - 04 - 05 - 06 - 07 - 08 - 09 - 11-12 - 13 - 14 - 15 - 17 - 18 - 0106.
Available on demand 10 -16 -19 - 20 - 21 - 22 - 23 - 24 - 25 - 26 - 27 - 28 - 29 with a minimum quantity order of 800 pcs.
The code of the selected colour must be added to the article code.
E.g.: PJ 06... (chosen colour white) PJ 06-01.

WHITE NOT FOR SALE SINGLY

NON-TOXIC SHOCKPROOF VINYL RESIN

MIRROR LINE EXTRA POLISHED - bar length **2,7 lm**

pack. **54 lm** (colour white pack. **108 lm**)

Article	H mm		
PJML 06-00/01	6		
PJML 06-...	6		
PJML 08-00/01	8		
PJML 08-...	8		
PJML 10-00/01	10		
PJML 10-...	10		
PJML 125-00/01	12,5		
PJML 125-...	12,5		

MIRROR LINE

available in the color: 01 - 00 (Available on demand 0106-02-03-04-05-07-08-09-10-11-14-15-16-17-0106-19-20-21-22-23-24-25-26-27-28-29 with a minimum quantity order of 800 pcs.)
The code of the selected colour must be added to the article code.
E.g.: PJ 06... (chosen colour white) PJ 06-01.
Prices per metre are approximate. Articles not for sale singly.

WHITE NOT FOR SALE SINGLY

COLOURS

00 - White ice	01 - White	0106 - White ivory	02 - Light grey	03 - Cement grey
04 - Light beige	05 - Dark beige	06 - Ivory	07 - Pink	08 - Sky Blue
09 - Yellow	11 - Black	12 - Silver	13 - Gold	14 - Green
15 - Brown	17 - Bahama beige	18 - Grey		

AVAILABLE MINIMUM QUANTITY 800 PCS by colour and height
(Price to be agreed. Production delay 4/5 weeks)

10 - Red	16 - Blue	19 - Beige	20 - Dark ivory
21 - Light pink	22 - Dark pink	23 - Dark antique pink	24 - Dark sky blue
25 - Brick red	26 - Turquoise green	27 - Dark green	28 - Hazel brown
29 - Dark brown			

CAPSULES for three-ways joints

POLYPROPYLENE/POLYETHYLENE UV RESISTANT

* Capsules & end caps of the on demand profiles are also on demand

POLYPROPYLENE / POLYETHYLENE UV RESISTANT

Article	H mm	Pack, 20 pcs	Pack, 5 pcs
CPJ 06-.../...	6		
IPJ 06-.../...	6		
CPJ 08-.../...	8		
IPJ 08-.../...	8		
CPJ 10-.../...	10		
IPJ 10-.../...	10		
CPJ 125-.../...	12,5		
IPJ 125-.../...	12,5		

EXTERNAL CAPSULES




CPJ .../.../...

INTERNAL CAPSULES



IPJ .../.../...




Available in the colours: 01-02-03-04-05-06-07-08-09-10-11-12-13-14-15-16-17-18-0106 (not available 19-20-21-22-23-24-25-26-27-28-29).
The code of the selected colour must be added to the article code.
E.g.: CPJ 06-.../... (chosen colour white) CPJ 06-01/20.

* = Production on demand with minimum quantity of 800 pcs. Production delay 4/5 weeks. Price to be agreed

PROJOLLY MARBLE is a rounded bead profile in shockproof non - toxic marbled vinyl resin that can be applied on external corners of coverings. It can be used to close the perimeter of coverings. Its particular section, the availability of different marble effect finishes also on demand and special pieces such as internal and external corners make **PROJOLLY MARBLE** a much sought-after profile. It can be easily matched with the wall covering and allows an elegant workmanlike application.

PROJOLLY MARBLE

SHOCKPROOF NON - TOXIC MARBLED VINYL RESIN



MARBLED NON-TOXIC VYNIL RESIN
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm
PJ... 06	6
PJ... 08	8
PJ... 10	10
PJ... 125	12,5

Available on demand MC - MB - MR - MA - MV - MVA - MAS - MBS - MRS - MVAS - MTC - MTS (MAB - MBC - MBO - MAM - MBD - MCRI - MCRC - MBDX - MG - MGVC - MNA - MBPS - MVBL with a minimum quantity order of 800 pcs).

The code of the selected colour must be added to the article code. E.g.: PJ... 10 (chosen colour carrara) PJMC 10.

INSTRUCTIONS FOR LAYING

1. Choose "PROJOLLY MARBLE" according to the tile thickness and desired colour. 2. Cut "PROJOLLY MARBLE" to the desired length and apply the adhesive on the support where the profile will be laid. 3. Press the anchoring flange of "PROJOLLY MARBLE" into the adhesive. 4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. 5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation.

EXAMPLES OF LAYING



COLOURS



AVAILABLE MINIMUM QUANTITY 800 PCS by colour and height (Price to be agreed. Production delay 4/5 weeks)



PROJOLLY OPEN is a rounded bead profile in shockproof non - toxic marbled vinyl resin that can be applied on external corners of coverings. It can be used to close the perimeter of coverings. Its particular open section and the availability in white colour make **PROJOLLY OPEN** a practical and economic profile. It can be used where low cost and workmanlike application are required.

PROJOLLY OPEN

SHOCKPROOF NON - TOXIC WHITE VINYL RESIN




WHITE VINYL RESIN
bar length 2,7 lm - pack. 80 Pcs - 216 lm

Article	H mm
PJP 06-01	6
PJP 09-01	9

ARTICLES NOT FOR SALE SINGLY

INSTRUCTIONS FOR LAYING

1. Choose "PROJOLLY OPEN" according to the tile thickness. 2. Cut "PROJOLLY OPEN" to the desired length and apply the adhesive on the support where the profile will be laid. 3. Press the anchoring flange of "PROJOLLY OPEN" into the adhesive. 4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. 5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation.



EXAMPLES OF LAYING



COLOURS




OTHER COLOURS ON DEMAND FOR A MINIMUM OF 800 pcs

* = Production on demand with minimum quantity of 800 pcs. Production delay 4/5 weeks. Price to be agreed

PROJOLLY ECO

SHOCKPROOF NON - TOXIC
COLOURED VINYL RESIN

PROJOLLY ECO is a rounded bead profile in shockproof non - toxic colored vinyl resin that can be applied on external corners of coverings. It can be used to close the perimeter of coverings. Its particular section, the availability of different colours also on demand and special pieces such as internal and external corners make **PROJOLLY ECO** a practical and economic profile. It can be easily matched with the wall covering and allows an elegant workmanlike application.



COLOURED VINYL RESIN
bar length 2,7 lm - pack. 80 Pcs - 216 lm

Article	H mm		
PJE 06-01/06/18	6		*
PJE 08-...	8		
PJE 10-...	10		
PJE 125-...	12,5		

ARTICLES NOT FOR SALE SINGLY

H 6 mm available the colours 01 - 06 - 18, other colours on demand.
Available on demand in the colours 01 - 02 - 03 - 04 - 05 - 06 - 07 - 08 - 09 - 10 - 11 - 12 - 13 - 14 - 15 - 16 - 17 - 18 (0106 - 19 - 20 - 21 - 22 - 23 - 24 - 25 - 26 - 27 - 28 - 29 with a minimum quantity order of 800 pcs. The code of the selected colour must be added to the article code. E.g.: PJE 08... (chosen colour white) PJE 08-01.

COLOURED VINYL RESIN
bar length 2,7 lm - pack. 80 Pcs - 216 lm


Article	H mm		
PJE 07-...	7		*
PJE 09-...	9		*

ARTICLES NOT FOR SALE SINGLY

PRODUCTION ON DEMAND
MINIMUM QUANTITY 800 PCS BY COLOUR AND HEIGHT
(Production delay 4/5 weeks)

Available on demand in the colours: 01 - 02 - 03 - 04 - 05 - 06 - 07 - 08 - 09 - 10 - 11 - 12 - 13 - 14 - 15 - 16 - 17 - 18 - 19 - 20 - 21 - 22 - 23 - 24 - 25 - 26 - 27 - 28 - 29 - 0106 with a minimum quantity order of 800 pcs. The code of the selected colour must be added to the article code. E.g.: PJE 07... (chosen colour white) PJE 07-01.

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROJOLLY ECO" according to the tile thickness and desired colour. 2. Cut "PROJOLLY ECO" to the desired length and apply the adhesive on the support where the profile will be laid. 3. Press the anchoring flange of "PROJOLLY ECO" into the adhesive. 4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. 5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation.

COLOURS

01 - White	02 - Light grey	03 - Cement gray	04 - Light beige	05 - Dark beige	06 - Ivory
07 - Pink	08 - Sky blue	09 - Yellow	10 - Red	11 - Black	12 - Silver
13 - Gold	14 - Green	15 - Brown	16 - Blue	17 - Bahama beige	18 - Grey

AVAILABLE MINIMUM QUANTITY 800 PCS by colour and height
(Price to be agreed. Production delay 4/5 weeks)

0106 - White ivory	19 - Beige	20 - Dark ivory
21 - Light pink	22 - Dark pink	23 - Dark antique pink
24 - Dark sky blue	25 - Brick red	26 - Turquoise green
27 - Dark green	28 - Hazel brown	29 - Dak brown

CAPSULES for three-ways joints

COLOURED PLASTIC

* Capsules & end caps of the on demand profiles are also on demand



EXTERNAL CAPSULES



CPJE .../.../...

COLOURED PLASTIC

Article	H mm	Pack. 20 pcs	Pack. 5 pcs
CPJE 06-01/06/18/...	6		
CPJE 08-.../.../...	8		
CPJE 10-.../.../...	10		
CPJE 125-.../.../...	12,5		

ARTICLES NOT FOR SALE SINGLY

H 6 mm available the colours 01 - 06 - 18, other colours on demand. Available in the colours: 01 - 02 - 03 - 04 - 05 - 06 - 07 - 08 - 09 - 10 - 11 - 12 - 13 - 14 - 15 - 16 - 17 - 18 (not available 0106 - 19 - 20 - 21 - 22 - 23 - 24 - 25 - 26 - 27 - 28 - 29).

The code of the selected colour must be added to the article code. E.g.: CPJE 08-.../.../... (chosen colour white) CPJE 08-01/20.

* = Production on demand with minimum quantity of 800 pcs. Production delay 4/5 weeks. Price to be agreed

PROJOLLY ECO MARBLE is a rounded bead profile in shockproof non-toxic marbled vinyl resin that can be applied on external corners of coverings. It can be used to close the perimeter of coverings. Its particular section and the availability of different marble effect finishes, also on demand, and special pieces such as internal and external corners make **PROJOLLY ECO MARBLE** a much sought-after profile. It can be easily matched with the wall covering and allows an elegant workmanlike application.

PROJOLLY ECO MARBLE

SHOCKPROOF NON - TOXIC
MARBLED VINYL RESIN



SHOCKPROOF MARBLED VINYL RESIN
bar length 2,7 lm - pack. 80 Pcs - 216 lm

Article	H mm		
PJE... 06	6		*
PJE... 08	8		
PJE... 10	10		

ARTICLES NOT FOR SALE SINGLY

PJE... 125 available on demand.

Available in the colours: MC - MB - MR - MA - MV - MVA - MAS - MBS - MRS - MVAS - MTC - MTS (on demand MAB - MBC - MBO - MAM - MBD - MCRI - MCRC - MBDX - MGVC - MNA - MBPS - MVBL with a minimum quantity order of 800 pcs).

The code of the selected colour must be added to the article code.
E.g.: PJE... 06 (chosen colour carrara) PJEMC 06.

SHOCKPROOF MARBLED VINYL RESIN
bar length 2,7 lm - pack. 80 Pcs - 216 lm


Article	H mm		
PJE... 07	7		*
PJE... 09	9		*

ARTICLES NOT FOR SALE SINGLY


PRODUCTION ON DEMAND
MINIMUM QUANTITY 800 PCS BY COLOUR AND HEIGHT
(Production delay 4/5 weeks)

Available on demand in the colours: MC - MB - MR - MA - MV - MVA - MAS - MBS - MRS - MVAS - MTC - MTS - MAB - MBC - MBO - MAM - MBD - MCRI - MCRC - MBDX - MGVC - MNA - MBPS - MVBL with a minimum quantity order of 800 pcs.

The code of the selected colour must be added to the article code.
E.g.: PJE... 06 (chosen colour carrara) PJEMC 06.



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROJOLLY ECO MARBLE" according to the tile thickness and desired finish. 2. Cut "PROJOLLY ECO MARBLE" to the desired length and apply the adhesive on the support where the profile will be laid. 3. Press the anchoring flange of "PROJOLLY ECO MARBLE" into the adhesive. 4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. 5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation.

COLOURS



AVAILABLE MINIMUM QUANTITY 800 PCS by colour and height (Price to be agreed. Production delay 4/5 weeks)




* = Production on demand with minimum quantity of 800 pcs. Production delay 4/5 weeks. Price to be agreed

PROJOLLY TRIANGLE

POLISHED, SUPER POLISHED AND BRUSHED STAINLESS STEEL AISI 304/1.4301-V2A

PROJOLLY TRIANGLE is a triangle-shaped bead profile polished, super polished and brushed stainless steel AISI 304/1.4301-V2A that can be applied on external corners of coverings. It can be used to close the perimeter of coverings and like a connection profile between step tread and riser of stairs coated with ceramic or natural stone tiles. Its particular section, the availability in three different finishes and special pieces such as internal and external corners, end caps and joints make **PROJOLLY TRIANGLE** a much sought-after profile that allows a workmanlike application even in environments subject to high mechanical stresses.



POLISHED STAINLESS STEEL AISI 304/1.4301-V2A with protective film
bar length 2,7 lm - pack. 20 Pcs - 54 lm - 8/10 mm

Article	H mm		
PJTRAC 06	6		
PJTRAC 08	8		
PJTRAC 10	10		
PJTRAC 11	11		
PJTRAC 125	12,5		
PJTRAC 15	15		

BRUSHED STAINLESS STEEL AISI 304/1.4301-V2A
bar length 2,7 lm - pack. 20 Pcs - 54 lm - 8/10 mm

Article	H mm		
PJTRACS 06	6		
PJTRACS 08	8		
PJTRACS 10	10		
PJTRACS 11	11		
PJTRACS 125	12,5		
PJTRACS 15	15		

SUPER POLISHED STAINLESS STEEL AISI 304/1.4301-V2A thermo packed
bar length 2,7 lm - pack. 20 Pcs - 54 lm - 8/10 mm


Article	H mm		
PJTRACML 06	6		
PJTRACML 08	8		
PJTRACML 10	10		
PJTRACML 11	11		
PJTRACML 125	12,5		
PJTRACML 15	15		



COLOURS



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROJOLLY TRIANGLE" according to the tile thickness and desired finish.
2. Cut "PROJOLLY TRIANGLE" to the desired length and apply the adhesive on the support where the profile will be laid.
3. Press the anchoring flange of "PROJOLLY TRIANGLE" into the adhesive.
4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile.
5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.

SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS.

CAPSULES, END CAPS, THREE-WAYS JOINTS and JOINTS

POLISHED, SUPER POLISHED AND BRUSHED STAINLESS STEEL AISI 304/1.4301-V2A / PLASTIC

EXTERNAL / INTERNAL / THREE-WAYS CAPSULES and END CAPS - POLISHED STAINLESS STEEL

Article	H mm	Pack. 10 pcs	Pack. 2 pcs
CPJTRAC .../...	06-08-10-11-12,5-15		
IPJTRAC .../...	06-08-10-11-12,5-15		
CTPJTRAC .../...	06-08-10-11-12,5-15		
TPJTRAC .../...	06-08-10-11-12,5-15		

Choose the desired packaging: E.g.: CPJTRAC.../10 (Pack. 10 Pcs)
CPJTRAC.../2 (Pack. 2 Pcs)

ARTICLES NOT FOR SALE SINGLY

EXTERNAL / INTERNAL / THREE-WAYS CAPSULES and END CAPS - SUPER POLISHED STAINLESS STEEL

Article	H mm	Pack. 10 pcs	Pack. 2 pcs
CPJTRACML .../...	06-08-10-11-12,5-15		
IPJTRACML .../...	06-08-10-11-12,5-15		
CTPJTRACML .../...	06-08-10-11-12,5-15		
TPJTRACML .../...	06-08-10-11-12,5-15		

Choose the desired packaging: E.g.: CPJTRACML.../10 (Pack. 10 Pcs)
CPJTRACML.../2 (Pack. 2 Pcs)

ARTICLES NOT FOR SALE SINGLY

EXTERNAL / INTERNAL / THREE-WAYS CAPSULES AND CAPS - BRUSHED STAINLESS STEEL

Article	H mm	Pack. 10 pcs	Pack. 2 pcs
CPJTRACS .../...	06-08-10-11-12,5-15		
IPJTRACS .../...	06-08-10-11-12,5-15		
CTPJTRACS .../...	06-08-10-11-12,5-15		
TPJTRACS .../...	06-08-10-11-12,5-15		

Choose the desired packaging: E.g.: CPJTRACS.../10 (Pack. 10 Pcs)
CPJTRACS.../2 (Pack. 2 Pcs)

ARTICLES NOT FOR SALE SINGLY

JOINTS - PLASTIC

Article	H mm	Pack. 10 pcs	Pack. 2 pcs
GIJTRA .../...	06-08-10-11-12,5-15		

Choose the desired packaging: E.g.: GIJTRA.../10 (Pack. 10 Pcs)
GIJTRA.../2 (Pack. 2 Pcs)

ARTICLES NOT FOR SALE SINGLY

EXTERNAL CAPSULE INTERNAL CAPSULE THREE-WAYS CAPSULE END CAPS JOINTS




CPJTR.../... IPJTR.../... CTPJTR.../... TPJTR.../... GIJTRA.../...

PROJOLLY TRIANGLE is a triangle-shaped bead profile in brass that can be applied on external corners of coverings. It can be used to close the perimeter of coverings and like a connection profile between step tread and riser of stairs coated with ceramic or natural stone tiles. Its particular section, the availability in different finishes make **PROJOLLY TRIANGLE** a much sought-after profile that allows an elegant workmanlike application.

PROJOLLY TRIANGLE

NATURAL, POLISHED VARNISHED, CHROMED AND ANTIQUE BRASS



NATURAL BRASS thermo packed
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H mm
PJTRON 10	10
PJTRON 125	12,5

SUPER POLISHED CHROMED BRASS
thermo packed bar length 2,7 lm - pack. 20 Pcs - 54 lm



Article	H mm
PJTROC 10	10
PJTROC 125	12,5


POLISHED VARNISHED BRASS thermo packed
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H mm
PJTROL 10	10
PJTROL 125	12,5

ANTIQUÉ BRASS thermo packed
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H mm
PJTROB 10	10
PJTROB 125	12,5

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROJOLLY TRIANGLE" according to the tile thickness and desired finish.
2. Cut "PROJOLLY TRIANGLE" to the desired length and apply the adhesive on the support where the profile will be laid.
3. Press the anchoring flange of "PROJOLLY TRIANGLE" into the adhesive.
4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile.
5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.


COLOURS




PROJOLLY TRIANGLE

ANODIZED, POLISHED AND BRUSHED ALUMINIUM

PROJOLLY TRIANGLE is a triangle-shaped bead profile in anodized, polished and brushed aluminium that can be applied on external corners of coverings. It can be used to close the perimeter of coverings and like a connection profile between step tread and riser of stairs coated with ceramic or natural stone tiles. Its particular section, the availability in seven different finishes and special pieces such as internal and external corners, end caps and joints make **PROJOLLY TRIANGLE** a much sought-after profile that allows an elegant workmanlike application.



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROJOLLY TRIANGLE" according to the tile thickness and desired finish.
2. Cut "PROJOLLY TRIANGLE" to the desired length and apply the adhesive on the support where the profile will be laid.
3. Press the anchoring flange of "PROJOLLY TRIANGLE" into the adhesive.
4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile.
5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.

ANODIZED ALUMINIUM (silver - titanium - gold) thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm		
PJTRAA 08	8		
PJTRAA 10	10		
PJTRAA 125	12,5		
PJTRAT 08	8		
PJTRAT 10	10		
PJTRAT 125	12,5		
PJTRAO 08	8		
PJTRAO 10	10		
PJTRAO 125	12,5		

POLISHED ALUMINIUM (chrome - titanium - gold) thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm		
PJTRBC 08	8		
PJTRBC 10	10		
PJTRBC 125	12,5		
PJTRBT 08	8		
PJTRBT 10	10		
PJTRBT 125	12,5		
PJTRBO 08	8		
PJTRBO 10	10		
PJTRBO 125	12,5		

BRUSHED POLISHED ALUMINIUM (silver - gold) thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm		
PJTRBS 08	8		
PJTRBS 10	10		
PJTRBS 125	12,5		
PJTRBOS 08	8		
PJTRBOS 10	10		
PJTRBOS 125	12,5		

ON DEMAND MAY BE REALISED IN OTHER FINISHES OF THE COLOUR CHART.

CONTACT OUR CUSTOMER SERVICE FOR MINIMAL QUANTITY, TIMING AND PRICE.

COLOURS

ANODIZED			POLISHED			BRUSHED POLISHED	
AA - Anodized silver alum.	AT - Anodized titanium alum.	AO - Anodized gold alum.	BC - Polished chrome alum.	BT - Polished titanium alum.	BO - Polished gold alum.	BS - Brushed pol. silver alum.	BOS - Brushed pol. gold alum.

CAPSULES, END CAPS, THREE-WAYS JOINTS and JOINTS

* Capsules & end caps of the on demand profiles are also on demand

ANODIZED, POLISHED, BRUSHED POLISHED ALUMINIUM

CAPSULES, END CAPS, THREE-WAYS - ANODIZED ALUMINIUM

Article	H mm	Pack 10 Pcs	Pack 2 Pcs
CPJTRAA .../...	08/10/125		
IPJTRAA .../...	08/10/125		
TPJTRAA .../...	08/10/125		
CPJTRAT .../...	08/10/125		
IPJTRAT .../...	08/10/125		
TPJTRAT .../...	08/10/125		
CPJTRAO .../...	08/10/125		
IPJTRAO .../...	08/10/125		
TPJTRAO .../...	08/10/125		

Choose the desired pack. & height
Ex.: 4,5 mm capsule in 10 Pcs Pack - CPJTRAA 10/10

CAPSULES, END CAPS, THREE-WAYS - POLISHED ALUM.

Article	H mm	Pack 10 Pcs	Pack 2 Pcs
CPJTRBC .../...	08/10/125		
IPJTRBC .../...	08/10/125		
TPJTRBC .../...	08/10/125		
CPJTRBT .../...	08/10/125		
IPJTRBT .../...	08/10/125		
TPJTRBT .../...	08/10/125		
CPJTRBO .../...	08/10/125		
IPJTRBO .../...	08/10/125		
TPJTRBO .../...	08/10/125		

Choose the desired pack. & height
Ex.: 4,5 mm capsule in 10 Pcs Pack - CPJTRBC 10/10

CAPSULES, END CAPS, THREE-WAYS - BRUSHED POLISHED ALUM.

Article	H mm	Pack 10 Pcs	Pack 2 Pcs
CPJTRBS .../...	08/10/125		
IPJTRBS .../...	08/10/125		
TPJTRBS .../...	08/10/125		
CPJTRBOS .../...	08/10/125		
IPJTRBOS .../...	08/10/125		
TPJTRBOS .../...	08/10/125		

Choose the desired pack. & height
Ex.: 4,5 mm capsule in 10 Pcs Pack - CPJTRBS 10/10

JOINTS - PLASTIC

Article	H mm	Pack 10 Pcs	Pack 2 Pcs
GIJTRA .../...	08/10/125		

Choose the desired pack. & height
Ex.: 10 mm joint in 10 Pcs Pack - GIJTRA 10/10



* = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed

PROJOLLY ANGLE 135 is a polished and satin stainless steel profile that can be used as protection for the 135° corners of coverings. Its particular section, the availability in two different finishes make **PROJOLLY ANGLE 135** a much sought-after profile that allows an elegant workmanlike application.

PROJOLLY ANGLE 135

POLISHED AND BRUSHED STAINLESS STEEL AISI 304/1.4301-V2A



POLISHED STAINLESS STEEL AISI 304/1.4301-V2A with protective film
bar length 2,7 lm - pack. 20 Pcs - 54 lm - 10/10 mm

Article	H mm
PJTR135AC 08	8
PJTR135AC 10	10
PJTR135AC 11	11
PJTR135AC 125	12,5



BRUSHED STAINLESS STEEL AISI 304/1.4301-V2A with protective film
bar length 2,7 lm - pack. 20 Pcs - 54 lm - 10/10 mm


Article	H mm
PJTR135ACS 08	8
PJTR135ACS 10	10
PJTR135ACS 11	11
PJTR135ACS 125	12,5

COLOURS




AC - Polished stainless steel AISI 304/1.4301-V2A
ACS - Brushed stainless steel AISI 304/1.4301-V2A

SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS




1. Choose "PROJOLLY ANGLE 135" according to the tile thickness and desired finish.
2. Cut "PROJOLLY ANGLE 135" to the desired length and apply the adhesive on the support where the profile will be laid.
3. Press the anchoring flange of "PROJOLLY ANGLE 135" into the adhesive.
4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile.
5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.




PROINTER AC

POLISHED, SUPER POLISHED AND BRUSHED STAINLESS STEEL AISI 304/1.4301-V2A

PROINTER AC is a cove-shaped profile in polished, super polished and brushed stainless steel AISI 304 / 1.4301 - V2A. It is particularly suitable to ensure cleanliness and hygiene in every kind of environment where high resistance to mechanical and chemical stresses are required. Its particular section and the availability in three finishes and special pieces, such as internal and external corners, make **PROINTER AC** a much sought after profile. The profile is easy to match with the wall covering and allows a workmanlike application even in environments subject to high mechanical stresses.



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROINTER AC" according to the tile thickness and desired finish.
2. Cut "PROINTER AC" to the desired length and apply the adhesive on the support where the profile will be laid.
3. Press the anchoring flange of "PROINTER AC" into the adhesive.
4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile.
5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.



POLISHED STAINLESS STEEL AISI 304/1.4301 V2A with protective film
bar length 2,7 lm - pack. 20 Pcs - 54 lm - 10/10 mm

Article	H mm
PIAC 08	8
PIAC 10	10
PIAC 125	12,5
PIAC 15	15

SUPER POLISHED STAINLESS STEEL AISI 304/1.4301-V2A
thermo packed

bar length 2,7 lm - pack. 20 Pcs - 54 lm - 10/10 mm

Article	H mm
PIACML 08	8
PIACML 10	10
PIACML 125	12,5
PIACML 15	15

COLOURS



AC - Polished stainless steel AISI 304/1.4301-V2A ACML - Super polished stainless steel AISI 304/1.4301-V2A ACS - Brushed stainless steel AISI 304/1.4301-V2A

SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS.

Corners of the on demand profiles are also on demand *



BRUSHED STAINLESS STEEL AISI 304/1.4301 V2A with protective film
bar length 2,7 lm - pack. 20 Pcs - 54 lm - 10/10 mm

Article	H mm
PIACS 08	8
PIACS 10	10
PIACS 125	12,5
PIACS 15	15

INTERNAL, EXTERNAL, THREE-WAYS PROINTER CORNER JOINTS

POLISHED STAINLESS STEEL AISI 316/1.4404-V4A - pack. 2 Pcs

Article	Pack. 2 Pcs
REPIACM/2	
RIPIACM/2	
RITPIACM/2	

INTERNAL, EXTERNAL, THREE-WAYS PROINTER CORNER JOINTS


BRUSHED STAINLESS STEEL AISI 316/1.4404-V4A - pack. 2 Pcs

Article	Pack. 2 Pcs
REPIACMS/2	
RIPIACMS/2	
RITPIACMS/2	


PROINTER KL ACC

STAINLESS STEEL AISI 304/1.4301-V2A

PROINTER KL ACC is a cove-shaped profile in stainless steel AISI 304/1.4301-V2A. The profile allows to connect the floor and wall coverings in ceramic and mosaic also with low thickness. It is particularly suitable to ensure cleanliness and hygiene in every kind of environment where good resistance to mechanical and chemical stresses are required. Its particular section makes **PROSHELL KL ALL** a much sought after profile.



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROINTER KL ACC" according to the desired finish.
2. Cut "PROINTER KL ACC" to the desired length.
3. Apply the silicone along the floor-wall connection.
4. Press the arrowhead of "PROINTER KL ACC" into the silicone evenly until it is completely adherent to the floor and wall.

SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS



POLISHED STAINLESS ST. AISI 304/1.4301-V2A with protective film
bar length 2,7 lm - pack. 40 Pcs - 108 lm - 10/10mm

Article	H mm
PIKLAC 15	15


BRUSHED STAINLESS ST. AISI 304/1.4301-V2A with protective film
bar length 2,7 lm - pack. 40 Pcs - 108 lm - 8/10mm

Article	H mm
PIKLACS 15	15

COLOURS



AC - Polished stainless steel AISI 304/1.4301-V2A ACS - Brushed stainless steel AISI 304/1.4301-V2A



SANDED STAINLESS ST. AISI 304/1.4301-V2A with protective film
bar length 2,7 lm - pack. 40 Pcs - 108 lm - 10/10mm

Article	H mm
PIKLACSB 15	40,50

SUPER POLISHED ST. AISI 304/1.4301-V2A with protective film
bar length 2,7 lm - pack. 40 Pcs - 108 lm - 10/10mm

Article	H mm
PIKLACML 15	15

AVAILABLE MINIMUM QUANTITY 100 PCS



ACSB - Sanded stainless steel AISI 304/1.4301-V2A ACML - Super polished stainless steel AISI 304/1.4301-V2A ACSB - SPECIAL FINISH, REQUEST AVAILABILITY

* = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed

PRINTER AC 316 is a cove-shaped profile in polished, super polished and brushed stainless steel AISI 316 / 1.404 - V4A. It is particularly suitable to ensure cleanliness and hygiene in every kind of environment where high resistance to mechanical and chemical stresses are required. Its particular section and the availability in three finishes and special pieces, such as internal and external corners, make **PRINTER AC 316** a much sought after profile. The profile is easy to match with the wall covering and allows a workmanlike application even in environments subject to high mechanical stresses.

PRINTER AC

POLISHED AND BRUSHED STAINLESS STEEL
AISI 316/1.4401-V4A



POLISHED STAINLESS STEEL AISI 316/1.4404-V4A
bar length 2,7 lm - pack. 20 Pcs - 54 lm - 10/10 mm



Article	H mm		
PIACM 08	8		
PIACM 10	10		
PIACM 125	12,5		
PIACM 15	15		



BRUSHED STAINLESS STEEL AISI 316/1.4404-V4A
bar length 2,7 lm - pack. 20 Pcs - 54 lm - 10/10 mm



Article	H mm		
PIACMS 08	8		
PIACMS 10	10		
PIACMS 125	12,5		
PIACMS 15	15		

COLOURS




ACM - Polished stainless steel
AISI 316/1.4404-V4A


ACMS - Brushed stainless steel
AISI 316/1.4404-V4A

SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS.

Corners of the on demand profiles are also on demand *



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PRINTERAC316" according to the tile thickness and desired finish.
2. Cut "PRINTER AC 316" to the desired length and apply the adhesive on the support where the profile will be laid.
3. Press the anchoring flange of "PRINTER AC 316" into the adhesive.
4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile.
5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.

PRINTER KL ACC 316 is a cove-shaped profile in stainless steel AISI 316/1.4404-V4A. The profile allows to connect the floor and wall coverings in ceramic and mosaic also with low thickness. It is particularly suitable to ensure cleanliness and hygiene in every kind of environment where good resistance to mechanical and chemical stresses are required. Its particular section makes **PROSHELL KL ALL 316** a much sought after profile.

PRINTER KL ACC

STAINLESS STEEL AISI 316/1.4401-V4A



POLISHED STAINLESS STEEL AISI 316/1.4404-V4A
bar length 2,7 lm - pack. 20 Pcs - 54 lm - 10/10 mm



Article	H mm		
PIKLACM 15	15		



BRUSHED STAINLESS STEEL AISI 316/1.4404-V4A
bar length 2,7 lm - pack. 20 Pcs - 54 lm - 10/10 mm




Article	H mm		
PIKLACMS 15	15		

COLOURS




ACM - Polished stainless steel
AISI 316/1.4404-V4A

ACMS - Brushed stainless steel
AISI 316/1.4404-V4A



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PRINTER KL ACC 316" according to the desired finish.
2. Cut "PRINTER KL ACC 316" to the desired length.
3. Apply the silicone along the floor-wall connection.
4. Press the arrowhead of "PRINTER KL ACC 316" into the silicone evenly until it is completely adherent to the floor and wall.

SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS


News 2023

* = Production on demand with minimum quantity of 200 pcs. Production delay 4/5 weeks. Price to be agreed


PROINTER AL

ANODIZED AND POLISHED ALUMINIUM

PROINTER AL is a cove-shaped profile in anodized and polished aluminium. It is particularly suitable to ensure cleanliness and hygiene is suitable in indoors environment where good resistance to mechanical and chemical stresses are required. Its particular section and the availability in four finishes and special pieces, such as internal and external corners, make **PROINTER AL** a much sought after profile. The profile is easy to match with the wall covering and allows a workmanlike application.



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROINTER AL" according to the tile thickness and desired finish.
2. Cut "PROINTER AL" to the desired length and apply the adhesive on the support where the profile will be laid.
3. Press the anchoring flange of "PROINTER AL" into the adhesive.
4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile.
5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.



ANODIZED GOLD OR SILVER ALUMINIUM thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm		
PIAA 08	8		
PIAA 10	10		
PIAO 08	8		
PIAO 10	10		

INTERNAL, EXTERNAL, THREE-WAYS PROINTER CORNER JOINTS

ANODIZED GOLD (AO) or SILVER ALUMINIUM (AA) - pack. 2 Pcs

Article	Pack. 2 Pcs
REPI.../2	
RIP.../2	
RITPI.../2	

Corners of the on demand profiles are also on demand *

COLOURS

ANODIZED	
AA - Anodized silver alum.	AO - Anodized gold alum.
POLISHED	
BC - Polished chrome alum.	BO - Polished gold alum.



POLISHED GOLD OR CHROMED ALUMINIUM thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm		
PIBC 08	8		
PIBC 10	10		
PIBO 08	8		
PIBO 10	10		

INTERNAL, EXTERNAL, THREE-WAYS PROINTER CORNER JOINTS

POLISHED GOLD (BO) or CHROMED ALUMINIUM (BC) - pack. 2 Pcs

Article	Pack. 2 Pcs
REPI.../2	
RIP.../2	
RITPI.../2	

RITPI...

EXTERNAL CORNER



PROTERMINAL, PROJOLLY SQUARE, PROJOLLY QUART (NO PROINTER)

RIP...


INTERNAL CORNER




PROINTER KL ALL

POLISHED AND CHROMED BRASS AND ANODIZED AND POLISHED ALUMINIUM

PROSHELL KL ALL is a cove-shaped profile in polished and chromed brass and anodized and polished aluminium. The profile allows to connect the floor and wall coverings in ceramic and mosaic also with low thickness. It is particularly suitable to ensure cleanliness and hygiene in every kind of environment where good resistance to mechanical and chemical stresses are required. Its particular section and availability in five different finishes, make **PROSHELL KL ALL** a much sought after profile.



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROINTER KL ALL" according to the desired finish.
2. Cut "PROINTER KL ALL" to the desired length.
3. Apply the silicone along the floor-wall connection.
4. Press the arrowhead of "PROINTER KL ALL" into the silicone evenly until it is completely adherent to the floor and wall.



POLISHED / CHROMED BRASS thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm		
PIKLOL 045	4,5		
PIKLOC 045	4,5		

CAPS - VARNISHED PLASTIC

Article	Pack. 2 Pcs	Pack. 10 Pcs
TPIKL .../...		

COLOURS

OL - Polished brass	OC - Chromed brass
---------------------	--------------------



POLISHED CHROME ALUMINIUM / GOLD thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm		
PIKLBC 045	4,5		
PIKLBO 045	4,5		

ANODIZED SILVER ALUMINIUM thermo packed

bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm		
PIKLAA 045	4,5		

CAPS - VARNISHED PLASTIC

Article	Pack. 2 Pcs	Pack. 10 Pcs
TPTPIKL .../...		

COLOURS

AA - Anodized silver alum.	BC - Polished chrome alum.	BO - Polished gold alum.
----------------------------	----------------------------	--------------------------

Corners of the on demand profiles are also on demand *

* = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed


PROINTER is a cove-shaped profile in shockproof non-toxic colored vinyl resin. It is particularly suitable to ensure cleanliness and hygiene in public and industrial environments. Its particular section and the availability in twelve colours and special pieces, such as internal and external corners, make **PROINTER** a much sought after profile. It can be easily matched with the wall covering and allows an elegant workmanlike application.

PROINTER

SHOCKPROOF NON - TOXIC COLORED VINYL RESIN



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS




1. Choose "PROINTER" according to the tile thickness and desired colour. 2. Cut "PROINTER" to the desired length and apply the adhesive on the support where the profile will be laid. 3. Press the anchoring flange of "PROINTER" into the adhesive. 4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. 5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation.

NON-TOXIC SHOCKPROOF VINYL RESIN
bar length 2,7 lm - pack. 20 Pcs - 54 lm (white 108 lm)

Article	H mm		
PI 06-01	6		
PI 07-01	7		
PI 08-...	8		
PI 09-01	9		
PI 10-...	10		

H 6 mm available in white. Other colours on demand.
Available on demand in the colours 01-02-03-05-06-10-11-12-15-17-18-0106 (04-07-08-09-13-14-19-20-21-22-23-24-25-26-27-28-29 with a minimum quantity order of 800 pcs.
The code of the selected colour must be added to the article code.
E.g.: PI 06-... (chosen colour white) PI 06-01.

WHITE NOT FOR SALE SINGLY



PI 07-... E PI 09-...
PRODUCTION ON DEMAND
MINIMUM QUANTITY 800 PCS BY COLOUR AND HEIGHT
(PRODUCTION DELAY 4/5 WEEKS)

COLOURS

01 - White	0106 - White ivory	02 - Light grey	03 - Cement gray
05 - Dark beige	06 - Ivory	10 - Red	11 - Black
12 - Silver	15 - Brown	17 - Bahama beige	18 - Grey

AVAILABLE MINIMUM QUANTITY 800 PCS by colour and height (Price to be agreed. Production delay 4/5 weeks)

04 - Light beige	07 - Pink	19 - Beige	20 - Dark ivory	21 - Light pink
08 - Sky blue	09 - Yellow	22 - Dark pink	23 - Dark antique pink	24 - Dark sky blue
13 - Gold	14 - Green	25 - Brick red	26 - Turquoise green	27 - Dark green
16 - Blue	28 - Hazel brown	29 - Dak brown		

COLOURS

INTERNAL, EXTERNAL, THREE-WAYS PROINTER CORNER JOINTS
VARNISHED PLASTIC (Vinyl Resin) - pack. 10 Pcs

Article	
REPI .../...	
RIPi .../...	
RITPI .../...	

COLOURS

01 - White	0106 - White ivory	02 - Light grey	03 - Cement gray	05 - Dark beige	06 - Ivory
10 - Red	11 - Black	12 - Silver	15 - Brown	17 - Bahama beige	18 - Grey

Available in the colours: 01-02-03-05-06-10-11-12-15-17-18-0106.
Available on demand 04-07-08-09-13-14-19-20-21-22-23-24-25-26-27-28-29.
The code of the selected colour must be added to the article code.
E.g.: RPI... (Chosen colour Ivory 06) RPI 06.
PLEASE CHOOSE THE DESIRED COLOUR CODE FROM OUR COLOUR CHART. SPECIFICATION OF THE HEIGHT IS NOT REQUIRED.



REPI...

RITPI...


Corners of the on demand profiles are also on demand *

PROLISTEL CHANNEL


STAINLESS STEEL AISI 304/1.4301-V2A

PROLISTEL CHANNEL is a F-shaped strip in polished an satin-finish stainless steel AISI 304/1.4301-V2A suitable to decorate the wall coverings in ceramic tiles and natural stones. Its section allows the realization of a decorative joint which can also be used as a guide for the fixing of sheets of glass on floors and walls. Its particular section and the availability in two different finishes make **PROLISTEL CHANNEL** a much sought-after profile that allows an easy workmanlike application.

PLTCH... 08 - 10 - 11 - 12,5




EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROLISTEL CHANNEL" according to the visible surface and desired finish.
2. Cut "PROLISTEL CHANNEL" to the desired length and apply the adhesive on the surface where the profile will be laid.
3. Press "PROLISTEL CHANNEL" into the adhesive, aligning it with the tiles leaving a 2 mm. joint. Remove immediately all remains of adhesive from the surface of the profile.
4. Fill the joint between the profile and tiles with grout in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.

COLOURS



POLISHED STAINLESS STEEL AISI 304/1.4301-V2A
bar length 2,7 lm - pack. 1 Pc

Article	H mm	L mm
PLTCHAC 0812	8	12
PLTCHAC 1012	10	12
PLTCHAC 1112	11	12
PLTCHAC 12512	12,5	12



SATIN-FINISH STAINLESS STEEL AISI 304/1.4301-V2A
bar length 2,7 lm - pack. 1 Pc

Article	H mm	L mm
PLTCHACS 0812	8	12
PLTCHACS 1012	10	12
PLTCHACS 1112	11	12
PLTCHACS 12512	12,5	12

POLISHED STAINLESS STEEL AISI 304/1.4301-V2A
bar length 2,7 lm - pack. 1 Pc

Article	H mm	L mm
PLTCHAC 0808	8	08
PLTCHAC 1008	10	08
PLTCHAC 1108	11	08
PLTCHAC 12508	12,5	08

SATIN-FINISH STAINLESS STEEL AISI 304/1.4301-V2A
bar length 2,7 lm - pack. 1 Pc

Article	H mm	L mm
PLTCHACS 0808	8	08
PLTCHACS 1008	10	08
PLTCHACS 1108	11	08
PLTCHACS 12508	12,5	08

POLISHED STAINLESS STEEL AISI 304/1.4301-V2A
bar length 2,7 lm - pack. 1 Pc

Article	H mm	L mm
PLTCHAC 0810	8	10
PLTCHAC 1010	10	10
PLTCHAC 1110	11	10
PLTCHAC 12510	12,5	10

SATIN-FINISH STAINLESS STEEL AISI 304/1.4301-V2A
bar length 2,7 lm - pack. 1 Pc


Article	H mm	L mm
PLTCHACS 0810	8	10
PLTCHACS 1010	10	10
PLTCHACS 1110	11	10
PLTCHACS 12510	12,5	10

PROLISTEL CHANNEL


ANODIZED AND POLISHED ALUMINIUM

PROLISTEL CHANNEL is a F-shaped strip in anodized and polished aluminum suitable to decorate the wall coverings in ceramic tiles and natural stones. Its section allows the realization of a decorative joint which can also be used as a guide for the fixing of sheets of glass on floors and walls. Its particular section and the availability in two different finishes make **PROLISTEL CHANNEL** a much sought-after profile that allows an easy workmanlike application.

PLTCH... 08 - 10 - 11 - 12,5



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Scegliere "PROLISTEL CHANNEL" in funzione della superficie a vista e della finitura desiderata.
2. Tagliare "PROLISTEL CHANNEL" della lunghezza desiderata ed applicare l'adesivo sul supporto dove sarà applicato il listello.
3. Premere "PROLISTEL CHANNEL" nell'adesivo avendo cura di allinearne i bordi con la superficie del rivestimento e di lasciare una fuga di circa 2 mm. Rimuovere immediatamente residui di adesivo dalla superficie del profilo.
4. Stuccare accuratamente le fughe tra profilo e piastrella onde evitare il ristagno di eventuale acqua. Rimuovere immediatamente residui di stucco dalla superficie del profilo.



ANODIZED SILVER ALUMINIUM
bar length 2,7 lm - pack. 40 Pcs - 108 lm


Article	H mm
PLTCHAA 08	8
PLTCHAA 10	10
PLTCHAA 11	11
PLTCHAA 125	12,5



POLISHED CHROME ALUMINIUM
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm
PLTCHBC 08	8
PLTCHBC 10	10
PLTCHBC 11	11
PLTCHBC 125	12,5

COLOURS




= News 2023

= Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed

PROTERMINAL INT is a profile in anodized and polished aluminium that can be applied on external corners of coverings. It can be used to close the perimeter of coverings and like a connection profile between step tread and riser of stairs coated with ceramic or natural stone tiles. Its particular section and the availability in four different finishes make **PROTERMINAL INT** a much sought-after profile that allows an elegant workmanlike application.

PROTERMINAL INT

ANODIZED AND POLISHED ALUMINIUM



ANODIZED ALUMINIUM (silver - titanium) thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm
PTIAA 08	8
PTIAA 10	10
PTIAA 125	12,5
PTIAT 08	8
PTIAT 10	10
PTIAT 125	12,5

POLISHED ALUMINIUM (chrome - titanium) thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm
PTIBC 08	8
PTIBC 10	10
PTIBC 125	12,5
PTIBT 08	8
PTIBT 10	10
PTIBT 125	12,5

INTERNAL, EXTERNAL, THREE-WAYS JOINTS
ANODIZED POLISHED ALUMINIUM - pack. 3 Pcs

Article
RIPTI ... 08 - 10 - 125/3
REPTI ... 08 - 10 - 125/3
RTPIT ... 08 - 10 - 125/3

INTERNAL CORNER
RIPTI ... 08 - 10 - 125




EXTERNAL CORNER
REPTI ... 08 - 10 - 125



3 WAYS JOINT
RTPIT ... 08 - 10 - 125



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROTERMINAL INT" according to the tile thickness and desired finish.
2. Cut "PROTERMINAL INT" to the desired length and apply the adhesive on the support where the profile will be laid.
3. Press the anchoring flange of "PROTERMINAL INT" into the adhesive.
4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile.
5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.

COLOURS

ANODIZED		POLISHED	
AA - Anodized silver alum.	AT - Anodized titanium alum.	BC - Polished chrome alum.	BT - Polished titanium alum.


On demand may be realised in other finishes of the colour chart. Contact our customer service for minimal quantity, timing and price.



PROTERMINAL

POLISHED AND BRUSHED
STAINLESS STEEL AISI 304/1.4301-V2A

PROTERMINAL is a L-shaped profile in polished and brushed stainless steel AISI 304/1.4301-V2A that can be applied on external corners of coverings. It can be used to close the perimeter of coverings, like a connection profile between step tread and riser of stairs coated with ceramic and natural stone tiles, and also as separation profile for floor coverings. Its particular section and the availability in two different finishes make **PROTERMINAL** a much sought-after profile that allows a workmanlike application even in environments subject to high mechanical stresses.




POLISHED STAINLESS ST. AISI 304/1.4301-V2A with protective film
bar length 2,7 lm - pack. 40 Pcs - 108 lm - 10/10 mm

Article	H mm
PTAC 03	3
PTAC 045	4,5
PTAC 06	6
PTAC 08	8
PTAC 10	10
PTAC 11	11
PTAC 125	12,5



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROTERMINAL" according to the tile thickness and desired finish. 2. Cut "PROTERMINAL" to the desired length and apply the adhesive on the support where the profile will be laid. 3. Press the anchoring flange of "PROTERMINAL" into the adhesive. 4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile. 5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.

BRUSHED STAINLESS STEEL AISI 304/1.4301-V2A with protective film
bar length 2,7 lm - pack. 40 Pcs - 108 lm - 10/10 mm

Article	H mm
PTACS 03	3
PTACS 045	4,5
PTACS 06	6
PTACS 08	8
PTACS 10	10
PTACS 11	11
PTACS 125	12,5



Curve version available

COLOURS




SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS.

PROTERMINAL

POLISHED STAINLESS STEEL
AISI 316L/1.4404-V4A

PROTERMINAL is a L-shaped profile in polished stainless steel AISI 304/1.4301-V2A that can be applied on external corners of coverings. It can be used to close the perimeter of coverings, like a connection profile between step tread and riser of stairs coated with ceramic and natural stone tiles and also as separation profile for floor and wall coverings. Its particular section and the availability in two different finishes make **PROTERMINAL** a much sought-after profile that allows a workmanlike application even in environments subject to high mechanical and chemical stresses.




POLISHED STAINLESS ST. AISI 316/1.4404-V4A
with protective film
bar length 2,7 lm - pack. 40 Pcs - 108 lm - 10/10 mm



Article	H mm
PTACM 06	6
PTACM 08	8
PTACM 10	10
PTACM 125	12,5

COLOURS



ACM - Polished stainless steel
AISI 316L

1. Choose "PROTERMINAL" according to the tile thickness. 2. Cut "PROTERMINAL" to the desired length and apply the adhesive on the support where the profile will be laid. 3. Press the anchoring flange of "PROTERMINAL" into the adhesive. 4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile. 5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.

SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS.

* = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed

PROTERMINAL is a L-shaped profile in chromed and antique brass that can be applied on external corners of coverings. It can be used to close the perimeter of coverings, like a connection profile between step tread and riser of stairs coated with ceramic or natural stone tiles and also as separation profile for floor and wall coverings. Its particular section and elegance make PROJOLLY a much sought-after profile that allows a workmanlike application.

PROTERMINAL

CHROMED BRASS, BRUSHED BRASS AND ANTIQUE BRASS



CHROMED BRASS thermo packed
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H mm
PTOC 06	6
PTOC 08	8
PTOC 10	10
PTOC 125	12,5

COLOURS



BRUSHED BRASS thermo packed
bar length 2,7 lm - pack. 20 Pcs - 54 lm


Article	H mm
PTOS 06	6
PTOS 08	8
PTOS 10	10
PTOS 125	12,5

ANTIQUÉ BRASS thermo packed
bar length 2,7 lm - pack. 20 Pcs - 54 lm


Article	H mm
PTOB 06	6
PTOB 08	8
PTOB 10	10
PTOB 125	12,5

INSTRUCTIONS FOR LAYING METHODS

1. Choose "PROTERMINAL" according to the tile thickness. 2. Cut "PROTERMINAL" to the desired length and apply the adhesive on the support where the profile will be laid. 3. Press the anchoring flange of "PROTERMINAL" into the adhesive. 4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile. 5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.



EXAMPLES OF LAYING



PROTERMINAL is a L-shaped profile in natural and anodized aluminium that can be applied on external corners of coverings. It can be used to close the perimeter of coverings, like a connection profile between step tread and riser of stairs coated with ceramic or natural stone tiles and also as separation profile for floor and wall coverings. Its particular section and the availability in six different finishes make **PROTERMINAL** a much sought-after profile that allows a workmanlike application.

PROTERMINAL

NATURAL AND ANODIZED ALUMINIUM



ANODIZED ALUMINIUM (gold - silver) thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm
PTAA 03	3
PTAA 045	4,5
PTAA 06	6
PTAA 08	8
PTAA 10	10
PTAA 11	11
PTAA 125	12,5
PTAA 15	15
PTAA 20	20
PTAO 03	3
PTAO 045	4,5
PTAO 06	6
PTAO 08	8
PTAO 10	10
PTAO 11	11
PTAO 125	12,5

COLOURS



ANODIZED ALUMINIUM (black-titanium-copper-bronze- antique bronze) thermo packed - bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm
PTNE 08	8
PTNE 10	10
PTNE 125	12,5
PTAT 08	8
PTAT 10	10
PTAT 11	11
PTAT 125	12,5
PTAR 08	8
PTAR 10	10
PTAR 125	12,5
PTAB 08	8
PTAB 10	10
PTAB 125	12,5
PTBRA 10	10
PTBRA 125	12,5

NATURAL ALUMINIUM


bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm
PTAN 03	3
PTAN 045	4,5


COLOURS



On demand may be realised in other finishes of the colour chart. Contact our customer service for minimal quantity, timing and price.



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS




1. Choose "PROTERMINAL" according to the tile thickness and desired finish. 2. Cut "PROTERMINAL" to the desired length and apply the adhesive on the support where the profile will be laid. 3. Press the anchoring flange of "PROTERMINAL" into the adhesive. 4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile. 5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.

PROTERMINAL

POLISHED, BRUSHED AND VARNISHED ALUMINIUM

PROTERMINAL is a L-shaped profile in polished, brushed and varnished aluminium that can be applied on external corners of coverings. It can be used to close the perimeter of coverings, like a connection profile between step tread and riser of stairs coated with ceramic or natural stone tiles and also as separation profile for floor and wall coverings (the varnished only for wall application). Its particular section and the availability in different finishes make **PROTERMINAL** a much sought-after profile that allows a workmanlike application.



POLISHED ALUMINIUM (chrome, gold, copper, titanium, black)
thermo packed - bar length 2,7 lm - pack. 40 Pcs - 108 lm


Article	H mm		
PTBC 03	3		
PTBC 045	4,5		
PTBC 06	6		
PTBC 08	8		
PTBC 10	10		
PTBC 11	11		
PTBC 125	12,5		
PTBO 03	3		
PTBO 045	4,5		
PTBO 06	6		
PTBO 08	8		
PTBO 10	10		
PTBO 11	11		
PTBO 125	12,5		
PTBT 08	8		
PTBT 10	10		
PTBT 11	11		*
PTBT 125	12,5		
PTBR 08	8		*
PTBR 10	10		
PTBR 125	12,5		*
PTBN 06	6		
PTBN 08	8		*
PTBN 10	10		
PTBN 125	12,5		



BRUSHED ALUMINIUM (silver, titanium, black, copper, antique bronze)
thermo packed - bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm		
PTBS 045	4,5		*
PTBS 08	8		
PTBS 10	10		
PTBS 11	11		
PTBS 125	12,5		
PTRS 045	4,5		*
PTRS 08	8		
PTRS 10	10		
PTRS 125	12,5		
PTTS 045	4,5		*
PTTS 08	8		
PTTS 10	10		
PTTS 11	11		
PTTS 125	12,5		
PTBOS 08	8		
PTBOS 10	10		
PTBOS 125	12,5		
PTNS 08	8		
PTNS 10	10		
PTNS 125	12,5		
PTBRAS 10	10		
PTBRAS 125	12,5		

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROTERMINAL" according to the tile thickness and desired finish (color).
2. Cut "PROTERMINAL" to the desired length and apply the adhesive on the support where the profile will be laid.
3. Press the anchoring flange of "PROTERMINAL" into the adhesive.
4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile.
5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.

COATED ALUMINIUM thermo packed

bar length 2,7 lm - pack. 20 Pcs - 54 lm (colour white 40 Pcs - 108 lm)

Article	H mm		
PTA 06-01	6		
PTA 08-01	8		
PTA 10-...	10		
PTA 11-01	11		
PTA 125-01	12,5		


H 10 available in the colours: 01 - 0106 - 11.

The code of the selected colour must be added to the article code.

E.g.: PTA 10-... (chosen colour white ivory varnished alum.)


PTA 10-0106.

COLOURS



PTA 06-... & PTA 125-... For other colours different from white, please contact our company for quantity and price. Production on demand, production delay 4/5 weeks. (minimum quantity order of 100 pcs).

AVAILABLE MINIMUM QUANTITY 100 PCS by colour and height (Price to be agreed. Production delay 4/5 weeks)



* = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed

PROTERMINAL is a L-shaper profile in powder coated aluminum that can be applied on external corners of coverings. It can be used to close the perimeter of coverings. Its particular section and the availability in different finishes make **PROTERMINAL** an elegant and much-sought after profile.

PROTERMINAL

STONE LINE ALUMINIUM AND TUSCANY LINE



STONE LINE thermo packed
bar length 2,7 lm - pack. 20 Pcs - 54 lm


Article	H mm		
PTA 06-SL...	6		
PTA 08-SL...	8		
PTA 10-SL...	10		
PTA 11-SL...	11		
PTA 125-SL...	12,5		

The code of the selected colour must be added to the article code.
E.g.: PTA 08... (chosen colour Stone white) PTA 08-SL01.

TUSCANY LINE thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm		
PTA 08-...	8		
PTA 10-...	10		
PTA 125-...	12,5		

The code of the selected colour must be added to the article code.
E.g.: PTA 08-... (chosen colour tuscanly grey) PTA 08-03TU.



COLOURS


STONE LINE

SL01 - Stone white	SL02 - Stone cream	SL03 - Stone greivory	SL04 - Stone sand	SL05 - Stone gray	SL06 - Stone cristal gray	SL07 - Stone antragray
SL08 - Stone antradark	SL09 - Stone bronze	SL10 - Stone corten	SL11 - Stone brown	SL12 - Stone black	SL13 - Stone oyster grey	

TUSCANY

03TU - Tuscanly grey	05TU - Tuscanly beige	20TU - Tuscanly bronze

EXAMPLES FOR LAYING METHODS



PROTERMINAL is a L-shaped profile in shockproof non - toxic colored vinyl resin that can be applied on external corners of coverings. It can be used to close the perimeter of coverings. Its particular section and the availability in different colours also on demand make **PROTERMINAL** a much sought-after profile. It can be easily matched with the wall covering and allows an elegant workmanlike application.

PROTERMINAL

SHOCKPROOF NON - TOXIC COLOURED VINYL RESIN

NON-TOXIC SHOCKPROOF COLOURED VINYL RESIN
bar length 2,7 lm - pack. 54 lm (white 108 lm)

Article	H mm		
PT 06-...	6		
PT 08-...	8		
PT 10-...	10		
PT 125-...	12,5		


Available in the colours: 01-0106-02-03-04-05-06-11-12-17-18
Available on demand 19-20-21-22-23-24-25-26-27-28-29-07-08-09-10-13-14-15-16 with a minimum quantity order of 800 pcs. The code of the selected colour must be added to the article code.
E.g.: PT 06-... (chosen colour white) PT 06-01.

WHITE NOT FOR SALE SINGLY



EXAMPLE AND INSTRUCTIONS FOR LAYING METHODS

1. Choose "PROTERMINAL" according to the tile thickness and desired colour. 2. Cut "PROTERMINAL" to the desired length and apply the adhesive on the support where the profile will be laid. 3. Press the anchoring flange of "PROTERMINAL" into the adhesive. 4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. 5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation.



COLOURS

01 - White	0106 - White ivory	02 - Light grey	03 - Cement gray
04 - Light Beige	05 - Dark Beige	06 - Ivory	11 - Black
12 - Silver	17 - Bahama Beige	18 - Grey	


AVAILABLE MINIMUM QUANTITY 800 PCS by colour and height (Price to be agreed. Production delay 4/5 weeks)

19 - Beige	20 - Dark ivory	21 - Light pink	22 - Dark pink	23 - Dark antique pink
24 - Dark sky blue	25 - Brick red	26 - Turquoise green	27 - Dark green	28 - Hazel brown
29 - Dak brown	07 - Pink	08 - Sky blue	09 - Yellow	10 - Red
13 - Gold	14 - Green	15 - Brown	16 - Blue	


PROLISTEL ACC

POLISHED, BRUSHED, SANDED
STAINLESS STEEL AISI 304/1.4301-V2A

PROLISTEL ACC is a listel in polished, brushed, sanded stainless steel AISI 304/1.4301-V2A with a flat and U-shaped (internal use) visible surface, suitable to decorate the wall coverings in ceramic, mosaic and natural stone. Its particular section and availability in different finishes, make **PROLISTEL ACC** a much sought after profile. It can be used with the range of PROJOLLY profiles to decorate the wall coverings and to allow an elegant workmanlike application.



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROLISTEL ACC" according to the width and desired finish. 2. Cut "PROLISTEL ACC" to the desired length and apply the adhesive on the support where the profile will be laid. 3. Press "PROLISTEL ACC" into the adhesive. 4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile. 5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.

POLISHED STAINLESS ST. AISI 304/1.4301-V2A with protective film
bar length 2,7 lm - pack. 40 Pcs - 108 lm - 8/10mm

Article	HxL mm		
PLTAC 10	10 x 10		
PLTAC 1045	10 x 4,5		
PLTAC 15	15 x 10		
PLTAC 20	20 x 10		
PLTAC 25	25 x 10		
PLTAC 2545	25 x 4,5		*

POLISHED STAINLESS STEEL AISI 304/1.4301-V2A - INTERNAL USE
with protective film - bar length 2,7 lm
pack. 40 Pcs 108 lm - 8/10mm

Article	HxL mm		
PLTACI 10	10 x 10		*
PLTACI 1045	10 x 4,5		*
PLTACI 15	15 x 10		*
PLTACI 20	20 x 10		*
PLTACI 25	25 x 10		*
PLTACI 2545	25 x 4,5		*

Brushed STAINLESS ST. AISI 304/1.4301-V2A with protective film
bar length 2,7 lm - pack. 40 Pcs - 108 lm - 8/10mm

Article	HxL mm		
PLTACS 10	10 x 10		
PLTACS 1045	10 x 4,5		
PLTACS 15	15 x 10		
PLTACS 20	20 x 10		
PLTACS 25	25 x 10		
PLTACS 2545	25 x 4,5		*

Brushed STAINLESS STEEL AISI 304/1.4301-V2A - INTERNAL USE
with protective film - bar length 2,7 lm pack. 40 Pcs 108 lm - 8/10mm

Article	HxL mm		
PLTACSI 10	10 x 10		*
PLTACSI 1045	10 x 4,5		*
PLTACSI 15	15 x 10		*
PLTACSI 20	20 x 10		*
PLTACSI 25	25 x 10		*
PLTACSI 2545	25 x 4,5		*

SANDED STAINLESS ST. AISI 304/1.4301-V2A with protective film
bar length 2,7 lm - pack. 40 Pcs 108 lm - 8/10mm

Article	HxL mm		
PLTACSB 10	10 x 10		*

ACSB - SPECIAL FINISH, REQUEST AVAILABILITY

SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS.



* = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed

PROLISTEL ACC is a range of decorative profiles/strips that are ideal for easily creating chromatic effects on ceramic tile/marble/mosaic coverings or, in the stainless steel AISI 316LL/1.4301-V4A range, for creating separations and decorations between floors in the same or differing material. Thanks to their design, shape and thickness of 4.5 and 10 mm, may be laid using the same adhesive to create horizontal and vertical lines, on the wall or on the floor, irrespective of the thickness of the covering. Various widths available in stainless steel AISI 04/1.4301-V2A, polished. Match with the same basic colours in the PROJOLLY, PROTERMINAL and PROJOLLY SQUARE and the new PROKERLAM SQUARE-LINE-JOLLY range.

PROLISTEL ACC

POLISHED STAINLESS STEEL
AISI 316L/1.4404 - V4A



POLISHED STAINLESS STEEL AISI 316LL/1.4404-V4A
with protective film - bar length 2,7 lm
pack. 40 Pcs - 108 lm - 8/10mm




POLISHED STAINLESS STEEL AISI 316LL/1.4404-V4A - INTERNAL USE with protective film - bar length 2,7 lm
pack. 40 Pcs - 108 lm - 8/10mm




Article	HxL mm		
PLTACM 10	10 X 10		*
PLTACM 1045	10 X 4,5		*
PLTACM 15	15 X 10		*
PLTACM 20	20 X 10		*
PLTACM 25	25 X 10		*
PLTACM 2545	25 X 4,5		*

Article	HxL mm		
PLTACMI 10	10 X 10		*
PLTACMI 1045	10 X 4,5		*
PLTACMI 15	15 X 10		*
PLTACMI 20	20 X 10		*
PLTACMI 25	25 X 10		*
PLTACMI 2545	25 X 4,5		*




EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the PROLISTEL ACC in the required width. 2. Apply the adhesive onto the area of application of the profile. 3. Lay and align the profile, cut to the necessary length, pressing it into the adhesive. 4. Lay the tiles, aligning them so that the top edge of the profile is flush with the tile. 5. Fill the profile/tile area of contact with adhesive to prevent the accumulation of water in any voids. Pay attention to the external edges of the PROLISTEL ACC. They must be protected against agents such as adhesives and sealants and against grinding or scraping actions.

SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS.


COLOURS



PROLISTEL P OTT is a decorative listel in polished, chromed and antique brass with a flat visible surface. The profile is suitable to decorate the wall coverings in ceramic, mosaic and natural stone. Its particular section and availability in different finishes and two widths, make **PROLISTEL P OTT** a much sought after profile. It could be matched with PROJOLLY, PROJOLLY SQUARE e PROTERMINAL profiles to decorate the wall coverings and to allow an elegant workmanlike application.

PROLISTEL P OTT

POLISHED, CHROMED,
ANTIQU BRASS



POLISHED, CHROMED AND ANTIQU BRASS thermo packed - Bar length 2,7 lm - pack 40 PCS - 108 lm

COLOURS



Article	H mm		
PLTPOL 25	25		*
PLTPOC 25	25		*
PLTPOB 25	25		*

EXAMPLES AND INSTRUCTIONS FOR LAYING




1. Choose "PROLISTEL P OTT" according to the width and desired finish. 2. Cut "PROLISTEL P OTT" to the desired length and apply the adhesive on the support where the profile will be laid. 3. Press "PROLISTEL P OTT" into the adhesive. 4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile. 5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.


PROLISTEL P ALL

ANODIZED, POLISHED, STONE LINE, BRUSHED, TUSCANY AND TILTEX ALUMINIUM

PROLISTEL P ALL is a decorative listel in anodized, polished, brushed, tiltex aluminium and varnished tuscany and stone aluminium with a flat visible surface. The profile is suitable to decorate the wall coverings in ceramic, mosaic and natural stone. Its particular section and availability in different finishes and two widths, make PROLISTEL P ALL a much sought after profile. It could be matched with PROJOLLY, PROJOLLY SQUARE e PROTERMINAL profiles to decorate the wall coverings and to allow an elegant workmanlike application.



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROLISTEL P ALL" according to the width and desired finish. 2. Cut "PROLISTEL P ALL" to the desired length and apply the adhesive on the support where the profile will be laid. 3. Press "PROLISTEL P ALL" into the adhesive. 4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile. 5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.

ANODIZED ALUMINIUM

thermo packed - bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm		
PLTPAA 10	10		
PLTPAO 10	10		*
PLTPAR 10	10		
PLTPAT 10	10		
PLTPNE 10	10		
PLTPAA 25	25		
PLTPAO 25	25		*
PLTPAR 25	25		*
PLTPAT 25	25		
PLTPNE 25	25		

POLISHED ALUMINIUM

thermo packed - bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm		
PLTPBC 10	10		
PLTPBO 10	10		
PLTPBR 10	10		
PLTPBT 10	10		
PLTPBN 10	10		
PLTPBC 25	25		
PLTPBO 25	25		
PLTPBR 25	25		*
PLTPBT 25	25		
PLTPBN 25	25		*

ALUMINIUM TUSCANY LINE

thermo packed - bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm		
PLTPA 10-...TU	10		*
PLTPA 25-...TU	25		*

STONE LINE ALUMINIUM

thermo packed - bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm		
PLTPA 10-SL01	10		
PLTPA 10-SL08	10		
PLTPA 10-SL12	10		
PLTPA 10-...	10		**
PLTPA 25-SL01	25		
PLTPA 25-SL08	25		
PLTPA 25-SL12	25		
PLTPA 25-...	25		**

POLISHED BRUSHED ALUMINIUM

thermo packed - bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm		
PLTPBS 10	10		
PLTPBOS 10	10		
PLTPRS 10	10		*
PLTPPTS 10	10		
PLTPNS 10	10		*
PLTPBS 25	25		
PLTPBOS 25	25		
PLTPRS 25	25		*
PLTPPTS 25	25		
PLTPNS 25	25		*

ANODIZED BRUSHED ALUMINIUM TILTEX

thermo packed - bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm		
PLTPBX 10	10		
PLTPRX 10	10		*
PLTPTX 10	10		
PLTPBX 25	25		
PLTPRX 25	25		*
PLTPTX 25	25		

COLOURS

ANODIZED				POLISHED				BLACK LINE			
AA - Anodized silver aluminium	AR - Anodized copper aluminium	AT - Anodized titanium aluminium	AO - Anodized gold aluminium	BC - Polished chrome aluminium	BO - Polished gold aluminium	BR - Polished bronze aluminium	BT - Polished titanium aluminium	BN - Polished black aluminium	NE - Anodized black aluminium	NS - Polished brushed black aluminium	
			ON DEMAND							ON DEMAND	
POLISHED BRUSHED				BRUSHED TILTEX			TUSCANY				
BS - Polished brushed aluminium	BOS - Polished brushed gold aluminium	TS - Polished brushed titanium aluminium	RS - Polished brushed copper aluminium	BX - Tiltex silver aluminium	TX - Tiltex titanium aluminium	RX - Tiltex copper aluminium	ON DEMAND	ON DEMAND	ON DEMAND	ON DEMAND	
			ON DEMAND								
							03TU - Tuscany grey	05TU - Tuscany Beige	20TU - Tuscany Bronze		
STONE LINE											
SL01 - Stone white	SL08 - Antradark	SL12 - Stone black									

AVAILABLE MINIMUM QUANTITY 100 PCS by colour and height (Price to be agreed. Production delay 4/5 weeks) **STONE LINE**

SL02 - Stone cream	SL03 - Stone greyvory	SL04 - Stone sand	SL05 - Stone gray	SL06 - Stone cristal gray	SL07 - Stone antragray	SL09 - Stone bronze	SL10 - Stone corten	SL11 - Stone brown	SL13 - Stone oyster gray
--------------------	-----------------------	-------------------	-------------------	---------------------------	------------------------	---------------------	---------------------	--------------------	--------------------------

* = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed

** = Production on demand with minimum quantity of 80 pcs. Production delay 4/5 weeks. Price to be agreed

PROLISTEL ALL is a listel in anodized, polished and brushed aluminium with a rounded visible surface, suitable to decorate the wall coverings in ceramic, mosaic and natural stone. Its particular section and availability in different finishes, make **PROLISTEL P ALL** a much sought after profile. It can be used with the range of PROJOLLY profiles to decorate the wall coverings and to allow an elegant workmanlike application.


PROLISTEL ALL

ANODIZED, POLISHED AND BRUSHED ALUMINIUM



ANODIZED ALUMINIUM (silver-gold-copper-titanium-black)
thermo packed - bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm		
PLTAA 15	15	5,73	15,47
PLTAR 15	15	7,01	18,93
PLTAT 15	15	7,01	18,93
PLTAO 15	15	5,73	15,47
PLTNE 15	15	7,10	19,17
PLTAA 25	25	7,15	19,31
PLTAR 25	25	9,12	24,62
PLTAT 25	25	9,12	24,62
PLTAO 25	25	7,15	19,31
PLTNE 25	25	9,25	24,98



POLISHED ALUMINIUM (chrome-gold-copper-titanium-black)
thermo packed - bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm		
PLTBC 15	15		
PLTBR 15	15		*
PLTBT 15	15		*
PLTBO 15	15		*
PLTBN 15	15		*
PLTBC 25	25		
PLTBR 25	25		*
PLTBT 25	25		*
PLTBO 25	25		*
PLTBN 25	25		*

BRUSHED POLISHED ALUMINIUM (silver-gold-copper-titanium-black)
thermo packed - bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm		
PLTBS 15	15		*
PLTRS 15	15		*
PLTTS 15	15		*
PLTBOS 15	15		*
PLTNS 15	15		*
PLTBS 25	25		*
PLTRS 25	25		*
PLTTS 25	25		*
PLTBOS 25	25		*
PLTNS 25	25		*

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROLISTEL ALL" according to the width and desired finish.
2. Cut "PROLISTEL ALL" to the desired length and apply the adhesive on the support where the profile will be laid.
3. Press "PROLISTEL ALL" into the adhesive.
4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile.
5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.

COLOURS

ANODIZED			POLISHED		BRUSHED POLISHED	
AA - Anodized silver alum.	AT - Anodized titanium alum.	NE - Anodized black alum.	BC - Polished chrome alum.	BT - Polished titanium alum.	BS - Brushed polished silver alum.	TS - Brushed Polished titanium alum.

AVAILABLE MINIMUM QUANTITY 100 PCS by colour and height (Price to be agreed. Production delay 4/5 weeks)


ANODIZED			POLISHED			BRUSHED POLISHED		
AO - Anodized Gold alum.	AR - Anodized copper alum.	BO - Polished Gold alum.	BR - Polished copper alum.	BN - Polished black alum.	BOS - Brushed Gold alum.	RS - Brushed Polished copper alum.	NS - Brushed Polished black alum.	

On demand may be realised in other finishes of the colour chart. Contact our customer service for minimal quantity, timing and price.

PROLISTEL LED is a listel in anodized and polished aluminium equipped with an integrated LED lighting system that can generate a cold, hot and neutral suffused light. It is suitable to decorate the wall coverings in ceramic, mosaic and natural stone. Its particular section and availability in different finishes, make **PROLISTEL LED** a much sought after profile that decorates the wall coverings.

PROLISTEL LED

ANODIZED AND POLISHED ALUMINIUM



ANODIZED ALUM. SILVER, POLISHED CHROME ALUMINIUM
thermo packed - bar length 2,7 lm - pack. 40 Pcs - 108 lm
ADAPTOR LED, LED & FLAT NOT INCLUDED

Article	H mm		
PLTLEDA 20	20		
PLTLEDBC 20	20		

ADHESIVE FLEXIBLE LED COIL
length 5 lm - pack. 1 ROLL

Article			
LEDN			
LEDF			
LEDC			

COLOURS

AA - Anodized silver alum.	BC - Polished chrome alum.
----------------------------	----------------------------

POLYCARBONATE FLAT bar length 2,7 lm - pack. 20 Pc - 54 lm
(AL = transparent / AO = matt)

Article			
PIAL 17			
PIAO 17			

END CAPS - R/L (3 right & 3 left)

Article	H mm		
TPLTLEDA 20	20		
TPLTLEDBC 20	20		


LED ADAPTOR AC/DC 75W - 12V (15 lm)

Article			
ALL 7512			

LED ADAPTOR AC/DC 25W - 12V (5 lm)

Article			
ALL 2512			

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS




1. Choose "PROLISTEL LED" according to the width and desired finish.
2. Cut "PROLISTEL LED" to the desired length and apply the adhesive on the support where the profile will be laid.
3. Press "PROLISTEL LED" into the adhesive.
4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile.
5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.

* = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed


PROFINLIST 20

ANODIZED, POLISHED, BRUSHED
AND TILTEX ALUMINIUM

PROFINLIST 20 is a listel in anodized, polished, brushed and tiltex aluminium with a flat visible surface, suitable to decorate the wall coverings in ceramic, mosaic and natural stone. Its particular section and availability in different finishes, make **PROFINLIST 20** a much sought after profile. It can be used with the range of PROJOLLY profiles to decorate the wall coverings and to allow an elegant workmanlike application.



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROFINLIST 20" according to the width and desired finish.
2. Cut "PROFINLIST 20" to the desired length and apply the adhesive on the support where the profile will be laid.
3. Press the anchoring flange of "PROFINLIST 20" into the adhesive.
4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile.
5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.



ANODIZED ALUMINIUM thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm		
PFLTAA 2045	4,5		*
PFLTAA 2008	8		
PFLTAR 2008	8		*
PFLTAT 2008	8		*
PFLTAA 2010	10		
PFLTAR 2010	10		*
PFLTAT 2010	10		*

POLISHED ALUMINIUM thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm		
PFLTBC 2045	4,5		*
PFLTBO 2045	4,5		
PFLTBC 2008	8		
PFLTBR 2008	8		*
PFLTBT 2008	8		*
PFLTBC 2010	10		
PFLTBO 2010	10		
PFLTBR 2010	10		*
PFLTBT 2010	10		*

BRUSHED POLISHED ALUMINIUM thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm		
PFLTBS 2045	4,5		*
PFLTBS 2008	8		
PFLTBS 2008	8		*
PFLTTS 2008	8		*
PFLTBS 2010	10		
PFLTBS 2010	10		*
PFLTTS 2010	10		*
PFLTBS 2010	10		*


BRUSHED TILTEX ALUMINIUM thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm		
PFLTBX 2008	8		*
PFLTRX 2008	8		*
PFLTXX 2008	8		
PFLTBX 2010	10		*
PFLTRX 2010	10		*
PFLTXX 2010	10		




COLOURS

ANODIZED



AA - Satin anodized silver alu.

POLISHED



BC - Polished chrome alu. BO - Polished gold alu.

BRUSHED POLISHED



BS - Brushed silver alu. BOS - Brushed gold alu.

ANOD. BRUSHED TILTEX



BX - Silver TILTEX

AVAILABLE MINIMUM QUANTITY 100 PCS

by colour and height (Price to be agreed. Production delay 4/5 weeks)

ANODIZED




AR - Anodized copper alu. AT - Anodized titanium alu.

POLISHED



BR - Polished copper alu. BT - Polished titanium alu.

SPAZZ. BRILLANT.



RS - All. spazz. brill. rame TS - All. spazz. brill. titanio

ANOD. SPAZZOLATI TILTEX



RX - Brushed tiltex copper alu. TX - Titanium tiltex

* = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed

PROBORD is a round corner bead profile in polished and brushed stainless steel AISI 304/1.4301-V2A suitable to protect the external corner of wall coverings in ceramic. Its particular section and availability in different finishes, make **PROBORD** a much sought after profile. It can be used with the range of PROLISTEL and PROSHELL profiles to obtain an elegant workmanlike application even in environments subject to high mechanical stresses.

PROBORD

POLISHED AND BRUSHED STAINLESS STEEL
AISI 304/1.4301-V2A



POLISHED STAINLESS ST. AISI 304/1.4301-V2A with protective film
bar length 2,7 lm - pack. 15 Pcs - 40,5 lm - 10/10mm

Article	H mm		
PEBDAC 08	08		
PEBDAC 10	10		
PEBDAC 125	12,5		

BRUSHED STAINLESS ST. AISI 304/1.4301-V2A with protective film
bar length 2,7 lm - pack. 15 Pcs - 40,5 lm - 10/10mm

Article	H mm		
PEBDACS 08	08		
PEBDACS 10	10		
PEBDACS 125	12,5		

COLOURS




AC - Polished stainless steel
AISI 304/1.4301-V2A

ACS - Brushed stainless steel AISI
304/1.4301-V2A


SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS.

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS




1. Choose "PROBORD" according to the tile thickness and desired finish.
2. Cut "PROBORD" to the desired length and apply the adhesive on the support where the profile will be laid.
3. Press the anchoring flange of "PROBORD" into the adhesive.
4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile.
5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.


PEBDAC/ACS 08



PEBDAC/ACS 10



PEBDAC/ACS 125



PROEDGE FLEX is a corner bead profile in shockproof non-toxic co-extruded colored vinyl resin composed by an internal rigid structure and by a soft external one. The profile is suitably shaped to protect the external corner of wall coverings. Its particular section and the availability in different colours make **PROEDGE FLEX** a much sought after and easy to lay profile that allows a workmanlike application.

PROEDGE FLEX

SHOCKPROOF NON - TOXIC CO-EXTRUDED
COLORED VINYL RESIN




CO-EXTRUDED PVC - L 40 X 40 mm
bar length 2,7 lm - pack. 15 Pcs - 40,5 lm

Article	H mm		
PFC...40	40		

CO-EXTRUDED PVC WITH ADHESIVE - L 40 X 40 mm
bar length 2,7 lm - pack. 15 Pcs - 40,5 lm

Article	H mm		
PFC...40A	40		

PFC... 40/40A



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROEDGE FLEX" according to the desired colour.
2. Cut "PROEDGE FLEX" to the desired length.
3. Remove carefully any remains of oil, fat and dirt from the surface where the profile will be laid.
4. When the surface is perfectly dry, remove the protective film (version with adhesive), place correctly the profile and press it without hitting / apply the silicone on the surface where the profile will be laid (version without adhesive) and press it without hitting.

COLOURS



01 - White

AVAILABLE MINIMUM QUANTITY 100 PCS by colour and height (Price to be agreed. Production delay 4/5 weeks)



09 - Yellow

10 - Red


11 - Black

16 - Blue

PROEDGE AC

POLISHED AND BRUSHED
STAINLESS STEEL AISI 304/1.4301-V2A

PROEDGE AC is a corner bead profile in polished and brushed stainless steel AISI 304/1.4301-V2A, with a radius of curvature of 1.5 mm, suitably shaped to protect the external corner of wall coverings. Its particular section, the availability in two finishes and different widths make **PROEDGE AC** a much sought-after profile that allows a workmanlike application even in environments subject to high mechanical stresses.



POLISHED AND BRUSHED STAINLESS STEEL
with protective film - bar length 2,7 lm - pack. 81 lm - 8/10 mm

Article	LxH mm		
PEGAC 10	10 x 10		
PEGACS 10	10 x 10		

POLISHED AND BRUSHED STAINLESS STEEL WITH ADHESIVE
with protective film - bar length 2,7 lm - pack. 81 lm - 8/10 mm

Article	LxH mm		
PEGAC 15A	15 x 15		
PEGACS 15A	15 x 15		
PEGAC 20A	20 x 20		
PEGACS 20A	20 x 20		

For items without adhesive, write the item without the last A.
E.g.: PEGAC 15

COLOURS



Suitable for use in contact with foodstuffs.



POLISHED AND BRUSHED STAINLESS STEEL WITH ADHESIVE
with protective film - bar length 2,7 lm - pack. 40,5 lm - 10/10 mm

Article	LxH mm		
PEGAC 25A	25 x 25		
PEGACS 25A	25 x 25		
PEGAC 30A	30 x 30		
PEGACS 30A	30 x 30		

For items without adhesive write the item without the last A.
E.g.: PEGAC 10

POLISHED AND BRUSHED STAINLESS STEEL WITH ADHESIVE
with protective film - bar length 2,7 lm - pack. 27 lm - 10/10 mm

Article	LxH mm		
PEGAC 40A	40 x 40		
PEGACS 40A	40 x 40		
PEGAC 50A	50 x 50		
PEGACS 50A	50 x 50		

For items without adhesive, write the item without the last A.
E.g.: PEGAC 40


PEG... 40A / 50A on demand with thickness 12/10.
Quantity, timing and prices to be agreed.

PROEDGE OT

POLISHED AND CHROMED BRASS

PROEDGE OT is a corner bead profile in polished and chromed brass, with a radius of curvature of 1.5 mm, suitably shaped to protect the external corner of wall coverings. Its particular section, the availability in two finishes and different widths make **PROEDGE OT** a much sought-after profile that allows an elegant workmanlike application.

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROEDGE OT" according to the desired finish and width.
2. Cut "PROEDGE OT" to the desired length.
3. Remove carefully any remains of oil, fat and dirt from the surface where the profile will be laid.
4. When the surface is perfectly dry, remove the protective film, place correctly the profile and press it without hitting / apply the silicone on the surface where the profile will be laid (version without adhesive) and press it without hitting.

COLOURS



POLISHED AND CHROMED BRASS
bar length 2,7 lm - pack. 54 lm - 8/10 mm

Article	LxH mm		
PEGOL 10	10 x 10		
PEGOC 10	10 x 10		

POLISHED AND CHROMED BRASS WITH ADHESIVE
bar length 2,7 lm - pack. 54 lm - 8/10 mm

Article	LxH mm		
PEGOL 15A	15 x 15		*
PEGOC 15A	15 x 15		
PEGOL 20A	20 x 20		*
PEGOC 20A	20 x 20		
PEGOC 25A	25 x 25		
PEGOC 30A	30 x 30		

For items without adhesive, write the item without the last A.
E.g.: PEGOL 15



POLISHED BRASS WITH ADHESIVE
bar length 2,7 lm - pack. 27 lm - 10/10 mm

Article	LxH mm		
PEGOL 25A	25 x 25		*
PEGOL 30A	30 x 30		*

POLISHED BRASS WITH ADHESIVE
bar length 2,7 lm - pack. 27 lm - 12/10 mm

Article	LxH mm		
PEGOL 40A	40 x 40		*
PEGOL 50A	50 x 50		*

PEG... 40A / 50A on demand with thickness 12/10.
Quantity, timing and prices to be agreed.

For items without adhesive, write the item without the last A.
E.g.: PEGOL 40

PROEDGE R AC is a corner bead profile in polished and brushed stainless steel AISI 304/1.4301-V2A, with a radius of curvature of 5 mm, suitably shaped to protect the external corner of wall coverings. Its particular section, the availability in two finishes and different widths make **PROEDGE R AC** a much sought-after profile that allows a workmanlike application even in environments subject to high mechanical stresses.

PROEDGE R AC

POLISHED AND BRUSHED STAINLESS STEEL AISI 304/1.4301-V2A



POLISHED AND BRUSHED STAINLESS STEEL WITH ADHESIVE with protective film - bar length 2,7 lm - pack. 81 lm - 8/10 mm

Article	LxH mm			
PEGRAC 15A	15 x 15	9,58	25,87	*
PEGRACS 15A	15 x 15	11,43	30,86	*
PEGRAC 20A	20 x 20	10,86	29,32	*
PEGRACS 20A	20 x 20	12,72	34,34	*

POLISHED AND BRUSHED STAINLESS STEEL WITH ADHESIVE with protective film - bar length 2,7 lm - pack. 40,5 lm - 10/10 mm

Article	LxH mm			
PEGRAC 25A	25 x 25			*
PEGRACS 25A	25 x 25			*
PEGRAC 30A	30 x 30			*
PEGRACS 30A	30 x 30			*

For items without adhesive write the item without the last A. E.g.: PEGRAC 15

Suitable for use in contact with foodstuffs.


POLISHED AND BRUSHED STAINLESS STEEL WITH ADHESIVE with protective film - bar length 2,7 lm - pack. 27 lm - 10/10 mm

Article	LxH mm			
PEGRAC 40A	40 x 40			*
PEGRACS 40A	40 x 40			*
PEGRAC 50A	50 x 50			*
PEGRACS 50A	50 x 50			*

PEGR... 40A / 50A on demand with thickness 12/10. Quantity, timing and prices to be agreed.

For items without adhesive, write the item without the last A. E.g.: PEGRAC 40

COLOURS



PROEDGE R OT is a corner bead profile in polished and chromed brass, with a radius of curvature of 5 mm, suitably shaped to protect the external corner of wall coverings. Its particular section, the availability in two finishes and different widths make **PROEDGE R OT** a much sought-after profile that allows an elegant workmanlike application.

PROEDGE R OT

POLISHED AND CHROMED BRASS



CHROMED BRASS WITH ADHESIVE thermo packed - bar length 2,7 lm - pack. 54 lm

Article	LxH mm			
PEGROC 15A	15 x 15			*
PEGROC 20A	20 x 20			*
PEGROC 25A	25 x 25			*
PEGROC 30A	30 x 30			*



POLISHED BRASS WITH ADHESIVE bar length 2,7 lm - pack. 27 lm - 10/10 mm

Article	LxH mm			
PEGROL 25A	25 x 25			*
PEGROL 30A	30 x 30			*



POLISHED BRASS WITH ADHESIVE bar length 2,7 lm - pack. 54 lm - 8/10 mm

Article	LxH mm			
PEGROL 15A	15 x 15			*
PEGROL 20A	20 x 20			*



POLISHED BRASS WITH ADHESIVE bar length 2,7 lm - pack. 27 lm - 12/10 mm

Article	LxH mm			
PEGROL 40A	40 x 40			*
PEGROL 50A	50 x 50			*




For items without adhesive, write the item without the last A. E.g.: PEGROL 15

PEGR... 40A / 50A on demand with thickness 12/10. Quantity, timing and prices to be agreed.


For items without adhesive, write the item without the last A. E.g.: PEGROL 25

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROEDGE R OT" according to the desired finish and width.
2. Cut "PROEDGE R OT" to the desired length.
3. Remove carefully any remains of oil, fat and dirt from the surface where the profile will be laid.
4. When the surface is perfectly dry, remove the protective film, place correctly the profile and press it without hitting / apply the silicone on the surface where the profile will be laid (version without adhesive) and press it without hitting.

COLOURS




* = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed

PROEDGE AL

PROEDGE AL is a corner bead profile in anodized and varnished aluminium suitably shaped to protect the external corner of wall coverings. Its particular section and the availability in four different finishes make **PROEDGE AL** a much sought-after profile that allows a workmanlike application.

ANODIZED AND VARNISHED ALUMINIUM

PEG... 25A
PEGA 25-01A



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROEDGE AL" according to the desired finish and width.
2. Cut "PROEDGE AL" to the desired length.
3. Remove carefully any remains of oil, fat and dirt from the surface where the profile will be laid.
4. When the surface is perfectly dry, remove the protective film, place correctly the profile and press it without hitting / apply the silicone on the surface where the profile will be laid (version without adhesive) and press it without hitting.



ANODIZED ALUM. (gold, silver and bronze) **WITH ADHESIVE**
thermo packed - bar length 2,7 lm - pack. 30 Pcs - 81 lm

Article	LxH mm		
PEGAO 25A	25 x 25		
PEGAA 25A	25 x 25		
PEGAB 25A	25 x 25		

For items without adhesive, write the article without the last A.
E.g.: PEGAO 25

WHITE VARNISHED ALUMINIUM - WITH ADHESIVE
thermo packed - bar length 2,7 lm - pack. 30 Pcs - 81 lm

Article	LxH mm		
PEGA 25-01A	25 x 25		


COLOURS

ANODIZED		
AO - Anodized gold alum.	AA - Anodized silver alum.	AB - Anod. bronze alum.
01 - White varnished alum.		

PROEDGE PVC

PROEDGE PVC is a corner bead profile in shockproof non-toxic co-extruded white vinyl resin suitably shaped to protect the external corner of wall coverings. Its particular section and the availability in four different widths make **PROEDGE PVC** a much sought-after profile that allows a workmanlike application.

SHOCKPROOF NON - TOXIC CO-EXTRUDED
WHITE VINYL RESIN



SHOCKPROOF VINYL RESIN WITH ADHESIVE
bar length 2,7 lm - pack. 30 Pcs - 81 lm

Article	LxH mm		
PEG 25-01A	25 x 25		
PEG 30-01A	30 x 30		

SHOCKPROOF VINYL RESIN WITHOUT ADHESIVE
bar length 2,7 lm - pack. 30 Pcs - 81 lm

Article	LxH mm		
PEG 25-01	25 x 25		
PEG 30-01	30 x 30		

SHOCKPROOF VINYL RESIN WITH ADHESIVE
bar length 2,7 lm - pack. 15 Pcs - 40,5 lm

Article	LxH mm		
PEG 40-01A	40 x 40		
PEG 50-01A	50 x 50		

SHOCKPROOF VINYL RESIN WITHOUT ADHESIVE
bar length 2,7 lm - pack. 15 Pcs - 40,5 lm

Article	LxH mm		
PEG 40-01	40 x 40		
PEG 50-01	50 x 50		

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROEDGE PVC" according to the desired width.
2. Cut "PROEDGE PVC" to the desired length.
3. Remove carefully any remains of oil, fat and dirt from the surface where the profile will be laid.
4. When the surface is perfectly dry, remove the protective film, place correctly the profile and press it without hitting / apply the silicone on the surface where the profile will be laid (version without adhesive) and press it without hitting.

COLOURS

	FOR OTHER COLORS MINIMUM ORDER 400 pcs
01 - White	




PROSHELL

POLISHED AND BRUSHED STAINLESS STEEL AISI 304/1.4301-V2A


PROSHELL is a cove-shaped profile in polished and brushed stainless steel AISI 304/1.4301-V2A particularly suitable to ensure cleanliness and hygiene in every kind of environment where high resistance to mechanical and chemical stresses are required. Its particular section and the availability in two finishes, four heights and special pieces, such as internal and external corners, end caps and junctions, make PROSHELL a much sought-after profile that allows a workmanlike application even in environments subject to high mechanical stresses.

Internal seal hygienic profiles



BUY PROTERMINAL PVC OR ALUMINIUM TO CREATE THE DUAL HEIGHT (SEE BELOW):
 Use proterminal PT 06 to reach H 8 mm
 Use proterminal PT 08 to reach H 10 mm
 Use proterminal PT 10 to reach H12,5 mm
 Use proterminal PT 12,5 to reach H 15 mm

EXAMPLES FOR LAYING



POLISHED STAINLESS STEEL AISI 304/1.4301-V2A with protective film - bar length 2,7 lm - pack. 20 Pcs - 54 lm - 10/10 mm

Article	H mm		
PSHAC 08	8		
PSHAC 10	10		
PSHAC 125	12,5		
PSHAC 15	15		



BRUSHED STAINLESS STEEL AISI 304/1.4301-V2A with protective film - bar length 2,7 lm - pack. 20 Pcs - 54 lm - 10/10 mm

Article	H mm		
PSHACS 08	8		
PSHACS 10	10		
PSHACS 125	12,5		
PSHACS 15	15		

Suitable for use in contact with foodstuffs.

INSTRUCTIONS FOR LAYING


1. Choose "PROSHELL" according to the tile thickness and desired finish. (*) 2. Cut "PROSHELL" to the desired length and apply the adhesive on the support where the profile will be laid. 3. Press the anchoring flange of "PROSHELL" into the adhesive. 4. Lay the tiles on floor and wall aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile. 5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile. (*) to obtain double height, use the joint of the same size as the selected profile and choose the PROTERMINAL PVC or ALUMINIUM according to the required thickness, see INSTRUCTIONS FOR LAYING.

COLOURS



PREWELDED CORNER, CAPS and THREE-WAYS JOINTS

POLISHED AND BRUSHED STAINLESS STEEL



PREWELDED CORNER - POLISHED STAINLESS STEEL L 100 mm - pack. 10 Pcs

Article	H mm		
RPI .../10	08/10/125		
RPI 15/10	15		
RPE .../10	08/10/125		
RPE 15/10	15		
RPT .../10	08/10/125		
RPT 15/10	15		

Specify height of joint: E.g.: RPI 8 for H 8 mm.

PREWELDED CORNER - BRUSHED STAINLESS STEEL L 100 mm - pack. 10 Pcs

Article	H mm		
RPIS .../10	08/10/125		
RPIS 15/10	15		
RPES .../10	08/10/125		
RPES 15/10	15		
RPTS .../10	08/10/125		
RPTS 15/10	15		

Specify height of joint: E.g.: RPIS 8 for H 8 mm.





OVERLAPPING JOINTS POLISHED AISI 316/.4404 V4A STAINLESS STEEL - pack. 10 Pcs

Article			
⊕ RPSIACMS/10			
⊕ RPSEACMS/10			
⊕ RPSTACMS/10			
⊕ GPSACMS/10			
⊕ TPSACMS/10			

OVERLAPPING JOINTS BRUSHED AISI 316/.4404 V4A STAINLESS STEEL - pack. 10 Pcs

Article			
⊕ RPSIACMS/10			
⊕ RPSEACMS/10			
⊕ RPSTACMS/10			
⊕ GPSACMS/10			
⊕ TPSACMS/10			



CAPS AND JOINTS IN RIGID GREY PLASTIC pack. 10 Pcs

Article			
TPSHAC/10			
TPSHACS/10			
⊕ GISHN 08/10			
⊕ GISHN 10/10			
⊕ GISHN 125/10			
⊕ GISHN 15/10			

PROSHELL is a cove-shaped profile in polished and brushed stainless steel AISI 316L/1.4404-V4A particularly suitable to ensure cleanliness and hygiene in every kind of environment where high resistance to mechanical and chemical stresses are required. Its particular section and the availability in two finishes, four heights and special pieces, such as internal and external corners, end caps and junctions, make **PROSHELL** a much sought-after profile that allows a workmanlike application even in environments subject to high mechanical stresses.

PROSHELL

POLISHED AND BRUSHED STAINLESS STEEL AISI 316L/1.4404-V4A



POLISHED STAINLESS STEEL AISI 316L/1.4404-V4A with protective film
- bar length 2,7 lm - pack. 20 Pcs - 54 lm - 10/10 mm




Article	H mm
PSHACM 08	8
PSHACM 10	10
PSHACM 125	12,5
PSHACM 15	15



BRUSHED STAINLESS STEEL AISI 316L/1.4404-V4A with protective film
- bar length 2,7 lm - pack. 20 Pcs - 54 lm - 10/10 mm



Article	H mm
PSHACMS 08	8
PSHACMS 10	10
PSHACMS 125	12,5
PSHACMS 15	15




Internal seal hygienic profiles

Suitable for use in contact with foodstuffs.

BUY PROTERMINAL PVC OR ALUMINIUM TO CREATE THE DUAL HEIGHT (SEE BELOW):
Use proterminal PT 06 to reach H 8 mm Use proterminal PT 10 to reach H12,5 mm
Use proterminal PT 08 to reach H 10 mm Use proterminal PT 12,5 to reach H 15 mm

EXAMPLES AND INSTRUCTIONS FOR LAYING

1. Choose "PROSHELL" according to the tile thickness and desired finish. (*) 2. Cut "PROSHELL" to the desired length and apply the adhesive on the support where the profile will be laid. 3. Press the anchoring flange of "PROSHELL" into the adhesive. 4. Lay the tiles on floor and wall aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile. 5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile. (*) to obtain double height, use the joint of the same size as the selected profile and choose the PROTERMINAL PVC or ALUMINIUM according to the required thickness, see INSTRUCTIONS FOR LAYING.



COLOURS



PREWELDED CORNER, CAPS and THREE-WAYS JOINTS

POLISHED AND BRUSHED STAINLESS STEEL

PREWELDED CORNER - POLISHED STAINLESS STEEL
L 100 mm - pack. 10 Pcs

Article	H mm
RPIACM .../10	08/10/125
RPIACM 15/10	15
RPEACM .../10	08/10/125
RPEACM 15/10	15
RPTACM .../10	08/10/125
RPTACM 15/10	15


Specify height of joint: E.g.: RPI 8 for H 8 mm.

PREWELDED CORNER - BRUSHED STAINLESS STEEL
L 100 mm - pack. 10 Pcs

Article	H mm
RPIACMS .../10	08/10/125
RPIACMS 15/10	15
RPESACMS .../10	08/10/125
RPESACMS 15/10	15
RPTSACMS .../10	08/10/125
RPTSACMS 15/10	15

Specify height of joint: E.g.: RPIS 8 for H 8 mm.

INTERNAL CORNER EXTERNAL CORNER THREE WAYS CORNER



OVERLAPPING JOINTS
POLISHED AISI 316/1.4404 V4A STAINLESS STEEL - pack. 10 Pcs



Article
RPSIACM/10
RPSEACM/10
RPSTACM/10
GPSACM/10
TPSACM/10

OVERLAPPING JOINTS
BRUSHED AISI 316/1.4404 V4A STAINLESS STEEL - pack. 10 Pcs




Article
RPSIACMS/10
RPSEACMS/10
RPSTACMS/10
GPSACMS/10
TPSACMS/10




CAPS AND JOINTS IN RIGID GREY PLASTIC
pack. 10 Pcs

Article
TPSHAC/10
TPSHACS/10
GISHN 08/10
GISHN 10/10
GISHN 125/10
GISHN 15/10



END CAPS



** = Production on demand with minimum quantity of 20 pcs. Production delay 4/5 weeks. Price to be agreed


* = Production on demand with minimum quantity of 200 pcs. Production delay 4/5 weeks. Price to be agreed

News 2023

PROSHELL ALL

ANODIZED, POLISHED AND VARNISHED ALUMINIUM

PROSHELL ALL is a cove-shaped profile in anodized, polished and varnished aluminium particularly suitable to ensure cleanliness and hygiene in indoors environment where good resistance to mechanical and chemical stresses are required. Its particular section and the availability in three finishes, three heights and special pieces, such as internal and external corners, end caps and junctions, make **PROSHELL ALL** a much sought-after profile that allows a workmanlike application.



BUY PROTERMINAL PVC OR ALUMINIUM TO CREATE THE DUAL HEIGHT (SEE NEXT PIC):
 Use proterminal PT 08 to reach H 10 mm
 Use proterminal PT 10 to reach H 12,5 mm
 Use proterminal PT 12,5 to reach H 15 mm




ANODIZED SILVER ALUMINIUM thermo packed
 bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H mm
PSHAA 08	8
PSHAA 10	10
PSHAA 125	12,5

VARNISHED WHITE ALUMINIUM thermo packed
 bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H mm
PSHA 08-01	8
PSHA 10-01	10
PSHA 125-01	12,5




POLISHED CHROME ALUMINIUM thermo packed
 bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H mm
PSHBC 08	8
PSHBC 10	10
PSHBC 125	12,5

COLOURS

AA - Anod. Silver alum.	BC - Polished chrome alum.	01 - White varnished alum.

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROSHELL ALL" according to the tile thickness and desired finish. 2. Cut "PROSHELL ALL" to the desired length and apply the adhesive on the support where the profile will be laid. 3. Press the anchoring flange of "PROSHELL ALL" into the adhesive. 4. Lay the tiles on floor and wall aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile. 5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile. (*) to obtain double height, use the joint of the same size as the selected profile and choose the PROTERMINAL PVC or ALUMINIUM according to the required thickness, see INSTRUCTIONS FOR LAYING.

CORNERS, END CAPS and JOINTS

SILVER ANODIZED, POLISHED CHROME AND VARNISHED WHITE ALUMINIUM / PLASTIC

* accessories of the on demand profiles are also on demand




INTERNAL CORNER
RPSH.../...



EXTERNAL CORNER
RPSHE.../...



END CAP
TPSH.../...



JOINT
GISHN.../...



EXTERNAL/INTERNAL CORNER - ANODIZED SILVER ALUMINIUM

Article	H mm	Pack 10 Pcs	Pack 2 Pcs
RPSHIAA .../...	08/10/125		
RPSHEAA .../...	08/10/125		

EXTERNAL/INTERNAL CORNER VARNISHED WHITE ALUMINIUM

Article	H mm	Pack 10 Pcs	Pack 2 Pcs
RPSHIA ...-01/...	08/10/125		
RPSHEA ...-01/...	08/10/125		

JOINTS IN RIGID GREY PLASTIC - pack. 10 Pcs

Article	H mm	Pack
GISHN 08/...	8	
GISHN 10/...	10	
GISHN 125/...	12,5	

EXTERNAL/INTERNAL CORNER POLISHED CHROME ALUMINIUM

Article	H mm	Pack 10 Pcs	Pack 2 Pcs
RPSHIBC .../...	08/10/125		
RPSHEBC .../...	08/10/125		

CAPS - ANODIZED SILVER ALUMINIUM/POLISHED CHROME/VARNISHED WHITE ALUM.

pack. 10 Pcs (5 right and 5 left) - pack. 2 Pcs (1 right and 1 left)

Article	H mm	Pack 10 Pcs	Pack 2 Pcs
TPSHAA 08/...	8		
TPSHBC 08/...	8		
TPSHA 08/...	8		
TPSHAA 10/...	10		
TPSHBC 10/...	10		
TPSHA 10/...	10		
TPSHAA 125/...	12,5		
TPSHBC 125/...	12,5		
TPSHA 125/...	12,5		

Choose the desired packaging. E.g.: TPSH...-01/5 (Pack 10 Pcs)
 TPSH...-01/1 (Pack 2 Pcs)

News 2023

* = Production on demand with minimum quantity of 200 pcs. Production delay 4/5 weeks. Price to be agreed



PROGUSCIO DA is a cove-shaped profile in shockproof non - toxic coloured vinyl resin particularly suitable to ensure cleanliness and hygiene in public and industrial environments. Its particular section, the availability in three finishes, four heights and special pieces, such as internal and external corners, end caps and junctions, make **PROGUSCIO DA** a much sought-after profile that allows a workmanlike application.

PROGUSCIO DA

SHOCKPROOF NON - TOXIC COLOURED VINYL RESIN



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROGUSCIO DA" according to the tile thickness and desired colour. 2. Cut "PROGUSCIO DA" to the desired length and apply the adhesive on the support where the profile will be laid. 3. Press the anchoring flange of "PROGUSCIO DA" into the adhesive. 4. Lay the tiles on floor and wall aligning them with the profile leaving a 2 mm joint. 5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation.




NON-TOXIC SHOCKPROOF VINYL RESIN


bar length 2,5 lm - pack. 20 Pcs - 50 lm

Article	H mm
PS 06-...	6
PS 08-...	8
PS 10-...	10
PS 125-...	12,5

H 06 available in the colours: 01-04.
H 08, H 10 and H 125 available in the colours: 01-03-04.
The code of the selected colour must be added to the article code.
E.g.: PS 06... (chosen colour white) PS 06-01. The interchangeable flange corresponds to white Proterminal pvc H 6-8-10 mm.

COLOURS

		
01 - White	03 - Cement gray	04 - Light Beige



BUY WHITE PROTERMINAL TO CREATE THE DUAL HEIGHT:
Use proterminal PT 06 to reach H 8 mm
Use proterminal PT 08 to reach H 10 mm
Use proterminal PT 10 to reach H 12,5 mm

CORNERS, END CAPS and JOINTS

NON- TOXIC VINYL RESIN - 3 COLOURS

EXTERNAL / INTERNAL CORNER - RVA COLOURED

Article	H mm	Pack 2 Pcs	Pack 10 Pcs
RAI ...-.../...	06/08/10/125		
RAE ...-.../...	06/08/10/125		

Available in the colours: 01 - 03 - 04.
The code of the selected colour must be added to the article code.
E.g.: RAI 06-... (chosen colour white) RAI 06-01.

Choose the desired packaging. Ex. RAI 06-01/10 (pack. 10 Pcs)
RAI 06-01/2 (pack. 2 Pcs)

END CAP RT / LF - RVA COLOURED

pack. 10 Pcs (5 right and 5 left) - pack. 2 Pcs (1 right and 1 left)

Article	H mm	Pack 2 Pcs	Pack 10 Pcs
TCE 06-.../...	06/08/10/125		

Available in the colours: 01 - 03 - 04.
The code of the selected colour must be added to the article code.
E.g.: TCE 08-... (chosen colour white) TCE 08-01.
Choose the desired packaging. Ex. TCE 08-01/5 (pack. 10 Pcs)
TCE 08-01/1 (pack. 2 Pcs)


JOINTS - RVA COLOURED

pack. 10 Pcs - pack. 2 Pcs

Article	H mm	Pack 2 Pcs	Pack 10 Pcs
GIN ...-.../...	06/08/10/125		

Available in the colours: 01 - 03 - 04.
The code of the selected colour must be added to the article code.
E.g.: GIN 08-... (chosen colour white) GIN 08-01.

Choose the desired packaging. Ex. GIN 08-01/10 (pack. 10 Pcs)
GIN 08-01/2 (pack. 2 Pcs)




PROJOLLY - PROJOLLY QUART

INTERNAL CORNER RAI...-.../...



END CAP TCE...-.../...



EXTERNAL CORNER RAE...-.../...



JOINT GIN...-.../...




PROROUND


POLISHED AND BRUSHED STAINLESS STEEL AISI 304/1.4301-V2A

PROROUND is a cove-shaped profile in polished and brushed stainless steel AISI 304/1.4301-V2A particularly suitable to ensure cleanliness and hygiene in every kind of environment where high resistance to mechanical and chemical stresses are required. Its particular section and the availability in two finishes and special pieces, such as internal and external corners, make **PROROUND** a much sought-after profile that allows a workmanlike application even in environments subject to high mechanical stresses.

internal seal hygienic profiles



EXAMPLES OF LAYING



POLISHED STAINLESS ST. AISI 304/1.4301-V2A with protective film
35 x 35 mm - bar length 2,7 lm - pack. 20 Pcs - 54 lm - 10/10 mm

Article	H mm
PRDAC 35	35
PRDAC 35A	35

BRUSHED STAINLESS ST. AISI 304/1.4301-V2A with protective film
35 x 35 mm - bar length 2,7 lm - pack. 20 Pcs - 54 lm - 10/10 mm

Article	H mm
PRDACS 35	35
PRDACS 35A	35

1. Choose "PROROUND" according to the desired finish and width. 2. Cut "PROROUND" to the desired length. 3. Remove carefully any remains of oil, fat and dirt from the surface where the profile will be laid. 4. When the surface is perfectly dry, remove the protective film, place correctly the profile and press it without hitting / apply the silicone on the surface where the profile will be laid (version without adhesive) and press it without hitting.


COLOURS



Suitable for use in contact with foodstuffs.

PREWELDED CORNERS and THREE-WAYS JOINTS without gaps

POLISHED AND BRUSHED STAINLESS STEEL



POLISHED STAINLESS STEEL AISI 304/1.4301-V2A - pack. 10 Pcs

Article	L mm
PRDI/10	100
PRDE/10	100
PRTE/10	80

Brushed STAINLESS STEEL AISI 304/1.4301-V2A - pack. 10 Pcs


Article	L mm
PRDIS/10	100
PRDES/10	100
PRTES/10	80

PROSANI STRIP & PROSANI STRIP KIT


NON-TOXIC FLEXIBLE WHITE VINYL RESIN

PROSANI STRIP and **PROSANI STRIP KIT** are profiles in non-toxic flexible white vinyl resin particularly suitable to ensure cleanliness and hygiene along the connection between the wall tile coverings and sinks, bathtubs and shower trays. **PROSANI STRIP KIT** is provided with a double-sided butyl tape while **PROSANI STRIP** can be applied with silicone. Their particular section and ease of application, and make **PROSANI STRIP KIT** and **PROSANI STRIP** a much sought after profiles that allow a workmanlike application.


internal seal hygienic profiles



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the desired profile. 2. Cut the profile to the desired length. 3. Remove carefully any remains of oil, fat and dirt from the surface where the profile will be laid. 4. When the surface is perfectly dry, remove the protective film (PROSANI STRIP KIT), place correctly the profile and press it without hitting / apply the equipment double-sided butyl tape on the back of the profile (PROSANI STRIP), apply the silicone along the floor-wall joint and place the profile.



FLEXIBLE WHITE VINYL RESIN
roll 25 lm

Article	LxH mm
PSS 10	10 X 10

PROSANI STRIP KIT ROLL - WHITE
roll 3,5 lm

Article	LxH mm
PSS 1035	11 X 11

COLOURS




PROSEAL 50 is a cove-shaped profile in shockproof non-toxic coextruded coloured vinyl resin particularly suitable to ensure cleanliness and hygiene in public and industrial environments. Its particular section and the availability in two different colours and special pieces, such as internal and external corners, end caps and joints, make **PROSEAL 50** a much sought-after profile that allows a workmanlike application.

PROSEAL 50

SHOCKPROOF NON - TOXIC COEXTRUDED COLORED VINYL RESIN



PSA 50-... / PSAA 50-...



Internal seal hygienic profiles

COEXTRUDED VINYL RESIN NON-TOXIC SHOCKPROOF
bar length 2,5 lm - Pack. 40 LM

Article	
PSA 50-...	

Available in the colours: 01 - 03 (on demand 04).
The code of the selected colour must be added to the article code.
E.g.: PSA 50-... (chosen colour white) PSA 50-01.


COEXTRUDED VINYL RESIN NON-TOXIC SHOCKPROOF - ADHESIVE
bar length 2,5 lm - Pack. 30 LM

Article	
PSAA 50-...	

Available in the colours: 01 - 03 (on demand 04).
The code of the selected colour must be added to the article code.
E.g.: PSAA 50-... (chosen colour white) PSAA 50-01.




EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROSEAL 50" according to the tile thickness and desired finish.
2. Cut "PROSEAL 50" to the desired length.
3. Remove carefully any remains of oil, fat and dirt from the surface where the profile will be laid.
4. When the surface is perfectly dry, remove the protective film (version with adhesive), place the profile and press it without hitting / apply the double-sided butyl tape on the back of the profile (version without adhesive), apply the silicone along the floor-wall joint and place the profile.

AVAILABLE MINIMUM QUANTITY 100 PCS By colour and height
(Price and delivery time to be agreed)

COLOURS



CORNERS and END CAPS

NON - TOXIC VINYL RESIN

INTERNAL / EXTERNAL CORNER AND END CAPS (for PROSEAL 50)

Article	Pack. 2 Pcs	Pack. 10 Pcs
TRI 50-.../...		
TRE 50-.../...		
TRT 50-.../...		
TRC 50-.../...		
TGN 50-.../...		

Available in the colours: 01 - 03 - 04. TRI 50-01/10 (pack. 10 Pcs)
The code of the selected colour must be added to the article code.
E.g.: TRI 50-... (chosen colour white) TRI 50-01.





EXTERNAL CORNER

THREE WAYS

END CAP

JOINTS

INTERNAL CORNER



TRI 50-.../...

TRT 50-.../...

TRC 50-.../...

TGN 50-.../...


TRI 50-.../...

PROSEAL 25


SHOCKPROOF NON - TOXIC COEXTRUDED COLORED VINYL RESIN

PROSEAL 25 is a cove-shaped profile in shockproof non - toxic coextruded coloured vinyl resin particularly suitable to ensure cleanliness and hygiene in public and industrial environments. Its particular section and the availability in three different colours and special pieces, such as internal and external corners, end caps and joints, make **PROSEAL 25** a much sought-after profile that allows a workmanlike application.

internal seal hygienic profiles



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROSEAL 25" according to the tile thickness and desired finish. 2. Cut "PROSEAL 25" to the desired length. 3. Remove carefully any remains of oil, fat and dirt from the surface where the profile will be laid. 4. When the surface is perfectly dry, remove the protective film (version with adhesive), place the profile and press it without hitting / apply the double-sided butyl tape on the back of the profile (version without adhesive), apply the silicone along the floor-wall joint and place the profile.



COEXTRUDED VINYL RESIN NON-TOXIC SHOCKPROOF
bar length 2,5 lm - pack. 50 LM

Article		
PSA 25-...		

Available in the colours: 01 - 03 - 04.
The code of the selected colour must be added to the article code.
E.g.: PSA 25-... (chosen colour white) PSA 25-01..

COEXTRUDED VINYL RESIN NON-TOXIC SHOCKPROOF ADHESIVE
bar length 2,5 lm - pack. 50 LM

Article		
PSAA 25-...		

Available in the colours: 01 - 03 - 04.
The code of the selected colour must be added to the article code.
E.g.: PSAA 25-... (chosen colour white) PSAA 25-01..

COLOURS




PROSEAL KIT 25 (1 Pc of 1,80 lm + 2 Pcs of 0,90 lm + 2 INTERNAL CORNERS and 2 END CAPS 1 R and 1 L)

Description	Article
Kit PROSEAL 25	KTPSA 25-01
1 Pc PROSEAL 25 of 1,80 lm	PSA 25-01
2 Pcs PROSEAL 25 of 0,90 lm	PSA 25-01
2 Internal corner	TRI 25-01
2 End caps	TRC 2501

CORNERS, END CAPS and THREE-WAYS JOINTS


NON - TOXIC VINYL RESIN



INTERNAL / EXTERNAL CORNERS AND END CAPS (for PROSEAL 25)

Article	Pack. 2 Pcs	Pack. 10 Pcs
TRI 25-.../...		
TRE 25-.../...		
TRT 25-.../...		
TRC 25-.../...		
TGN 25-.../...		


Available in the colours: 01 - 03 - 04.
The code of the selected colour must be added to the article code.
E.g.: TRI 25-... (chosen colour white) TRI 25-01.
Choose the desired packaging. Ex. TRI 25-01/10 (pack. 10 Pcs)
TRI 25-01/2 (pack. 2 Pcs)



PROSEAL FLEX

NON-TOXIC FLEXIBLE VINYL RESIN

PROSEAL FLEX is a flexible non-toxic vinyl resin profile suitable to realize cove-shaped connection with resilient flooring in public and industrial environments. Its particular section makes **PROSEAL FLEX** a very sought after profile that allows that allows a workmanlike application.



INSTRUCTIONS FOR LAYING


1. Apply a suitable adhesive for resilient flooring on the support. 2. Place "PROSEAL FLEX" over the adhesive. 3. Apply the adhesive on the profile and the support and lay the resilient flooring.



FLEXIBLE BLACK NON-TOXIC VINYL RESIN
bar length 2,5 lm - pack. 40 Pcs - 100 lm

Article	L x H mm	
PSF 15-11	15x15	
PSF 20-11	20x20	
PSF 25-11	25x25	


COLOURS



PROBATH is a cove-shaped profile in shockproof non - toxic coextruded white vinyl resin particularly suitable to ensure cleanliness and hygiene along the connection between the wall tile coverings and sinks, bathtubs and shower trays. Its particular section and the availability in two different height and special pieces, such as internal and external corners, (only for PSB-20) end caps and joints, make **PROBATH** a much sought-after and easy to lay profile that allows a workmanlike application.

PROBATH

SHOCKPROOF NON - TOXIC
COEXTRUDED VINYL RESIN



Internal seal hygienic profiles

CO-EXTRUDED VINYL RESIN NON - TOXIC IMPACT - RESISTANT
bar length 2,5 lm - pack. 40 Pcs - 100 lm

Article	H mm
PSB 15-01	15
PSB 20-01	20

AVAILABLE ONLY IN WHITE

COLOURS




FOR OTHER COLORS MINIMUM ORDER 400 pcs

PROBATH KIT (1 PC of 1,80 LM + 2 PCS of 0,90 LM + 2 INTERNAL CORNERS and 2 END CAPS 1 R and 1 L)

Description	Article
Kit PROBATH	KTPSB 20-01
1 Pc PROBATH of 1,80 lm	PSB 20-01
2 Pc PROBATH of 0,90 lm	PSB 20-01
2 Internal Corner	TRI 25-01
2 End caps	TRC 25-01

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS




1. Choose "PROBATH" according to the desired height. 2. Cut "PROBATH" to the desired length. 3. Remove carefully any remains of oil, fat and dirt from the surface where the profile will be laid. 4. When the surface is perfectly dry apply the silicone on the back of the profile and place it without hitting.

PROBATH FLEX is a cove-shaped profile in shockproof non - toxic flexible white vinyl resin particularly suitable to ensure cleanliness and hygiene along the connection between the wall tile coverings and sinks, bathtubs and shower trays. Its particular section and the availability in two different height and special pieces, such as internal and external corners, (only for PSB-20) end caps and joints, make **PROBATH FLEX** a much sought-after and easy to lay profile that allows a workmanlike application.

PROBATH FLEX

SHOCKPROOF NON - TOXIC FLEXIBLE
VINYL RESIN



Internal seal hygienic profiles

FLEXIBLE WHITE VYNIL RESIN
bar length 2,5 lm - pack. 40 Pcs - 100 lm

Article	H mm
PSBF 15-01	15
PSBF 20-01	20

AVAILABLE ONLY IN WHITE



1. Choose "PROBATH FLEX" according to the desired height. 2. Cut "PROBATH FLEX" to the desired length. 3. Remove carefully any remains of oil, fat and dirt from the surface where the profile will be laid. 4. When the surface is perfectly dry apply the silicone on the back of the profile and place it without hitting.

CORNERS, END CAPS and THREE-WAYS JOINTS

NON-TOXIC VINYL RESIN

CORNERS INTERNAL / EXTERNAL, THREE-WAYS, JOINTS AND END CAP


Article	Pack. 2 Pcs	Pack. 10 Pcs
TRI 25-01/...		
TRE 25-01/...		
TRT 25-01/...		
TRC 25-01/...		
TGN 25-01/...		

Choose the desired packaging. Ex. TRI 25-01/10 (pack. 10 Pcs)
TRI 25-01/2 (pack. 2 Pcs)


CORNERS INTERNAL / EXTERNAL AND END CAP - (for PSB 15 - PSBF 15)

Article	Pack. 2 Pcs	Pack. 10 Pcs
TPSB 15-01/...		
RIPSB 15-01/...		
REPSB 15-01/...		

Choose the desired packaging. Ex. TPSB 15-01/10 (pack. 10 Pcs)
TPSB 15-01/2 (pack. 2 Pcs)



EXTERNAL CORNER REPSB 15-01
END CAP TPSB 15-01
INTERNAL CORNER RIPSB 15-01
INTERNAL CORNER TRI 25-01
EXTERNAL CORNER TRE 25-01




END CAP TRC 25-01
JOINTS TGN 25-01
THREE WAYS TRT 25-01

* = Production on demand with minimum quantity of 400 pcs. Production delay 4/5 weeks. Price to be agreed


PROKERLAM LINE

POLISHED AND BRUSHED STAINLESS STEEL AISI 304/1.4301-V2A

PROKERLAM LINE is a profile in polished and brushed stainless steel AISI 304/1.4301-V2A suitable to protect the external corners of coverings in low thickness. It can be used like connection profile between step tread and riser of stairs coated with ceramic and mosaic with low thickness. Its particular section and the availability in three different heights and finishes and special pieces such as internal and external corners, end caps and joints make **PROKERLAM LINE** a much sought-after profile that allows a workmanlike application even with low thickness coverings.



LAYING INSTRUCTIONS



POLISHED STAINLESS ST. AISI 304/1.4301-V2A with protective film
Bar length 2,7 lm - Pack 40 PCS - 108 lm

Article	H mm		
PKLLAC 06	6		
PKLLAC 08	8		
PKLLAC 10	10		
PKLLAC 125	12,5		


1. Choose "PROKERLAM LINE" according to the desired finish.
2. Cut "PROKERLAM LINE" to the desired length and apply the adhesive on the support where the profile will be laid.
3. Press the anchoring flange of "PROKERLAM LINE" into the adhesive.
4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile.
5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.



BRUSHED STAINLESS ST. AISI 304/1.4301-V2A with protective film
Bar length 2,7 lm - Pack 40 PCS - 108 lm

Article	H mm		
PKLLACS 06	6		
PKLLACS 08	8		
PKLLACS 10	10		
PKLLACS 125	12,5		


COLOURS



PROKERLAM LINE

ANODIZED, VARNISHED AND STONE LINE ALUMINIUM

PROKERLAM LINE is a Y-shaped profile in anodized and polished aluminium suitable to protect the external corners of coverings in low thickness. It can be used like connection profile between step tread and riser of stairs coated with ceramic and mosaic with low thickness. Its particular section and the availability in three different heights and finishes and special pieces such as internal and external corners, end caps and joints make **PROKERLAM LINE** a much sought-after profile that allows a workmanlike application even with low thickness coverings.



LAYING INSTRUCTIONS



1. Choose "PROKERLAM LINE" according to the desired finish.
2. Cut "PROKERLAM LINE" to the desired length and apply the adhesive on the support where the profile will be laid.
3. Press the anchoring flange of "PROKERLAM LINE" into the adhesive.
4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile.
5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.



ANODISED SILVER ALUMINIUM thermo packed
Bar length 2,7 lm - Pack 40 PCS - 108 lm

Article	H mm		
PKLLAA 06	6		
PKLLAA 08	8		
PKLLAA 10	10		
PKLLAA 125	12,5		

POLISHED CHROME ALUMINIUM thermo packed
Bar length 2,7 lm - Pack 40 PCS - 108 lm

Article	H mm		
PKLLBC 10	10		
PKLLBC 125	125		

COLOURS

ANODIZED		POLISHED	
AA - Anodized Silver Alu.		BC - Polished chrome alu.	

VARNISHED	
01 - White Varnished Alu.	11 - Black Varnished Alu.

STONE LINE				
SL02 - Stone cream	SL03 - Stone greywory	SL04 - Stone sand	SL05 - Stone grey	SL08 - Stone antradarck



VARNISHED ALUMINIUM (White-Black) thermo packed
Bar length 2,7 lm - Pack 40 PCS - 108 lm

Article	H mm		
PKLLA 06-01	6		
PKLLA 06-11	6		
PKLLA 08-01	8		
PKLLA 08-11	8		
PKLLA 10-01	10		
PKLLA 10-11	10		
PKLLA 125-01	12,5		
PKLLA 125-11	12,5		

STONE LINE ALUMINIUM thermo packed
Bar length 2,7 lm - Pack 40 PCS - 108 lm

Article	H mm		
PKLLA 06-SL...	6		
PKLLA 08-SL...	8		
PKLLA 10-SL...	10		
PKLLA 125-SL...	12,5		

The code of the selected colour must be added to the article code.
E.g.: PKLLA 06-... (chosen colour stone cream) PKLLA 06-SL02.

PROTERMSTEP ACC is a profile for stair in polished and brushed stainless steel AISI 304/1.4301-V2A. The profile protects the tread and cover the joint between the tread and the riser of the step. It can also be used overturned and for this reason it is suitable for two different tile thickness. Its particular geometry and the availability of two finishes and different heights make **PROTERMSTEP ACC** suitable for every kind of stair with ceramic, terracotta floorings, wood and natural stone coverings.

PROTERMSTEP ACC

POLISHED AND BRUSHED STAINLESS STEEL
AISI 304/1.4301-V2A



POLISHED STAINLESS ST. AISI 304/1.4301-V2A with protective film
bar length 2,7 lm - pack. 15 Pcs - 40,5 lm

Article	h / H mm		
PTSPAC 0815	08 / 15		
PTSPAC 10125	10 / 12,5		
PTSPAC 1530	15 / 30		
PTSPAC 2025	20 / 25		

COLOURS




AC - Polished stainless steel AISI 304/1.4301-V2A




BRUSHED STAINLESS STEEL AISI 304/1.4301-V2A
bar length 2,7 lm - pack. 15 Pcs - 40,5 lm

Article	h / H mm		
PTSPACS 0815	08 / 15		
PTSPACS 10125	10 / 12,5		
PTSPACS 1530	15 / 30		
PTSPACS 2025	20 / 25		

ON DEMAND



ACS - Brushed stainless steel AISI 304/1.4301-V2A



INSTRUCTIONS FOR LAYING METHODS

1. Choose "PROTERMSTEP ACC" according to the tile thickness and desired finish.
2. Cut "PROTERMSTEP ACC" to the desired length.
3. Lay the raiser of the step and apply the adhesive on the support where the profile will be laid.
4. Press the anchoring flange of "PROTERMSTEP ACC" into the adhesive.
5. Lay the tiles aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile.
6. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.

ANGLE AND JOINT

CORNER - pack. 10 Pcs

Article	h / H mm		
REPTSAC 0815/10	08 / 15		
REPTSAC 10125/10	10 / 12,5		
REPTSAC 1530/10	15 / 30		
REPTSAC 2025/10	20 / 25		


JOINT - pack. 10 Pcs

Article	h / H mm		
GIPTSAC 0815/10	08 / 15		
GIPTSAC 10125/10	10 / 12,5		
GIPTSAC 1530/10	15 / 30		
GIPTSAC 2025/10	20 / 25		

JOINT GIPTSAC ..




CORNER REPTSAC ..



PROTOP

ANODIZED AND POLISHED ALUMINIUM

PROTOP is a rounded profile in anodized and polished aluminium. The profile protects the tile edges and decorates the countertops of kitchens realized with ceramic. Its particular section and elegance, the availability of three different finishes and special pieces such as internal and external corner at 90° and 135°, make **PROTOP** a much sought-after profile that allows an elegant workmanlike application.



ANODIZED SILVER ALUMINIUM
bar length 2,7 lm - pack. 10 Pcs - 27 lm

Article	H mm
PCTAA 10	10
PCTAA 125	12,5



POLISHED TITANIUM ALUMINIUM
bar length 2,7 lm - pack. 10 Pcs - 27 lm

Article	H mm
PCTBT 10	10
PCTBT 125	12,5

POLISHED CHROME ALUMINIUM
bar length 2,7 lm - pack. 10 Pcs - 27 lm

Article	H mm
PCTBC 10	10
PCTBC 125	12,5

COLOURS




EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS

1. Choose "PROTOP" according to the tile thickness and desired finish.
2. Cut "PROTOP" to the desired length and apply the adhesive on the support where the profile will be laid.
3. Press the anchoring flange of "PROTOP" into the adhesive.
4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile.
5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.

CORNERS


INTERNAL / EXTERNAL CORNERS ANODIZED SILVER ALUMINIUM
pack. 10 Pcs

Article
EPCTAA 90/10 (90°)
IPCTAA 90/10 (90°)
EPCTAA 135/10 (135°)
IPCTAA 135/10 (135°)



INTERNAL / EXTERNAL CORNERS POLISHED TITANIUM ALUMINIUM
pack. 10 Pcs

Article
EPCTBT 90/10 (90°)
IPCTBT 90/10 (90°)
EPCTBT 135/10 (135°)
IPCTBT 135/10 (135°)



INTERNAL / EXTERNAL CORNERS POLISHED CHROME ALUMINIUM
pack. 10 Pcs


Article
EPCTBC 90/10 (90°)
IPCTBC 90/10 (90°)
EPCTBC 135/10 (135°)
IPCTBC 135/10 (135°)



PROTOP T

ANODIZED AND POLISHED ALUMINIUM

PROTOP T is a square profile in anodized and polished aluminium. The profile protects the tile edges and decorates the countertops of kitchens realized with ceramic. Its particular section and elegance, the availability of two different finishes and special pieces such as internal and external corner at 90° and 135°, make **PROTOP T** a much sought-after profile that allows an elegant workmanlike application.



ANODIZED SILVER ALUMINIUM
bar length 2,7 lm - pack. 10 Pcs - 27 lm

Article	H mm
PCTAA 10T	10
PCTAA 125T	12,5



POLISHED CHROME ALUMINIUM
bar length 2,7 lm - pack. 10 Pcs - 27 lm

Article	H mm
PCTBC 10T	10
PCTBC 125T	12,5

INTERNAL / EXTERNAL CORNER ANODIZED SILVER ALUMINIUM
pack. 10 Pcs

Article
IEPCTAA 12590T/10 (90°)
IEPCTAA 1090T/10 (90°)
IEPCTAA 10135T/10 (135°)
IEPCTAA 125135T/10 (135°)

INTERNAL / EXTERNAL CORNER ANODIZED CHROME ALUMINIUM
pack. 10 Pcs


Article
IEPCTBC 12590T/10 (90°)
IEPCTBC 1090T/10 (90°)
IEPCTBC 10135T/10 (135°)
IEPCTBC 125135T/10 (135°)

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS


1. Choose "PROTOP T" according to the tile thickness and desired finish.
2. Cut "PROTOP T" to the desired length and apply the adhesive on the support where the profile will be laid.
3. Press the anchoring flange of "PROTOP T" into the adhesive.
4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile.
5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.



COLOURS







An interpretation of:
Rublyovo - Arkhangelskoye smart city, Zaha Hadid, MOSCOW (Russia)

PROFILES FOR FLOORS




PROTERMINAL

POLISHED AND BRUSHED
STAINLESS STEEL AISI 304/1.4301-V2A

PROTERMINAL is a professional edging profile used mainly to join similar or different floor materials (e.g. tiles/tiles - tiles/parquet/marble/laminates/carpeting /linoleum, etc.) of differing thickness.

PROTERMINAL in stainless steel is also used to protect steps and decking, as a floor edging profile and skirting covering. Match with PROLISTEL strips in stainless steel AISI 304/1.4301-V2A with polished or brushed and in aluminium with anodized or polished chrome finish.



POLISHED STAINLESS ST. AISI 304/1.4301-V2A with protective film
bar length 2,7 lm - pack. 40 Pcs - 108 lm - 10/10 mm
(H 15 to H 30 mm - pack. 20 Pcs - 54 lm)

Article	H mm		
PTAC 03	3		
PTAC 045	4,5		
PTAC 06	6		
PTAC 08	8		
PTAC 10	10		
PTAC 11	11		
PTAC 125	12,5		
PTAC 15	15		
PTAC 175	17,5		
PTAC 20	20		
PTAC 225	22,5		
PTAC 25	25		
PTAC 275	27,5		
PTAC 30	30		

BRUSHED STAINLESS ST. AISI 304/1.4301-V2A with protective film
bar length 2,7 lm - pack. 40 Pcs - 108 lm - 10/10 mm
(H 15 to H 30 mm - pack. 20 Pcs - 54 lm)

Article	H mm		
PTACS 03	3		
PTACS 045	4,5		
PTACS 06	6		
PTACS 08	8		
PTACS 10	10		
PTACS 11	11		
PTACS 125	12,5		
PTACS 15	15		
PTACS 20	20		

COLOURS




POLISHED STAINLESS ST. AISI 304/1.4301-V2A with protective film
bar length 1 lm - pack. 40 Pcs - 40 lm - 10/10 mm

Article	H mm		
PTAC 081	8		*
PTAC 101	10		*
PTAC 1251	12,5		*

POLISHED STAINLESS ST. AISI 304/1.4301-V2A with protective film
bar length 0,9 lm - pack. 40 Pcs - 36 lm - 10/10 mm

Article	H mm		
PTAC 089	8		*
PTAC 109	10		*
PTAC 1259	12,5		*

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the PROTERMINAL with the same height as the thickness of the covering. 2. Apply the adhesive onto the area of application of the profile. 3. Lay and align the profile pressing the perforated flange into the adhesive. 4. Lay the tiles, aligning them so that the top edge of the profile is "flush" with the tile. 5. Use the adhesive to seal any empty interstices.

SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS.



News 2023

* = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed

PROTERMINAL are manufactured with the same forms and sections, as well as in the very resistant material, the stainless shiny steel 316/1.4401-V4A, suitable for outdoors and marine environment with much presence of saltiness and considerable atmospheric agents. They are used as protection for the external angles of tiles, in order to separate or to create the separating joints in the pavements, to terminate the finishing of wall coverings, for platforms, stair steps, bathtubs, etc. They guarantee the impeccable work, ensuring considerable aesthetic effect as well. They strengthen the tile edge and prevents from chipping and breakages. Required by new European regulations on safety and accident prevention in public and private places.

PROTERMINAL

POLISHED STAINLESS STEEL
AISI 316/1.4404-V4A




POLISHED STAINLESS ST. AISI 316L/1.4404-V4A with protective film
bar length 2,7 lm - pack. 40 Pcs - 108 lm - 10/10 mm



Article	H mm		
PTACM 06	6		
PTACM 08	8		
PTACM 10	10		
PTACM 125	12,5		

EXAMPLES OF LAYING



COLOURS



ACM - Polished stainless steel
AISI 316L

SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS.

PROTERMINAL is a professional edging profile used mainly to join similar or different floor materials (e.g. tiles/tiles - tiles/parquet/marble/granite, etc.) of differing thickness. **PROTERMINAL** in brass is also used to protect steps and decking, as a floor edging profile, to cover skirting, decking and worktops and to frame doormats.

PROTERMINAL

POLISHED, NATURAL, ANTIQUE BRASS and BRUSHED



POLISHED BRASS thermo packed
bar length 2,70 lm - pack. 20 Pcs 54 lm


Article	H mm		
PTOL 06	6		
PTOL 08	8		
PTOL 10	10		
PTOL 125	12,5		
PTOL 15	15		*
PTOL 20	20		*
PTOL 25	25		*

ANTIQUÉ BRASS thermo packed
bar length 2,70 lm - pack. 20 Pcs - 54 lm

Article	H mm		
PTOB 06	6		
PTOB 08	8		
PTOB 10	10		
PTOB 125	12,5		
PTOB 15	15		*
PTOB 20	20		*
PTOB 25	25		*

BRUSHED BRASS thermo packed
bar length 2,70 lm - pack. 20 Pcs - 54 lm

Article	H mm		
PTOS 06	6		*
PTOS 08	8		*
PTOS 10	10		*
PTOS 125	12,5		*
PTOS 15	15		*
PTOS 20	20		*
PTOS 25	25		*



NATURAL BRASS thermo packed
bar length 2,70 lm pack. 20 Pcs 54 lm (H 6 mm - 40 Pcs 108 lm)

Article	H mm		
PTON 06	6		
PTON 08	8		
PTON 10	10		
PTON 125	12,5		
PTON 15	15		
PTON 20	20		
PTON 25	25		


NATURAL BRASS thermo packed
bar length 1 lm - pack. 40 Pcs - 40 lm

Article	H mm		
PTON 061	6		*
PTON 081	8		*
PTON 101	10		*
PTON 1251	12,5		*

NATURAL BRASS thermo packed
bar length 0,90 lm - pack. 40 Pcs - 36 lm

Article	H mm		
PTON 069	6		*
PTON 089	8		*
PTON 109	10		*
PTON 1259	12,5		*

COLOURS




Chrome-plated Brass version page 37



Curve version is also available

1. Choose the "PROTERMINAL" with the same height as the thickness of the floor/wall covering. 2. Apply the adhesive onto the area of application of the profile. 3. Lay and align the profile pressing the perforated flange into the adhesive. 4. Lay the tiles, aligning them so that the top edge of the profile is "flush" with the tile. Use the adhesive to seal any empty interstices. Oxidation marks may be easily removed by polishing the profiles with specific products to be found on sale such as Sidol, Smac and similar.

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS




PROTERMINAL

NATURAL ALUMINIUM AND ANODIZED SILVER ALUMINIUM

PROTERMINAL is a professional edging profile designed to protect and decorate the outside corners of tile, mosaic and marble coverings of differing thickness.

PROTERMINAL in aluminium is also used to join different floor materials and to protect steps and decking. Excellent as the edging trim skirtings and for bathroom and kitchen wall coverings. Match with PROLISTEL ALL strips in anodized aluminium with silver and polished chrome finish and with PROLISTEL ACC strips in AISI 304-1.4301 stainless steel with polished or brushed.



NATURAL ALUMINIUM thermo packed 10 Pcs
bar length 2,70 lm - pack. 40 Pcs - 108 lm

Article	H mm		
PTAN 03	3		
PTAN 045	4,5		
PTAN 06	6		
PTAN 08	8		
PTAN 10	10		
PTAN 11	11		
PTAN 125	12,5		
PTAN 15	15		
PTAN 20	20		
PTAN 25	25		

ANODIZED SILVER ALUMINIUM thermo packed
bar length 2,70 lm - pack. 40 Pcs - 108 lm

Article	H mm		
PTAA 03	3		
PTAA 045	4,5		
PTAA 06	6		
PTAA 08	8		
PTAA 10	10		
PTAA 11	11		
PTAA 125	12,5		
PTAA 15	15		
PTAA 20	20		


NATURAL ALUMINIUM thermo packed 10 Pcs
bar length 0,90 lm - pack. 40 Pcs - 36 lm

Article	H mm		
PTAN 069	6		*
PTAN 089	8		*
PTAN 109	10		*
PTAN 1259	12,5		*


NATURAL ALUMINIUM thermo packed 10 Pcs
bar length 1 lm - pack. 40 Pcs - 40 lm

Article	H mm		
PTAN 061	6		*
PTAN 081	8		*
PTAN 101	10		*
PTAN 1251	12,5		*

COLOURS





EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



Also available Polished version and curve version


1. Choose the "PROTERMINAL" with the same height as the thickness of the covering.
2. Apply the adhesive onto the area of application of the profile.
3. Lay and align the profile pressing the perforated flange into the adhesive.
4. Lay the tiles, aligning them so that the top edge of the profile is "flush" with the tile.
5. Use the adhesive to seal any empty interstices.



PROLEVIGAL are separating profiles used to create the technical joint in the special types of pavements such as marble- Venice- palladium ones, that must be smoothed after their laying process. The particular "L" shape with the cut/drilled base and 2,5 mm thick vertical edge consent the perfect smoothing and constant thickness as well. Available in natural aluminium and natural brass, various thickness, as well in outlined/bent **PROLEVIGAL CURVES** BRASS versions.


PROLEVIGAL

NATURAL BRASS




NATURAL BRASS thermo packed 10 Pcs
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H mm		
PLGON 08	8		
PLGON 10	10		
PLGON 125	12,5		
PLGON 125/5	12,5		
PLGON 15	15		
PLGON 175	17,5		
PLGON 20	20		
PLGON 30	30		



Curve available
ADD **CV** AFTER THE ARTICLE CODE.
E.g.: PLGON 08 (CURVE) PLGON**CV** 08

AVAILABLE MINIMUM QUANTITY 200 PCS by color and height



Price to be agreed. Production delay 4/5 weeks


COLOURS



PROLEVIGAL are separating profiles used to create the technical joint in the special types of pavements such as marble- Venice- palladium ones, that must be smoothed after their laying process. The particular "L" shape with the cut/drilled base and 2,5 mm thick vertical edge consent the perfect smoothing and constant thickness as well. Available in natural aluminium and natural brass, various thickness, as well in outlined/bent **PROLEVIGAL CURVE** AL versions.


PROLEVIGAL

NATURAL ALUMINIUM



NATURAL ALUMINIUM thermo packed 10 Pcs
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm		
PLGAN 045	4,5		
PLGAN 06	6		
PLGAN 08	8		
PLGAN 10	10		
PLGAN 125	12,5		
PLGAN 15	15		
PLGAN 175	17,5		
PLGAN 20	20		



Curve available
ADD **CV** AFTER THE ARTICLE CODE.
E.g.: PLGAN 08 (CURVES) PLGAN**CV** 08

COLOURS




= News 2023

= Production on demand with minimum quantity of 200 pcs. Production delay 4/5 weeks. Price to be agreed


PROELEGANT

NATURAL, POLISHED AND CHROMED BRASS

PROELEGANT is a refined profile, with 6 mm visible surface, designed to cover the joint between two types of floor covering, tiles - parquet, marble or granite, bestowing a prestige aesthetic effect that is ideal for indoor and outdoor finishes, even when subject to considerable loads. **PROELEGANT** is available in polished, natural and chromed brass. It is available in various heights in order to satisfy all technical, practical and, in particular, decorative requirements. The chromed version may be used as a decorative strip in the wall covering.



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the "PROELEGANT" with the same height as the thickness of the wall covering/floor. 2. Apply the adhesive onto the area of application of the profile. 3. Lay and align the profile pressing the perforated flange into the adhesive. 4. Lay the tiles, aligning them so that the top edge of the profile is "flush" with the tile. 5. Use the adhesive to seal any empty interstices. Oxidation marks may be easily removed by polishing the profiles with specific products to be found on sale such as Sidol, Srmac and similar.




POLISHED BRASS thermo packed
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H mm		
PELOL 08	8		
PELOL 10	10		
PELOL 125	12,5		
PELOL 14	14		

NATURAL BRASS thermo packed 10 Pcs
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H mm		
PELON 08	8		
PELON 10	10		
PELON 125	12,5		
PELON 14	14		

COLOURS



CHROMED BRASS thermo packed
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H mm		
PELOC 08	8		
PELOC 10	10		
PELOC 125	12,5		
PELOC 14	14		

NATURAL BRASS thermo packed 5 Pcs
bar length 0,90 lm - pack. 40 Pcs - 36 lm



Article	H mm		
PELON 089	8		*
PELON 109	10		*
PELON 1259	12,5		*

PROELEGANT

NATURAL ALUMINIUM AND ANODIZED SILVER ALUMINIUM

PROELEGANT is a refined profile, with 6 mm visible surface, designed to cover the joint between two types of floor covering, tiles - parquet, marble or granite, bestowing a prestige aesthetic effect that is ideal for indoor and outdoor finishes, even when subject to considerable loads. **PROELEGANT** is available in natural and anodized silver aluminium. It is available in various heights in order to satisfy all technical, practical and, in particular, decorative requirements. The anodized version may be used as a decorative strip in the wall covering.

EXAMPLES OF LAYING (for instructions see the product above)




Curve available, see page 103



NATURAL ALUMINIUM thermo packed 10 Pcs
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm		
PELAN 08	8		
PELAN 10	10		
PELAN 125	12,5		

COLOURS



ANODIZED SILVER ALUMINIUM thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm


Article	H mm		
PELAA 08	8		
PELAA 10	10		
PELAA 125	12,5		




PROFINAL

POLISHED, BRUSHED AND SANDED
STAINLESS STEEL AISI 304/1.4301-V2A

PROFINAL is a profile in stainless steel AISI 304/1.4301-V2A polished, brushed and sanded. It is available in three widths 8, 10 and 12.5 mm. Ideal for joining two types of floor on the same level (e.g. tile/tile or tile/wood), creating a decorative separating profile. It is also suitable as a step nosing or to create a decorative strip in the covering. It protects the edge and withstands high loads and frequent traffic.



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the "PROFINAL" with the same height as the thickness of the covering.
2. Apply the adhesive onto the area of application of the profile.
3. Lay and align the profile pressing the perforated flange into the adhesive.
4. Lay the tiles, aligning them so that the top edge of the profile is "flush" with the tile.
5. Use the adhesive to seal any empty interstices.



POLISHED STAINLESS ST. AISI 304/1.4301-V2A with protective film
bar length 2,7 lm - pack. 20 Pcs - 54 lm - 10/10 mm

Article	H mm		
PRFAC 08	8		
PRFAC 10	10		
PRFAC 125	12,5		

COLOURS



AC - Polished stainless steel AISI 304/1.4301-V2A ACS - Brushed stainless steel AISI 304/1.4301-V2A ACSB - Sanded stainless steel AISI 304/1.4301-V2A



BRUSHED STAINLESS ST. AISI 304/1.4301-V2A with protective film bar
length 2,7 lm - pack. 20 Pcs - 54 lm - 10/10 mm

Article	H mm		
PRFACS 08	8		
PRFACS 10	10		
PRFACS 125	12,5		

SANDED STAINLESS STEEL AISI 304/1.4301-V2A with protective film
bar length 2,7 lm - pack. 20 Pcs - 54 lm - 10/10 mm

Article	H mm		
PRFACSB 08	8		
PRFACSB 10	10		
PRFACSB 125	12,5		


ACSB - SPECIAL FINISH, REQUEST AVAILABILITY

SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS.


PROFINAL

NATURAL, POLISHED,
CHROMED AND ANTIQUE BRASS

PROFINAL is a profile in natural, polished, chromed and antique brass. It is available in three widths 8, 10 and 12.5 mm. Ideal for joining two types of floor on the same level (e.g. tile/tile or tile/wood), creating a decorative separating profile. It is also suitable as a step nosing or to create a decorative strip in the covering. It protects the edge and withstands high loads and frequent traffic.




EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



NATURAL BRASS thermo packed 5 Pcs
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H mm		
PRFON 08	8		
PRFON 10	10		
PRFON 125	12,5		

COLOURS



1. Choose the "PROFINAL" with the same height as the thickness of the covering.
2. Apply the adhesive onto the area of application of the profile.
3. Lay and align the profile pressing the perforated flange into the adhesive.
4. Lay the tiles, aligning them so that the top edge of the profile is "flush" with the tile.
5. Use the adhesive to seal any empty interstices. Oxidation marks may be easily removed by polishing the profiles with specific products to be found on sale such as Sidol, Smac and similar.



POLISHED BRASS thermo packed
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H mm		
PRFOL 08	8		
PRFOL 10	10		
PRFOL 125	12,5		

CHROMED BRASS thermo packed

bar length 2,7 lm - pack. 20 Pcs - 54 lm (H 15 mm - 40,5 lm)

Article	H mm		
PRFOC 08	8		
PRFOC 10	10		
PRFOC 11	11		
PRFOC 125	12,5		
PRFOC 15	15		

ANTIQUÉ BRASS thermo packed

bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H mm		
PRFOB 08	8		
PRFOB 10	10		
PRFOB 125	12,5		

PROFINAL is a profile in natural and anodized silver aluminium. It is available in three widths 8, 10 and 12.5 mm. Ideal for joining two types of floor on the same level (e.g. tile/tile or tile/wood), creating a decorative separating profile. It is also suitable as a step nosing or to create a decorative strip in the covering. It protects the edge and withstands high loads and frequent traffic.

PROFINAL

NATURAL ALUMINIUM AND ANODIZED SILVER ALUMINIUM



NATURAL ALUMINIUM thermo packed 10 Pcs
bar length 2,7 lm - pack. 40 Pcs - 108 lm


Article	H mm		
PRFAN 08	8		
PRFAN 10	10		
PRFAN 125	12,5		

COLOURS




ANODIZED SILVER ALUMINIUM thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm		
PRFAA 08	8		
PRFAA 10	10		
PRFAA 125	12,5		



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the "PROFINAL" with the same height as the thickness of the covering.
2. Apply the adhesive onto the area of application of the profile.
3. Lay and align the profile pressing the perforated flange into the adhesive.
4. Lay the tiles, aligning them so that the top edge of the profile is "flush" with the tile.
5. Use the adhesive to seal any empty interstices. Oxidation marks may be easily removed by polishing the profiles with specific products to be found on sale such as Sidol, Smac and similar.

PROSQUARE

NATURAL BRASS




NATURAL BRASS
bar length 3 lm - pack. 20 Pcs - 60 lm

Article	L x H mm		
PQEON 108	10 X 8		

COLOURS



PQEON 108



PROANGLE

CHROMED, POLISHED BRASS



CHROMED, POLISHED BRASS thermo packed
bar length 2,7 lm - pack. 20 Pcs - 54 lm (PGAOC 10 : 27 lm)


Article	L x H mm		
PGAOC 10	10 X 10		
PGAOL 10	10 X 10		



COLOURS



PGAOL/OC 10




* = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed

PROJOINT

NATURAL AND POLISHED BRASS

PROJOINT is a brass profile for joining two floors at the same level. It can be laid with mortar or glue/adhesive. The head thickness allows perfect smoothing and sanding of over 3 mm. It is usually used for tile-wood-marble-Venetian-Palladian floors. Available in various heights and widths. The vertical arrowhead in the PIT 510 and PIT 514 version allows excellent anchorage with the adhesive.



POLISHABLE NATURAL BRASS

bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	L x H mm		
PITON 1025	10 X 25		
PITON 525	5 X 25		
PITON 514	5 X 14		
PITON 510	5 X 10		

POLISHABLE NATURAL BRASS

bar length 0,90 lm - pack. 40 Pcs

Article	L x H mm		
PITON 5109	5 X 10		

CONSISTING OF 1 ECOBLISTER WITH 2 PCS. OF 0.90 LM

POLISHED BRASS

bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	L x H mm		
PITON 1025	10 X 25		
PITON 525	5 X 25		
PITON 514	5 X 14		
PITON 510	5 X 10		*


POLISHED BRASS

bar length 0,90 lm - pack. 40 Pcs

Article	L x H mm		
PITON 5109	5 X 10		*

CONSISTING OF 1 ECOBLISTER WITH 2 PCS. OF 0.90 LM

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROJOINT" according to the desired height.
2. Cut "PROJOINT" to the desired length.

Mortar laying

3. Cut with a trowel the fresh screed following the floor edges.
4. Apply the profile inside the fresh screed taking care to align it with the surface of the floor. After laying the joint should be 0,5 mm below the floor covering surface.
5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all grout remains from the profile surface.

Adhesive laying

3. Apply the adhesive on the support where the profile will be laid. After laying the joint should be 0,5 mm below the floor covering surface.
4. Lay the tiles aligning them with the profile leaving a 2 mm joint. Remove immediately all the remains of adhesive from the profile surface.
5. Fill the joints between the profile and the tile with grout, in order to avoid water stagnation. Remove immediately all grout remains from the profile surface.


COLOURS

	ON DEMAND
ON - Natural brass	OL - Polished brass


PROJOINT

NATURAL ALUMINIUM

PROJOINT is a natural aluminium profile for joining two floors at the same level. It can be laid with mortar or glue/adhesive. The head thickness allows perfect smoothing and sanding of over 3 mm. It is usually used for tile-wood-marble-Venetian-Palladian floors. Available in various heights and widths. The vertical arrowhead in the PIT 510 and PIT 514 version allows excellent anchorage with the adhesive.



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROJOINT" according to the desired height.
2. Cut "PROJOINT" to the desired length.

Mortar laying

3. Cut with a trowel the fresh screed following the floor edges.
4. Apply the profile inside the fresh screed taking care to align it with the surface of the floor. After laying the joint should be 0,5 mm below the floor covering surface.
5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all grout remains from the profile surface.

Adhesive laying

3. Apply the adhesive on the support where the profile will be laid. After laying the joint should be 0,5 mm below the floor covering surface.
4. Lay the tiles aligning them with the profile leaving a 2 mm joint. Remove immediately all the remains of adhesive from the profile surface.
5. Fill the joints between the profile and the tile with grout, in order to avoid water stagnation. Remove immediately all grout remains from the profile surface.

NATURAL ALUMINIUM

bar length 2,70 lm - pack. 40 Pcs - 108 lm

Article	L x H mm		
PITAN 525	5 X 25		
PITAN 514	5 X 14		
PITAN 510	5 X 10		

COLOURS

AN - Natural alum.

* = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed


PROCANAL is a channel for joining floors and also for use as strips in wall coverings. This profile is made in natural, polished and chromed brass as well as natural or anodized silver aluminium. It is also used as a cable channel for the insertion of wires and conduits in all types of floor.

PROCANAL

NATURAL, POLISHED,
CHROMED, ANTIQUE AND BRUSHED BRASS
NATURAL AND ANODIZED SILVER ALUMINIUM



PCL... 10



NATURAL BRASS thermo packed 10 Pcs - POLISHED, CHROMED, NATURAL, ANTIQUE AND BRUSHED BRASS thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm (PCLOC 10 - 81 lm)

Article	L x H mm
PCLON 10	10 X 10
PCLOL 10	10 X 10
PCLOC 10	10 X 10
PCLOB 10	10 X 10
PCLOS 10	10 X 10

NATURAL ALUMINIUM thermo packed 10 Pcs ANODIZED SILVER ALUMINIUM thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm


Article	L x H mm
PCLAN 10	10 X 10
PCLAA 10	10 X 10

Available Stainless steel AISI 304/1.4301-V2A
"PROLISTEL" 10x10 PLTAC 10 / PLTACS 10


COLOURS



COLOURS



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the profile in the required material and finish. 2. Apply the adhesive onto the area of application. 3. Lay the "PROCANAL". 4. Continue laying by aligning it "flush" with the covering. 5. Use the adhesive to seal any empty interstices. Oxidation marks may be easily removed by polishing the profiles with specific products to be found on sale such as Sidol, Smac and similar.

PROFLAT is a range of 20 and 40 mm natural brass or steel strips 3 mm thick. Ideal for dividing up flooring on the same level, they may be polished in situ and also curved/shaped to create decorative patterns that are particularly recommended for marble, Palladian, Venetian and cement or resin-based floors.

PROFLAT

STAINLESS STEEL AISI 304/1.4301-V2A
NATURAL BRASS



STAINLESS STEEL AISI 304/1.4301-V2A
bar length 3 lm - pack. 5 Pcs - 15 lm

Article	L x H mm
GPLAC 2033	3 X 20
GPLAC 4033	3 X 40

STAINLESS STEEL AISI 304/1.4301-V2A
bar length 3 lm - pack. 5 Pcs - 15 lm

Article	L x H mm
GPLAC 2053	5 X 20
GPLAC 5053	5 X 50

SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS.
Available ON REQUEST IN Brushed Stainless steel

POLISHABLE NATURAL BRASS
bar length 2,7 lm - pack. 5 Pcs - 13,5 lm


Article	L x H mm
GPLON 2025	2,5 X 20
GPLON 4025	2,5 X 40

COLOURS



1. Choose "PROFLAT" according to the desired height and visible surface. 2. Cut "PROFLAT" to the desired length. 3. Cut with a trowel the fresh screed following the floor edges. 4. Apply the profile inside the fresh screed taking care to align it with the surface of the floor. After laying the joint should be 0,5 mm below the floor covering surface. 5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all grout remains from the profile surface.


GPLAC 203../ 205..




GPLON 2025




GPLAC 403../ 505..



GPLON 4025




EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



PROSLIDER

POLISHED AND BRUSHED
STAINLESS STEEL AISI 304/1.4301-V2A

PROSLIDER is a sloping terminal transition profile in stainless steel AISI 304/1.4301-V2A designed to join different height floors in a perfect, stepless way. This particularly sturdy profile with the bent base sloping inwards withstands and supports high loads and frequent passage of manual trolleys and vehicles in addition to protecting the edge of the higher floor. **PROSLIDER** is used in particular to join tile or wood to an existing floor. Available in AISI 304/1.4301-V2A stainless steel in various heights to accommodate all differences in level.



POLISHED STAINLESS ST. AISI 304/1.4301-V2A with protective film
bar length 2,7 lm - pack. 20 Pcs - 54 lm - 10/10 mm


Article	H mm		
PDAC 08	8		
PDAC 10	10		
PDAC 125	12,5		
PDAC 15	15		
PDAC 20	20		

BRUSHED STAINLESS ST. AISI 304/1.4301-V2A with protective film
bar length 2,7 lm - pack. 20 Pcs - 54 lm - 10/10 mm

Article	H mm		
PDACS 08	8		
PDACS 10	10		
PDACS 125	12,5		
PDACS 15	15		
PDACS 20	20		

SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS.

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the profile with the required height and finish.
2. Fill the profile cavity with adhesive and apply the adhesive onto the area of application.
3. Lay the "PROSLIDER".
4. Align it "flush" with the floor/covering.
5. Use the adhesive to seal any empty interstices.

COLOURS




AC - Polished stainless steel AISI 304/1.4301-V2A
ACS - Brushed stainless steel AISI 304/1.4301-V2A

PROSLIDER

POLISHED AND NATURAL BRASS

PROSLIDER is a sloping terminal transition profile designed to join different height floors in a perfect, stepless way. This particularly sturdy profile withstands and supports high loads and frequent passage of manual trolleys and vehicles in addition to protecting the edge of the higher floor. **PROSLIDER** is used in particular to join tile or wood to an existing floor. Available in natural and polished brass in various heights to accommodate all differences in level.

transition profiles



NATURAL BRASS thermo packed 5 Pcs
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H mm		
PDON 08	8		*
PDON 10	10		
PDON 125	12,5		*
PDON 15	15		*

POLISHED BRASS thermo packed
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H mm		
PDOL 08	8		*
PDOL 10	10		
PDOL 125	12,5		*
PDOL 15	15		*

INSTRUCTIONS FOR LAYING


1. Choose the profile with the required height H, material and finish.
 2. Fill the profile cavity with adhesive and apply the adhesive onto the area of application.
 3. Lay the "PROSLIDER".
 4. Align it "flush" with the floor/covering.
 5. Use the adhesive to seal any empty interstices.
- Oxidation marks on profiles in natural and polished brass may be easily removed by polishing the profiles with specific products to be found on sale such as Sidol, Smac and similar.

COLOURS



ON - Natural brass
OL - Polished brass

EXAMPLES OF LAYING



* = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed

PROSLIDER is a sloping terminal transition profile designed to join different height floors in a perfect, stepless way. This particularly sturdy profile withstands and supports high loads and frequent passage of manual trolleys and vehicles in addition to protecting the edge of the higher floor. **PROSLIDER** is used in particular to join tile or wood to an existing floor.

Available in natural and anodized silver aluminium in various heights to accommodate all differences in level.

PROSLIDER

NATURAL ALUMINIUM AND ANODIZED SILVER ALUMINIUM




NATURAL ALUMINIUM thermo packed 5 Pcs
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm		
PDAN 08	8		
PDAN 10	10		
PDAN 125	12,5		


ANODIZED SILVER ALUMINIUM thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm		
PDAAN 08	8		
PDAAN 10	10		
PDAAN 125	12,5		

COLOURS



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the profile with the required height H, material and finish.
2. Fill the profile cavity with adhesive and apply the adhesive onto the area of application.
3. Lay the "PROSLIDER".
4. Align it "flush" with the floor/covering.
5. Use the adhesive to seal any empty interstices.

PROSLIDER LR is a sloping terminal transition profile designed to join different height floors in a perfect, stepless way. This particularly sturdy profile withstands and supports high loads and frequent passage of manual trolleys and vehicles in addition to protecting the edge of the higher floor. **PROSLIDER LR** is used in particular to join tile or wood to an existing floor.

Available in natural and anodized silver aluminium in various heights to accommodate all differences in level.

PROSLIDER LR

NATURAL ALUMINIUM AND ANODIZED SILVER ALUMINIUM




NATURAL ALUMINIUM thermo packed 5 Pcs
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H mm		
PDLRAN 10	10		
PDLRAN 125	12,5		
PDLRAN 15	15		
PDLRAN 20	20		

ANODIZED SILVER ALUMINIUM thermo packed
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H mm		
PDLRAA 10	10		
PDLRAA 125	12,5		
PDLRAA 15	15		
PDLRAA 20	20		


COLOURS



INSTRUCTIONS FOR LAYING

1. Choose the profile with the required height H, material and finish.
2. Fill the profile cavity with adhesive and apply the adhesive onto the area of application.
3. Lay the "PROSLIDER LR".
4. Align it "flush" with the floor/covering.
5. Use the adhesive to seal any empty interstices.


EXAMPLES OF LAYING



PROSLIDER WOOD

NATURAL OAK WITH ALUMINIUM BASE

PROSLIDER WOOD is a sloping terminal transition profile in real natural oak with glued-on, punched aluminium base, designed to join different height floors in a perfect, stepless way. This particularly sturdy profile withstands and supports high loads and frequent passage of manual trolleys and vehicles in addition to protecting the edge of the higher floor. Available in various heights to accommodate all differences in level.




NATURAL OAK with ALUMINIUM BASE
bar length 2,7 lm - pack. 10 Pcs - 27 lm

Article	H mm		
PDWR 10	10		
PDWR 125	12,5		
PDWR 15	15		

NATURAL OAK with ALUMINIUM BASE
bar length 1,35 lm - pack. 20 Pcs - 27 lm

Article	H mm		
PDWR 1013	10		*
PDWR 12513	12,5		*
PDWR 1513	15		*


EXAMPLES OF LAYING



INSTRUCTIONS FOR LAYING

1. Choose the "PROSLIDER WOOD" with the required height.
2. Apply the adhesive onto the area of application of the profile.
3. Lay and align the profile pressing the perforated flange into the adhesive.
4. Align it "flush" with the floor/covering.
5. Use the adhesive to seal any empty interstices.

COLOURS



PROCARPET ACC is a profile in stainless steel 304/1.4301-V2A used for joining two floors of differing thickness and in particular for joining a tiled or parquet floor to wall-to-wall carpeting, making a perfect join thanks to the vertical part of less than 4 mm. In addition to completely protecting the edge of the higher floor, this particularly sturdy profile withstands high loads and supports the frequent passage of manual trolleys, vehicles and intense pedestrian traffic.

PROCARPET ACC

STAINLESS STEEL AISI 304/1.4301-V2A



POLISHED STAINLESS ST. AISI 304/1.4301-V2A with protective film
bar length 2,7 lm - pack. 20 Pcs - 54 lm - 10/10 mm

Article	H mm
PRTAC 08	8
PRTAC 10	10
PRTAC 125	12,5

BRUSHED STAINLESS ST. AISI 304/1.4301-V2A with protective film
bar length 2,7 lm - pack. 20 Pcs - 54 lm - 10/10 mm

Article	H mm
PRTACS 08	8
PRTACS 10	10
PRTACS 125	12,5

COLOURS




AC - Polished stainless steel AISI 304/1.4301-V2A
ACS - Brushed stainless steel AISI 304/1.4301-V2A

INSTRUCTIONS FOR LAYING


1. Choose the "PROCARPET ACC" taking into consideration the exact height of the floor. 2. Using a notched spreader apply the adhesive onto the area of application of the profile. 3. Lay and align the profile, cut to the necessary length, pressing the perforated flange into the adhesive. 4. Lay the tiles, aligning them so that the top edge of the profile is "flush" with the tile. 5. Fill the profile/tile area of contact with adhesive to prevent the accumulation of water in any voids.

SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS.



transition profiles

EXAMPLES OF LAYING



PROCARPET OTT is a profile in brass (natural or polished) used for joining two floors of differing thickness and in particular for joining a tiled or parquet floor to wall-to-wall carpeting, making a perfect join thanks to the vertical part of less than 4 mm. In addition to completely protecting the edge of the higher floor, this particularly sturdy profile withstands high loads and supports the frequent passage of manual trolleys, vehicles and intense pedestrian traffic.

PROCARPET OTT

POLISHED AND NATURAL BRASS




NATURAL BRASS thermo packed 5 Pcs
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H mm
PRTON 08	8
PRTON 10	10

POLISHED BRASS thermo packed
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H mm
PRTOL 08	8
PRTOL 10	10


COLOURS



ON - Natural brass
OL - Polished brass


INSTRUCTIONS FOR LAYING

1. Choose the "PROCARPET OTT" taking into consideration the exact height of the floor. 2. Using a notched spreader apply the adhesive onto the area of application of the profile. 3. Lay and align the profile, cut to the necessary length, pressing the perforated flange into the adhesive. 4. Lay the tiles, aligning them so that the top edge of the profile is "flush" with the tile. 5. Fill the profile/tile area of contact with adhesive to prevent the accumulation of water in any voids. Profiles in natural or polished brass may be subject to oxidation in environments with high degrees of humidity. Resulting marks may be easily removed by polishing the profiles with specific products to be found on sale such as Sidol, Smac and.



transition profiles


EXAMPLES OF LAYING



PROCARPET ALL

NATURAL AND ANODIZED SILVER ALUMINIUM

PROCARPET ALL is a profile in aluminium (natural or silver anodized) used for joining two floors of differing thickness and in particular for joining a tiled or parquet floor to wall-to-wall carpeting, making a perfect join thanks to the vertical part of less than 4 mm. In addition to completely protecting the edge of the higher floor, this particularly sturdy profile withstands high loads and supports the frequent passage of manual trolleys, vehicles and intense pedestrian traffic.




NATURAL ALUMINIUM thermo packed 5 Pcs
bar length 2,70 lm - pack. 20 Pcs - 54 lm

Article	H mm		
PRTAN 08	8		
PRTAN 10	10		
PRTAN 125	12,5		

ANODIZED SILVER ALUMINIUM thermo packed
bar length 2,70 lm - pack. 20 Pcs - 54 lm

Article	H mm		
PRTAA 08	8		
PRTAA 10	10		
PRTAA 125	12,5		

EXAMPLES OF LAYING



INSTRUCTIONS FOR LAYING

1. Choose the "PROCARPET ALL" taking into consideration the exact height of the floor. 2. Using a notched spreader apply the adhesive onto the area of application of the profile. 3. Lay and align the profile, cut to the necessary length, pressing the perforated flange into the adhesive. 4. Lay the tiles, aligning them so that the top edge of the profile is "flush" with the tile. 5. Fill the profile/tile area of contact with adhesive to prevent the accumulation of water in any voids.


COLOURS




PROSKID

POLISHED BRASS AND ANODIZED SILVER ALUMINIUM

PROSKID is a sloping profile ideal for the stepless joining of two existing floors of differing heights where no transition profile was installed at the time of laying. Silicone is used for the laying. The notching on the profile helps anchorage of the silicone or adhesive. Hardwearing and attractive.



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the "PROCARPET" taking into consideration the exact height of the floor. 2. Using a notched spreader apply the adhesive onto the area of application of the profile. 3. Lay and align the profile, cut to the necessary length, pressing the perforated flange into the adhesive. 4. Lay the tiles, aligning them so that the top edge of the profile is "flush" with the tile. 5. Fill the profile/tile area of contact with adhesive to prevent the accumulation of water in any voids.

POLISHED BRASS thermo packed
bar length 2,70 lm - pack. 20 Pcs - 54 lm

Article	H mm		
PSLDOL 10	10		
PSLDOL 10A	10		

"A" at the end of the product code = Item with adhesive

ANODIZED SILVER ALUMINIUM thermo packed
bar length 2,70 lm - pack. 20 Pcs - 54 lm

Article	H mm		
PSLDAA 10	10		
PSLDAA 10A	10		

"A" at the end of the product code = Item with adhesive

POLISHED BRASS thermo packed
bar length 0,90 lm - pack. 20 Pcs



Article	H mm		
PSLDOL 109AS	10		

"AS" at the end of the product code = Item with adhesive

COLOURS



POLISHED BRASS thermo packed
bar length 0,90 lm - pack. 20 Pcs



Article	H mm		
PSLDOL 109	10		
PSLDOL 109A	10		

"A" at the end of the product code = Item with adhesive

* = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed


PROLEVALL 29 is a transition profile in anodized aluminium available in the self-adhesive or punched versions. It is used to give a clean-cut, elegant finish when joining and compensating differences in level of floors that are already laid and in differing or same materials e.g. ceramic tiles-wood-parquet-marble, etc. It joins and compensates a thickness between 4 and 6mm. **PROLEVALL 29** ensures a perfect finish with little height, covering any flaws created during laying, while the contoured edges guarantee perfect adherence to the floor.

PROLEVALL 29


ANODIZED ALUMINIUM WITH SELF-ADHESIVE AND PUNCHED



PLV... 29A
PLV... 299AS
PLV... 2910AS




PLV... 29F
PLV... 298FS
PLV... 299FS
PLV... 2910FS




transition profiles

ANODIZED ALUM. with adhesive thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm


Article	H x L mm		
PLV... 29A	5,5 X 29		

ANODIZED ALUM. with adhesive thermo packed  **SELF PACK**
bar length 0,83 lm - pack. 20 Pc

Article	H x L mm		
PLV... 298AS	5,5 X 29		

ANODIZED ALUM. with adhesive thermo packed  **SELF PACK**
bar length 0,93 lm - pack. 20 Pc

Article	H x L mm		
PLV... 299AS	5,5 X 29		

ANODIZED ALUM. with adhesive thermo packed  **SELF PACK**
bar length 1,03 lm - pack. 20 Pc

Article	H x L mm		
PLV... 2910AS	5,5 X 29		

ANODIZED ALUM. punched thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H x L mm		
PLV... 29F	5,5 X 29		

ANODIZED ALUM. punched with screws and screw anchors thermo packed - bar length 0,83 lm - pack. 20 Pc  **SELF PACK**

Article	H x L mm		
PLV... 298FS	5,5 X 29		

ANODIZED ALUM. punched with screws and screw anchors thermo packed - bar length 0,93 lm - pack. 20 Pc  **SELF PACK**


Article	H x L mm		
PLV... 299FS	5,5 X 29		

ANODIZED ALUM. punched with screws and screw anchors thermo packed - bar length 1,03 lm - pack. 20 Pc  **SELF PACK**


Article	H x L mm		
PLV... 2910FS	5,5 X 29		

Available in the colours: AA - AO (AB, AT, CH e SB available on demand with a minimum quantity order of 100 pcs). The code of the selected colour must be added to the article code. E.g.: PLV... 29A (chosen colour anodized gold alum.) PLVAO 29A.


COLOURS



AVAILABLE MINIMUM QUANTITY 100 PCS by color and height



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



Adhesive version

1. Choose the suitable profile and cut it to the necessary length.
2. Degrease, wash and clean the solid surface thoroughly.
3. Remove the protective paper from the adhesive.
4. Lay the profile by applying pressure evenly over the whole surface without using a hammer.

Punched version

1. Choose the suitable profile and cut it to the necessary length.
2. Mark the position of the holes using the existing holes in the profile as reference.
3. Insert the screw anchors into the drilled holes.
4. Fix the profile using flathead screws suitable for the relative slots in the profile.


PROLEVALL 33 is a transition profile in extruded polished brass, available in the self-adhesive or punched versions. It is used to give a clean-cut, elegant finish when joining and compensating differences in level of floors that are already laid and in differing or same materials e.g. ceramic tiles-wood-parquet-marble, etc. It joins and compensates a thickness between 4 and 6mm. **PROLEVALL 33** ensures a perfect finish with little height, covering any flaws created during laying, while the contoured edges guarantee perfect adherence to the floor.

PROLEVALL 33


POLISHED BRASS WITH SELF-ADHESIVE AND PUNCHED

POLISHED BRASS with adhesive thermo packed
bar length 2,7 lm - pack. 20 Pcs - 54 lm


Article	H x L mm		
PLVOL 33A	5,5 X 33		

POLISHED BRASS with adhesive thermo packed  **SELF PACK**
bar length 0,83 lm - pack. 20 Pc

Article	H x L mm		
PLVOL 338AS	5,5 X 33		

POLISHED BRASS with adhesive thermo packed  **SELF PACK**
bar length 0,93 lm - pack. 20 Pc

Article	H x L mm		
PLVOL 339AS	5,5 X 33		

POLISHED BRASS with adhesive thermo packed  **SELF PACK**
bar length 1,03 lm - pack. 20 Pc

Article	H x L mm		
PLVOL 3310AS	5,5 X 33		

POLISHED BRASS punched thermo packed
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H x L mm		
PLVOL 33F	5,5 X 33		

POLISHED BRASS punched with screws and screw anchors thermo packed - bar length 0,83 lm - pack. 20 Pc  **SELF PACK**

Article	H x L mm		
PLVOL 338FS	5,5 X 33		


POLISHED BRASS punched with screws and screw anchors thermo packed - bar length 0,93 lm - pack. 20 Pc  **SELF PACK**

Article	H x L mm		
PLVOL 339FS	5,5 X 33		


POLISHED BRASS punched with screws and screw anchors thermo packed - bar length 1,03 lm - pack. 20 Pc  **SELF PACK**

Article	H x L mm		
PLVOL 3310FS	5,5 X 33		


COLOURS



PLVOL 33A
PLVOL 338AS
PLVOL 339AS
PLVOL 3310AS




PLVOL 33F
PLVOL 338FS
PLVOL 339FS
PLVOL 3310FS



transition profiles

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the suitable profile and cut it to the necessary length.

Adhesive version

2. Degrease, wash and clean the solid surface thoroughly.
3. Remove the protective paper from the adhesive.
4. Lay the profile by applying pressure evenly over the whole surface without using a hammer.

Punched version


2. Mark the position of the holes using the existing holes in the profile as reference.
3. Insert the screw anchors into the drilled holes.
4. Fix the profile using flathead screws suitable for the relative slots in the profile.

* = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed


PROLEVALL 305

POLISHED STAINLESS STEEL 1.4016
AND POLISHED BRASS
WITH SELF-ADHESIVE AND PUNCHED

PROLEVALL 305 is a transition/terminal profile for floors of medium thickness (from 3 to 7 mm), used to join and compensate two floors of differing height, material and thickness. Ideal as a finishing terminal, it covers flaws and chipping or splintering of tiles, wood and carpeting. Available in stainless steel 1.4016 and polished brass. A protective film protects the finish of the 2.70 m long bars with either self-adhesive backing or punched for fixing with screws and anchors. The 93 cm blister pack version (self pack) is shrink-wrapped with bar code.



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



Adhesive version

1. Choose the suitable profile and cut it to the necessary length.
2. Degrease, wash and clean the solid surface thoroughly.
3. Remove the protective paper from the adhesive.
4. Lay the profile by applying pressure evenly over the whole surface without using a hammer.

Punched version

1. Choose the suitable profile and cut it to the necessary length.
2. Mark the position of the holes using the existing holes in the profile as reference.
3. Insert the screw anchors into the drilled holes.
4. Fix the profile using flathead screws suitable for the relative slots in the profile.



POLISHED STAINLESS ST. 1.4016 with adhesive thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H x L mm		
PLVAC 30A	5 X 30		

POLISHED STAINLESS ST. 1.4016 with adhesive thermo packed - bar length 0,93 lm - pack. 20 Pcs  **SELF PACK**

Article	H x L mm		
PLVAC 309AS	5 X 30		


POLISHED BRASS with adhesive thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H x L mm		
PLVOL 30A	5 X 30		

POLISHED BRASS with adhesive thermo packed - bar length 0,93 lm - pack. 20 Pcs  **SELF PACK**

Article	H x L mm		
PLVOL 309AS	5 X 30		

COLOURS



POLISHED STAINLESS ST. 1.4016 punched with protective film
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H x L mm		
PLVAC 30F	5 X 30		

POL. STAINLESS ST. 1.4016 punched with screws and screw anchors thermo packed - bar length 0,93 lm - pack. 20 Pcs  **SELF PACK**

Article	H x L mm		
PLVAC 309FS	5 X 30		

POLISHED BRASS punched with protective film
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H x L mm		
PLVOL 30F	5 X 30		

POL. BRASS punched with screws and screw anchors thermo packed - bar length 0,93 lm - pack. 20 Pcs  **SELF PACK**


Article	H x L mm		
PLVOL 309FS	5 X 30		

ON DEMAND HAND-BRUSHED STAINLESS STEEL
(Price to be agreed. Production delay 4/5 weeks)


PROLEVALL 32

ANODIZED ALUMINIUM WITH
SELF-ADHESIVE AND PUNCHED

PROLEVALL 32 are transition profiles in anodized aluminium available in the self-adhesive or punched versions. They are used to give a clean-cut, elegant finish when joining and compensating differences in level of floors that are already laid and in differing or same materials e.g. ceramic tiles-wood-parquet-marble, etc. They join and compensate a thickness between 7 and 9 mm. **PROLEVALL 32** ensures a perfect finish with little height, covering any flaws created during laying, while the contoured edges guarantee perfect adherence to the floor.



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



Adhesive version

1. Choose the suitable profile and cut it to the necessary length.
2. Degrease, wash and clean the solid surface thoroughly.
3. Remove the protective paper from the adhesive.
4. Lay the profile by applying pressure evenly over the whole surface without using a hammer.

Punched version

1. Choose the suitable profile and cut it to the necessary length.
2. Mark the position of the holes using the existing holes in the profile as reference.
3. Insert the screw anchors into the drilled holes.
4. Fix the profile using flathead screws suitable for the relative slots in the profile.




ANODIZED SILVER and GOLD ALUMINIUM thermo packed - bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	L x H mm		
PLV... 32A	32 X 8		
PLV... 32F	32 X 8		

"A" at the end of the product code = Item with adhesive
"F" at the end of the product code = Punched Item

Available in the colours: AA - AO (AB - AT, CH e SB available on demand with a minimum quantity order of 100 pcs).
The code of the selected colour must be added to the article code. E.g.: PLV... 32F (chosen colour Anodized gold alum.) PLVAO 32F.

COLOURS




ANODIZED SILVER and GOLD ALUMINIUM thermo packed - bar length 0,93 lm - pack. 20 Pcs  **SELF PACK**

Article	L x H mm		
PLV... 329AS	32 X 8		
PLV... 329FS	32 X 8		

"AS" at the end of the product code = Item with adhesive
"FS" at the end of the product code = Punched Item

AVAILABLE MINIMUM QUANTITY 100 PCS by color and height



(Price to be agreed. Production delay 4/5 weeks)

*** = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed**


PROLEVALL 358 are transition profiles in polished extruded brass, available in the self-adhesive or punched versions. They are used to give a clean-cut, elegant finish when joining and compensating differences in level of floors that are already laid and in differing or same materials e.g. ceramic tiles-wood-parquet-marble, etc. They join and compensate a thickness between 7 and 9 mm. **PROLEVALL 358** ensures a perfect finish with little height, covering any flaws created during laying, while the contoured edges guarantee perfect adherence to the floor.

PROLEVALL 358

POLISHED BRASS
WITH SELF-ADHESIVE AND PUNCHED



PLVOL 358A/PLVOL 3589AS
PLVOL 358F/PLVOL 3589FS



POLISHED BRASS thermo packed - bar length 2,7 lm
pack. 20 Pcs - 54 lm (PLVOL 358F: 15 Pcs - 40,5 lm)

Article	L x H mm
PLVOL 358A	35 X 8
PLVOL 358F	35 X 8

"A" at the end of the product code = Item with adhesive
"F" at the end of the product code = Punched Item


POLISHED BRASS thermo packed
bar length 0,90 lm - pack. 20 Pc



Article	L x H mm
PLVOL 3589AS	35 X 8
PLVOL 3589FS	35 X 8


"AS" at the end of the product code = Item with adhesive
"FS" at the end of the product code = Punched Item

COLOURS



OL - Polished brass

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



Adhesive version

1. Choose the suitable profile and cut it to the necessary length.
2. Degrease, wash and clean the solid surface thoroughly.
3. Remove the protective paper from the adhesive.
4. Lay the profile by applying pressure evenly over the whole surface without using a hammer.

Punched version

1. Choose the suitable profile and cut it to the necessary length.
2. Mark the position of the holes using the existing holes in the profile as reference.
3. Insert the screw anchors into the drilled holes.
4. Fix the profile using flathead screws suitable for the relative slots in the profile.


PROLEVALL 4413 are transition profiles in polished extruded brass and anodized aluminium available in the self-adhesive or punched versions. They are used to give a clean-cut, elegant finish when joining and compensating differences in level of floors that are already laid and in differing or same materials e.g. ceramic tiles-wood-parquet-marble, etc. They join and compensate a thickness between 13 and 15 mm. **PROLEVALL 4413** ensures a perfect finish with little height, covering any flaws created during laying, while the contoured edges guarantee perfect adherence to the floor.

PROLEVALL 4413


POLISHED BRASS AND
ANODIZED SILVER ALUMINIUM
WITH SELF-ADHESIVE AND PUNCHED



PLVOL 4413A /PLVOL 44139AS
PLVOL 4413F /PLVOL 44139FS



PLV... 4413A /PLV... 4413F



transition profiles

POLISHED BRASS thermo packed
bar length 2,7 lm - pack. 10 Pcs - 27 lm

Article	L x H mm
PLVOL 4413A	44 X 13
PLVOL 4413F	44 X 13

"A" at the end of the product code = Item with adhesive
"F" at the end of the product code = Punched Item

ANODIZED SILVER and GOLD ALUMINIUM thermo packed
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	L x H mm
PLV... 4413A	44 X 13
PLV... 4413F	44 X 13

"A" at the end of the product code = Item with adhesive
"F" at the end of the product code = Punched Item

POLISHED BRASS thermo packed
bar length 0,90 lm - pack. 20 Pc




Article	L x H mm
PLVOL 44139AS	44 X 13
PLVOL 44139FS	44 X 13

"AS" at the end of the product code = Item with adhesive
"FS" at the end of the product code = Punched Item

Available in the colours: AA - AO (OL, AT, CH e SB available on demand with a minimum quantity order of 100 pcs). The code of the selected colour must be added to the article code. E.g.: PLV... 4413F (chosen colour anodized gold alum.) PLVAO 4413F.

COLOURS




AA - Anodized silver alum. AO - Anodized gold alum.

AVAILABLE MINIMUM QUANTITY 100 PCS by color and height



OL - Polished brass AT - Anodized titanium alum. CH - Anod. champagne alum. SB - Anodized sand alum.
(Price to be agreed. Production delay 4/5 weeks)

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



Adhesive version

1. Choose the suitable profile and cut it to the necessary length.
2. Degrease, wash and clean the solid surface thoroughly.
3. Remove the protective paper from the adhesive.
4. Lay the profile by applying pressure evenly over the whole surface without using a hammer.

Punched version


1. Choose the suitable profile and cut it to the necessary length.
2. Mark the position of the holes using the existing holes in the profile as reference.
3. Insert the screw anchors into the drilled holes.
4. Fix the profile using flathead screws suitable for the relative slots in the profile.

* = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed


PRONIVO

ANODIZED ALUMINIUM

PRONIVO is a transition and edging profile with a rounded shape in anodized aluminium with tap-down edge. It is ideal to give a clean-cut, elegant finish when joining and compensating differences in level of floors that are already laid and in differing or same materials e.g. ceramic tiles-wood-parquet. With its rounded shape it compensates for differences in thickness between 7 and 13 mm where no profile was installed at the time of laying. **PRONIVO** ensures a perfect finish and is easy to lay with the self-adhesive backing guaranteeing perfect adherence to the floor.



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the suitable profile and cut it to the necessary length.
2. Degrease, wash and clean the solid surface thoroughly.
3. Remove the protective paper from the adhesive.
4. Lay the profile by applying pressure evenly over the whole surface without using a hammer.




ANODIZED ALUMINIUM self-adhesive thermo packed
bar length 2,7 lm - pack. 30 Pcs - 81 lm

Article	H mm
PNVAA 713A	7/13


Available in the colours: AA (AO available on demand with a minimum quantity order of 100 pcs). The code of the selected colour must be added to the article code.
E.g.: PNV... 713 (chosen colour anodized gold alum.) PNVAA 713A.



COLOURS



AVAILABLE MINIMUM QUANTITY 100 PCS by color and height




(Price to be agreed. Production delay 4/5 weeks)


PROTRANS

ANODIZED ALUMINIUM

PROTRANS is a transition and edging profile with a rounded shape in anodized aluminium. It is ideal to give a clean-cut, elegant finish when joining and compensating differences in level of floors that are already laid and in differing or same materials e.g. ceramic tiles-wood-parquet. With its rounded shape it compensates for differences in thickness between 6 and 13 mm where no profile was installed at the time of laying. **PROTRANS** ensures a perfect finish and is easy to lay with the self-adhesive backing guaranteeing perfect adherence to the floor.



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the suitable profile and cut it to the necessary length.
2. Degrease, wash and clean the solid surface thoroughly.
3. Remove the protective paper from the adhesive.
4. Lay the profile by applying pressure evenly over the whole surface without using a hammer.



ANODIZED ALUMINIUM self-adhesive thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm
PTSAA 613A	6 / 13

Available in the colours: AA (AO, AT, CH e SB available on demand with a minimum quantity order of 100 pcs). The code of the selected colour must be added to the article code. E.g.: PTS... 613A (chosen colour anodized gold alum.) PTSAA 613A.



ANODIZED ALUMINIUM self-adhesive thermo packed - bar length 0,90 lm - pack. 20 Pcs



Article	H mm
PTS... 6139AS	6 / 13

COLOURS



AVAILABLE MINIMUM QUANTITY 100 PCS by color and height




(Price to be agreed. Production delay 4/5 weeks)

PROFLOOR 712 is a self-adhesive sloping terminal transition profile in AISI 304/1.4301-V2A stainless steel with protective film. It is used to give a clean-cut, elegant finish when joining and compensating differences in level of floors that are already laid and in differing or same materials e.g. ceramic tiles-wood-parquet-marble. It joins and compensates a thickness between 7 and 12mm. **PROFLOOR 712** ensures a perfect finish with little height, covering any flaws created during laying of the floor. Easy to lay; the high-strength elastomer adhesive ensures an excellent grip.

PROFLOOR 712

POLISHED STAINLESS STEEL
AISI 304/1.4301-V2A WITH SELF-ADHESIVE



POLISHED STAINLESS ST. AISI 304/1.4301-V2A self-adhesive thermo packed - bar length 0,93 lm - pack. 20 Pcs  SELF PACK


Article	L x H mm
PFRAC 7129AS	38 X 7/12

POLISHED STAINLESS ST. AISI 304/1.4301-V2A self-adhesive thermo packed - bar length 1,66 lm - pack. 20 Pcs  SELF PACK


Article	L x H mm
PFRAC 71216AS	38 X 7/12

POLISHED STAINLESS ST. AISI 304/1.4301-V2A self-adhesive thermo packed - bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	L x H mm
PFRAC 712A	38 X 7/12

POLISHED STAINLESS ST. AISI 304/1.4301-V2A self-adhesive thermo packed - bar length 0,83 lm - pack. 20 Pcs  SELF PACK

Article	L x H mm
PFRAC 7128AS	38 X 7/12

POLISHED STAINLESS ST. AISI 304/1.4301-V2A self-adhesive thermo packed - bar length 1,03 lm - pack. 20 Pcs  SELF PACK


Article	L x H mm
PFRAC 71210AS	38 X 7/12

COLOURS




On demand hand-brushed stainless steel (Price to be agreed. Production delay 4/5 weeks)

PFRAC 712A/7128AS/7129AS/71210AS/71216AS



transition profiles

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the suitable profile and cut it to the necessary length.
2. Degrease, wash and clean the solid surface thoroughly.
3. Remove the protective paper from the adhesive.
4. Lay the profile by applying pressure evenly over the whole surface without using a hammer.


SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS.

PROFLOOR 712 is a self-adhesive sloping terminal transition profile in polished brass with protective film. It is used to give a clean-cut, elegant finish when joining and compensating differences in level of floors that are already laid and in differing or same materials e.g. ceramic tiles-wood-parquet-marble. It joins and compensates a thickness between 7 and 12mm. **PROFLOOR 712** ensures a perfect finish with little height, covering any flaws created during laying of the floor. Easy to lay; the high-strength elastomer adhesive ensures an excellent grip.


PROFLOOR 712

POLISHED BRASS
WITH SELF-ADHESIVE



POLISHED BRASS self-adhesive thermo packed bar length 0,93 lm - pack. 20 Pcs  SELF PACK


Article	L x H mm
PFROL 7129AS	38 X 7/12

POLISHED BRASS self-adhesive thermo packed bar length 1,66 lm - pack. 20 Pcs  SELF PACK


Article	L x H mm
PFROL 71216AS	38 X 7/12

POLISHED BRASS self-adhesive thermo packed bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	L x H mm
PFROL 712A	38 X 7/12


POLISHED BRASS self-adhesive thermo packed bar length 0,83 lm - pack. 20 Pcs  SELF PACK

Article	L x H mm
PFROL 7128AS	38 X 7/12

POLISHED BRASS self-adhesive thermo packed bar length 1,03 lm - pack. 20 Pcs  SELF PACK


Article	L x H mm
PFROL 71210AS	38 X 7/12

COLOURS




OL - Polished brass

PFROL 712A/7128AS/7129AS/71210AS/71216AS



transition profiles

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the suitable profile and cut it to the necessary length.
2. Degrease, wash and clean the solid surface thoroughly.
3. Remove the protective paper from the adhesive.
4. Lay the profile by applying pressure evenly over the whole surface without using a hammer.

PROFLOOR 712 is a self-adhesive sloping terminal transition profile in anodized aluminium with silver-gold-bronze finish with protective film. It is used to give a clean-cut, elegant finish when joining and compensating differences in level of floors that are already laid and in differing or same materials e.g. ceramic tiles-wood-parquet-marble. It joins and compensates a thickness between 7 and 12mm. **PROFLOOR 712** ensures a perfect finish with little height, covering any flaws created during laying of the floor. Easy to lay; the high-strength elastomer adhesive ensures an excellent grip.

PROFLOOR 712

ANODIZED GOLD, SILVER AND BRONZE
ALUMINIUM WITH SELF-ADHESIVE



Anodized ALUMINIUM self-adhesive thermo packed bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	L x H mm
PFR... 712A	38 X 7/12



Anodized ALUMINIUM self-adhesive thermo packed - bar length 0,93 lm - pack. 20 Pcs  SELF PACK


Article	L x H mm
PFR... 7129AS	38 X 7/12

PFR... 712A/7129AS



transition profiles

COLOURS



AVAILABLE MINIMUM QUANTITY 100 PCS by color and height



(Price to be agreed. Production delay 4/5 weeks)

Available in the colours: AA - AO - AB (AT, CH and SB available on demand with a minimum quantity order of 100 pcs). The code of the selected colour must be added to the article code. E.g.: PFR... 712A (chosen colour anodized gold alum.) PFRAO 712A.

PROGRESS 712


POLISHED STAINLESS STEEL AISI 304/1.4301 AND POLISHED BRASS WITH SELF-ADHESIVE

PROGRESS 712 is a self-adhesive sloping terminal transition profile in stainless steel 1.4301 and polished brass with protective film. It is used to give a clean-cut, elegant finish when joining and compensating differences in level of floors that are already laid and in differing or same materials e.g. ceramic tiles-wood-parquet-marble, etc. It joins and compensates a thickness between 7 and 12mm.


PROGRESS 712 ensures a perfect finish with little height, covering any flaws created during laying of the floor. Easy to lay; the high-strength elastomer adhesive ensures an excellent grip.

transition profiles

PR SAC 712A/7129AS
PR SOL 712A/7129AS



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS




1. Choose the suitable profile and cut it to the necessary length.
2. Degrease, wash and clean the solid surface thoroughly.
3. Remove the protective paper from the adhesive.
4. Lay the profile by applying pressure evenly over the whole surface without using a hammer.



POLISHED STAINLESS ST. AISI 304/1.4301-V2A self-adhesive thermo packed - bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H x L mm		
PR SAC 712A	27 X 7/12		

POLISHED STAINLESS ST. AISI 304/1.4301-V2A self-adhesive thermo packed - bar length 0,90 lm - pack. 20 Pcs 

Article	L x H mm		
PR SAC 7129AS	27 X 7/12		

COLOURS



POLISHED BRASS self-adhesive thermo packed bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H x L mm		
PR SOL 712A	27 X 7/12		

POLISHED BRASS self-adhesive thermo packed bar length 0,90 lm - pack. 20 Pcs 

Article	L x H mm		
PR SOL 7129AS	27 X 7/12		

SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS.

On demand hand-brushed stainless steel
(Price to be agreed. Production delay 4/5 weeks)


PROFLOOR 1216

POLISHED STAINLESS STEEL AISI 304/1.4301 AND POLISHED BRASS WITH SELF-ADHESIVE


PROFLOOR 1216 is a self-adhesive chamfered terminal transition profile in stainless steel AISI 304/1.4301-V2A and polished brass with protective film. It is used to give a clean-cut, elegant finish when joining and compensating differences in level of floors that are already laid and in differing or same materials e.g. ceramic tiles-wood-parquet-marble, etc. It joins and compensates a thickness between 12 and 16mm. **PROFLOOR 1216** ensures a perfect finish with little height, covering any flaws created during laying of the floor. Easy to lay; the high-strength elastomer adhesive ensures an excellent grip.

transition profiles

PFR AC 1216A/12169AS
PFR OL 1216A/12169AS



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS




1. Choose the suitable profile and cut it to the necessary length.
2. Degrease, wash and clean the solid surface thoroughly.
3. Remove the protective paper from the adhesive.
4. Lay the profile by applying pressure evenly over the whole surface without using a hammer.



POLISHED STAINLESS ST. AISI 304/1.4301-V2A self-adhesive thermo packed - bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	L x H mm		
PFR AC 1216A	48 X 12/16		

POLISHED STAINLESS ST. AISI 304/1.4301-V2A self-adhesive thermo packed - bar length 0,93 lm - pack. 20 Pcs 

Article	L x H mm		
PFR AC 12169AS	48 X 12/16		


SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS.

On demand hand-brushed stainless steel
(Price to be agreed. Production delay 4/5 weeks)



POLISHED BRASS self-adhesive thermo packed bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	L x H mm		
PFR OL 1216A	48 X 12/16		

POLISHED BRASS self-adhesive thermo packed bar length 0,93 lm - pack. 20 Pcs 

Article	L x H mm		
PFR OL 12169AS	48 X 12/16		

COLOURS



PROLINOLEUM is a self-adhesive transition profile in anodized aluminium with gold/silver finish. It is used to give a clean-cut, elegant finish to hardwearing surfaces in PVC or linoleum and other thin materials between 2-3 mm thick. **PROLINOLEUM** ensures a perfect finish with little height, covering any flaws created during laying of the floor. Easy to lay; the high-strength elastomer adhesive ensures an excellent grip.

PROLINOLEUM

ANODIZED GOLD AND SILVER ALUMINIUM WITH AND WITHOUT SELF-ADHESIVE



ANODIZED GOLD AND SILVER ALUMINIUM thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H x L mm
PLU ... 16	2,5 X 16

Available in the colours: AA (AO, AT, CH and SB available on demand with a minimum quantity order of 100 pcs). The code of the selected colour must be added to the article code.
E.g.: PLU ... 16 (chosen finish anod. gold) PLUAO 16.

COLOURS



AA - Anodized silver alum.

AVAILABLE MINIMUM QUANTITY 100 PCS by color and height



AO - Anodized gold alum. AT - Anodized titanium alum. CH - Anod. champagne alum. SB - Anod. sand aluminium


(Price to be agreed. Production delay 4/5 weeks)




ANODIZED GOLD AND SILVER ALUMINIUM thermo packed - WITH ADHESIVE - bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H x L mm
PLU ... 16A	2,5 X 16

PLU ... 16
PLU ... 16A



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the suitable profile and cut it to the necessary length.
2. Degrease, wash and clean the solid surface thoroughly.
3. Remove the protective paper from the adhesive.
4. Lay the profile by applying pressure evenly over the whole surface without using a hammer.

profiles for low thicknesses

PROFLOOR 24 is a self-adhesive transition profile with chamfered edges in stainless steel 1.4016 and polished brass with protective film. It is used to give a clean-cut, elegant finish to hardwearing surfaces in PVC and linoleum - carpeting and other thin materials between 2 and 5mm thick. **PROFLOOR 24** ensures a perfect finish with little height, covering any flaws created during laying of the floor. Easy to lay; the high-strength elastomer adhesive ensures an excellent grip.


PROFLOOR 24

POLISHED STAINLESS STEEL AISI 304/1.4301 AND POLISHED BRASS WITH SELF-ADHESIVE



POLISHED STAINLESS ST. AISI 304/1.4301-V2A self-adhesive thermo packed - bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	L x H mm
PFRAC 24A	2/4,5 X 30

POLISHED STAINLESS ST. AISI 304/1.4301-V2A self-adhesive thermo packed - bar length 0,93 lm - pack. 20 Pcs 

Article	L x H mm
PFRAC 249AS	2/4,5 X 30


SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS.

On demand hand-brushed stainless steel
(Price to be agreed. Production delay 4/5 weeks)




POLISHED BRASS self-adhesive thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	L x H mm
PFRAC 24A	2/4,5 X 30

POLISHED BRASS self-adhesive thermo packed
bar length 0,93 lm - pack. 20 Pcs 


Article	L x H mm
PFRAC 249AS	2/4,5 X 30

COLOURS




AC - Polished stainless steel AISI 304/1.4301-V2A OL - Polished brass

PFRAC 24A/249A
PFRAC 24A/249A



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the suitable profile and cut it to the necessary length.
2. Degrease, wash and clean the solid surface thoroughly.
3. Remove the protective paper from the adhesive.
4. Lay the profile by applying pressure evenly over the whole surface without using a hammer.

profiles for low thicknesses


PROSLIDER KL ALL

ANODIZED SILVER ALUMINIUM


PROSLIDER KL ALL is a slide shape progressive transition terminal square suitable for connecting perfectly without steps two floor levels. The particular strength of the square allows to resist and bear heavy loads and frequent passages of manual trolleys and motor vehicles besides protecting the edge of the higher floor. The **PROSLIDER KL ALL** is especially used to connect LA Kerlite/Laminam and thin ceramic tiles to each other or else it is used with wood and/or a pre-existing floor. Available in anodized aluminium.

profiles for low thicknesses

PDKLAA 045



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS




1. Choose the profile with the required finish.
2. Fill the profile cavity with adhesive and apply the adhesive onto the area of application.
3. Lay the "PROSLIDER KL ALL".
4. Align it flush with the floor/covering.
5. Use the adhesive to seal any empty interstices.

ANODIZED SILVER ALUMINIUM thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm		
PDKLAA 045	4,5		

COLOURS



AA - Anodized silver alum.


PROCOVER 1045 ALL

ANODIZED AND POLISHED
SILVER, CHROME AND GOLD ALUMINIUM


PROCOVER 1045 ALL is a joint cover profile in anodized aluminium. It is applied at the end of the laying process between two adjoining floors placed at the same level, with a gap of 3 to 6 mm between the two kerlite /laminam/ or thin ceramic tile floors laid with the adhesive. It protects the external edge of the floor/covering. It is easy to lay and aesthetically pleasing. The design of the profile with lower vertical arrowhead part allows excellent anchorage with silicone / adhesive.

profiles for low thicknesses

PCR...1045



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROCOVER 1045 ALL" in the desired finish considering a side lap of 2/3 mm.
2. Fill the gap with single-pack silicone or with the adhesive used for laying the floor.
3. Bury the profile into the adhesive, making sure that both side laps of the profile rest on the coverings to be joined.

IMPORTANT: Take care of the external edges of the aluminium "PROCOVER 1045 ALL". They must be protected from aggressive substances such as adhesives and sealants and from smoothing or scraping action.


ANODIZED SILVER ALUMINIUM thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm		
PCRAA 1045	4,5		

POLISHED CHROME/GOLD ALUMINIUM thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm		
PCRBC 1045	4,5		
PCRBO 1045	4,5		

COLOURS



AA - Anodized silver alum.

BC - Polished chrome alum.


BO - Polished gold alum.






PROCOVER

POLISHED AND BRUSHED
STAINLESS STEEL AISI 304/1.4301-V2A



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the "PROCOVER" with the width suitable for the gap between the two floors to be joined, taking into consideration 2/3 mm side lap. 2. Fill the gap with single-pack silicone or with the adhesive used for laying the floor. 3. Bury the profile into the adhesive, making sure that both side laps of the profile rest on the coverings to be joined.

PROCOVER is a joint-cover profile in stainless steel (polished or brushed) with aluminium supports. It is applied at the end of laying two adjoining floors with the same height, having left a 6 - 24 mm gap between the two floors set in a thin bed of adhesive. It protects the outside edges of the floor/covering. It is easy to lay and attractive. The design of the profile with lower vertical arrowhead part allows excellent anchorage with the silicone/adhesive. The aluminium structure with the stainless steel lining provides it with a high level of resistance to cuts and deformation.



POLISHED STAINLESS ST. AISI 304/1.4301-V2A
with protective film - bar length 2,7 lm
(PCRAC 1499 - bar length 0,90 lm) - 4/10 mm



Article	Pcs/Pack	L x H mm
PCRAC 149	40	14 X 9
PCRAC 1499	20	14 X 9
PCRAC 209	40	20 X 9
PCRAC 269	30	26 X 9
PCRAC 409	20	40 X 9

COLOURS



AC - Polished stainless steel AISI 304/1.4301-V2A ACS - Brushed stainless steel AISI 304/1.4301-V2A



BRUSHED STAINLESS ST. AISI 304/1.4301-V2A
with protective film - bar length 2,7 lm - 4/10 mm
(PCRACS 1499 - bar length 0,90 lm - pack. 20 Pcs)




Article	Pcs/Pack	L x H mm
PCRACS 149	40	14 X 9
PCRACS 1499	20	14 X 9
PCRACS 209	40	20 X 9
PCRACS 269	30	26 X 9
PCRACS 409	20	40 X 9


SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS.

PROCOVER

POLISHED, CHROMED AND ANTIQUE BRASS



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the "PROCOVER" with the width suitable for the gap between the two floors to be joined, taking into consideration 2/3 mm side lap. 2. Fill the gap with single-pack silicone or with the adhesive used for laying the floor. 3. Bury the profile into the adhesive, making sure that both side laps of the profile rest on the coverings to be joined. Profiles in natural or polished brass may be subject to oxidation in environments with high degrees of humidity. Resulting marks may be easily removed by polishing the profiles with specific products to be found on sale such as Sidol, Smac and similar.

PROCOVER is a joint-cover profile in polished, chromed and antique brass. It is applied at the end of laying two adjoining floors with the same height, having left a 6 - 24 mm gap between the two floors set in a thin bed of adhesive. It protects the outside edges of the floor/covering. It is easy to lay and attractive. The design of the profile with lower vertical arrowhead part allows excellent anchorage with the silicone/adhesive.



POLISHED BRASS thermo packed - bar length 2,7 lm
(PCROL 1499 - bar length 0,90 lm - pack. 40 Pcs)



Article	Pcs/Pack	L x H mm
PCROL 149	20	14 X 9
PCROL 1499	40	14 X 9
PCROL 209	20	20 X 9
PCROL 269	20	26 X 9

CHROMED BRASS (polished stainless st. effect) thermo packed
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	L x H mm
PCROC 149	14 X 9
PCROC 209	20 X 9
PCROC 269	26 X 9




ANTIQUÉ BRASS thermo packed
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	L x H mm
PCROB 149	14 X 9
PCROB 209	20 X 9
PCROB 269	26 X 9

BRUSHED BRASS thermo packed
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	L x H mm
PCROS 149	14 X 9
PCROS 209	20 X 9
PCROS 269	26 X 9

COLOURS



= News 2023

= Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed

PROCOVER is a joint-cover profile in anodized aluminium. It is applied at the end of laying two adjoining floors with the same height, having left a 6 - 24 mm gap between the two floors set in a thin bed of adhesive. It protects the outside edges of the floor/covering. It is easy to lay and attractive. The design of the profile with lower vertical arrowhead part allows excellent anchorage with the silicone/adhesive.

PROCOVER

ANODIZED SILVER, DARK BRONZE ALUMINIUM




ANODIZED SILVER, DARK BRONZE ALUMINIUM thermo packed - bar length 2,7 lm
(PCRAA 1499 - bar length 0,90 lm - pack. 40 Pcs)




Article	Pcs/Pack	L x H mm
PCRAA 149	40	14 X 9
PCRDB 149	40	14 X 9
PCRAA 1499	40	14 X 9
PCRAA 209	40	20 X 9
PCRDB 209	40	20 X 9
PCRAA 269	40	26 X 9
PCRDB 269	40	26 X 9
PCRAA 409	20	40 X 9
PCRDB 409	20	40 X 9

COLOURS




AVAILABLE MINIMUM QUANTITY 100 PCS by color and height




Available on demand PCRAA, PCRAA and PCRAO.

PCRAA - DB 149 curvable available



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the "PROCOVER" with the width suitable for the gap between the two floors to be joined, taking into consideration 2/3 mm side lap. 2. Fill the gap with single-pack silicone or with the adhesive used for laying the floor. 3. Bury the profile into the adhesive, making sure that both side laps of the profile rest on the coverings to be joined.

threshold - joint-cover profiles

PROCOVER WOOD is a joint-cover profile in aluminium covered with a very strong film available in 77 wooden finishes (72 on demand). It is applied at the end of laying two adjoining floors with the same height, having left a 6 - 24 mm gap between the two floors set in a thin bed of adhesive. It protects the outside edges of the floor/covering. It is easy to lay and attractive. The design of the profile with lower vertical arrowhead part allows excellent anchorage with the silicone/adhesive.


PROCOVER WOOD

ALUMINIUM COVERED WITH PROTECTIVE FILM IN 77 WOODEN FINISHES (72 on demand)


ALUMINIUM COVERED WOODEN FINISHES thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm (L 26 mm - 54 lm)

Article	L x H mm
PCRA... 149	14 X 9
PCRA... 269	26 X 9

Available in the wood finishes: 05W - 11W - 28W - 29W - 30W.
The code of the selected colour must be added to the article code.
Es.: PCRA... 149 (chosen finish light oak) PCRA04W 149.



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the "PROCOVER" with the width suitable for the gap between the two floors to be joined, taking into consideration 2/3 mm side lap. 2. Fill the gap with single-pack silicone or with the adhesive used for laying the floor. 3. Bury the profile into the adhesive, making sure that both side laps of the profile rest on the coverings to be joined.

threshold - joint-cover profiles

PROCOVER INSERT for inserting Procover profiles

VINYL RESIN / BLACK RUBBER



Vinyl resin/rubber profile "U-form" for inserting PROCOVER with PINBFT 45 or PINBFT 40 Proinsert System base.

VINYL RESIN/RUBBER
length 2,7 lm and/or in rolls 100 lm

Article
PCPCR 2,7ML
PCPCR 100ML

PROINSERT BASE 45 AND BASE 40 - alum. punched - perfored
bar length 2,7 lm - pack. 20 Pcs - 54 lm


Article	Larg. mm
PINBFT 45	45
PINBFT 40	40



* = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed

PROPLATE

POLISHED STAINLESS 1.4016 STEEL
SELF-ADHESIVE OR PUNCHED




EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROPLATE" in the required width and material and whether punched or with self-adhesive backing.
2. Cut the profile to the required length. When laying the self-adhesive Proplate, clean, degrease and dry the surface, checking that the temperature for application is at least 15°.
3. Remove the protective paper from the adhesive and lay the profile correctly applying a uniform vertical pressure by hand without moving the profile and without using iron/steel hammers.
4. When laying the punched version, align the profile and mark the position of the holes using the holes in the profile as reference.
5. Insert suitable screw anchors (usually Ø 3mm screws & 5x25mm screw anchors)
6. Align the profile and tighten the galvanised or brassed flathead screws.

PROPLATE is a flat joint-cover profile with special profiled edges for perfect adherence to flooring. Made in stainless steel 1.4016 with a protective film and available with or without adhesive or for certain widths also in the punched version. Available in widths of 20 - 30 - 40 - 60 - 80 mm with protective film.



POLISHED STAINLESS 1.4016 ST. thermo packed - ADHESIVE
bar length 2,70 lm - pack. 20 Pcs - 54 lm (L 20-30mm - 108 lm) - 10/10 mm

Article	Width		
PETAC 20A	20mm		
PETAC 30A	30mm		
PETAC 40A	40mm		
PETAC 60A	60mm		
PETAC 80A	80mm		

POLISHED STAINLESS 1.4016 STEEL thermo packed - without holes
bar length 2,70 lm - pack. 20 Pcs - 54 lm - 10/10 mm

Article	Width		
PETAC 60	60mm		
PETAC 80	80mm		

PETAC 60A/80A/60/80, with 12/10 thickness available on demand.

PUNCHED POLISHED STAINLESS 1.4016 ST. with protective film
bar length 2,70 lm - pack. 20 Pcs - 54 lm (L 30mm - 108 lm) - 10/10 mm

Article	Width		
PETAC 30F	30mm		
PETAC 40F	40mm		



POLISHED STAINLESS 1.4016 ST. thermo packed
ADHESIVE bar length 0,93 lm - pack. 20 Pcs - 10/10 mm

Article	Width		
PETAC 309AS	30mm		
PETAC 609AS	60mm		
PETAC 809AS	80mm		

POLISHED STAINLESS 1.4016 ST. thermo packed -
PUNCHED WITH SCREWS bar length 0,93 lm - pack. 20 Pcs - 10/10 mm


Article	Width		
PETAC 309FS	30mm		

COLOURS




PROPLATE

POLISHED BRASS
SELF-ADHESIVE OR PUNCHED



1. Choose "PROPLATE" in the required width and material and whether punched or with self-adhesive backing.
2. Cut the profile to the required length. When laying the self-adhesive Proplate, clean, degrease and dry the surface, checking that the temperature for application is at least 15°.
3. Remove the protective paper from the adhesive and lay the profile correctly applying a uniform vertical pressure by hand without moving the profile and without using iron/steel hammers.
4. When laying the punched version, align the profile and mark the position of the holes using the holes in the profile as reference.
5. Insert suitable screw anchors (usually Ø 3mm screws & 5x25mm screw anchors)
6. Align the profile and tighten the galvanised or brassed flathead screws.

COLOURS



PROPLATE is a flat joint-cover profile with special profiled edges for perfect adherence to flooring. Made in polished brass with a protective film and available with or without adhesive or for certain widths also in the punched version. Available in widths of 20 - 30 - 40 - 60 - 80 mm with protective film.



POLISHED BRASS thermo packed ADHESIVE
bar length 2,70 lm - pack. 20 Pcs - 54 lm (L 20/30mm - 108 lm) - 10/10 mm

Article	Width		
PETOL 20A	20mm		
PETOL 30A	30mm		
PETOL 40A	40mm		
PETOL 60A	60mm		
PETOL 80A	80mm		

POLISHED BRASS thermo packed WITHOUT HOLES
bar length 2,70 lm - pack. 20 Pcs - 54 lm (L 20 mm - 108 lm) - 10/10 mm

Article	Width		
PETOL 20	20mm		
PETOL 60	60mm		
PETOL 80	80mm		

PETOL 60A/80A/60/80 with 13/10 thickness available on demand.

POLISHED BRASS with protective film PUNCHED
bar length 2,70 lm - pack. 20 Pcs - 54 lm (L 30 mm - 108 lm) - 10/10 mm

Article	Width		
PETOL 30F	30mm		
PETOL 40F	40mm		

POLISHED BRASS thermo packed ADHESIVE
bar length 0,83 lm - pack. 20 Pcs - 10/10 mm

Article	Width		
PETOL 308AS	30mm		*
PETOL 408AS	40mm		*

POLISHED BRASS thermo packed
bar length 0,93 lm - pack. 20 Pcs - 10/10 mm

Article	Width		
PETOL 309AS	30mm		
PETOL 309FS	30mm		
PETOL 409AS	40mm		
PETOL 409FS	40mm		*
PETOL 609AS	60mm		*
PETOL 809AS	80mm		*

*"AS" at the end of the product code = Item with adhesive
*"FS" at the end of the product code = Punched Item

POLISHED BRASS thermo packed
bar length 1,03 lm - pack. 20 Pcs - 10/10 mm

Article	Width		
PETOL 3010AS	30mm		
PETOL 4010AS	40mm		
PETOL 4010FS	40mm		*

*"AS" at the end of the product code = Item with adhesive
*"FS" at the end of the product code = Punched Item

POLISHED BRASS thermo packed ADHESIVE
bar length 1,66 lm - pack. 20 Pcs - 10/10 mm

Article	Width		
PETOL 3016AS	30mm		*
PETOL 4016AS	40mm		*

* = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed

PROPLATE 80 ALZ is a new aluminium joint cover, threshold cover. It is very resistant and suitable for covering the expanding joint of two different supporting structures, or to connect a floor with an adjoining one of the same or different kind. Particularly used in Industrial field, in the malls, sport facilities and gyms equipped with wood and/or resin floors.

PROPLATE 80 ALZ

KNURLED ANODIZED SILVER ALUMINIUM




PETAA 80ZA
PETAA 80Z



threshold - joint-cover profiles

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROPLATE 80ALZ" model with or without sticker and cut it to the required length.

Adhesive version

2. Degrease, wash and clean accurately the solid floor. 3. Remove the protective label from the sticker (sticker model). 4. Rest the square pressing evenly without hammering.

Punched version

2. Perforate on one side and insert the nogs in the holes. 3. Fix and screw the square equipped with flared head screws suitable to the holes made.

ANODIZED SILVER ALUMINIUM thermo packed ADHESIVE
bar length 2,7 lm - pack. 20 Pcs - 54 lm (PETAA 80Z - 40,5 lm)


Article	Width mm		
PETAA 80ZA	80		

ANODIZED SILVER ALUMINIUM thermo packed
bar length 2,7 lm - pack. 20 Pcs - 54 lm (PETAA 80Z - 40,5 lm)

Article	Width mm		
PETAA 80Z	80		

Punched version available on demand.

COLOURS



AA - Anodized silver alum.


PROCOVER 14PT is a small aluminium joint cover / threshold cover square. It is used to finish technically floors laid at the same level in ceramic tiles/ ceramics ceramics / wood. It covers eventual laying flaws and guarantees that the floors which are underneath expand enough. In Gold-Silk anodized Aluminium and Bronze with sticker.

PROCOVER 14PT

ANODIZED SILVER, GOLD AND BRONZE ALUMINIUM




PCRAA 14PTA
PCRAO 14PTA
PCRAB 14PTA



threshold - joint-cover profiles

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS




1. Choose the superficial finish of "PROCOVER 14PT" and cut it to the required length. 2. Degrease, wash and clean accurately the solid floor. 3. Remove the protective label from the sticker. 4. Lay the square pressing evenly without hammering.

ANODIZED ALUMINIUM WITH ADHESIVE thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	Width mm		
PCRAA 14PTA	14		
PCRAO 14PTA	14		
PCRAB 14PTA	14		

COLOURS



AA - Anodized silver alum.

AVAILABLE MINIMUM QUANTITY 100 PCS by color and height



AO - Anodized gold alum. AB - Anodized bronze alum.

(Price to be agreed. Production delay 4/5 weeks)

* = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed






PROSOL 18-30-35-40 in steel are self-adhesive joint - covers in stainless steel 1.4016 available in various widths. They are used to join floors of the same or differing material and thickness. The rounded shape also allows the profile to be used to edge shallow floors/parquet max. 5 mm thick. **PROSOL** is normally used to cover flaws and defects created during laying of ceramic/wood/parquet floors by covering the joint/threshold. **PROSOL** is recommended for all sorts of public environments: hotels, offices, shops and private dwellings; it guarantees an impeccable and attractive finish.

PROSOL 18-30-35-40

STAINLESS STEEL 1.4016 WITH
SELF-ADHESIVE WITH PROTECTIVE FILM

threshold - joint-cover profiles



STAINLESS ST. 1.4016 with adhesive thermo packed - bar length 2,7 lm - pack. 40 Pcs - 108 lm (L 35/40 mm - 54 lm)

Article	Width-thick.
PLSAC 18A	18 mm - 10/10
PLSAC 30A	30 mm - 10/10
PLSAC 35A	35 mm - 10/10
PLSAC 40A	40 mm - 12/10

STAINLESS ST. 1.4016 with adhesive thermo packed - bar length 0,83 lm - pack. 20 Pcs SELF PACK

Article	Width-thick.
PLSAC 308AS	30 mm - 10/10
PLSAC 358AS	35 mm - 10/10

On demand 0,73 or 0,63 lm bar length (quantity and prices to be agreed. Production delay 4/5 weeks).

STAINLESS ST. 1.4016 with adhesive thermo packed - bar length 0,83 lm - pack. 20 Pcs ECO BLISTER

Article	Width-thick.
PLSAC 308A	30 mm - 10/10
PLSAC 358A	35 mm - 10/10

On demand 0,73 or 0,63 lm bar length (quantity and prices to be agreed. Production delay 4/5 weeks).

STAINLESS ST. 1.4016 with adhesive thermo packed - bar length 0,90 lm - pack. 20 Pcs ECO BLISTER

Article	Width-thick.
PLSAC 189A	18 mm - 10/10

STAINLESS ST. 1.4016 with adhesive thermo packed - bar length 0,93 lm - pack. 20 Pcs ECO BLISTER

Article	Width-thick.
PLSAC 309A	30 mm - 10/10
PLSAC 359A	35 mm - 10/10

STAINLESS ST. 1.4016 with adhesive thermo packed - bar length 0,93 lm - pack. 20 Pcs SELF PACK

Article	Width-thick.
PLSAC 309AS	30 mm - 10/10
PLSAC 359AS	35 mm - 10/10
PLSAC 409AS	40 mm - 12/10


STAINLESS ST. 1.4016 with adhesive thermo packed - bar length 1,03 lm - pack. 20 Pcs SELF PACK

Article	Width-thick.
PLSAC 3010AS	30 mm - 10/10

STAINLESS ST. 1.4016 with adhesive thermo packed - bar length 1,66 lm - pack. 20 Pcs SELF PACK

Article	Width-thick.
PLSAC 3016AS	30 mm - 10/10
PLSAC 3516AS	35 mm - 10/10

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS




1. Choose the suitable profile and cut it to the necessary length.
2. Degrease, wash and clean the solid surface thoroughly.
3. Remove the protective paper from the adhesive.
4. Lay the profile by applying pressure evenly over the whole surface without using a hammer.

COLOURS



On demand hand-brushed stainless steel (Prices to be agreed. Production delay 4/5 weeks)




* = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed

PROSOL 30-35-40


PUNCHED STAINLESS STEEL 1.4016
WITH PROTECTIVE FILM

PROSOL 30-35-40 in steel are punched joint - covers in stainless steel 1.4016 available in various widths. They are used to join floors of the same or differing material and thickness. The rounded shape also allows the profile to be used to edge shallow floors max. 5 mm thick. **PROSOL** is normally used to cover flaws and defects created during laying of ceramic/wood/parquet floors by covering the joint/threshold. **PROSOL** is recommended for all sorts of public environments: hotels, offices, shops and private dwellings; it guarantees an impeccable and attractive finish.


PLSAC 30F/308F/309F/308FS/309FS/3010FS/3016FS




PLSAC 35F/358F/359F/358FS/359FS/3516FS



PLSAC 40F/409FS



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the suitable profile and cut it to the necessary length.
2. Mark the position of the holes using the existing holes in the profile as reference.
3. Insert the screw anchors into the drilled holes.
4. Fix the profile using flathead screws suitable for the relative slots in the profile.



STAINLESS ST. 1.4016 punched - with protective film
bar length 2,7 lm - pack. 20 Pcs - 54 lm (L 30 mm - 108 lm)

Article	Width-thick.		
PLSAC 30F	30 mm - 10/10		
PLSAC 35F	35 mm - 10/10		
PLSAC 40F	40 mm - 12/10		

STAINLESS ST. 1.4016 punched thermo packed
bar length 0,83 lm - pack. 20 Pcs



Article	Width-thick.		
PLSAC 308F	30 mm - 10/10		
PLSAC 358F	35 mm - 10/10		*

STAINLESS ST. 1.4016 punched thermo packed
bar length 0,93 lm - pack. 20 Pcs



Article	Width-thick.		
PLSAC 309F	30 mm - 10/10		
PLSAC 359F	35 mm - 10/10		*

COLOURS



On demand hand-brushed stainless steel (Prices to be agreed. Production delay 4/5 weeks)

STAINLESS ST. 1.4016 punched with screws and screw anchors
thermo packed - bar length 0,83 lm - pack. 20 Pcs



Article	Width-thick.		
PLSAC 308FS	30 mm - 10/10		
PLSAC 358FS	35 mm - 10/10		*

STAINLESS ST. 1.4016 punched with screws and screw anchors
thermo packed - bar length 0,93 lm - pack. 20 Pcs



Article	Width-thick.		
PLSAC 309FS	30 mm - 10/10		
PLSAC 359FS	35 mm - 10/10		*
PLSAC 409FS	40 mm - 12/10		*

STAINLESS ST. 1.4016 punched with screws and screw anchors
thermo packed - bar length 1,03 lm - pack. 20 Pcs



Article	Width-thick.		
PLSAC 3010FS	30 mm - 10/10		

STAINLESS ST. 1.4016 punched with screws and screw anchors
thermo packed - bar length 1,66 lm - pack. 20 Pcs



Article	Width-thick.		
PLSAC 3016FS	30 mm - 10/10		
PLSAC 3516FS	35 mm - 10/10		*

PROSOL 18-30-35-40 in brass are self-adhesive joint - covers in polished brass available in various widths. They are used to join floors of the same or differing material and thickness. The rounded shape also allows the profile to be used to edge shallow floors max. 5 mm thick. **PROSOL** is normally used to cover flaws and defects created during laying of ceramic/wood/parquet floors by covering the joint/threshold. **PROSOL** is recommended for all sorts of public environments: hotels, offices, shops and private dwellings; it guarantees an impeccable and attractive finish.


PROSOL 18-30-35-40

POLISHED BRASS WITH SELF-ADHESIVE WITH PROTECTIVE FILM




POLISHED BRASS with adhesive thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm (L 35/40mm - 54 lm)

Article	Width-thick.		
PLSOL 18A	18 mm - 10/10		
PLSOL 30A	30 mm - 10/10		
PLSOL 35A	35 mm - 10/10		
PLSOL 40A	40 mm - 10/10		


POLISHED BRASS with adhesive thermo packed  **ECO BLISTER**
bar length 0,83 lm - pack. 20 Pcs

Article	Width-thick.		
PLSOL 308A	30 mm - 10/10		*


On demand 0,73 or 0,63 lm bar length (quantity and prices to be agreed. Production delay 4/5 weeks).

POLISHED BRASS with adhesive thermo packed  **ECO BLISTER**
bar length 0,90 lm - pack. 20 Pcs


Article	Width-thick.		
PLSOL 189A	10 mm - 10/10		

POLISHED BRASS with adhesive thermo packed  **ECO BLISTER**
bar length 0,93 lm - pack. 20 Pcs

Article	Width-thick.		
PLSOL 309A	30 mm - 10/10		
PLSOL 359A	35 mm - 10/10		*
PLSOL 409A	40 mm - 10/10		*

POLISHED BRASS with adhesive thermo packed  **ECO BLISTER**
bar length 1,03 lm - pack. 20 Pcs


Article	Width-thick.		
PLSOL 3010A	30 mm - 10/10		

POLISHED BRASS with adhesive thermo packed  **ECO BLISTER**
bar length 1,66 lm - pack. 20 Pcs

Article	Width-thick.		
PLSOL 3016A	30 mm - 10/10		*

POLISHED BRASS with adhesive thermo packed  **SELF PACK**
bar length 0,83 lm - pack. 20 Pcs


Article	Width-thick.		
PLSOL 308AS	30 mm - 10/10		
PLSOL 358AS	35 mm - 10/10		

POLISHED BRASS with adhesive thermo packed  **SELF PACK**
bar length 0,93 lm - pack. 20 Pcs

Article	Width-thick.		
PLSOL 309AS	30 mm - 10/10		
PLSOL 359AS	35 mm - 10/10		
PLSOL 409AS	40 mm - 10/10		*


POLISHED BRASS with adhesive thermo packed  **SELF PACK**
bar length 1,03 lm - pack. 20 Pcs

Article	Width-thick.		
PLSOL 3010AS	30 mm - 10/10		
PLSOL 3510AS	35 mm - 10/10		


POLISHED BRASS with adhesive thermo packed  **SELF PACK**
bar length 1,66 lm - pack. 20 Pcs

Article	Width-thick.		
PLSOL 3016AS	30 mm - 10/10		*
PLSOL 3516AS	35 mm - 10/10		*
PLSOL 4016AS	40 mm - 10/10		*


COLOURS




PLSOL 18A/189A




PLSOL 30A/308A/309A/3010A/3016A/308AS/309AS/3010AS/3016AS



PLSOL 35A/359A/358AS/359AS/3510AS/3516AS





PLSOL 40S/409S/409SS/416SS



threshold - joint-cover profiles

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS




1. Choose the suitable profile and cut it to the necessary length.
2. Degrease, wash and clean the solid surface thoroughly.
3. Remove the protective paper from the adhesive.
4. Lay the profile by applying pressure evenly over the whole surface without using a hammer.

PROSOL 30-35-40


PUNCHED POLISHED BRASS
WITH PROTECTIVE FILM

PROSOL 30-35-40 in brass are punched joint - covers in polished brass available in various widths. They are used to join floors of the same or differing material and thickness. The rounded shape also allows the profile to be used to edge shallow floors max. 5 mm thick. **PROSOL** is normally used to cover flaws and defects created during laying of ceramic/wood/parquet floors by covering the joint/threshold. **PROSOL** is recommended for all sorts of public environments: hotels, offices, shops and private dwellings; it guarantees an impeccable and attractive finish.


PLSOL 30F/308F/309F/3010F/3016F/308FS/309FS/3010FS/3016FS




PLSOL 35F/359F/358FS/359FS/3510FS/3516FS



PLSOL 40F/409F/409FS/4016FS



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the suitable profile and cut it to the necessary length.
2. Mark the position of the holes using the existing holes in the profile as reference.
3. Insert the screw anchors into the drilled holes.
4. Fix the profile using flathead screws suitable for the relative slots in the profile.



POLISHED BRASS punched with protective film
bar length **2,7 lm** - pack. **40 Pcs - 108 lm** (L 35/40mm - 54 lm)

Article	Width-thick.		
PLSOL 30F	30 mm - 10/10		
PLSOL 35F	35 mm - 10/10		
PLSOL 40F	40 mm - 10/10		

POLISHED BRASS punched thermo packed
bar length **0,83 lm** - pack. **20 Pcs**



Article	Width-thick.		
PLSOL 308F	30 mm - 10/10		*

POLISHED BRASS punched thermo packed
bar length **0,93 lm** - pack. **20 Pcs**



Article	Width-thick.		
PLSOL 309F	30 mm - 10/10		*
PLSOL 359F	35 mm - 10/10		*
PLSOL 409F	40 mm - 10/10		*

POLISHED BRASS punched thermo packed
bar length **1,03 lm** - pack. **20 Pcs**



Article	Width-thick.		
PLSOL 3010F	30 mm - 10/10		*

POLISHED BRASS punched thermo packed
bar length **1,66 lm** - pack. **20 Pcs**



Article	Width-thick.		
PLSOL 3016F	30 mm - 10/10		*

POLISHED BRASS punched with screws and screw anchors thermo packed - bar length **0,83 lm** - pack. **20 Pcs**



Article	Width-thick.		
PLSOL 308FS	30 mm - 10/10		*
PLSOL 358FS	35 mm - 10/10		*

On demand 0,73 or 0,63 lm bar length (quantity and prices to be agreed. Production delay 4/5 weeks).

POLISHED BRASS punched with screws and screw anchors thermo packed - bar length **0,93 lm** - pack. **20 Pcs**



Article	Width-thick.		
PLSOL 309FS	30 mm - 10/10		*
PLSOL 359FS	35 mm - 10/10		*
PLSOL 409FS	40 mm - 10/10		*

POLISHED BRASS punched with screws and screw anchors thermo packed - bar length **1,03 lm** - pack. **20 Pcs**




Article	Width-thick.		
PLSOL 3010FS	30 mm - 10/10		*
PLSOL 3510FS	35 mm - 10/10		*

POLISHED BRASS punched with screws and screw anchors thermo packed - bar length **1,66 lm** - pack. **20 Pcs**



Article	Width-thick.		
PLSOL 3016FS	30 mm - 10/10		*
PLSOL 3516FS	35 mm - 10/10		*
PLSOL 4016FS	40 mm - 10/10		*

COLOURS



OL - Polished brass

* = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed

PROSOL 30-35-40 are self-adhesive or punched joint - covers in polished brass available in various widths. They are used to join floors of the same or differing material and thickness. The rounded shape also allows the profile to be used to edge shallow floors max. 5 mm thick. **PROSOL** is normally used to cover flaws and defects created during laying of ceramic/wood/parquet floors by covering the joint/threshold. **PROSOL** is recommended for all sorts of public environments: hotels, offices, shops and private dwellings; it guarantees an impeccable and attractive finish.

PROSOL 30-35-40

ANODIZED GOLD AND SILVER ALUMINIUM WITH SELF-ADHESIVE AND PUNCHED



ANODIZED ALUMINIUM with adhesive thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	Width-thick.
PLS... 30A	30 mm - 1,3
PLSAA 35A	35 mm - 1,5
PLSAA 40A	40 mm - 2

Available in the colours: AA - AO (AB, AT, CH and SB available on demand with a minimum quantity order of 100 pcs). The code of the selected colour must be added to the article code. E.g.: PLS... 30A (chosen finish anod. silver) PLSAA 30A.

ANODIZED ALUMINIUM punched thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	Width-thick.
PLS... 30F	30 mm - 1,3
PLSAA 35F	35 mm - 1,5
PLSAA 40F	40 mm - 2

ANODIZED ALUMINIUM with adhesive thermo packed - bar length 0,83 lm - pack. 20 Pcs



Article	Width-thick.
PLSAA 308AS	30 mm - 10/10

On demand 0,73 or 0,63 lm bar length (quantity and prices to be agreed. Production delay 4/5 weeks).

ANODIZED ALUMINIUM with adhesive thermo packed - bar length 0,93 lm - pack. 20 Pcs



Article	Width-thick.
PLS... 309AS	30 mm - 10/10

ANODIZED ALUMINIUM with adhesive thermo packed - bar length 1,03 lm - pack. 20 Pcs



Article	Width-thick.
PLS... 3010AS	30 mm - 10/10

ANODIZED ALUMINIUM with adhesive thermo packed - bar length 1,66 lm - pack. 20 Pcs



Article	Width-thick.
PLSAA 3016AS	30 mm - 10/10

ANODIZED ALUMINIUM with adhesive thermo packed - bar length 0,93 lm - pack. 20 Pcs



Article	Width-thick.
PLS... 309A	30 mm - 10/10

Available in the colours: AA - AO (AB, AT, CH and SB available on demand with a minimum quantity order of 100 pcs). The code of the selected colour must be added to the article code. E.g.: PLS... 309A (chosen finish anod. silver) PLSAA 309A.

ANODIZED ALUM. punched with screws and screw anchors thermo packed - bar length 0,83 lm - pack. 20 Pcs



Article	Width-thick.
PLS... 308FS	30 mm - 10/10

ANODIZED ALUM. punched with screws and screw anchors thermo packed - bar length 0,93 lm - pack. 20 Pcs



Article	Width-thick.
PLSAA 309FS	30 mm - 10/10

ANODIZED ALUMINIUM punched with screws and screw anchors thermo packed - bar length 1,66 lm - pack. 20 Pcs




Article	Width-thick.
PLS... 3016FS	30 mm - 10/10

ANODIZED ALUMINIUM punched thermo packed - bar length 0,93 lm - pack. 20 Pcs




Article	Width-thick.
PLSAA 309F	30 mm - 10/10

PLS... 30A/309A/308AS/309AS/3010AS/3016AS




PLS... 35A




PLS... 40A




PLS... 30F/309F/308FS/309FS/3016FS



PLS... 35F






PLS... 40F



threshold - joint-cover profiles

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the suitable profile and cut it to the necessary length.


Adhesive version

2. Degrease, wash and clean the solid surface thoroughly.
3. Remove the protective paper from the adhesive. 4. Lay the profile by applying pressure evenly over the whole surface without using a hammer.


Punched version

2. Mark the position of the holes using the existing holes in the profile as reference. 3. Insert the screw anchors into the drilled holes. 4. Fix the profile using flathead screws suitable for the relative slots in the profile.

COLOURS



ON DEMAND MINIMUM 100 PCS by color and height



(Prices to be agreed. Production delay 4/5 weeks)



PROLEVALL 25-35-38-50 are joint - covers in anodized aluminium with gold, silver and bronze finish in various widths with a more or less knurled flat surface, available with self-adhesive backing or punched in various lengths. They are used to join floors of the same or differing material e.g. ceramic tiles, wood, marble, parquet or laminated, mainly to cover flaws created during laying or expansion joints. The chamfered edges ensure perfect adhesion to the floor, while the flat top allows perfect door closure. Recommended for dwellings and public environments with intense pedestrian traffic. Easy to lay; the high-strength elastomer adhesive ensures an excellent grip.

PROLEVALL 25-35-38-50

ANODIZED GOLD AND SILVER
ALUMINIUM WITH SELF-ADHESIVE AND PUNCHED



ANODIZED ALUMINIUM with adhesive thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	Width mm
PLV... 25A	25
PLV... 35A	35
PLV... 38A	38
PLV... 50A	50

Available in the colours: AA - AO (AB, AT, CH and SB available on demand with a minimum quantity order of 100 pcs). The code of the selected colour must be added to the article code. E.g.: PLV... 25A (chosen finish anod. silver) PLVAA 25A.

ANODIZED ALUMINIUM punched thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	Width mm
PLV... 25F	25
PLV... 35F	35
PLV... 38F	38
PLV... 50F	50

Available in the colours: AA - AO (AB, AT, CH and SB available on demand with a minimum quantity order of 100 pcs). The code of the selected colour must be added to the article code. E.g.: PLV... 25F (chosen finish anod. silver) PLVAA 25F.

OFF-CENTRE HOLES ON DEMAND

ANODIZED ALUMINIUM with adhesive thermo packed - bar length 0,93 lm - pack. 20 Pcs



Article	Width mm
PLV... 259AS	25
PLV... 359AS	35
PLV... 389AS	38
PLV... 509AS	50

Available in the colours: AA - AO (AB, AT, CH and SB available on demand with a minimum quantity order of 100 pcs). The code of the selected colour must be added to the article code. E.g.: PLV... 259AS (chosen finish anod. silver) PLVAA 259AS.

ANODIZED ALUM. punched with screws and screw anchors thermo packed - bar length 0,93 lm - pack. 20 Pcs



Article	Width mm
PLV... 259FS	25
PLV... 359FS	35
PLV... 389FS	38
PLV... 509FS	50

PLV... 259FS-359FS available in the colours: AA - AO (AB, AT, CH and SB available on demand with a minimum quantity order of 100 pcs). The code of the selected colour must be added to the article code. E.g.: PLV... 359FS (chosen finish anod. silver) PLVAA 359FS.

ANODIZED ALUMINIUM with adhesive thermo packed - bar length 1,03 lm - pack. 20 Pcs



Article	Width mm
PLV... 3510AS	35

ANODIZED ALUMINIUM with adhesive thermo packed - bar length 1,66 lm - pack. 20 Pcs



Article	Width mm
PLV... 3516AS	35

The code of the selected colour must be added to the article code. E.g.: PLV... 3510AS (chosen colour anodized gold alum.) PLVAO 3510AS.

ANODIZED ALUM. punched with screws and screw anchors thermo packed - bar length 1,03 lm - pack. 20 Pcs




Article	Width mm
PLV... 3510FS	35

ANODIZED ALUM. punched with screws and screw anchors thermo packed - bar length 1,66 lm - pack. 20 Pcs




Article	Width mm
PLV... 3516FS	35

COLOURS




ON DEMAND MINIMUM 100 PCS by color and height




(Prices to be agreed. Production delay 4/5 weeks)

1. Choose the suitable profile and cut it to the necessary length.
- Adhesive version**
2. Degrease, wash and clean the solid surface thoroughly.
3. Remove the protective paper from the adhesive.
4. Lay the profile by applying pressure evenly over the whole surface without using a hammer.
- Punched version**
2. Mark the position of the holes using the existing holes in the profile as reference.
3. Insert the screw anchors into the drilled holes.
4. Fix the profile using flathead screws suitable for the relative slots in the profile.



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS




PROMOQUETTE


ANODIZED GOLD AND SILVER ALUMINIUM WITH OR WITHOUT SELF-ADHESIVE

PROMOQUETTE is an anodized aluminium rounded edging profile with tap-down edge, which is ideal for the clean-cut, elegant finishing of carpeted floors. The carpeting is inserted inside the curved/rounded section, which is then pressed down until the carpeting is secured, thereby also protecting the edge. **PROMOQUETTE** ensures a perfect finish, covering any flaws created during laying and protecting the edge. Easy to lay with the self-adhesive backing ensuring perfect adherence to the floor.

carpet gripper profiles



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Cut the profile to the necessary length.
2. Fix the "PROMOQUETTE" to the floor using screws/nails or double-sided adhesive tape.
3. Insert the carpeting into the curved side with the necessary tension.
4. Apply pressure evenly over the edge of the profile until it closes over and secures the carpeting.



ANODIZED GOLD and SILVER ALUMINIUM ADHESIVE thermo packed - bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm		
PMQ... 12A	7/12		
PMQ... 12	7/12		

"A" at the end of the product code = Item with adhesive
Available in the colours: AA - AO. (AB available on demand with a minimum quantity order of 100 pcs). The code of the selected colour must be added to the article code. E.g.: PMQ... 12A (chosen colour Anodized gold alum.) PMQAO 12A.

ANODIZED GOLD and SILVER ALUMINIUM thermo packed - bar length 0,67 lm - pack. 2 Pcs

Article	H mm		
PMQ... 126/2	7/12		

ANODIZED SILVER ALUMINIUM ADHESIVE thermo packed - bar length 0,73 lm - pack. 20 Pcs

Article	H mm		
PMQAA 127AS	7/12		


ANODIZED GOLD, SILVER and BRONZE ALUM. ADHESIVE thermo packed - bar length 0,83 lm - pack. 20 Pcs

Article	H mm		
PMQ... 128AS	7/12		

ANODIZED GOLD, SILVER and BRONZE ALUM. ADHESIVE thermo packed - bar length 0,93 lm - pack. 20 Pcs

Article	H mm		
PMQ... 129AS	7/12		

COLOURS



ON DEMAND MINIMUM 100 PCS by color and height




(Prices to be agreed. Production delay 4/5 weeks)

PROMOQUETTE FIX


ANODIZED GOLD AND SILVER ALUMINIUM PUNCHED OR NOTCHED

PROMOQUETTE FIX is a profile in anodized aluminium made as a terminal profile to edge carpeted floors held under tension or simply laid with double-sided adhesive tape. Two versions are available: notched or with holes/notches for laying under tension and then permanently fixed with screws/nails; or the punched version to edge without holding under tension. **PROMOQUETTE FIX** ensures an impeccable finish to the edge of carpeting that is not always perfectly cut. It speeds up laying time and the result is attractive.

carpet gripper profiles



EXAMPLES OF LAYING



ANODIZED GOLD and SILVER ALUMINIUM thermo packed - bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H mm		
PMF... 14F	14		
PMFAA 14D	14		


"D" at the end of the product code = Item with notched
"F" at the end of the product code = Punched Item

Available in the colours: AO - AA. (AB available on demand with a minimum quantity order of 100 pcs).
The code of the selected colour must be added to the article code.
E.g.: PMF... 14F (chosen colour anodized gold alum.) PMFAO 14F.


INSTRUCTIONS FOR LAYING

1. Cut the profile to the necessary length.
2. Fix the "PROMOQUETTE FIX" to the floor using screws/nails.
3. Insert the carpeting into the curved side with the necessary tension.
4. Apply pressure evenly over the edge of the profile until it closes over and secures the carpeting.

COLOURS



ON DEMAND MINIMUM 100 PCS by color and height



(Prices to be agreed. Production delay 4/5 weeks)

PROMOQUETTE GIN is a profile in anodized aluminium with tap-down edge for edging or joining floors in carpeting, PVC, linoleum, ceramic tiles/wood, etc. Two versions are available: punched for laying under tension and then permanently fixed with screws/nails or the adhesive version for laying with glue and which can be taken up if required. **PROMOQUETTE GIN** guarantees an impeccable finish and offers the dual function of both joining and of covering any flawed edges of the floors. It speeds up laying time and the result is attractive.

PROMOQUETTE GIN

ANODIZED GOLD, SILVER AND BRONZE ALUMINIUM WITH SELF-ADHESIVE AND PUNCHED



ANODIZED GOLD, SILVER AND BRONZE ALUMINIUM ADHESIVE thermo packed - bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H mm		
PMGAA 813A	8/13		
PMGAO 813A	8/13		
PMGAB 813A	8/13		
PMGAT 813A	8/13		
PMGCH 813A	8/13		
PMGSB 813A	8/13		

Available in the colours: AO - AA - AB (AT, CH and SB available on demand with a minimum quantity order of 100 pcs). The code of the selected colour must be added to the article code. E.g.: PMG... 813F(chosen colour anodized gold alum.) PMGAO 813F.

ANODIZED GOLD, SILVER AND BRONZE ALUMINIUM PUNCHED thermo packed - bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H mm		
PMGAA 813F	8/13		
PMGAO 813F	8/13		
PMGAB 813F	8/13		
PMGAT 813F	8/13		
PMGCH 813F	8/13		
PMGSB 813F	8/13		

COLOURS




ON DEMAND MINIMUM 100 PCS by color and height




(Prices to be agreed. Production delay 4/5 weeks)


carpet gripper profiles



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS




1. Cut the profile to the necessary length. **2.** Fix the "PROMOQUETTE GIN" to the floor using screws/nails or two-sided adhesive tape. **3.** Lay the required floor, inserting the carpeting, PVC, linoleum, ceramic tile or wood under the upper curved part. **4.** Apply pressure evenly on the edges of the profile until they close and secure the flooring on both sides.



An interpretation of:
Heydar Aliyev Cultural Center, Zaha Hadid, BAKU (Azerbaijan), 2012

CURVE AND BENDABLE PROFILES




PRO CURVE LINE

PRO CURVE LINE are a range of profiles that may be curved/shaped, with a special system of perforations allowing them to be bent so that particular geometric shapes may be easily obtained in situ. This allows decorative patterns to be created at will according to technical and aesthetic requirements. The profiles in the PRO CURVE LINE may be used as transition or edging profiles or to create joining and expansion joints on any type of ceramic, parquet, wood, laminated/melamine coated wood, marble, carpeted, Palladian, Venetian floor, etc. The profiles are made in AISI 304/1.4301-V2A stainless steel, aluminium and brass and may be easily shaped by using the PROCURVE MACHINE to bend the profiles mechanically.

PROTERMINAL CURVE

STAINLESS STEEL AISI 304/1.4301-V2A
CURVABLE

PROTERMINAL CURVE are a range of edging and joining profiles that may be curved/shaped, with a special system of perforations allowing them to be bent so that particular geometric shapes may be easily obtained in situ. This allows decorative patterns to be created at will according to technical and aesthetic requirements and with a separation of 3 mm. The product is made in stainless steel AISI 304/1.4301-V2A in various heights (6, 8, 10, 12,5, 15 and 20 mm) in 2.7 m bars.



POLISHED STAINLESS STEEL AISI 304/1.4301-V2A with protective film
bar length 2,7 lm - pack. 20 Pcs - 54 lm - 10/10 mm


Article	H mm
PTACCV 06	6
PTACCV 08	8
PTACCV 10	10
PTACCV 125	12,5
PTACCV 15	15
PTACCV 20	20



COLOURS



EXAMPLES OF LAYING



LAYING INSTRUCTIONS

1. Choose the "PROTERMINAL CURVE" with the required height and material. 2. Cut the profile to the necessary length, calculating the total length. 3. Bend the profile mechanically with the PROCURVE MACHINE. 4. If necessary fix with screws and screw anchors or simply insert the punched base under the floor laid with the same adhesive. If it is used as a joining profile, bring each floor to the edge of the profile.





SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS

PROTERMINAL CURVE are a range of edging and joining profiles that may be curved/shaped. They feature a special system of perforations allowing them to be bent easily so that particular geometric shapes may be easily obtained in situ. This allows decorative patterns to be created at will according to technical and aesthetic requirements and with a separation of 3 mm of sandable profile. The product is made in natural brass in 2.7 m bars and heights of 6, 8, 10, 12.5, 15 and 20 mm.

PROTERMINAL CURVE


NATURAL BRASS CURVABLE




NATURAL BRASS CURVABLE thermo packed 10pcs
bar length 2,7 lm - pack. 40 Pcs - 108 lm (H:15; 20 mm - 54 lm)

Article	H mm
PTONCV 06	6
PTONCV 08	8
PTONCV 10	10
PTONCV 125	12,5
PTONCV 15	15
PTONCV 20	20


COLOURS



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the "PROTERMINAL CURVE" in the required height and material. 2. Cut the profile to the necessary length, calculating the total length. 3. Bend the profile mechanically with the PROCURVE MACHINE. 4. If necessary fix with screws and screw anchors or simply insert the punched base under the floor laid with the same adhesive. Any oxidation marks may be easily removed with specific chemical products (Sidol-Smac, etc.). If it is used as a joining profile, bring each floor to the edge of the profile.



PROTERMINAL CURVE are a range of edging and joining profiles that may be curved/shaped. They feature a special system of perforations allowing them to be bent easily so that particular geometric shapes may be easily obtained in situ. This allows decorative patterns to be created at will according to technical and aesthetic requirements and with a separation of 3 mm of sandable profile. The product is made in natural aluminium in 2.7 m bars and heights of 6, 8, 10, 12.5, 15 and 20 mm.

PROTERMINAL CURVE


NATURAL ALUMINIUM CURVABLE



NATURAL ALUMINIUM CURVABLE thermo packed 10 Pcs
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm
PTANCV 06	6
PTANCV 08	8
PTANCV 10	10
PTANCV 125	12,5
PTANCV 15	15
PTANCV 20	20



COLOURS



ANODIZED SILVER ALUMINIUM CURVABLE thermo packed 10 Pcs
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm
PTAACV 08	8
PTAACV 10	10
PTAACV 125	12,5
PTAACV 15	15

EXAMPLES OF LAYING (for laying instructions, see above)






PROLEGANT CURVE are a range of edging and joining profiles that may be curved/shaped. They feature a special system of perforations allowing them to be bent easily so that particular geometric shapes may be easily obtained in situ. This allows decorative patterns to be created at will according to technical and aesthetic requirements and with a separation of 6 mm of sandable profile. The product is made in natural brass in 2.7 m bars and heights of 8-10-12.5 and 14 mm.

PROLEGANT CURVE



NATURAL BRASS CURVABLE




NATURAL BRASS CURVABLE thermo packed 5 Pcs
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H mm		
PELONCV 08	8		
PELONCV 10	10		
PELONCV 125	12,5		
PELONCV 14	14		

COLOURS



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS




1. Choose the "PROLEGANT CURVE" in the required height and material. 2. Cut the profile to the necessary length, calculating the total length. 3. Bend the profile mechanically with the PROCURVE MACHINE. 4. If necessary fix with screws and screw anchors or simply insert the punched base under the floor laid with the same adhesive. Any oxidation marks may be easily removed with specific chemical products (Sidol-Smac, etc.).

PROLEGANT CURVE are a range of edging and joining profiles that may be curved/shaped. They feature a special system of perforations allowing them to be bent easily so that particular geometric shapes may be easily obtained in situ. This allows decorative patterns to be created at will according to technical and aesthetic requirements and with a separation of 6 mm of sandable profile. The product is made in silver anodized aluminium in 2.7 m bars and heights of 8-10-12.5 mm.


PROLEGANT CURVE

ANODIZED SILVER ALUMINIUM CURVABLE




ANODIZED SILVER ALUMINIUM CURVABLE thermo packed
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H mm		
PELAACV 08	8		
PELAACV 10	10		
PELAACV 125	12,5		



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS




1. Choose the "PROLEGANT CURVE" in the required height and material. 2. Cut the profile to the necessary length, calculating the total length. 3. Bend the profile mechanically with the PROCURVE MACHINE. 4. If necessary fix with screws and screw anchors or simply insert the punched base under the floor laid with the same adhesive. Any oxidation marks may be easily removed with specific chemical products (Sidol-Smac, etc.).

* = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed


PROFINAL CURVE

NATURAL BRASS
CURVABLE


PROFINAL CURVE are a range of edging and joining profiles that may be curved/shaped. They feature a special system of perforations allowing them to be bent easily so that particular geometric shapes may be easily obtained in situ. This allows decorative patterns to be created at will according to technical and aesthetic requirements and with a separation of 8 mm of sandable profile. The product is made in natural brass in 2.7 m bars and heights of 8, 10 and 12.5 mm.



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS




1. Choose the "PROFINAL CURVE" in the required height and material. 2. Cut the profile to the necessary length, calculating the total length. 3. Bend the profile mechanically with the PROCURVE MACHINE. 4. If necessary fix with screws and screw anchors or simply insert the punched base under the floor laid with the same adhesive. Any oxidation marks may be easily removed with specific chemical products (Sidel-Smac, etc.). If it is used as a joining profile, bring each floor to the edge of the profile.



NATURAL BRASS CURVABLE thermo packed 5 Pcs
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H mm		
PRFONCV 08	8		
PRFONCV 10	10		
PRFONCV 125	12,5		


COLOURS




PROFINAL CURVE

ANODIZED SILVER ALUMINIUM
CURVABLE

PROFINAL CURVE are a range of edging and joining profiles that may be curved/shaped. They feature a special system of perforations allowing them to be bent easily so that particular geometric shapes may be easily obtained in situ. This allows decorative patterns to be created at will according to technical and aesthetic requirements and with a separation of 8 mm of sandable profile. The product is made in silver anodized aluminium in 2.7 m bars and heights of 8, 10 and 12.5 mm.



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the "PROFINAL CURVE" in the required height and material. 2. Cut the profile to the necessary length, calculating the total length. 3. Bend the profile mechanically with the PROCURVE MACHINE. 4. If necessary fix with screws and screw anchors or simply insert the punched base under the floor laid with the same adhesive. Any oxidation marks may be easily removed with specific chemical products (Sidel-Smac, etc.). If it is used as a joining profile, bring each floor to the edge of the profile.



ANODIZED SILVER ALUMINIUM CURVABLE thermo packed - bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H mm		
PRFAACV 08	8		
PRFAACV 10	10		
PRFAACV 125	12,5		


COLOURS



PROJOLLY CURVE is a range of terminal transition profiles that may be curved/shaped, with a special system of perforations allowing it to be bent so that particular geometric shapes may be easily obtained in situ. This allows decorative patterns to be created at will according to technical and aesthetic requirements. It is made in natural brass, height H 8 - H 10mm, length 2.7 lm.

PROJOLLY CURVE

NATURAL BRASS CURVABLE



PJONCV 08




PJONCV 10




NATURAL BRASS CURVABLE thermo packed 5 Pcs
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H mm		
PJONCV 08	8		
PJONCV 10	10		


COLOURS



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the "PROJOLLY CURVE" in the required height and material.
2. Cut the profile to the necessary length, calculating the total length.
3. Bend the profile mechanically with the PROCURVE MACHINE.
4. If necessary fix with screws and screw anchors or simply insert the punched base under the floor laid with the same adhesive.



PROJOLLY CURVE is a range of terminal transition profiles that may be curved/shaped, with a special system of perforations allowing it to be bent so that particular geometric shapes may be easily obtained in situ. This allows decorative patterns to be created at will according to technical and aesthetic requirements. It is made in anodized aluminium, height H 8 -H 10mm, length 2.7 lm.

PROJOLLY CURVE

ANODIZED SILVER ALUMINIUM CURVABLE



PJAACV 08



PJAACV 10




ANODIZED SILVER ALUMINIUM CURVABLE thermo packed
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H mm		
PJAACV 08	8		
PJAACV 10	10		

COLOURS



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS




1. Choose the "PROJOLLY CURVE" in the required height and material.
2. Cut the profile to the necessary length, calculating the total length.
3. Bend the profile mechanically with the PROCURVE MACHINE.
4. If necessary fix with screws and screw anchors or simply insert the punched base under the floor laid with the same adhesive.



TERMINAL CURVE

ANODIZED SILVER ALUMINIUM AND 10 WOOD FINISHES - CURVABLE

TERMINAL CURVE is a range of edging and joining profiles that may be curved/shaped, with a special system of perforations allowing it to be bent so that particular geometric shapes may be easily obtained in situ. This allows decorative patterns to be created at will according to technical and aesthetic requirements. Recommended for edging and/or joining floating floors in wood & melamine-laminated wood. It is made in anodized aluminium and in 10 wood effect finishes; it comes in various heights, length 2.7m.



ANODIZED SILVER ALUMINIUM CURVABLE thermo packed
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H mm		
PINTAACV 07	7		
PINTAACV 09	9		
PINTAACV 11	11		
PINTAACV 15	15		


ALUMINIUM 10 WOOD FINISHES thermo packed
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H mm		
PINT... CV 09	9		
PINT... CV 15	15		

Available in the wood finishes: 04W-05W-07W-08W-09W-10W-11W-28W-29W-30W.

The code of the selected colour must be added to the article code. E.g.: PINT... CV 09 (chosen finish Dark beech) PINT04W CV 09.

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS




1. Choose the "TERMINAL CURVE" in the required height and material.
2. Cut the profile to the necessary length, calculating the total length.
3. Bend the profile mechanically with the PROCURVE MACHINE.
4. If necessary fix with screws and screw anchors or simply insert the punched base under the floor laid with the same adhesive.

ANODIZED COLOURS ON DEMAND




WOODEN COLOURS




PROCOVER PROCOVER WOOD

ANODIZED ALUMINIUM AND WOOD FINISHES - CURVABLE

PROCOVER is a joint-cover profile in anodized aluminium and aluminium covered with a very strong film available in wood finishes. It is applied at the end of laying two adjoining floors with the same height, having left a 6 - 24 mm gap between the two floors set in a thin bed of adhesive. It protects the outside edges of the floor/covering. It is easy to lay and attractive. The design of the profile with lower vertical arrowhead part allows excellent anchorage with the silicone/adhesive.



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the "PROCOVER" with the width suitable for the gap between the two floors to be joined, taking into consideration 2/3 mm side lap.
2. Fill the gap with single-pack silicone or with the adhesive used for laying the floor.
3. Bury the profile into the adhesive, making sure that both side laps of the profile rest on the coverings to be joined.



ANODIZED SILVER ALUMINIUM CURVABLE thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm


Article	H mm		
PCRAA 149	14 x 9		
PCRDB 149	14 x 9		

ALUMINIUM WOOD FINISHES thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	L x H mm		
PCRA... 149	14 x 9		

Available in the wood finishes: 05W-11W-28W-29W-30W. The code of the selected colour must be added to the article code. E.g.: PCRA...149 (chosen finish Dark beech) PCRA 04W 149.

COLOURS



PROSLIDER CURVE is a range of transition profiles that may be curved/shaped, with a special system of perforations allowing it to be bent so that particular geometric shapes may be easily obtained in situ. This allows decorative patterns to be created at will according to technical and aesthetic requirements. Recommended for joining floating floors in wood, melamine laminated wood and ceramics. It is made in natural brass in various heights, length 2.7 lm.

PROSLIDER CURVE


NATURAL BRASS CURVABLE



NATURAL BRASS CURVABLE thermo packed
bar length 2,7 lm - pack. 15 Pcs - 40,5 lm

Article	H mm		
PDONCV 08	8		
PDONCV 10	10		

COLOURS



LAYING INSTRUCTIONS

1. Choose the "PROSLIDER CURVE" in the required height and material.
2. Cut the profile to the necessary length, calculating the total length.
3. Bend the profile mechanically with the PROCURVE MACHINE.
4. If necessary fix with screws and screw anchors, if used for floating floors in melamine/laminated wood, or simply insert the punched base under the floor laid with the same adhesive.


PDONCV 08



PDONCV 10



EXAMPLES OF LAYING



PROSLIDER CURVE is a range of transition profiles that may be curved/shaped, with a special system of perforations allowing it to be bent so that particular geometric shapes may be easily obtained in situ. This allows decorative patterns to be created at will according to technical and aesthetic requirements. Recommended for joining floating floors in wood, melamine laminated wood and ceramics. It is made in anodized aluminium in various heights, length 2.7 lm.

PROSLIDER CURVE

ANODIZED SILVER ALUMINIUM CURVABLE



ANODIZED SILVER ALUMINIUM CURVABLE thermo packed
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H mm		
PDAACV 08	8		
PDAACV 10	10		

COLOURS



PDAACV 08



PDAACV 10



PROCURVE MACHINE is a manual profile bending machine for profiles of the CURVE SERIES. complete with wheels for all profiles

PROCURVE MACHINE

Article	
PCM 08	PROCURVE MACHINE







Page	Items / series available for	MINIMUM INSIDE RADIUS	MINIMUM OUTSIDE RADIUS
100	PTACCV	30 cm	30 cm
101	PTONCV	30 cm	30 cm
101	PTANCV	30 cm	30 cm
103	PELONCV	150 cm	300 cm
103	PELAACV	200 cm	300 cm
104	PRFONCV	200 cm	
104	PRFAACV	200 cm	
105	PJONCV	200 cm	300 cm
105	PJAACV	200 cm	300 cm
106	PINTAACV	300 cm	
106	PCRAA 149	80 cm	80 cm
106	PCRA... 149	100 cm	100 cm
107	PDONCV	300 cm	
107	PDAACV	300 cm	

* = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed



An interpretation of:
Elbphilharmonie, Herzog & De Meuron, HAMBURG (Germany), 2017


STAIR NOSINGS PROFILES




PROSTAIR ACC

BRUSHED STAINLESS STEEL AISI 304/1.4301-V2A

PROSTAIR ACC is steps protecting technical profile, designed and conceived to make the step scales made of ceramic, porcelain stoneware and others nonskid and non-slip ones ; it's to be applied before the step laying process. Manufactured in aisi 304/1.4301-V2A glazed stainless steel, with the superior side level crimped in order to increase its adhesion. It replaces special ceramic elements in refined, resistant and economic way. It is compulsory in public places for the accident prevention. It is recommended for elegant, refined industrial, commercial and private environments; available in H 4,5-6-8-10-12,5-15 mm versions. Combining with the entire series of steel profiles recommended.



EXAMPLES OF LAYING



BRUSHED STAINLESS ST. AISI 304/1.4301-V2A with protective film
bar length 2,7 lm - pack. 15 Pcs - 40,5 lm - 10/10 mm

Article	H mm		
PTRACS 045	4,5		
PTRACS 06	6		
PTRACS 08	8		
PTRACS 10	10		
PTRACS 125	12,5		
PTRACS 15	15		

Available in Brushed STAINLESS STEEL AISI 316L/1.440-V4A (minimum quantity order 100 pcs - price to be agreed. Production delay 4/5 weeks).


LAYING INSTRUCTIONS

1. Choose the PROSTAR ACC of the desired height and material on the basis of the tile (steps) thickness. 2. Fix the first rising part laying it down at its appropriate and definitive level. 3. Fill completely the empty spaces under the profile with the tile adhesive. 4. Spread out the adhesive on the tread, lay down the profile with its cut base immersed completely in adhesive and align it so that the profile covers the riser tile edge. 5. Lay down the tread tiles and align them with the superior grazing part of the profile by drawing its back close and filling the inner space with the adhesive.


END CAP IN VARNISHED PLASTIC BRUSHED STAINLESS STEEL EFFECT
pack. 2 Pcs (1 right and 1 left)

Article	H mm		
TPTRACS/1	4,5 ÷ 15		

Articles not for sale singly



COLOURS




ACS - Brushed stainless st. AISI 304/1.4301-V2A

SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS


PROSTYLE 2610

BRUSHED STAINLESS STEEL AISI 304/1.4301-V2A
SELF ADHESIVE OR PUNCHED

PROSTYLE 2610 is steps protecting technical profile, designed and conceived to keep the step scales made of ceramic, porcelain stoneware, wood, marble and others nonskid and non-slip ones ; it's to be applied after the step laying process or in the already present rooms. Manufactured in aisi 304/1.4301-V2A glazed stainless steel, with the superior side level crimped in order to increase its adhesion. It replaces special ceramic elements in refined, resistant and economic way. It's ideal for the edges protection and screening as well as of the corner between the rising and the tread which is the point of the greatest strain. It is compulsory in public places for the accident prevention. It is recommended for elegant, refined industrial, commercial and private environments. Available in drilled version or in with adhesive one.



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



Adhesive version

1. Choose the suitable profile and cut it to the necessary length. 2. Degrease, wash and clean the solid surface thoroughly. 3. Remove the protective paper from the adhesive. 4. Lay the profile by applying pressure evenly over the whole surface without using a hammer.

Punched version

1. Choose the suitable profile and cut it to the necessary length. 2. Mark the position of the holes using the existing holes in the profile as reference. 3. Insert the screw anchors into the drilled holes. 4. Fix the profile using flathead screws suitable for the relative slots in the profile.



BRUSHED STAINLESS STEEL AISI 304/1.4301-V2A PUNCHED with
protective film - bar length 2,7 lm - pack. 20 Pcs - 54 lm - 10/10mm


Article	H mm		
PSYACS 2610F	10		

Available in Brushed STAINLESS STEEL AISI 316L/1.440-V4A (minimum quantity order 100 pcs - price to be agreed. Production delay 4/5 weeks).

BRUSHED STAINLESS STEEL AISI 304/1.4301-V2A WITH ADHESIVE with
protective film - bar length 2,7 lm - pack. 20 Pcs - 54 lm - 10/10mm

Article	H mm		
PSYACS 2610A	10		

COLOURS



ACS - Brushed stainless st. AISI 304/1.4301-V2A

SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS







PROSTAIR GRIP ACC is an AISI 304/1.4301-V2A brushed stainless steel profile, consisting of a punched flange, ensuring perfect anchorage to the substrate, a 36,5 and 56,5mm horizontal visually exposed surface with the carborundum stripe insert and a 20mm vertical visually exposed surface. The profile is available in the heights 4,5/6/8/10/12,5/15/20 mm and is equipped with end caps made of varnished plastic in brushed steel-effect finish. The design of this profile together with the completing elements make it an elegant and appreciated solution also for modern stairs.

PROSTAIR GRIP ACC

BRUSHED STAINLESS STEEL AISI 304/1.4301-V2A



BRUSHED STAINLESS STEEL AISI 304/1.4301-V2A with protective film - bar length 2,7 lm - width 36,50 mm

Article	H mm	Pcs/Pack
PTRGRACS 04535	4,5	20
PTRGRACS 0635	6	20
PTRGRACS 0835	8	20
PTRGRACS 1035	10	10
PTRGRACS 12535	12,5	10
PTRGRACS 1535	15	7
PTRGRACS 2035	20	7

BRUSHED STAINLESS STEEL AISI 304/1.4301-V2A with protective film - bar length 2,7 lm - width 56,50 mm


Article	H mm	Pcs/Pack
PTRGRACS 04555	4,5	20
PTRGRACS 0655	6	20
PTRGRACS 0855	8	20
PTRGRACS 1055	10	10
PTRGRACS 12555	12,5	10
PTRGRACS 1555	15	7
PTRGRACS 2055	20	7

THE ADHESIVE CARBORUNDUM STRIP (PROGRIP) IS NOT INCLUDED WITH THE PROFILE.

FOR PTRGRACS ...35 ORDER PGR... 25 (SPECIFY THE CHOSEN COLOUR).

FOR PTRGRACS ...55 ORDER PGR... 40 (SPECIFY THE CHOSEN COLOUR).

COLOURS




ACS - Brushed stainless st. AISI 304/1.4301-V2A

END CAPS - R/L - pack. 2 Pcs (1 R and 1 L)


Article	H mm	L mm
TPTRGRACS 55/1	4,5+20	56,5
TPTRGRACS 35/1	4,5+20	36,5

Articles not for sale singly



SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the PROSTAIR GRIP ACC in the required height, according to the thickness of the floor covering and the desired profile width;
2. Lay the floor covering on the stair riser and apply the adhesive on the of stair tread, where the profile will be installed;
3. Fill the empty spaces under the profile with the adhesive for tiles. Lay the profile on the step tread, making sure that it is aligned with the stair riser;
4. Lay the floor covering on the stair tread and align;
5. Plaster the joints between the profile and the tiles.

PROGRIP is a carborundum adhesive stripe, consisting of an elastic film coated with high wear resistant abrasive grains. It is usually employed in public as well as in domestic environments to make stair steps non-slip. The stripe is available in different colors and widths to meet any technical and aesthetic requirement. If **PROGRIP** is applied directly on the step covering, it is advisable to apply two stripes on each step, rounding their ends.

PROGRIP

ADHESIVE CARBORUNDUM - 7 COLOURS

COLOURS

N - Black	B - White	T - Transparent
G - Gray	Y - Yellow	M - Brown
GN - Yellow/Black	The PGRN (transparent) are not suitable for outside use.	

ADHESIVE NON-SLIP STRIP for STEPS - rolls length 18,2 lm

Article	Width mm
PGRGN 20	20
PGRGN 25	25
PGRGN 50	50

ADHESIVE NON-SLIP STRIP for STEPS - rolls length 18,2 lm

Article	Width mm
PGRN 25	25
PGRB 25	25
PGRT 25	25
PGRG 25	25
PGRY 25	25
PGRM 25	25
PGRN 40	40
PGRB 40	40
PGRT 40	40
PGRG 40	40
PGRY 40	40
PGRM 40	40





* = Production on demand with minimum quantity of 10 rolls. Production delay 4/5 weeks. Price to be agreed

News 2023

PROSTYLE GRIP ACC

BRUSHED STAINLESS STEEL
AISI 304/1.4301-V2A


PROSTYLE GRIP ACC is a non-slip profile in AISI 304/1.4301-V2A brushed stainless steel, consisting of a 40 or 60 mm horizontal top with a groove for the insertion of a non-slip carborundum stripe and a 20mm vertical flat side. The profile can be fixed with adhesive film or with screws. The particular design of this profile makes it an elegant and appreciated solution also for modern stairs.



PSYGRACS 6020

PSYGRACS 4020

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS





Version with adhesive

1. Choose the profile according to the desired width and cut it to the necessary length; 2. Clean the surface on which the profile is to be laid, ensuring that it is dry. Remove the protective film and place the profile, applying adequate pressure on it; 3. Apply the adhesive non-slip carborundum insert of the desired color.

Punched version

1. Choose the profile according to the desired width and cut it to the necessary length; 2. Mark the position of the holes using the existing holes on the profile as reference; 3. Drill the step using a drill with 5mm diameter and insert the 5x 25mm screws; 4. Screw the profile to the step; 5. Apply the adhesive non-slip carborundum insert of the desired color.



BRUSHED STAINLESS STEEL AISI 304/1.4301-V2A with protective film
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	L mm		
PSYGRACS 6020A	60		*
PSYGRACS 6020F	60		*

BRUSHED STAINLESS STEEL AISI 304/1.4301-V2A with protective film
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	L mm		
PSYGRACS 4020A	40		
PSYGRACS 4020F	40		

The adhesive carborundum strip (PROGRIP) is not included with the profile.

For PSYGRACS 6020A/F order PGR... 40 (Specify the chosen colour).

For PSYGRACS 4020A/F order PGR... 25 (Specify the chosen colour).

COLOURS



ACS - Brushed stainless steel
AISI 304/1.4301-V2A

END CAPS STAINLESS STEEL - R/L - pack. 2 Pcs - (1 R and 1 L)

Article	L mm		
TPSYGRACS 6020/1	60		
TPSYGRACS 4020/1	40		

Articles not for sale singly

SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS

* = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed

PROGRIP

ADHESIVE CARBORUNDUM - 7 COLOURS

PROGRIP is a carborundum adhesive stripe, consisting of an elastic film coated with high wear resistant abrasive grains. It is usually employed in public as well as in domestic environments to make stair steps non-slip. The stripe is available in different colors and widths to meet any technical and aesthetic requirement. If **PROGRIP** is applied directly on the step covering, it is advisable to apply two stripes on each step, rounding their ends.



ADHESIVE CARBORUNDUM NON-SLIP STRIP for STEPS

rolls length 18,2 lm

Article	Width mm		
PGRN 25	25		
PGRB 25	25		
PGRG 25	25		
PGRY 25	25		
PGRM 25	25		
PGRN 40	40		
PGRB 40	40		
PGRG 40	40		
PGRY 40	40		
PGRM 40	40		

COLOURS

N - Black	B - White	T - Transparent
G - Gray	Y - Yellow	M - Brown
GN - Yellow/Black	The PGRT (transparent) are not suitable for outside use.	

ADHESIVE NON-SLIP STRIP for STEPS - rolls length 18,2 lm

Article	Width mm		
PGRGN 20	20		
PGRGN 25	25		
PGRGN 50	50		

* = Production on demand with minimum quantity of 10 rolls. Production delay 4/5 weeks. Price to be agreed

News 2023

PROSTAIR 50 is a technical square used to make the step nonskid and non-slip, protects the ceramic stairs steps preventing from accidents. It is made up of a rigid aluminium base equipped with a particular toothing on the vertical stem which strengthens the anchorage of the adhesive/tile to the square. The aluminium base varies according to the thickness of the tile used in the step, and to a lined insert in vinyl rubber available in several colors. The insert is already applied to the aluminium base. It is compulsory in public places in compliance with EEC norms and prevents from accidents.

PROSTAIR 50

NATURAL ALUMINIUM
+ VINYL RESIN / RUBBER INSERT







NATURAL ALUMINIUM + VINYL RESIN / RUBBER INSERT
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H mm		
PTR50 08...	8		
PTR50 10...	10		
PTR50 125...	12,5		
PTR50 15...	15		

Available in the colours: G - N - B - A.
The code of the selected colour must be added to the article code.
E.g.: PTR50 08... (chosen colour grey) PTR50 08G.

COLOURS






		
G - Gray (E83)	N - Black (E85)	B - Beige (E84)
		
A - Ivory (E81)		

END CAP IN PVC - pack. 2 Pcs (1 R and 1 L)


Article	H mm
TPTR50 .../1	8-10-12,5-15

Available in the colours: G - N - B - A.
The code of the selected colour must be added to the article code.
E.g.: TPTR50 ... (chosen colour grey) TPTR50 G.

Articles not for sale singly



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose a PROSTAIR 50 height and color corresponding to the thickness of the tile. 2. Fix the riser laying it at the appropriate and definitive height. 3. Fill the empty spaces under the square completely with adhesive. 4. Rest the adhesive on the tread, lay the square with the base cut in the adhesive and line it up so that the square covers the tile edge of the riser. 5. Lay the tiles of the tread lining them up with upper part of the square so that it meets with the edge.

INTERCHANGEABLE INSERT for Prostairs 50

VINYL RESIN / RUBBER

INTERCHANGEABLE VINYL RESIN / RUBBER INSERT
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H mm		
PTG50...	8-10-12,5-15		


Universal insert suitable for four profile heights.
Available in the colours: G - N - B - A.
The code of the selected colour must be added to the article code.
E.g.: PTG50... (chosen colour grey) PTG50 G.




PROSTAIR

NATURAL ALUMINIUM
+ VINYL RESIN / RUBBER INSERT

PROSTAIR is a step nosing profile used to improve slip and slide resistance on the step, to protect ceramic steps and to prevent accidents. It consists of a rigid aluminium base and a changeable vinyl rubber insert available in various colours and widths. Compulsory in public environments to comply with EEC accident-prevention standards.



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the PROSTEP/PROSTAIR in the required width and colour according to the thickness of the tile. 2. First fix the riser part, placing it at the correct and final height. 3. Fill the empty spaces under the profile with the tile adhesive. 4. Apply the adhesive to the tread, lay the profile with the punched base fully sunk into the adhesive and align the profile so that its lip covers the edge of the riser tile. 5. Lay the tread tiles, aligning them so that they are flush with the upper and rear part of the profile.







INTERCHANGEABLE VINYL RESIN / RUBBER INSERT

bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article		
PTGRA		
PTGRB		
PTGRN		
PTGRG		



COLOURS

 G - Gray (E83)	 N - Black (E85)	 B - Beige (E84)
 A - Ivory (E81)		

NATURAL ALUMINIUM + VINYL RESIN / RUBBER INSERT

bar length 2,7 lm - pack. 10 Pcs - 27 lm


Article	H mm		
PTR 08...	8		
PTR 10...	10		
PTR 125...	12,5		

Available in the colours: G - N - B - A. The code of the selected colour must be added to the article code. E.g.: PTR 08... (chosen colour grey) PTR 08G.

END CAP IN PVC - pack. 2 Pcs (1 R and 1 L)

Article	H mm		
TPT 08.../1	8		
TPT 10.../1	10		
TPT 125.../1	12,5		


Available in the colours: G - N - B - A. The code of the selected colour must be added to the article code. E.g.: TPT 08... (chosen colour grey) TPT 08G. Articles not for sale singly



PROSTEP

RIGID VINYL RESIN
+ VINYL RESIN / RUBBER INSERT

PROSTEP is a step nosing profile used to improve slip and slide resistance on the step, to protect ceramic steps and to prevent accidents. It consists of a rigid base in high-strength vinyl resin and a changeable vinyl rubber insert available in various colours and widths. Compulsory in public environments to comply with EEC accident-prevention standards.




For instructions see the product above







INTERCHANGEABLE VINYL RESIN / RUBBER INSERT

bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article		
PTGRA		
PTGRB		
PTGRN		
PTGRG		



COLOURS

 G - Gray (E83)	 N - Black (E85)	 B - Beige (E84)	 A - Ivory (E81)
--	---	--	---

IMPACT PROOF VINYL RESIN + VINYL RESIN / RUBBER INSERT

bar length 2,7 lm - pack. 10 Pcs - 27 lm (PTP 08... - 54 lm)


Article	H mm		
PTP 08...	8		
PTP 10...	10		
PTP 125...	12,5		

Available in the colours: G - N - B - A. The code of the selected colour must be added to the article code. E.g.: PTP 08... (chosen colour grey) PTP 08G.

END CAP IN PVC - pack. 2 Pcs (1 R and 1 L)

Article	H mm		
TPT 08.../1	8		
TPT 10.../1	10		
TPT 125.../1	12,5		


Available in the colours: G - N - B - A. The code of the selected colour must be added to the article code. E.g.: TPT 08... (chosen colour grey) TPT 08G. Articles not for sale singly



PROBRASTE is a very elegant step nosing profile used to improve slip and slide resistance on the step. Made in natural and polished brass or natural and anodized silver aluminium, the upper part is knurled to increase adherence. Compulsory in public buildings to comply with accident-prevention regulations. Recommended for elegant, refined surroundings and for steps in wood, tiles, melamine-coated/laminated wood, marble or natural stones. Width: 8, 10, 12.5 mm.

PROBRASTE

KNURLED NATURAL AND POLISHED BRASS
NATURAL AND ANODIZED SILVER ALUMINIUM



NATURAL BRASS thermo packed 5 Pcs
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H mm		
PBPON 10	10		*
PBPON 125	12,5		

NATURAL ALUMINIUM thermo packed 5 Pcs
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H mm		
PBPAN 08	8		
PBPAN 10	10		
PBPAN 125	12,5		


POLISHED BRASS thermo packed
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H mm		
PBPOL 10	10		*
PBPOL 125	12,5		*

ANODIZED SILVER ALUMINIUM thermo packed
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H mm		
PBPAA 08	8		
PBPAA 10	10		
PBPAA 125	12,5		

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the PROBRASTE in the required width and colour according to the thickness of the tile (stairs). 2. First fix the riser part, placing it at the correct and final height. 3. Fill the empty spaces under the profile with the tile adhesive. 4. Apply the adhesive to the tread, lay the profile with the punched base fully sunk into the adhesive and align the profile so that its lip covers the edge of the riser tile. 5. Lay the tread tiles, aligning them so that they are flush with the upper and rear part of the profile and filling the internal part with adhesive. Oxidation marks in the polished/natural brass range may be easily removed with specific chemical products (Sidel-Smac).

COLOURS



PROSTAIR BOTTON / STRIP are a tactile anti-slip botton/strip made in stainless steel AISI 316/1.4401-V4A. **PROSTAIR BOTTON / STRIP** has the function to realize the signaling lanes to the floor, and warning stairs, able to guide the blind and visually impaired. It is available with a length of 28.5 cm, a width of 3.5 cm and a thickness of 5mm and is provided with 3 stems, 2 cm high, for its fastening.

PROSTAIR BOTTON / STRIP

POLISHED, BRUSHED STAINLESS STEEL AISI 316/1.4404-V4A



PROSTAIR BOTTON
POLISHED STAINLESS STEEL AISI 316/1.4404-V4A - pack. 20 Pcs

Article	Ø mm		
PTRB 3520/20	35		

PROSTAIR BOTTON STRIP
BRUSHED STAINLESS STEEL AISI 316/1.4404-V4A - pack. 10 Pcs

Article	L x H mm		
PTRB 28035/10	280 X 35		


INSTRUCTIONS FOR LAYING METHODS

1. Put PROSTAIR BOTTON TEMPLATE on the desired zone. 2. Score on the support the position of the necessary holes. 3. Remove the template and drill the substrate with a tip 4 mm for a depth of approximately 2.5 cm. 4. Open the holes already made with a 8mm drill bit. 5. Remove dust residues. 6. Fill the hole with PROBAND FIX. 7. Put in the hole PROSTAIR BOTTON.


INSTRUCTIONS FOR LAYING METHODS

1. Put PROSTAIR BOTTON STRIP on the desired zone. 2. Scoring on the support in correspondence of the stems the points at which pierce. 3. Drill the substrate with a tip 4 mm for a depth of approximately 2.5 cm. 4. Open the holes already made with a 8mm drill bit. 5. Remove dust residues. 6. Fill the hole with PROBAND FIX. 7. Put in the hole PROSTAIR BOTTON STRIP.

PTRB 3520



PTRB 28035




PROSTAIR BOTTON TEMPLATE for PROSTAIR BOTTON

ZINC-PLATED STEEL

PROSTAIR BOTTON TEMPLATE is a mold, made in zinc-plated steel, which allows to score the points where to drilling for the mounting of PROSTAIR BOTTON. **PROSTAIR BOTTON TEMPLATE** has a Size of 30 x 44.5 cm and is equipped with 48 holes of a diameter 4 mm. Provided with circular joints which can be connected to other molds.

ZINC-PLATED STEEL
pack. 4 Pcs

Article	L x H mm		
PTRTEM/4	445 x 300		





* = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed

PROTERMSTEP ACC

POLISHED, BRUSHED STAINLESS
STEEL AISI 304/1.4301-V2A

PROTERMSTEP ACC is the new step cover profile made of stainless steel. Designed to protect the edge of the step and to hide the joint between the tread and the step rise. The special notched shape in the upright stem provides it with excellent anchorage between floor/glue/profile. Reversible profile.



EXAMPLES OF LAYING for instructions see the product below



POLISHED STAINLESS STEEL AISI 304/1.4301-V2A with protective film
bar length 2,7 lm - pack. 15 Pcs - 40,5 lm

Article	h / H mm		
PTSPAC 0815	08 / 15		
PTSPAC 10125	10 / 12,5		
PTSPAC 1530	15 / 30		
PTSPAC 2025	20 / 25		

EXTERNAL CORNERS - pack. 10 Pcs

Article	h / H mm		
REPTSAC 0815/10	08 / 15		
REPTSAC 10125/10	10 / 12,5		
REPTSAC 1530/10	15 / 30		
REPTSAC 2025/10	20 / 25		

JUNCTION H 10 - 12,5 - 15 - 20 mm - pack. 10 Pcs

Article	h / H mm		
GIPTSAC 0815/10	08 / 15		
GIPTSAC 10125/10	10 / 12,5		
GIPTSAC 1530/10	15 / 30		
GIPTSAC 2025/10	20 / 25		


BRUSHED STAINLESS ST. AISI 304/1.4301-V2A
bar length 2,7 lm - pack. 15 Pcs - 40,5 lm

Article	h / H mm		
PTSPACS 0815	08 / 15		
PTSPACS 10125	10 / 12,5		
PTSPACS 1530	15 / 30		
PTSPACS 2025	20 / 25		


COLOURS

	ON DEMAND
AC - Polished stainless st. AISI 304/1.4301-V2A	ACS - Brushed stainless st. AISI 304/1.4301-V2A

JOINT GIPTSAC ..



EXTERNAL CORNER (WELDED) REPTSAC ..





SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS



PROTERMSTEP ALL

NATURAL AND ANODIZED SILVER
ALUMINIUM

PROTERMSTEP ALL is the new step cover profile made of natural and anodized aluminium. Designed to protect the edge of the step and to hide the joint between the tread and the step rise. The special notched shape in the upright stem provides it with excellent anchorage between floor/glue/profile.



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



NATURAL ALUMINIUM
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H mm		
PTSPAN 08	8		
PTSPAN 10	10		
PTSPAN 125	12,5		
PTSPAN 15	15		

ANODIZED SILVER ALUMINIUM thermo packed
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H mm		
PTSPAA 08	8		
PTSPAA 10	10		
PTSPAA 125	12,5		
PTSPAA 15	15		

COLOURS

AN - Natural aluminium	AA - Anodized silver aluminium

1. Choose the PROTERMSTEP in the required width and colour according to the thickness of the tile (stairs). 2. First fix the riser part, placing it at the correct and final height. 3. Fill the empty spaces under the profile with the tile adhesive. 4. Apply the adhesive to the tread, lay the profile with the punched base fully sunk into the adhesive and align the profile so that its lip covers the edge of the riser tile. 5. Lay the tread tiles, aligning them so that they are flush with the upper and rear part of the profile and filling the internal part with adhesive.


PROSIDE WALK is a perimeter profile in varnished aluminium, available in grey and anthracite colour. It is designed to protect the edges of the tiles and the screed on pavements. The profile is equipped with a punched flange that ensures its fixing to the support. The flange is also provided with small holes that allow the momentary fixing of the profile with nails. To reach a right connection between profile and the waterproofing system it's needed to use **PROBAND 150** with **PROBAND KOLL/AB**. The product is also available on request in **BENDABLE VERSION** and with a **SPECIAL SEASIDE PRE-TREATMENT** which increases its resistance to corrosion when installed at sea front environments.

PROSIDE WALK

VARNISHED / COATED ALUMINIUM



PSDWK 10AL / 125AL / 15AL



VARNISHED EMBOSSED ALUMINIUM

bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	h mm	H mm	L
PSDWK 10AL...	10	45	80
PSDWK 125AL...	12,5	45	80
PSDWK 15AL...	15	45	80
PSDWK 20AL...	20	45	80

EMBOSSED COLOURS

A - Anthracite grey (no RAL)	GF - Gray (7038)	TF - Dark brown (8019)

EMBOSSED COLOURS ON DEMAND

BF - White (9010)	C - Corten	EF - Beige (1019)


EXTERNAL CORNERS - pack. 10 Pcs

Article	h mm	H mm	L
AEPSDWK 10AL.../10	10	45	80
AEPSDWK 125AL.../10	12,5	45	80
AEPSDWK 15AL.../10	15	45	80
AEPSDWK 20AL.../10	20	45	80

JOINTS - pack. 10 Pcs

Article
GINSDWK 10AL.../10
GINSDWK 125AL.../10
GINSDWK 15AL.../10
GINSDWK 20AL.../10

AEPSDWK external corner (welded)



GINSDWK joint




EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose PROSIDE WALK according to the tile thickness and desired colour.
 2. Waterproof with PROBAND 150 and PROBAND KOLL the front of the screed.
 3. Fix the external corners with nails.
 4. Cut PROSIDE WALK to the desired length and fix it with nails; connect it with the corners using the junction element.
 5. Lay the tiles, leaving about 5 mm between tiles and profile.
 6. Seal the space between tiles and profile with **PROBAND FIX (PRBFX)**.
- PROFILE BENDING:** 1) Cut the anchoring flange into sections and engrave the metal close to the vertical side 2) bend the profile with the help of a template;

HOW TO REQUEST SEASIDE TREATMENT




* = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed

PROSTAIR LED

ANODIZED SILVER ALUMINIUM
- FLAT - LED

PROSTAIR LED is an aluminium profile available in the silver anodized finishes, that can be fixed with adhesive or dowels to the step tread. It has a grooved non-slip 52,5mm wide horizontal surface and an integrated LED lighting system, placed on its 43,5mm high vertical side. The integrated LED system generates cold or warm light and is protected by a matt or transparent polycarbonate plate, provided with a special fixing system, that allows it to be removed any time maintenance on the lighting system should be required. Its design and to the range of finishes available, together with its easy installation make **PROSTAIR LED** an appreciated solution both in public and in residential spaces.



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose PROSTAIR LED depending on the desired finish, light effect and polycarbonate plate;
2. If you are using the version with adhesive, clean first the surface where the profile will be installed. Once the surface has dried, remove the protective film and install the profile, applying adequate pressure on it;
3. If you are using the punched version, place the profile on the step tread and mark the position of the profile holes on the step tread;
4. Drill the step tread and fasten the profile using plugs;
5. Connect the LED to the low tension power supply and install the polycarbonate plate.



ANODIZED SILVER ALUMINIUM

bar length 2,7 lm - pack. 20 Pcs - 54 lm

ADAPTOR LED, LED & FLAT NOT INCLUDED

Article	H x L mm
PTRLEDAA 5040	43,5 X 52,5
PTRLEDAA 5040A	43,5 X 52,5
PTRLEDAA 5040F	43,5 X 52,5

"A" at the end of the product code = Item with adhesive
"F" at the end of the product code = Punched Item



ADHESIVE FLEXIBLE LED COIL

length 5 lm - pack. 1 ROLL

Article
LEDN
LEDF
LEDC

"N" at the end of the product code = neutral light
"F" at the end of the product code = cold light
"C" at the end of the product code = hot light

COLOURS



POLYCARBONATE FLAT bar length 2,7 lm - pack. 20 Pcs - 54 lm
(AL = transparent / AO = matt)

Article
PIAL 17
PIAO 17

ENDCAPS- R / L - pack. 6 Pcs (3 R and 3 L)

Article	H x L mm
TPTRLEDAA 5040/3	43,5 X 52,5



LED ADAPTOR AC/DC 75W - 12V (15 lm)

Article
ALL 7512

LED ADAPTOR AC/DC 25W - 12V (5 lm)

Article
ALL 2512






PROSTYLE

ROUNDED STEP NOSING
STAINLESS STEEL AISI 304/1.4301-V2A

PROSTYLE is a technical/decorative profile in stainless steel AISI 304/1.4301-V2A for ceramic tile/wood steps. Its particular rounded shape has been conceived to create the "torus" of the step, which is normally created with special pieces. Elegant profile for all public/private environments. In order to perfect placing and to look after details, external angles and closing caps are available.



POLISHED STAINLESS ST. AISI 304/1.4301-V2A with protective film
bar length 2,7 lm - pack. 20 Pcs - 54 lm - 10/10mm

Article	H mm
PSYAC 08	8
PSYAC 10	10
PSYAC 125	12,5

COLOURS




SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the PROSTYLE with suitable height for the thickness of the floor (stairs). 2. Apply the adhesive onto the area of application of the profile. 3. Lay and align the profile, cut to the necessary length, pressing the perforated flange into the adhesive. 4. Lay the tiles, aligning them so that the top edge of the profile is "flush" with the tile. 5. Fill the profile/tile area of contact with adhesive to prevent the accumulation of water in any voids.



VARNISHED PLASTIC STEEL EFFECT JOINT - pack. 20 Pcs

Article	H mm
RPSYAC 08/20	
RPSYAC 10/20	
RPSYAC 125/20	


STAINLESS ST. END CAPS H 8 - 10 - 12,5 mm - pack. 20 Pcs

Article	H mm
TPSYAC 08/20	
TPSYAC 10/20	
TPSYAC 125/20	

PROSTYLE

KNURLED, ROUNDED STEP NOSING
NATURAL, POLISHED AND CHROMED BRASS

PROSTYLE is a technical/decorative profile in natural brass, as well as with polished or chromed finish, for ceramic tile/wood steps. Its particular rounded shape has been conceived to create the "torus" of the step, which is normally created with special pieces. It is knurled on the top to make the profile non-slip. Elegant profile for all public/private environments. Shrink-wrapped profile with bar code.



CHROMED BRASS thermo packed
bar length 2,7 lm - pack. 10 Pcs - 27 lm

Article	H mm
PSYOC 08	8
PSYOC 10	10
PSYOC 125	12,5

POLISHED BRASS thermo packed
bar length 2,7 lm - pack. 10 Pcs - 27 lm

Article	H mm
PSYOL 08	8
PSYOL 10	10
PSYOL 125	12,5

NATURAL BRASS thermo packed
bar length 2,7 lm - pack. 10 Pcs - 27 lm

Article	H mm
PSYON 08	8
PSYON 10	10
PSYON 125	12,5

VARNISHED PLASTIC JOINT - pack. 20 Pcs

Article	H mm
RPSYOC 08-10-125/20	
RPSYOL 08-10-125/20	
RPSYON 08-10-125/20	

COLOURS




* = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed

PROSTYLE is a technical/decorative profile for ceramic tile/wood steps made in gold-silver anodized aluminium. Its particular rounded shape has been conceived to create the "torus" of the step, which is normally created with special pieces. It is knurled on the top to make the profile non-slip. Elegant profile for all public/private environments. Shrink-wrapped profile with bar code.

PROSTYLE

KNURLED, ROUNDED STEP NOSING
GOLD AND SILVER ANODIZED ALUMINIUM

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the PROSTYLE in the required width and colour according to the thickness of the tile.
2. First fix the riser part, placing it at the correct and final height.
3. Fill the empty spaces under the profile with the tile adhesive.
4. Apply the adhesive to the tread, lay the profile with the punched base fully sunk into the adhesive and align the profile so that its vertical part covers the edge of the riser tile.
5. Lay the tread tiles, aligning them so that they are flush with the upper and rear part of the profile and filling the internal part with adhesive. Oxidation marks in the polished/natural brass range may be easily removed with specific chemical products (Sidol-Smac).




ANODIZED SILVER ALUMINIUM thermo packed
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H mm
PSYAA 08	8
PSYAA 10	10
PSYAA 125	12,5

ANODIZED GOLD ALUMINIUM thermo packed
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H mm
PSYAO 08	8
PSYAO 10	10
PSYAO 125	12,5

COLOURS



VARNISHED PLASTIC JOINT - pack. 20 Pcs

Article
RPSYAO 08/20
RPSY... 08-10-125/20

Universal, suitable for three profile heights
Available: AA - AO.



The code of the selected colour must be added to the article code.
E.g.: RPSY... 08 (chosen colour polished brass) RPSYOL 08

ALUMINIUM CAPS H 8 - 10 - 12,5 mm - pack. 20 Pcs

Article
TPSYAO 08/20
TPSY... 08/20
TPSY... 10/20
TPSY... 125/20

Available: AA - AO.

The code of the selected colour must be added to the article code.
E.g.: TPSY... 08 (chosen colour polished brass) TPSYOL 08.



PROSTEP INS is a non-slip profile in aluminium that allows to connect the rise and the tread in case of stairs covered with wooden or laminate flooring. The profile has to be laid together with rise and tread. It is equipped with a punched flange that guarantees its fixing. **PROSTEP INS** in anodized aluminium is suitable for any stair covered with wooden flooring.

PROSTEP INS

ANODIZED SILVER ALUMINIUM



ANODIZED SILVER ALUMINIUM
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm
PTSAA 105	10,5
PTSAA 16	16


COLOURS



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROSTEP INS" according to the thickness of the tile.
2. Cut "PROSTEP INS" to the desired length.
3. Lay the wood or laminate on the step rise and apply adhesive on the area of the step tread, where the profile will be laid.
4. Lay the profile on the step tread, aligning it with the edge of the rise covering.
5. Lay the wood or laminate on the tread of the step taking care to insert it into the cavity.



stair nosing profiles


* = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed

PROSTAIR WOOD


NATURAL OAK
+ ALUMINIUM BASE

PROSTAIR WOOD is a step nosing profile in real oak with aluminium base. Its rounded "torus/convex" shape makes a perfect and elegant nosing for stairs and steps in ceramic-tile-terracotta-wood for indoor and outdoor environments. Attractive.

PROSTAIR WOOD may be treated and painted subsequently at the time of laying, according to the finishes chosen for the staircase.



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the PROSTAIR WOOD with suitable height for the thickness of the covering of the step or staircase.
2. Apply the adhesive onto the area of application of the profile.
3. Lay and align the profile, cut to the necessary length, pressing the perforated flange into the adhesive.
4. Lay the step covering, aligning it so that the top edge of the profile is "flush" with the covering.
5. Fill the profile/covering area of contact with adhesive to prevent any infiltration.



NATURAL OAK + ALUMINIUM BASE
bar length 2,7 lm - pack. 10 Pcs - 27 lm

Article	H mm		
PTRW 10	10		
PTRW 125	12,5		

H 15 mm on demand

COLOURS



NATURAL OAK + ALUMINIUM BASE
bar length 1,20 lm - pack. 10 Pcs - 12 lm

Article	H mm		
PTRW 1020	10		*
PTRW 12520	12,5		*

NATURAL OAK + ALUMINIUM BASE
bar length 1,80 lm - pack. 10 Pcs - 18 lm

Article	H mm		
PTRW 1080	10		*
PTRW 12580	12,5		*


ITEMS SUPPLIED ALREADY ASSEMBLED

Treat the wood appropriately with paint or oil.


PROSTAIR WOOD Z

KNURLED NATURAL OAK
+ ALUMINIUM BASE

PROSTAIR WOOD Z is a step nosing profile in real oak with aluminium base. The rounded shape of the "knurled convex" torus with non-slip surface makes a perfect and elegant nosing for stairs and steps in ceramic-tile-terracotta-wood for indoor and outdoor environments. Attractive. **PROSTAIR WOOD Z** may be treated and painted subsequently at the time of laying, according to the finishes chosen for the staircase.



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the PROSTAIR WOOD Z with suitable height for the thickness of the covering of the step or staircase.
2. Apply the adhesive onto the area of application of the profile.
3. Lay and align the profile, cut to the necessary length, pressing the perforated flange into the adhesive.
4. Lay the step covering, aligning it so that the top edge of the profile is "flush" with the covering.
5. Fill the profile/covering area of contact with adhesive to prevent any infiltration.




NATURAL OAK + ALUMINIUM BASE
bar length 2,7 lm - pack. 10 Pcs - 27 lm

Article	H mm		
PTRWZ 10	10		
PTRWZ 125	12,5		

H 15 mm on demand

COLOURS



NATURAL OAK + ALUMINIUM BASE
bar length 1,20 lm - pack. 10 Pcs - 12 lm

Article	H mm		
PTRWZ 1020	10		*
PTRWZ 12520	12,5		*

NATURAL OAK + ALUMINIUM BASE
bar length 1,80 lm - pack. 10 Pcs - 18 lm

Article	H mm		
PTRWZ 1080	10		*
PTRWZ 12580	12,5		*

ITEMS SUPPLIED ALREADY ASSEMBLED


Treat the wood appropriately with paint or oil.

PROSTEP WOOD is a step nosing profile in real oak with aluminium base. Its 90° shape makes a perfect and elegant nosing for modern stairs and steps in ceramic-tile-terracotta-wood for indoor and outdoor environments. Attractive.

PROSTEP WOOD may be treated and painted subsequently at the time of laying, according to the finishes chosen for the staircase.

PROSTEP WOOD

NATURAL OAK
+ ALUMINIUM BASE



NATURAL OAK + ALUMINIUM BASE
bar length 2,7 lm - pack. 10 Pcs - 27 lm

Article	H mm		
PTPW 10	10		
PTPW 125	12,5		

NATURAL OAK + ALUMINIUM BASE
bar length 1,20 lm - pack. 10 Pcs - 12 lm

Article	H mm		
PTPW 1020	10		*
PTPW 12520	12,5		*

COLOURS




Natural oak

NATURAL OAK + ALUMINIUM BASE
bar length 1,80 lm - pack. 10 Pcs - 18 lm

Article	H mm		
PTPW 1080	10		
PTPW 12580	12,5		

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the PROSTEP WOOD with suitable height for the thickness of the covering of the step or staircase.
2. Apply the adhesive onto the area of application of the profile.
3. Lay and align the profile, cut to the necessary length, pressing the perforated flange into the adhesive.
4. Lay the step covering, aligning it so that the top edge of the profile is "flush" with the covering.
5. Fill the profile/covering area of contact with adhesive to prevent any infiltration.

ITEMS SUPPLIED ALREADY ASSEMBLED


Treat the wood appropriately with paint or oil.

PROSTYLE WOOD is a step nosing profile in real oak with aluminium base. Its rounded "torus/fret" shape makes a perfect and elegant nosing for stairs and steps in ceramic-tile-terracotta-wood for indoor and outdoor environments. Attractive.

PROSTYLE WOOD may be treated and painted subsequently at the time of laying, according to the finishes chosen for the staircase.

PROSTYLE WOOD

NATURAL OAK
+ ALUMINIUM BASE



NATURAL OAK + ALUMINIUM BASE
bar length 2,7 lm - pack. 10 Pcs - 27 lm

Article	H mm		
PSYW 10	10		
PSYW 125	12,5		

NATURAL OAK + ALUMINIUM BASE
bar length 1,20 lm - pack. 10 Pcs - 12 lm

Article	H mm		
PSYW 1020	10		*
PSYW 12520	12,5		*

COLOURS




Natural oak

NATURAL OAK + ALUMINIUM BASE
bar length 1,80 lm - pack. 10 Pcs - 18 lm

Article	H mm		
PSYW 1080	10		*
PSYW 12580	12,5		*

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the PROSTYLE WOOD with suitable height for the thickness of the covering of the step or staircase.
2. Apply the adhesive onto the area of application of the profile.
3. Lay and align the profile, cut to the necessary length, pressing the perforated flange into the adhesive.
4. Lay the step covering, aligning it so that the top edge of the profile is "flush" with the covering.
5. Fill the profile/covering area of contact with adhesive to prevent any infiltration.



* = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed



TUBE and **ACCESSORIES** for runners and stair-carpet guides, available in the finishes in polished painted brass, polished gold aluminium and polished chrome aluminium.

TUBES and ACCESSORIES

GOLD AND CHROME POLISHED ALUMINIUM
POLISHED VARNISHED BRASS



BLISTER KIT - 2 TUBES AND 4 TUBE PLUGS - POLISHED BRASS COATED  length tube **0,8 lm** - pack. **60 Pcs**

Article	Ø mm		
TCTOL 118S	11		
TCTOL 138S	13		

BLISTER KIT - 2 TUBES AND 4 TUBE PLUGS - POLISHED BRASS COATED  length tube **0,9 lm** - pack. **60 Pcs**

Article	Ø mm		
TCTOL 119S	11		
TCTOL 139S	13		

BLISTER KIT - 2 TUBES AND 4 TUBE PLUGS - POLISHED BRASS COATED  length tube **1 lm** - pack. **60 Pcs**

Article	Ø mm		
TCTOL 1110S	11		
TCTOL 1310S	13		

BLISTER KIT - 2 TUBES and 4 TUBE PLUGS - POLISHED ALUM.  length tube **0,8 lm** - pack. **60 Pcs**

Article	Ø mm		
TCTBO 128S	12		
TCTBC 128S	12		

BLISTER KIT - 2 TUBES and 4 TUBE PLUGS - POLISHED ALUM.  length tube **0,9 lm** - pack. **60 Pcs**

Article	Ø mm		
TCTBO 129S	12		
TCTBC 129S	12		


BLISTER KIT - 2 TUBES and 4 TUBE PLUGS - POLISHED ALUM.  length tube **1 lm** - pack. **60 Pcs**

Article	Ø mm		
TCTBO 1210S	12		
TCTBC 1210S	12		

TCTOL 11/13S

TCTBO 12S

TCTBC 12S



tube and accessories for stairs

Varnished polished brass is not suitable for places subject to heavy foot-traffic and / or abrasion.

COLOURS



TUBE for runners and stair-carpet guides

GOLD AND CHROME POLISHED ALUMINIUM, POLISHED VARNISHED BRASS

POLISHED BRASS COATED
bar length **2 lm** - pack. **40 Pcs - 80 lm**

Article	Ø mm		
TGSOL 112	11		
TGSOL 132	13		

For different size bars, contact the sales office.

POLISHED ALUMINIUM
bar length **2 lm** - pack. **40 Pcs - 80 lm**

Article	Ø mm		
TGSBO 122	12		
TGSBC 122	12		

TGSOL 11/13

TGSBO 12

TGSBC 12



TUBE PLUGS/END CAPS for tube

POLISHED BRASS AND CHROMED BRASS

POLISHED BRASS AND CHROMED BRASS - pack. 60 Pcs

Article	Ø mm		
TETOL 11	11		
TETOC 12	12		
TETOL 12	12		
TETOL 13	13		

TETOL 11
TETOL 12
TETOL 13

TETOC 12



SUPPORT / EYELET for tube with screw

POLISHED BRASS AND CHROMED BRASS

POLISHED BRASS AND CHROMED BRASS - pack. 20 Pcs

Article	Ø mm		
SOOL 12	12		
SOOC 12	12		
SOOL 14	14		

SOOL 12
SOOL 14

SOOC 12



HINGE SUPPORT for tube

POLISHED BRASS

POLISHED BRASS - pack. 20 Pcs

Article	Ø mm		
SCOL 11	11		
SCOL 13	13		

Articles without bar code.
For bar code add the letter "C" after the article code. E.g.: SCOL 11C

SCOL 11
SCOL 13




* = Production on demand with minimum quantity of 200 pcs. Production delay 4/5 weeks. Price to be agreed

PROWALK ACC

POLISHED STAINLESS STEEL AISI 304/1.4301-V2A
PUNCHED OR SELF ADHESIVE

PROWALK ACC is steps protecting steel profile for existing scales. Its superior side level is crimped in order to increase its adhesion. Available in version or with holes either with adhesive. Available sizes: 30 x 10, 30 x 20, and 30 x 30 mm. All profiles are protected with protective film. It's ideal for the edges protection and screening as well as of the corner between the rising and the tread which is the point of the greatest strain.

stair nosing for existing steps



POLISHED STAINLESS STEEL AISI 304/1.4301-V2A with adhesive thermo packed - bar length 2,7 lm - pack. 20 Pcs - 54 lm - 10/10mm

Article	L x H mm		
PWKAC 3010A	30 X 10		
PWKAC 3020A	30 X 20		
PWKAC 3030A	30 X 30		

POLISHED STAINLESS STEEL AISI 304/1.4301-V2A punched - with protective film - bar length 2,7 lm - pack. 20 Pcs - 54 lm - 10/10mm

Article	L x H mm		
PWKAC 3010F	30 X 10		
PWKAC 3020F	30 X 20		
PWKAC 3030F	30 X 30		

INSTRUCTIONS FOR LAYING METHODS

Adhesive version

1. Choose the suitable profile and cut it to the necessary length. 2. Degrease, wash and clean the solid surface thoroughly. 3. Remove the protective paper from the adhesive. 4. Lay the profile by applying pressure evenly over the whole surface without using a hammer.

Punched version

1. Choose the suitable profile and cut it to the necessary length. 2. Mark the position of the holes using the existing holes in the profile as reference. 3. Insert the screw anchors into the drilled holes. 4. Fix the profile using flathead screws suitable for the relative slots in the profile.

COLOURS



AC - Polished stainless st.
AISI 304/1.4301-V2A

ON DEMAND HAND-BRUSHED STAINLESS STEEL
(Price to be agreed.
Production delay 4/5 weeks)

SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS


PROEND

GOLD, SILVER AND BRONZE ANOD. ALUMINIUM
WITH/ WITHOUT ADHESIVE AND PUNCHED


PROEND is a step nosing profile in anodized aluminium with silver-gold-bronze finish, available with self-adhesive backing or punched. Ideal for protecting existing steps and with knurled flat surface, it guarantees excellent safety features to prevent accidents in public and private environments.

PROEND ensures a perfect finish, covering laying defects and protecting the edge. Easy to lay with the self-adhesive backing ensuring perfect adherence to the step or using screws and screw anchors in the punched version.

stair nosing for existing steps



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS




Adhesive version

1. Choose the suitable profile and cut it to the necessary length. 2. Degrease, wash and clean the solid surface thoroughly. 3. Remove the protective paper from the adhesive. 4. Lay the profile by applying pressure evenly over the whole surface without using a hammer.

Punched version

1. Choose the suitable profile and cut it to the necessary length. 2. Mark the position of the holes using the existing holes in the profile as reference. 3. Insert the screw anchors into the drilled holes. 4. Fix the profile using flathead screws suitable for the relative slots in the profile.



ANOD. ALUMINIUM with and without adhesive thermo packed
bar length 2,7 lm - pack. 10 Pcs - 27 lm

Article	H x L mm		
PED... 48A	48 X 48		
PED... 48	48 X 48		


"A" at the end of the product code = Item with adhesive

ANODIZED ALUMINIUM punched thermo packed
bar length 2,7 lm - pack. 10 Pcs - 27 lm

Article	H x L mm		
PED... 48F	48 X 48		

On demand bar length 3 lm with minimum quantity of 200 pcs.
Production delay 4/5 weeks. Price to be agreed.

COLOURS



ANOD. ALU. punched with screws and screw anchors thermo packed - bar length 1,65 lm - pack. 20 Pcs




Article	H x L mm		
PED... 4816FS	48 X 48		

Available in the colours: AA - AO - AB. The code of the selected colour must be added to the article code. E.g.: PED... 48A (chosen colour anodized gold) PEDAO 48A.

PROWALK is a step nosing profile in polished brass and anodized aluminium for existing steps. The upper part is knurled to increase slip and slide resistance and is applied after laying. Available with holes or with adhesive. Ideal for protecting and shielding the edges and corner between riser and tread, which are the areas subjected to most stress.

PROWALK

POLISHED BRASS and ANODIZED ALUMINIUM
ADHESIVE and PUNCHED



KNURLED POLISHED BRASS with adhesive thermo packed
bar length 2,7 lm - pack. 15 Pcs - 40,5 lm

Article	H x L mm		
PWKOL 22A	22 X 22		
PWKOL 30A	30 X 30		



KNURLED POLISHED BRASS punched thermo packed
bar length 2,7 lm - pack. 15 Pcs - 40,5 lm

Article	H x L mm		
PWKOL 22F	22 X 22		
PWKOL 30F	30 X 30		

KNURLED POLISHED BRASS without holes thermo packed
bar length 2,7 lm - pack. 15 Pcs - 40,5 lm

Article	H x L mm		
PWKOL 22	22 X 22		
PWKOL 30	30 X 30		

KNURLED POLISHED BRASS with adhesive thermo packed
bar length 0,90 lm - pack. 20 Pcs




Article	H x L mm		
PWKOL 229AS	22 X 22		
PWKOL 309AS	30 X 30		*

KNURLED POLI. BRASS punched with screws and screw anchors thermo packed
bar length 0,90 lm - pack. 20 Pcs



Article	H x L mm		
PWKOL 309FS	30 X 30		*

COLOURS



OL - Polished brass



KNURLED ANODIZED ALUMINIUM with adhesive thermo packed
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H x L mm		
PWK... 22A	22 X 22		
PWK... 30A	30 X 30		



KNURLED ANODIZED ALUMINIUM punched thermo packed
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H x L mm		
PWK... 22F	22 X 22		
PWK... 30F	30 X 30		

KNURLED ANODIZED ALUM. WITHOUT HOLES thermo packed
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H x L mm		
PWK... 22	22 X 22		
PWK... 30	30 X 30		

KNURLED ANODIZED ALUMINIUM with adhesive thermo packed
bar length 0,90 lm - pack. 20 Pcs



Article	H x L mm		
PWK... 229AS	22 X 22		
PWK... 309AS	30 X 30		*


KNURLED ANOD. ALU. punched with screws and screw anchors thermo packed
bar length 0,90 lm - pack. 20 Pcs



Article	H x L mm		
PWK... 229FS	22 X 22		
PWK... 309FS	30 X 30		*


Available in the colours: AO - AA - AB (AT, CH and SB available on demand with a minimum quantity order of 100 pcs). The code of the selected colour must be added to the article code. E.g.: PWK... 22A (chosen colour anodized gold) PWKAO 22A.

COLOURS




AO - Anodized gold alum. AA - Anodized silver alum. AB - Anodized bronze alum.

ON DEMAND MINIMUM QUANTITY 100 PCS for color and height




AT - Anodized titanium alum. CH - Anod. champagne alum. SB - Anodized sand aluminium


PWK... 22A
PWK... 229AS




PWK... 30A
PWK... 309AS



PWK... 22F
PWK... 229FS




PWK... 30F
PWK... 309FS



stair nosing for existing steps

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



Adhesive version

1. Choose the suitable profile and cut it to the necessary length.
2. Degrease, wash and clean the solid surface thoroughly.
3. Remove the protective paper from the adhesive.
4. Lay the profile by applying pressure evenly over the whole surface without using a hammer.

Punched version


1. Choose the suitable profile and cut it to the necessary length.
2. Mark the position of the holes using the existing holes in the profile as reference.
3. Insert the screw anchors into the drilled holes.
4. Fix the profile using flathead screws suitable for the relative slots in the profile.

* = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed


PROWALK 2510 PROWALK 2520

ALUMINIUM 30 WOOD FINISHES AND 6
ANODIZED FINISHES PUNCHED OR SELF ADHESIVE

PROWALK 2510 e 2520 are new stair-nosing profiles for existing stairways. Designed to protect and restore stair steps made of wood, laminate, ceramic, etc. Made with anodized aluminium with silver, gold and bronze finish and available in self-adhesive or perforated versions. Sizes available: 2.7 m lengths and 0.9 m & 1.35 m Self-Pack.



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



Adhesive version

1. Choose the suitable profile and cut it to the necessary length.
2. Degrease, wash and clean the solid surface thoroughly.
3. Remove the protective paper from the adhesive.
4. Lay the profile by applying pressure evenly over the whole surface without using a hammer.

Punched version

1. Choose the suitable profile and cut it to the necessary length.
2. Mark the position of the holes using the existing holes in the profile as reference.
3. Insert the screw anchors into the drilled holes.
4. Fix the profile using flathead screws suitable for the relative slots in the profile.



ANODIZED ALUMINIUM with adhesive thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	L x H mm		
PWK... 2510A	24 X 10		
PWK... 2520A	24 X 20		

ANODIZED ALUMINIUM with adhesive thermo packed - bar length 0,90 lm - pack. 20 Pcs



Article	L x H mm		
PWK... 25109AS	24 X 10		
PWK... 25209AS	24 X 20		



ANODIZED ALUMINIUM punched thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	L x H mm		
PWK... 2510F	24 X 10		
PWK... 2520F	24 X 20		

ANODIZED ALUM. punched, screws and screw anchors thermo packed - bar length 0,90 lm - pack. 20 Pcs



Article	L x H mm		
PWK... 25109FS	24 X 10		

ANODIZED ALUM. punched, screws and screw anchors thermo packed - bar length 1,35 lm - pack. 20 Pcs



Article	L x H mm		
PWK... 251013FS	24 X 10		

Available in the finishes: AO - AA - AB (AT, CH e SB on demand with a minimum order of 100 pcs).

The code of the selected finish must be added to the article code. E.g.:PWK... 2510A (chosen finish anodized silver) PWKAA 2510A.

ALUMINIUM WOODEN FINISHES with adhesive thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	L x H mm		
PWK... 2510A	24 X 10		
PWK... 2520A	24 X 20		

Available on demand in the colours: 04W - 05W - 07W - 09W - 13W - 18W - 21W - 25W - 29W - 30W - 31W - 32W - 33W - 34W - 35W - 36W - 37W - 38W - 39W - 41W - 42W - 44W - 45W - 46W - 48W - 49W - 53W - 54W - 55W - 65W - 73W - 75W with a minimum quantity order of 100 pcs.


The code of the selected colour must be added to the article code. E.g.: PWK... 2510A (chosen finish dark beech) PWK04 2510A.

COLOURS



ON DEMAND MINIMUM QUANTITY 100 PCS for color and height

(For a precise assessment of colours request the wooden finishes sample range)



On demand it is possible to produce samples of wood finishes. Contact the office for negotiation, small amounts, timing and costs.


* = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed

PROEND INS 75 is a step nosing profile in anodized aluminium with interchangeable rubber insert: the upper part is knurled to increase slip and slide resistance and is applied after laying. Available anodized with gold, bronze or silver finish and with adhesive or punched.

PROEND INS 75 ensures a perfect finish, covering laying defects and protecting the edge. Easy to lay with the self-adhesive backing ensuring perfect adherence to the step or with screws and screw anchors in the punched version.

PROEND INS 75

GOLD, SILVER AND BRONZE ANOD. ALUMINIUM
ADHESIVE AND PUNCHED



stair nosing for existing steps

ANODIZED ALUMINIUM with DOUBLE INSERT thermo packed - with adhesive

bar length 2,7 lm - pack. 10 Pcs - 27 lm

Article	H x L mm
PED... 7537A	37 X 75,5

ANODIZED ALUMINIUM with DOUBLE INSERT thermo packed - punched

bar length 2,7 lm - pack. 10 Pcs - 27 lm

Article	H x L mm
PED... 7537F	37 X 75,5

On demand bar length 3 lm with minimum quantity of 200 pcs.
Production delay 4/5 weeks. Price to be agreed.

Available in the finishes: AA - AO - AB.

The code of the selected finish must be added to the article code.
E.g.: PED... 7537A (chosen finish anodized gold) PEDAO 7537A.

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



Adhesive version

1. Choose the suitable profile and cut it to the necessary length.
2. Degrease, wash and clean the solid surface thoroughly. 3. Remove the protective paper from the adhesive. 4. Lay the profile by applying pressure evenly over the whole surface without using a hammer.

Punched version

1. Choose the suitable profile and cut it to the necessary length.
2. Mark the position of the holes using the existing holes in the profile as reference. 3. Insert the screw anchors into the drilled holes. 4. Fix the profile using flathead screws suitable for the relative slots in the profile.

COLOURS




PROEND INS is a step nosing profile in anodized aluminium with interchangeable rubber insert: the upper part is knurled to increase slip and slide resistance and is applied after laying. Available anodized with gold, bronze or silver finish and with adhesive or punched.

PROEND INS ensures a perfect finish, covering laying defects and protecting the edge. Easy to lay with the self-adhesive backing ensuring perfect adherence to the step or with screws and screw anchors in the punched version.

PROEND INS

GOLD, SILVER AND BRONZE ANOD. ALUMINIUM
ADHESIVE AND PUNCHED



ANODIZED ALUM. with adhesive WITH INSERT thermo packed

bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H x L mm
PED... 4528A	28 X 45

On demand bar length 3 lm with minimum quantity of 200 pcs. Production delay 4/5 weeks. Price to be agreed.

AN. ALUM. punched WITH INSERT, screws and screw anchors thermo packed - bar length 1,65 lm - pack. 20 Pcs



Article	H x L mm
PED... 452816FS	28 X 45

Available in the finishes: AA - AO - AB.

The code of the selected colour must be added to the article code.
E.g.: PED... 4528A (chosen finish anodized gold) PEDAO 4528A.

ANODIZED ALUM. punched WITH INSERT thermo packed


bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H x L mm
PED... 4528F	28 X 45

COLOURS



EXAMPLES OF LAYING



For instructions see the product above


BLACK INTERCHANGEABLE INSERT

VINYL RESIN / RUBBER

VINYL RESIN / RUBBER

bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article
IIN 12




* = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed

PROEND GRIP 70

SILVER, GOLD AND BRONZE ANOD. ALUMINIUM
+ NON-SLIP INSERT ADHESIVE AND PUNCHED

PROEND GRIP 70 is a non-slip step nosing profile in anodized aluminium with adhesive non-slip 50mm thick insert in black carborundum to be fitted in the relative groove in the top of the profile upon completion of laying. The profile may be laid with fixing screws hidden afterwards by the adhesive carborundum, or with silicone and/or adhesive to be applied on the bottom of the profile, which is designed to ensure an excellent grip. It is made in anodized aluminium with silver, gold or bronze finish with anodizing coat of approx. 15/20 micron.

stair nosing for existing steps



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS




Adhesive version

1. Choose the suitable profile and cut it to the necessary length.
2. Degrease, wash and clean the solid surface thoroughly.
3. Remove the protective paper from the adhesive.
4. Lay the profile by applying pressure evenly over the whole surface without using a hammer.

Punched version


1. Choose the suitable profile and cut it to the necessary length.
2. Mark the position of the holes using the existing holes in the profile as reference.
3. Insert the screw anchors into the drilled holes.
4. Fix the profile using flathead screws suitable for the relative slots in the profile.



SILVER, GOLD AND BRONZE ANODIZED ALUM. with adhesive thermo packed - bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H x L mm		
PEGRAA... 7032A	32,5 X 70		

COLOURS



SILVER, GOLD AND BRONZE ANODIZED ALUM. punched thermo packed - bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H x L mm		
PEGRAA... 7032F	32,5 X 70		

Available in the finishes: AA - AO - AB.
The code of the selected finish must be added to the article code.
E.g.: PEGRAA... 7032A (chosen finish anodized gold) PEGRAO... 7032A.




On demand bar length 3 lm with minimum quantity of 200 pcs. Production delay 4/5 weeks. Price to be agreed.

**The adhesive carborundum strip (PROGRIP) is not included with the profile.
For PEGRAA... 7032... order PGR... 50 (Specify the chosen colour).**

PROEND 5050

ANODIZED SILVER ALUMINIUM
+ NON-SLIP INSERT ADHESIVE AND PUNCHED

PROEND 5050 is a non-slip profile for stairs in anodized silver aluminium, with a visible surface of 50x50 mm. The profile, available in the adhesive or punched version, is characterized of a horizontal surface partially milled, equipped with a specific groove where the non-slip adhesive Progrid in carborundum could be applied. The profile has also a vertical inclined of 83-degrees surface completely smooth. The ease of application and the availability of the carborundum in different colours, make it a much-sought profile.



ANODIZED SILVER ALUMINIUM punched / with adhesive
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	HxL mm		
PEGRAA 50F	50 X 50		
PEGRAA 50A	50 X 50		

COLOURS



On demand bar length 3 lm with minimum quantity of 200 pcs. Production delay 4/5 weeks. Price to be agreed.

**The adhesive carborundum strip (PROGRIP) is not included with the profile.
For PEGRAA 50... order PGR... 20 (Specify the chosen colour).**

INSTRUCTIONS FOR LAYING METHODS



Adhesive version

1. Cut PROEND 5050 to the desired length;
2. Remove all the remains of oil, grease and dirt from the surface where the profile will be laid;
3. When the surface is perfectly dry, remove the protective film and press the profile exerting the appropriate pressure;
4. Apply the non-slip strip in carborundum in the desired colour.

Punched version

1. Cut PROEND 5050 to the correct size;
2. Mark on the support the position of the holes present on the profile;
3. Drill holes in the bracket with a 5 mm diameter bit and insert the 5 x 25 mm rawlplugs;
4. Align the profiles over the holes and screw it to support;
5. Apply the non-slip carborundum adhesive insert in the desired color.

EXAMPLES OF LAYING



PROEND GRIP is a non-slip step nosing profile in anodized aluminium with adhesive non-slip 20mm thick insert in black carborundum to be fitted in the relative groove in the top of the profile upon completion of laying. The profile may be laid with fixing screws hidden afterwards by the adhesive carborundum, or with silicone and/or adhesive to be applied on the bottom of the profile, which is designed to ensure an excellent grip. It is made in anodized aluminium with silver, gold or bronze finish with anodizing coat of approx. 15/20 micron.

PROEND GRIP

SILVER, GOLD AND BRONZE ANOD. ALUMINIUM
+ NON-SLIP INSERT ADHESIVE AND PUNCHED



ANODIZED SILVER, GOLD AND BRONZE ALUM. with adhesive thermo packed - bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H x L mm		
PEGR... 5230A	30 X 52		

On demand bar length 3 lm with minimum quantity of 200 pcs. Production delay 4/5 weeks. Price to be agreed.

ANODIZED SILVER, GOLD AND BRONZE ALUM. with adhesive - thermo packed
bar length 1,66 lm - pack. 20 Pcs



Article	H x L mm		
PEGR... 523016AS	30 X 52		



ANODIZED SILVER, GOLD AND BRONZE ALUM. punched thermo packed - bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H x L mm		
PEGR... 5230F	30 X 52		

ANODIZED SILVER, GOLD AND BRONZE ALUM. punched, screws and screw anchors - thermo packed
bar length 1,66 lm - Pack 20 Pcs



Article	H x L mm		
PEGR... 523016FS	30 X 52		

Available in the finishes: AA - AO - AB.

The code of the selected finish must be added to the article code. E.g.: PEGR... 523016AS (chosen finish anodized silver) PEGRAA 523016AS.

The adhesive carborundum strip (**PROGRIP**) is not included with the profile.
For PEGR... 5230... order PGR... 20 (Specify the chosen colour).

COLOURS



* = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed

PROGRIP is a self-adhesive product in carborundum consisting of a plastic film plus abrasive granules with high resistance to wear. It is normally used to guarantee safety on steps in public and private environments, as required by accident-prevention laws. Available in various colours and widths to meet all technical and aesthetic requirements. It is advisable to apply 2 strips on each step, rounding off the ends.

PROGRIP

ADHESIVE CARBORUNDUM - 6 COLOURS



COLOURS

N - Black	B - White	T - Transparent
G - Gray	Y - Yellow	M - Brown
	The PGRT (transparent) are not suitable for outside use.	
GN - Yellow/Black		

ADHESIVE CARBORUNDUM NON-SLIP STRIP for STEPS

rolls length 18,2 lm

Article	Width mm		
PGRN 20	20		
PGRB 20	20		*
PGRT 20	20		
PGRG 20	20		
PGRY 20	20		
PGRM 20	20		
PGRN 25	25		
PGRB 25	25		*
PGRT 25	25		
PGRG 25	25		
PGRY 25	25		
PGRM 25	25		
PGRN 50	50		
PGRB 50	50		*
PGRT 50	50		
PGRG 50	50		
PGRY 50	50		
PGRM 50	50		

ADHESIVE NON-SLIP STRIP for STEPS - rolls length 18,2 lm


Article	Width mm		
PGRGN 20	20		
PGRGN 25	25		
PGRGN 50	50		



non-slip strip for steps


LAYING INSTRUCTIONS

1. Thoroughly clean and degrease the surface of application. 2. Round the ends of the strips. 3. Remove the protective paper from the adhesive and lay the PROGRIP using a roller. 4. Do not apply the strips at temperatures below 15°, otherwise heat the strips and the step. 5. When necessary clean away impurities with a brush and preserve the PROGRIP. 6. When laying on tiles, cut and round the corners of the strips on the inner part of the tile. 7. Carefully seal the outer edges of the strips to prevent water infiltration.




An interpretation of:
Milau Bridge, Norman Foster, MILAU (France), 2004

MOVEMENT AND EXPANSION JOINTS




PROFLEX ACC

STAINLESS STEEL AISI 304/1.4301-V2A
+ VINYL RESIN / RUBBER INSERT



EXAMPLES OF LAYING



PROFLEX ACC is a new, stainless steel expansion joint with interchangeable (H. 4,5 e 6 mm excluded) vinyl resin/rubber insert, available in black, grey, beige or ivory. **PROFLEX ACC** provides elastic expansion joints for various kinds of flooring, such as ceramic, marble, granite, Kerilite/Laminam or any other flooring material laid with glue/adhesive and having a thickness of 4.5 to 20 mm. The joint is specially designed to protect the edges of the tiles, and its exceptional strength makes it capable of supporting frequent traffic, both pedestrian and vehicular (forklifts, pallet trucks, automobiles). The joint must be installed at the same level of the floor or 0.5-1 mm lower (never above). Lay the joints according with the standards in force. **HIGH RESISTANCE TO LOADS AND TO FREQUENT TRAFFIC OF PALLET TRUCKS AND FORKLIFTS.**



**POLISHED STAINLESS STEEL AISI 304/1.4301-V2A
+ VINYL RESIN / RUBBER INSERT**
bar length 2,5 lm - pack. 10 Pcs - 25 lm (PFXAC 045/06/08 - 50 lm)

Article	H mm		
PFXAC 045...	4, 5		
PFXAC 06...	6		
PFXAC 08...	8		
PFXAC 10...	10		
PFXAC 125...	12,5		
PFXAC 15...	15		
PFXAC 20...	20		

LAYING INSTRUCTIONS

1. Choose the PROFLEX ACC with the same height as the thickness of the floor (tile) also choosing the colour of the insert.
2. Using a notched spreader apply the adhesive in the point where the joint will be laid.
3. Lay the PROFLEX ACC with the punched flanges in the adhesive (we recommend the expansion joint being laid in line with the joint in the screed/floor rough).
4. Lay the tiles, aligning them with and adjoining the upper edge of the profile (the joint must always be 0.5-1mm lower than the tile, never above). Always place the uncut side of the tile against the profile.
5. Use sealant to fill any spaces between the tile and the PROFLEX ACC joint.



VINYL RESIN/RUBBER INSERT length 2,5 lm

Article	H mm		


VINYL RESIN/RUBBER INSERT length 2,5 lm

Article	H mm		


ISPFXAC 045...	4,5		
ISPFXAC 06...	6		

Insert available in the colours: G - N (Beige and ivory available on demand with a minimum quantity order of 200 pcs). The code of the selected finish must be added to the article code. E.g.: PFXAC 045... (chosen insert colour grey) PFXAC 045G.

COLOURS



ON DEMAND MINIMUM QUANTITY 200 PCS for colour and height




(Price to be agreed. Production delay 4/5 weeks)

PROFLEX ACC PR

STAINLESS STEEL AISI 304/1.4301-V2A
+ VINYL RESIN / RUBBER INSERT

soundproof perimeter joints



**POLISHED STAINLESS STEEL AISI 304/1.4301- V2A
+ VINYL RESIN / RUBBER INSERT**
bar length 2,5 lm - pack. 20 Pcs - 50 lm

Article	H mm		
PFXACPR 08...	8		
PFXACPR 10...	10		
PFXACPR 125...	12,5		
PFXACPR 15...	15		
PFXACPR 20...	20		

COLOURS




VINYL RESIN / RUBBER INTERCHANGEABLE INSERT
length 2,5 lm

Article	H mm		


ISPFXACPR 820...	8-10-12,5-15-20		
------------------	-----------------	--	--

Insert available in the colours: G - N (Beige and ivory available on demand with a minimum quantity order of 200 pcs). The code of the selected finish must be added to the article code. E.g.: ISPFXACPR 820... (chosen insert colour grey) ISPFXACPR 820G.

COLOURS



ON DEMAND MINIMUM QUANTITY 200 pcs for colour and height




(Price to be agreed. Production delay 4/5 weeks)

PROFLEX OT is an expansion joint in natural brass with the interchangeable PVC/rubber insert. It is available in black, grey, beige or ivory and serves to fabricate expansion joints for ceramic tile, marble or granite floors and any floor laid with glue/adhesive between 8 and 20 mm thick. The special structure of the joint is designed to protect the corners of the tiles and its high strength withstands frequent pedestrian and vehicular (lift trucks, pallet trucks, cars) traffic. The joint must be placed level with or 0.5-1 mm below the floor level, never above. Lay the joints according with the standards in force. **HIGH RESISTANCE TO HEAVY LOADS AND TO FREQUENT PALLET TRUCK AND LIFT TRUCK TRAFFIC.**

PROFLEX OT

NATURAL BRASS
+ VINYL RESIN / RUBBER INSERT




NATURAL BRASS + VINYL RESIN / RUBBER INSERT
bar length 2,5 lm - pack. 10 Pcs - 25 lm

Article	H mm		
PFXOT 08...	8		
PFXOT 10...	10		
PFXOT 125...	12,5		
PFXOT 15...	15		
PFXOT 20...	20		
PFXOT 30...	30		

Insert available in the colours: G - N (Beige and ivory available on demand with a minimum quantity order of 200 pcs).

The code of the selected finish must be added to the article code. E.g.: PFXOT 08... (chosen insert colour grey) PFXOT 08G.

COLOURS



VINYL RESIN/RUBBER INSERT
bar length 2,5 lm - pack. 40 Pcs - 100 lm


Article	L x H mm		
IGC....	14 X 6		

Insert available in the colours: G - N (Beige and ivory available on demand).

The code of the selected finish must be added to the article code. E.g.: IGC ... (chosen insert colour grey) IGC.


***The inserts of the on demand profiles are also on demand**

ON DEMAND MINIMUM QUANTITY 200 pcs for colour and height



(Price to be agreed. Production delay 4/5 weeks)

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS







1. Choose the PROFLEX OT with the same height as the thickness of the floor (tile) also choosing the colour of the insert. 2. Using a notched spreader apply the adhesive in the point where the joint will be laid. 3. Lay the PROFLEX OT with the punched flanges in the adhesive (we recommend the expansion joint being laid in line with the joint in the screed/floor rough). 4. Lay the tiles, aligning them with and adjoining the upper edge of the profile (the joint must always be 0.5-1mm lower than the tile, never above). Always place the uncut side of the tile against the profile. 5. Use sealant to fill any spaces between the tile and the PROFLEX OT joint.

PROFLEX AL is an expansion joint in natural aluminium with the PVC/rubber insert. It is available in black, grey, beige or ivory and serves to fabricate expansion joints for ceramic tile, marble or granite floors and any floor laid with glue/adhesive between 8 and 20 mm thick. The special structure of the joint is designed to protect the corners of the tiles and its high strength withstands frequent pedestrian and vehicular (lift trucks, pallet trucks, cars) traffic. The joint must be placed level with or 0.5-1 mm below the floor level, never above. Lay the joints according with the standards in force. **HIGH RESISTANCE TO HEAVY LOADS AND TO FREQUENT PALLET TRUCK AND LIFT TRUCK TRAFFIC.**

PROFLEX AL

NATURAL ALUMINIUM
+ VINYL RESIN / RUBBER INSERT




NATURAL ALUMINIUM + VINYL RESIN / RUBBER INSERT
bar length 2,5 lm - pack. 20 Pcs - 50 lm

Article	H mm		
PFXAL 08...	8		
PFXAL 10...	10		
PFXAL 125...	12,5		
PFXAL 15...	15		
PFXAL 20...	20		

Insert available in the colours: G - N (Beige and ivory available on demand with a minimum quantity order of 200 pcs).

The code of the selected finish must be added to the article code. E.g.: PFXAL 08... (chosen insert colour grey) PFXAL 08G.

COLOURS




VINYL RESIN/RUBBER INSERT
bar length 2,5 lm - pack. 40 Pcs - 100 lm

Article	L x H mm		
IGC....	14 X 6		

Insert available in the colours: G - N (Beige and ivory available on demand).

The code of the selected finish must be added to the article code. E.g.: IGC ... (chosen insert colour grey) IGC.

ON DEMAND MINIMUM QUANTITY 200 pcs for colour and height



(Price to be agreed. Production delay 4/5 weeks)

LAYING INSTRUCTIONS


1. Choose "PROFLEX AL" according to the tile thickness and desired colour. 2. Cut "PROFLEX AL" to the desired length and apply the adhesive on the support where the profile will be laid. 3. Place the joint exactly over the screed joint and press the anchoring flange into the adhesive. 4. Lay the tiles aligning them with the profile leaving a 2 mm joint. After laying the joint should be 0,5 mm below the floor covering surface. Remove immediately all the remains of adhesive from the surface of the profile. 5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.

*** = Production on demand with minimum quantity of 200 pcs. Production delay 4/5 weeks. Price to be agreed**

PROFLEX ACN

STAINLESS STEEL AISI 304/1.4301-V2A

PROFLEX ACN is a movement joint suitable for vehicular traffic composed by two interlocked sliding stainless steel profiles. The two stainless steel profiles have punched flanges which guarantee a perfect fixing to the support and a correct movement. **PROFLEX ACN** stainless steel is suitable for all areas with heavy chemical and mechanical stress. Lay the joints according to UNI 11493-1.



AVAILABLE
H 11mm - PFXACN 11, H 25mm - PFXACN 25, H 30mm - PFXACN 30



SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS

POLISHED STAINLESS STEEL AISI 304/1.4301-V2A
bar length 2,5 lm - pack. 10 Pcs - 25 lm

Article	H mm		
PFXACN 08	8		
PFXACN 10	10		
PFXACN 11	11		
PFXACN 125	12,5		
PFXACN 15	15		
PFXACN 20	20		
PFXACN 25	25		
PFXACN 30	30		

COLOURS



Stainless steel AISI 304/1.4301-V2A

ON DEMAND*




ACM - Polished stainless st. AISI 316LL

*Minimum quantity 200 pcs.

Price to be agreed. Production delay 4/5 weeks.

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS




1. Choose the PROFLEX ACN with the same height as the thickness of the floor (tile).
2. Using a notched spreader apply the adhesive in the point where the joint will be laid.
3. Lay the PROFLEX ACN with the punched flanges in the adhesive (we recommend the expansion joint being laid in line with the joint in the screed/floor rough).
4. Lay the tiles, aligning them with and adjoining the upper edge of the profile (the joint must always be 0.5-1mm lower than the tile, never above). Always place the uncut side of the tile against the profile.
5. Use sealant to fill any spaces between the tile and the PROFLEX ACN joint.

PROFLEX ALN

NATURAL ALUMINIUM

PROFLEX ALN is a new, natural aluminium expansion joint consisting of two interlocked sliding profiles designed for glued floors. **PROFLEX ALN** provides elastic expansion joints for various kinds of flooring, such as ceramic, marble, granite, Kerilite or any other flooring material laid with glue/adhesive and having a thickness of 8 to 20 mm. The joint is specially designed to protect the edges of the tiles, and its exceptional strength makes it capable of supporting frequent traffic, both pedestrian and vehicular (forklifts, pallet trucks, automobiles). The joint must be installed at the same level of the floor or 0.5-1 mm lower (never above). Lay the joints according with the standards in force. HIGH RESISTANCE TO LOADS AND TO FREQUENT TRAFFIC OF PALLET TRUCKS AND FORKLIFTS.



NATURAL ALUMINIUM
bar length 2,5 lm - pack. 20 Pcs - 50 lm

Article	H mm		
PFXALN 08	8		
PFXALN 10	10		
PFXALN 125	12,5		
PFXALN 15	15		
PFXALN 20	20		


COLOURS



AN - Natural aluminium



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the PROFLEX ALN with the same height as the thickness of the floor (tile).
2. Using a notched spreader apply the adhesive in the point where the joint will be laid.
3. Lay the PROFLEX ALN with the punched flanges in the adhesive (we recommend the expansion joint being laid in line with the joint in the screed/floor rough).
4. Lay the tiles, aligning them with and adjoining the upper edge of the profile (the joint must always be 0.5-1mm lower than the tile, never above). Always place the uncut side of the tile against the profile.
5. Use sealant to fill any spaces between the tile and the PROFLEX ALN joint.

PRODILAT is an expansion joint in stainless steel inox AISI 304 / 1.4301 – V2A composed of two counterposed profiles in “L” shape, joined with a vulcanized EPDM which can be polished, available in black and grey colour. The counterposed profile in “L” shape have perforated wings for a perfect bond to the substrate and a correct movement of the joint. The expanding EPDM has a high resistance to mechanical & chemical stress, UV rays, to fungi and bacteria. **PRODILAT** in stainless steel is suitable to be used in all environments with high mechanical and chemical stress. Lay the joints according to UNI 11493-1 regulation.

PRODILAT

STAINLESS STEEL AISI 304/1.4301-V2A
WITH SANDABLE VULCANIZED EPDM



STAINLESS STEEL AISI 304/1.4301-V2A WITH SANDABLE VULCANIZED EPDM - bar length 2,7 lm - pack. 20 Pcs - 54 lm (GCAC 20 - 27 lm)

Article	H mm
GCAC 08... (8x10)	8
GCAC 10... (10x10)	10
GCAC 125... (12,5x10)	12,5
GCAC 15... (15x10)	15
GCAC 20... (20x10)	20


SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS

Insert available in the colours: N - G.
The code of the selected finish must be added to the article code.
E.g.: GCAC 08... (chosen insert colour grey) GCAC 08G.
H 25 / H 30 on demand.


COLOURS




COLOURS (EPDM)



Possible specks on the surface of the vulcanised rubber are due to the nature of the product itself, they disappear once the laid profile is polished or cleaned. Claims due to these specks will not be taken into consideration.



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS




1. Choose the PRODILAT with the same height as the thickness of the floor (tile) also choosing the colour of the insert.
2. Using a notched spreader apply the adhesive in the point where the joint will be laid.
3. Lay the PRODILAT with the punched flanges in the adhesive (we recommend the expansion joint being laid in line with the joint in the screed/floor rough).
4. Lay the tiles, aligning them with and adjoining the upper edge of the profile (the joint must always be 0.5-1mm lower than the tile, never above). Always place the uncut side of the tile against the profile.
5. Use sealant to fill any spaces between the tile and the PRODILAT.

PRODILAT is an expansion joint in natural aluminium composed of two counterposed profiles in “L” shape, joined with a vulcanized EPDM which can be polished, available in black and grey colour. The counterposed profile in “L” shape have perforated wings for a perfect bond to the substrate and a correct movement of the joint. The expanding EPDM has a high resistance to mechanical & chemical stress, UV rays, to fungi and bacteria. **PRODILAT** in aluminium is suitable to be used in all environments with high mechanical and chemical stress. Lay the joints according to UNI 11493-1 regulation.

PRODILAT

ALUMINIUM WITH
SANDABLE VULCANIZED EPDM



ALUMINIUM WITH SANDABLE VULCANIZED EPDM
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H mm
GCAN 08... (8x10)	8
GCAN 10... (10x10)	10
GCAN 125... (12,5x10)	12,5
GCAN 15... (15x10)	15
GCAN 20... (20x10)	20

COLOURS



COLOURS (EPDM)




Possible specks on the surface of the vulcanised rubber are due to the nature of the product itself, they disappear once the laid profile is polished or cleaned. Claims due to these specks will not be taken into consideration.


Insert available in the colours: N - G.
The code of the selected finish must be added to the article code.
E.g.: GCAN 08... (chosen insert colour grey) GCAN 08G.
H 25 / H 30 on demand.

EXAMPLES OF LAYING

1. Choose “PRODILAT” according to the desired finish, tile thickness and desired colour.
2. Cut “PRODILAT” to the desired length and apply the adhesive on the support where the profile will be laid.
3. Place the joint exactly over the screed joint and press the anchoring flange into the adhesive.
4. Lay the tiles, aligning them with the profile leaving a 2 mm. joint. After laying the joint should be 0,5 mm below the floor covering surface. Remove immediately all the remains of adhesive from the surface of the profile.
5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.




LAYING INSTRUCTIONS



PROFLEX

NON-TOXIC IMPACT-RESISTANT
CO-EXTRUDED VINYL RESIN (PVC)

PROFLEX is an expansion joint in PVC with PVC/rubber insert. Available in 3 standard colours, **PROFLEX** serves to fabricate expansion joints for ceramic tile, marble or granite floors and any floor laid with glue/adhesive between 8 and 20 mm thick. The special structure of the joint is designed to protect the corners of the tiles and its high strength withstands frequent pedestrian and vehicular (lift trucks - pallet trucks - cars) traffic. The joint must be placed level with or 0.5-1 mm below the floor level, never above. Lay the joints according with the standards in force.



NON - TOXIC CO-EXTRUDED VINYL RESIN - bar length 2,5 lm
pack. 40 Pcs - 100 lm (PFX 15 and PFX 20 - pack. 20 Pcs)


Article	H mm
PFX 08...	8
PFX 10...	10
PFX 125...	12,5
PFX 15...	15
PFX 20...	20

Available in the colours: GS-GT-GL (Beige and ivory available on demand). The code of the selected finish must be added to the article code. E.g.: PFX 08... (chosen colour dark grey) PFX 08GS.

COLOURS

GS - Dark grey for rigid and flexible part	GT - Dark grey for rigid part / Transparent for flexible part	GL - Light grey for rigid and flexible part
---	--	--

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the PROFLEX with suitable height for the thickness of the floor.
2. Apply the adhesive onto the area of application of the profile.
3. Lay and align the profile, cut to the necessary length, pressing the perforated flange into the adhesive.
4. Lay the tiles, aligning them so that the top edge of the profile is flush with the tile.
5. Fill the profile/tile area of contact with adhesive to prevent the accumulation of water in any voids.

ON DEMAND MINIMUM QUANTITY 200 pcs


B - Beige (E84)	A - Ivory (E81)
------------------------	------------------------

(Price to be agreed. Production delay 4/5 weeks)

PROFLEX 5

NON-TOXIC IMPACT-RESISTANT
CO-EXTRUDED VINYL RESIN (PVC)

PROFLEX 5 is a range of technical expansion joint profiles for floors laid with glue/adhesive. They are made in non-toxic, impact-resistant, co-extruded PVC with perforated horizontal lateral flanges in rigid PVC while the elastic central part is made in flexible vinyl resin 5 mm in width. They are able to absorb moderate tensile and compressive stress, while being resistant to most chemical agents, to wear and to UV rays. They may be used indoors and outdoors. Thanks to the limited widths, **PROFLEX 5** may be considered a "gap cover" because it blends in with the gaps between tiles. The joint profile must never be placed over a tiled floor and should preferably always be 0.5-1 mm lower. Lay the joints according with the standards in force.



NON - TOXIC CO-EXTRUDED VINYL RESIN - bar length 2,5 lm
pack. 40 Pcs - 100 lm (PFX5 15 - pack. 20 Pcs - 50 lm)


Article	H mm
PFX5 045...	4,5
PFX5 06...	6
PFX5 08...	8
PFX5 10...	10
PFX5 125...	12,5
PFX5 15...	15

Available in the colours: GS-GL (Beige and ivory available on demand with a minimum quantity order of 200 pcs). The code of the selected finish must be added to the article code. E.g.: PFX5 08... (chosen colour dark grey) PFX5 08GS.

COLOURS

GS - Dark grey for rigid and flexible part	GL - Light grey for rigid and flexible part
---	--

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the PROFLEX 5 with suitable height for the thickness of the floor.
2. Apply the adhesive onto the area of application of the profile.
3. Lay and align the profile, cut to the necessary length, pressing the perforated flange into the adhesive.
4. Lay the tiles, aligning them so that the top edge of the profile is flush with the tile.
5. Fill the profile/tile area of contact with adhesive to prevent the accumulation of water in any voids.

ON DEMAND MINIMUM QUANTITY 200 pcs for colour and height

B - Beige (E84)	A - Ivory (E81)
------------------------	------------------------

(Price to be agreed. Production delay 4/5 weeks)

PROFLEX 5 PR is a perimeter joint made of coextruded vinyl resin that can be used to connect the floor to the wall lining or the wall lining to doors and windows and/or to any other kind of lining. The 5 mm elastic part (exposed) allows the floor/lining to expand as necessary. **PROFLEX 5 PR** prevents and dampens the propagation of sound waves and the forming of sound bridges. Available in dark grey, light grey, Beige and ivory, in various heights H 4,5-6-8-10-12,5 mm. Lay the joints according with the standards in force.

PROFLEX 5 PR

NON-TOXIC IMPACT-RESISTANT CO-EXTRUDED VINYL RESIN (PVC)



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROFLEX 5 PR" higher than the thickness of the tile
2. Cut "PROFLEX 5 PR" to the desired length and apply the adhesive on the support where the joint will be laid.
3. Position the profile along the perimeter and press the anchoring flap into the adhesive layer.
4. Lay the tiles.
5. Lay the skirting board taking care to rest it on the profile.
6. Silicone between the floor and skirting board

VINYL RESIN - bar length 2,5 lm - pack. 40 Pcs - 100 lm



Article	H mm		
PFX5PR 045...	4,5		
PFX5PR 06...	6		
PFX5PR 08...	8		
PFX5PR 10...	10		
PFX5PR 125...	12,5		
PFX5PR 15...	15		

Available in the colours: GS-GL (Beige and ivory available on demand with a minimum quantity order of 200 pcs). The code of the selected finish must be added to the article code. E.g.: PFX5PR 045... (chosen insert colour dark grey) PFX5PR 045GS.


COLOURS

	
GS - Dark grey for rigid and flexible part	GL - Light grey for rigid and flexible part

ON DEMAND MINIMUM QUANTITY 200 pcs for colour and height

	
B - Beige (E84)	A - Ivory (E81)

(Price to be agreed. Production delay 4/5 weeks)




soundproof perimeter joints




* = Production on demand with minimum quantity of 200 pcs. Production delay 4/5 weeks. Price to be agreed

ADHESIVE-LAID JOINTS

CO-EXTRUDED VINYL RESIN



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the joint in accordance with the colour and thickness of the floor, calculating 0.5-1 mm less for laying the joint, which under no circumstances must protrude. 2. Place the joint over the cut/joint in the screed; if there is none, make a cut of 2/3 the thickness of the screed. 3. Apply the adhesive and lay the joint, pressing it into the glue. 4. Lay the tiles, aligning them with the rigid vertical part of the joint. 5. Using the special glue, fill the gap between the tiles and the profile.

ADHESIVE-LAID MOVEMENT JOINTS are a range of joints in co-extruded vinyl resin with the flanges and vertical supports made in rigid synthetic vinyl resin and the elastic central part in flexible synthetic vinyl resin. The glue-laid joints must be placed at least 0.5-1 mm below the level of the flooring (usually tiles) and never above. Suitable for pedestrian traffic, they absorb compressive and slip stress. Laying modules between 16 and 30 m3 inclusive are recommended and the joint laid in line with the joints in the underlying screed. Available in various colours and heights. Lay the joints according with the standards in force.




CO-EXTRUDED VINYL RESIN
bar length 2,5 lm - pack. 40 Pcs - 100 lm

Article	H mm
C514... (8x8)	7
C515... (10x8)	9
C516... (12x8)	11
C517... (14x8)	13
C518... (16x8)	15
C519... (20x8)	19

ARTICLES NOT FOR SALE SINGLY

Available combinations: GS-GT-GL (RT-MT-BIBI-B-A and N available on demand with a minimum quantity order of 400 pcs). The code of the selected colour must be added to the article code. E.g.: C514... (combination chosen colour Dark Grey / Transparent) C514 GT



On demand (at same price) also available **WITHOUT FLAP** with a minimum order of 200 pcs. **N.B.:** specify "WITHOUT FLAP" in order.



COLOURS

GS - Dark grey for rigid and flexible part	GT - Dark grey for rigid part / Transparent for flexible part	GL - Light grey for rigid and flexible part
--	---	---

ON DEMAND - MINIMUM QUANTITY 400 PCS for colour and height


RT - Red for rigid part / Transparent for flexible part	MT - Brown for rigid part / Transparent for flexible part	BIBI - White for rigid and flexible part
B - Beige (E84)	A - Ivory (E81)	N - Black for rigid and flexible part

(Price to be agreed. Production delay 4/5 weeks)


MORTAR-LAID JOINTS

POLISHED BRASS - STAINLESS STEEL AISI304/1.4301-V2A
NATURAL ALUMINIUM WITH SANDABLE VULCANIZED EPDM

The **MOVEMENT JOINT** has been specially created to relieve the stress in prestige floors (marble, granite, ceramic tiles or wood) laid on a mortar bed. The joint is simply inserted by hand and is levelled with a plastic hammer. It is available in brass and stainless steel with internal vulcanised expanded EPDM gasket. Strong, practical and top quality. Lay the joints according with the standards in force.



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the colour and the necessary height of the joint, calculating the thickness of the finished floor and the thickness of the screed. 2. Insert the joint into the screed letting it protrude slightly. 3. Proceed with laying the floor, aligning it with the rigid vertical part of the joint. 4. Complete laying by levelling the joint with the floor. 5. Using the mortar, grout the gap between the tiles and the profile.



POLISHED BRASS WITH SANDABLE VULCANIZED EPDM
bar length 2 lm - pack. 25 Pcs - 50 lm (GOT 40... - 20 lm)

Article	L x H mm
GOT 20...	10 X 20
GOT 40...	10 X 40

COLOURS

OL - Polished Brass	AC - Polished Stainless Steel AISI 304/1.4301-V2A	AN - Natural aluminium
---------------------	---	------------------------

COLOURS (EPDM)

N - Black	G - Grey
-----------	----------



POLISHED STAINLESS STEEL AISI 304/1.4301-V2A WITH SANDABLE VULCANIZED EPDM
bar length 2 lm - pack. 25 Pcs - 50 lm (GAC 40... - 20 lm)

Article	L x H mm
GAC 20...	10 X 20
GAC 40...	10 X 40

SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS

NATURAL ALUMINIUM WITH SANDABLE VULCANIZED EPDM
bar length 2 lm - pack. 25 Pcs - 50 lm (GAL 40... - 40 lm)

Article	L x H mm
GAL 20...	10 X 20
GAL 40...	10 X 40

Insert available in the colours: G - N. The code of the selected finish must be added to the article code. E.g.: GAC 20... (chosen insert colour grey) GAC 20G.

MORTAR-LAID MOVEMENT JOINTS are a range of joints in co-extruded vinyl resin with the flanges and vertical supports made in rigid synthetic vinyl resin and the elastic central part in flexible synthetic vinyl resin. The mortar-laid joints must be placed at least 0.5-1mm below the level of the ceramic tile-marble-granite floor and never above. Suitable for pedestrian traffic, they absorb compressive and slip stress. Laying modules between 16 and 30 m² inclusive are recommended and the joint laid in line with the joints in the underlying screed. Available in various colours and heights. Lay the joints according with the standards in force.

MORTAR-LAID JOINTS

CO-EXTRUDED VINYL RESIN




CO-EXTRUDED VINYL RESIN

bar length 2,5 lm - pack. 40 Pcs - 100 lm (C513 - pack. 50 lm)

Article	L x H mm
C511...	8 X 25
C512...	8 X 35
C513...	8 X 45

ARTICLES NOT FOR SALE SINGLY

Available combinations: GS-GT-GL (RT-MT-BIBI-B-A and N available on demand with a minimum quantity order of 400 pcs). The code of the selected colour must be added to the article code. E.g.: C511... (combination chosen colour dark grey/transparent) C511 GT.



movement joints

COLOURS


GS - Dark grey for rigid and flexible part	GT - Dark grey for rigid part / Transparent for flexible part	GL - Light grey for rigid and flexible part

ON DEMAND MINIMUM QUANTITY 400 PCS for colour and height

RT - Red for rigid part / Transparent for flexible part	MT - Brown for rigid part / Transparent for flexible part	BIBI - White for rigid and flexible part
B - Beige (E84)	A - Ivory (E81)	N - Black for rigid and flexible part

(Price to be agreed. Production delay 4/5 weeks)

EXAMPLES OF LAYING



1. Choose the colour and the necessary height of the joint, calculating the thickness of the finished floor and the thickness of the screed. 2. Insert the joint into the screed letting it protrude slightly (stage 1-2-3). 3. Proceed with laying the floor, aligning it with the rigid vertical part of the joint. 4. Complete laying by levelling the joint with the floor. 5. Using the mortar, grout the gap between the tiles and the profile.

This **DOUBLE SILICONE JOINT** is a co-extruded profile in hard and soft PVC. The double internal silicone provides a high degree of resistance to any type of compressive stress, heavy loads and foot traffic. The extension is designed to lengthen the joint, extending it to the total depth of auxiliary or insulation castings as required. Lay the joints according with the standards in force.

MORTAR-LAID DOUBLE JOINT

VINYL RESIN CO-EXTRUSION (PVC)



CO-EXTRUDED VINYL RESIN (PVC) WITH DOUBLE SILICONE

bar length 2,5 lm - pack. 40 Pcs - 100 lm (GDSP 43 - CONF. 50 lm)

Article	L x H mm
GDSP 43...	10 X 43
GDS 23...	10 X 25
GP 20	8 X 20



ARTICLES NOT FOR SALE SINGLY

Available combinations: GS - GT - GL.
The code of the selected colour must be added to the article code. E.g.: GDSP 43... (combination chosen colour dark grey/transparent) GDSP 43GT.

COLOURS

GS - Dark grey for rigid and flexible part	GT - Dark grey for rigid part / Transparent for flexible part	GL - Light grey for rigid and flexible part

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS




movement joints

1. Choose the colour and the necessary height of the joint, calculating the thickness of the finished floor and the thickness of the screed. 2. Insert the joint into the screed letting it protrude slightly. 3. Proceed with laying the floor, aligning it with the rigid vertical part of the joint. 4. Complete laying by levelling the joint with the floor. 5. Using the mortar, grout the gap between the tiles and the profile.

MORTAR LAYING FULL JOINT

CO-EXTRUDED VINYL RESIN (PVC)
WITH FULL SILICONE

FULL SILICONE JOINT is a co-extruded profile in hard and soft PVC. The double internal silicone provides a high degree of resistance to any type of compressive stress, heavy loads and foot traffic. The extension is designed to lengthen the joint, extending it to the total depth of auxiliary or insulation castings as required. Lay the joints according with the standards in force.




CO-EXTRUDED VINYL RESIN (PVC) WITH FULL SILICONE
bar length 2,5 lm - pack. 40 Pcs - 100 lm

Article	L x H mm		
GPSP 43...	10 x 43		
GPS 23...	10 x 25		
GP 20	8 x 20		

COLOURS

GS - Dark grey for rigid and flexible part	GT - Dark grey for rigid part / Transparent for flexible part	GL - Light grey for rigid and flexible part

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



ARTICLES NOT FOR SALE SINGLY


The code of the selected colour must be added to the article code.
E.g.: GPSP 43... (combination chosen colour dark grey/transparent)
GPSP 43GT.

1. Choose the colour and the necessary height of the joint, calculating the thickness of the finished floor and the thickness of the screed.
2. Insert the joint into the screed letting it protrude slightly.
3. Proceed with laying the floor, aligning it with the rigid vertical part of the joint.
4. Complete laying by levelling the joint with the floor.
5. Using the mortar, grout the gap between the tiles and the profile.

PROFLEX 25

NON-TOXIC IMPACT-RESISTANT
CO-EXTRUDED VINYL RESIN

PROFLEX 25 H 25 mm is a new expansion joint made of coextruded vinyl resin available in two standard colours - dark grey (GS) and light grey (GL). **PROFLEX 25** H 25 mm provides elastic expansion joints for various kinds of flooring, such as marble or granite, and especially floors made with Sasso Italia. The new decorative indoor and outdoor flooring also known as SASSO ITALIA is approx. 25 mm thick and laid over a 10-20 mm base of cement/concrete. This kind of floor needs an expansion/control joint every 16-30 m³ of material to avoid cracking caused by the floor's expansion. PROFLEX H 25 mm lets you place a GP 20 EXTENSION JOINT at the bottom in order to apply/lay the joint inside the concrete base. It can withstand the frequent passage of pedestrians and vehicles (forklifts, pallet trucks, automobiles). The joint must be installed at the same level of the floor or 0.5-1 mm lower (never above). Lay the joints according with the standards in force. HIGH RESISTANCE TO LOADS AND TO FREQUENT TRAFFIC OF PALLET TRUCKS AND FORKLIFTS.




CO-EXTRUDED VINYL RESIN
bar length 2,5 lm - pack. 20 Pcs - 50 lm

Article	H mm		
PFXGP 45...	45		
PFX 25...	25		
GP 20	20		

COLOURS

GS - Dark grey for rigid and flexible part	GL - Light grey for rigid and flexible part

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the colour of the joint. **1a:** For the version with the extension, insert it onto the fresh cement base leaving the cylindrical part out, for subsequent fitting with PROFLEX 25. **2.** Place and fix with screws/nails to the cement floor and snap the PROFLEX 25 into protruding extension. **3.** Begin laying the floor from the inside, near the joint aligning it with the edges. **4.** Finish laying the floor by levelling the joint with the floor. **5.** Plaster the gap between floor and joint with specific mortar.

The code of the selected colour must be added to the article code.
E.g.: PFX 25 ... (chosen colour dark grey) PFX 25GS.

PROEXPAN 115-130-190-210 is a range of structural expansion joints in natural aluminium with knurled flat surface and a black or grey synthetic rubber insert.

Made to withstand vertical, horizontal and transversal structural movements due to compressive and tensile stress in large buildings or complexes. The joint is laid on existing surfaces, also vertically, over the void between the two semi-detached surfaces of the same building or between two bays. It withstands frequent pedestrian traffic and also vehicles with rubber tyres that can load to 700 kgs. (PENF 190-210)

PROEXPAN 115-130-190-210

NATURAL ALUMINIUM
+ VINYL RESIN / RUBBER INSERT



NATURAL ALUMINIUM + VINYL RESIN / RUBBER INSERT

bar length 2,7 lm - pack. 10 Pcs - 27 lm


Article	LxHxLa mm		
PENF 115...	21 x 12 x 115		
PENF 130...	38 x 12 x 128		

NATURAL ALUMINIUM + NEOPRENE INSERT

bar length 3 lm - pack. 10 Pcs - 30 lm

Article	LxHxLa mm		
PENF 190N	65 x 19 x 185		
PENF 210...	90 x 19 x 210		

Movement mm: -10/+16 (PENF 190N) -15/+10 (PENF 210...)
Available in the colours: G - N (PENF 190N excluded).
The code of the selected finish must be added to the article code.
E.g.: PENF 130... (chosen insert colour grey) PENF 130G.



INTERCHANGEABLE INSERT IN VINYL RESIN/RUBBER INSERT

BLACK OR GREY - bar length 3 lm - pack. 10 Pcs - 30 lm

Article	L mm		
IPEN 20...	20		
IPEN 40...	35		


INTERCHANGEABLE NEOPRENE INSERT BLACK OR GREY

bar length 4 lm - pack. 10 Pcs - 40 lm


Article	L mm		
IPEN 65N	65		
IPEN 452...	45 x 2		

Insert available in the colours: G - N (IPEN 65N excluded).
The code of the selected finish must be added to the article code.
E.g.: IPEN 20... (chosen insert colour grey) IPEN 20G.


PENF 115...



PENF 130...




EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS




Fix the side wings/flanges in aluminium with:
1. Screws and screw anchors at 20 cm intervals along both sides of the whole joint
2. Two-pack epoxy adhesive or with strong fast-setting silicone.

Due to the nature of the product itself, natural aluminium, and its specific use on the floor as technical joint with no decorative role, light scratches on its surface will not be accepted for claims.


INSERT COLOURS



ON DEMAND - MINIMUM QUANTITY 100 lm
ONLY FOR: PENF 115, PENF 130



(Price to be agreed. Production delay 4/5 weeks)



ANGLES BAR / WALL

NATURAL ALUMINIUM + NEOPRENE INSERT

ANGLE BAR NATURAL ALUMINIUM + NEOPRENE INSERT

bar length 3 lm - pack. 10 Pcs - 30 lm

Article	LxHxLa mm		
PENFP 190N	65 x 19 x 125		
PENFP 210..	90 x 19 x 150		

INTERCHANGEABLE BLACK OR GREY VINYL RESIN/RUBBER INSERT


bar length 3 lm - pack. 10 Pcs - 30 lm

Article	L mm		
IPEN 65N	65		
IPEN 452...	45 x 2 Pz		

Available in the colours: G - N.
The code of the selected finish must be added to the article code.
E.g.: PENFP 210... (chosen insert colour grey) PENFP 210G.

PRODUCT SUPPLIED NOT ASSEMBLED

Due to the nature of the product itself, natural aluminium, and its specific use on the floor as technical joint with no decorative role, light scratches on its surface will not be accepted for claims.




* = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed


PROEXPAN H20 PROEXPAN H40

NATURAL ALUMINIUM
+ VINYL RESIN / RUBBER INSERT

PROEXPAN H20 - H40 is a range of professional structural joints for floors laid on mortar bed (PEN H20) and (PEN H 40). They are made with a punched aluminium base and a vinyl rubber insert available in black or grey. **PROEXPAN H20 - H40** profiles for laying with mortar must have the flanges fixed to the substrate by screws and screw anchors (approx. every 30 cm).



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the expansion joint with suitable height for the thickness of the floor and the screed/floor rough and choose the colour of the insert.
2. Fix the punched flanges to the substrate using screws and screw anchors, calculating the fixing points at 30cm intervals on both sides.
3. Make the screed over the punched flanges of the structural or expansion joint, calculating the thickness of the final floor, and then lay the floor as normal.



NATURAL ALUMINIUM + VINYL RESIN / RUBBER INSERT
bar length 3 lm - pack. 5 Pcs - 15 lm

Article	HxL mm
PEN 20...	20 x 24
PEN 40...	40 x 45



INTERCHANGEABLE INSERT IN VINYL RESIN/RUBBER INSERT
BLACK OR GREY - bar length 3 lm - pack. 10 Pcs - 30 lm


Article	L mm
IPEN 20...	20
IPEN 40...	35

NATURAL ALUMINIUM ANGLE BAR / WALL + VINYL RESIN / RUBBER INSERT - bar length 3 lm - pack. 5 Pcs - 15 lm


Article	HxL mm
PENP 20...	20 x 24
PENP 40...	40 x 45

Available in the colours: G - N (Beige and Ivory available on demand with a minimum quantity order of 300 lm).
The code of the selected finish must be added to the article code.
E.g.: PEN 20... (chosen insert colour grey) PEN 20G.

INSERT COLOURS





ON DEMAND - MINIMUM QUANTITY 100 PCS
(Price to be agreed. Production delay 4/5 weeks)



GDA 25 GDA 35


NATURAL ALUMINIUM
+ NEOPRENE INSERT

GDA 25 - GDA 35 is a range of professional structural joints for floors laid on mortar bed. They are made with a punched aluminium base and a vinyl rubber insert available in black or grey. It withstands traffic of vehicles with tyreload to 700 kgs and also trucks with maximum tyreload to 1000 kgs.




1. Choose the colour of the joint.
2. Fix the punched flanges to the substrate using screws and screw anchors, calculating the fixing points at 30cm intervals on both sides.
3. Make the screed over the punched flanges of the structural or expansion joint, calculating the thickness of the final floor, and then lay the floor as normal.
4. Using the special glue, fill the gap between the tiles and the profile.

INSERT COLOURS



ON DEMAND



NATURAL ALUMINIUM + NEOPRENE INSERT
bar length 3 lm

Article	HxL mm
GDA 25...	50 x 25
GDA 35...	50 x 35



Movement mm: +/- 5.
Insert in smooth neoprene on demand.

NATURAL ALUMINIUM ANGLE BAR / WALL + NEOPRENE INSERT
bar length 3 lm

Article	HxL mm
GDAP 25...	50 x 25
GDAP 35...	50 x 35

Available in the colours: G - N (Ivory on demand).
The code of the selected finish must be added to the article code.
E.g.: GDA 25... (chosen insert colour grey) GDA 25G.


Insert in smooth neoprene on demand.



GDA 55

ALUMINIUM
+ NEOPRENE INSERT

GDA 55 is a structural joint for floors, 35, 50 and 80 mm, in good quality natural aluminium with the interchangeable neoprene insert allowing the joint to expand and contract. Visible thickness 55 mm (**GDA 55**), bar length 3 lm. Black or Grey insert. Bear weights of cars, with the wheel loads up to 650 kg and trucks with a maximum load of 1000 kg on the wheel.



ALUMINIUM + BLACK / GREY NEOPRENE INSERT bar length 3 lm

Article	L x H x L1 mm
GDA 5535...	55 x 35 x 155
GDA 5550...	55 x 50 x 155
GDA 5580...	55 x 80 x 155

Movement mm: +/- 10

Available in the colours: N - G.

The code of the selected finish must be added to the article code.
E.g.: GDA 5535...(chosen insert colour black) GDA 5535N

Insert in smooth neoprene on demand.

ANGLES BAR ALUMINIUM + BLACK NEOPRENE INSERT bar length 3 lm


Article	L x H x L1 mm
GDAP 5535	55 x 35 x 105
GDAP 5550	55 x 50 x 105
GDAP 5580	55 x 80 x 105

Insert in smooth neoprene on demand.

COLOURS

N - Black (RAL 9005)	G - Grey (7038)
----------------------	-----------------

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the expansion joint with suitable height for the thickness of the floor and the screed/floor rough and choose the colour of the insert. 2. Fix the punched flanges to the substrate using screws and screw anchors, calculating the fixing points at 30 cm intervals on both sides. 3. Make the screed over the punched flanges of the structural or expansion joint, calculating the thickness of the final floor, and then lay the floor as normal.

FIREPROOF CORD

MINERAL WOOL AND FIBREGLASS

FIREPROOF GLUE FOR CORD FIXING

Article	Pack. Kg
CIC 014	1,4
CIC 7	7

The delivery of the test certificate depends on the use of silicate glue for the fixing of the same.

The cord is certified in accordance with the new European Standard EN 13501-2.

Consumption of sealant is of about 50 g per linear metre of cord.

FIREPROOF CORD - Diameter 20 - 60 mm

Article	Ø mm	lm Roll
CDT 20	20	30
CDT 30	30	30
CDT 40	40	30
CDT 50	50	25
CDT 60	60	25




* = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed

GNS 20 GNS 50

NATURAL ALUMINIUM

Structural joint **GNS 20 – GNS 50** is in good quality natural aluminium with neoprene in the lower central part and another aluminium profile in the upper visible part. It withstands heavy loads and frequent traffic of vehicles with a total truckload of 8 kgs/mm². Bar length 3 m, visible head width 30 mm.




NATURAL ALUMINIUM

bar length 3 lm

Article	L x H mm		
GNS 3020	30 x 20		
GNS 3050	30 x 50		

Movement mm: +/- 3

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the expansion joint with suitable height for the thickness of the floor and the screed/floor rough and choose the colour of the insert. 2. Fix the punched flanges to the substrate using screws and screw anchors, calculating the fixing points at 30cm intervals on both sides. 3. Make the screed over the punched flanges of the structural or expansion joint, calculating the thickness of the final floor, and then lay the floor as normal.

ANGLES BAR / WALL

NATURAL ALUMINIUM


GNSP 3050

GNSP 3020

NATURAL ALUMINIUM ANGLES BAR

bar length 3 lm - pack. 10 Pcs - 30 lm

Article	L x H mm		
GNSP 3020	30 x 20		
GNSP 3050	30 x 50		




COLOURS



GNS 75... 18/50/80

NATURAL ALUMINIUM

Structural joint **GNS 75** is in good quality natural aluminium with neoprene in the lower central part and another aluminium profile in the upper visible part. It withstands heavy loads and frequent pedestrian traffic. Bar length 3 m, visible head width 75 mm. It withstands forklift trucks with rubber tyre and transpallets to a maximum total load of 6,5 kgs/mm².




NATURAL ALUMINIUM

bar length 3 lm

Article	H mm		
GNS 7518	18		
GNS 7550	50		
GNS 7580	80		

Movement mm: +10/-5 Horiz. +/-5 Vert.

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the expansion joint with suitable height for the thickness of the floor and the screed/floor rough and choose the colour of the insert. 2. Fix the punched flanges to the substrate using screws and screw anchors, calculating the fixing points at 30cm intervals on both sides. 3. Make the screed over the punched flanges of the structural or expansion joint, calculating the thickness of the final floor, and then lay the floor as normal.

COLOURS



PROPLATE FIX is a range of flat joint-cover profiles to cover structural movements (contraction due to flexural or compressive stress) of two different load-bearing structures.

PROPLATE FIX made in silver anodized aluminium is recommended for environments with intense pedestrian and vehicular traffic. Available upon request with stainless steel fixing clips (5 Pcs. for vertical/façade use 10 Pcs. for horizontal/floor use); corner profiles are also available.

PROPLATE FIX

FLAT AND ANGLE PROFILE
IN ALUMINIUM



FLAT PROFILE - SILVER ANOD. ALUMINIUM

bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	L mm		
PETFXPAA 50	50		
PETFXPAA 70	70		



ANGLE PROFILE - SILVER ANOD. ALUMINIUM


bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H x L mm		
PETFAXA 50	22 x 50		
PETFAXA 70	24 x 70		

PRODUCT SUPPLIED NOT ASSEMBLED

Article	H mm		
CPFXAC 40/10	40		



COLOURS



AA - Anodized silver alum.

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS

1. Choose the profile in the required width and material. 2. Insert the fixing clips into the relative groove, one every 50/75 cm (5 Pcs. for wall applications - 10 Pcs. for floor applications). 3. Insert/Lay the PROPLATE FIX in the existing void, applying uniform pressure or using a plastic hammer, thereby creating a perfect joint cover. The same method is used for laying the corner profile.



PROPLATE FIX is a range of flat joint-cover profiles to cover structural movements (contraction due to flexural or compressive stress) of two different load-bearing structures.

PROPLATE FIX made in rigid PVC is recommended for walls and facades and for ceilings. Available upon request with stainless steel fixing clips (5 Pcs. for vertical/façade use 10 Pcs. for horizontal/floor use); corner profiles are also available.

PROPLATE FIX

FLAT AND ANGLE PROFILE
IN VINYL RESIN (PVC)



FLAT PROFILE - VINYL RESIN (PVC)

bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	L mm		
PETFXP 50-01	50		



ANGLE PROFILE - VINYL RESIN (PVC)

bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H x L mm		
PETFX 50-01	22 x 50		

PRODUCT SUPPLIED NOT ASSEMBLED

FIXING CLIPS BETWEEN 20 TO 45 mm - STAINLESS STEEL - pack. 10 Pcs



Article	H mm		
CPFXAC 40/...	40		

COLOURS




01 - White

CPFXAC 40



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS




1. Choose the profile in the required width and material. 2. Insert the fixing clips into the relative groove (5 Pcs. for wall applications - 10 Pcs. for floor applications). 3. Insert/Lay the PROPLATE FIX in the existing void, applying uniform pressure or using a plastic hammer, thereby creating a perfect joint cover. The same method is used for laying the corner profile.

* = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed

An interpretation of:
Norwegian National Opera House, Snøhetta, OSLO (Norway), 2008



LOW THICKNESS




PROKERLAM SQUARE

ANODIZED SILVER, POLISHED CHROME AND GOLD ALUMINIUM

PROKERLAM SQUARE is a square corner bead profile in anodized and polished aluminium suitable to protect the external corners of coverings with low thickness. It can be used like connection profile between step tread and riser of stairs coated with ceramic and mosaic with low thickness. Its particular section and the availability in three different finishes make **PROKERLAM SQUARE** a much sought-after profile that allows a workmanlike application even with low thickness coverings.

PKLQ... 045



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROKERLAM SQUARE" according to the desired finish.
2. Cut "PROKERLAM SQUARE" to the desired length and apply the adhesive on the support where the profile will be laid.
3. Press the anchoring flange of "PROKERLAM SQUARE" into the adhesive.
4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile.
5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.



ANODIZED SILVER ALUMINIUM thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm
PKLQAA 045	4,5



POLISHED GOLD ALUMINIUM thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm
PKLQBO 045	4,5

POLISHED CHROME ALUMINIUM thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm
PKLQBC 045	4,5

COLOURS




PROKERLAM JOLLY

ANODIZED AND POLISHED ALUMINIUM SILVER, CHROME AND GOLD

PROKERLAM JOLLY is a quarter-circle rounded bead profile in anodized and polished aluminium suitable to protect the external corners of coverings with low thickness. It can be used like connection profile between step tread and riser of stairs coated with ceramic and mosaic with low thickness. Its particular section and the availability in three different finishes make **PROKERLAM JOLLY** a much sought-after profile that allows a workmanlike application even with low thickness coverings.

PKLJ... 045



EXAMPLE FOR LAYING



1. Choose "PROKERLAM Jolly" according to the desired finish.
2. Cut "PROKERLAM Jolly" to the desired length and apply the adhesive on the support where the profile will be laid.
3. Press the anchoring flange of "PROKERLAM Jolly" into the adhesive.
4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile.
5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.



ANODIZED SILVER ALUMINIUM thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm
PKLJAA 045	4,5



POLISHED CHROME ALUMINIUM thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm
PKLJBC 045	4,5

POLISHED GOLD ALUMINIUM thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm
PKLJBO 045	4,5

COLOURS





PROKERLAM LINE is a profile in polished and brushed stainless steel AISI 304/1.4301-V2A suitable to protect the external corners of coverings in low thickness. It can be used like connection profile between step tread and riser of stairs coated with ceramic and mosaic with low thickness. Its particular section and the availability in three different heights and finishes and special pieces such as internal and external corners, end caps and joints make **PROKERLAM LINE** a much sought-after profile that allows a workmanlike application even with low thickness coverings.

PROKERLAM LINE

POLISHED AND BRUSHED STAINLESS STEEL AISI 304/1.4301-V2A



POLISHED STAINLESS ST. AISI 304/1.4301-V2A with protective film
Bar lenght 2,7 lm - Pack 40 PCS - 108 lm

Article	H mm		
PKLLAC 045	4,5		
PKLLAC 06	6		



BRUSHED STAINLESS ST. AISI 304/1.4301-V2A with protective film
Bar lenght 2,7 lm - Pack 40 PCS - 108 lm

Article	H mm		
PKLLACS 045	4,5		
PKLLACS 06	6		

COLOURS



AC - Polished stainless steel AISI 304/1.4301-V2A ACS - Brushed stainless steel AISI 304/1.4301-V2A



LAYING INSTRUCTIONS



1. Choose "PROKERLAM LINE" according to the desired finish.
2. Cut "PROKERLAM LINE" to the desired length and apply the adhesive on the support where the profile will be laid.
3. Press the anchoring flange of "PROKERLAM LINE" into the adhesive.
4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile.
5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.

PROKERLAM LINE is a Y-shaped profile in anodized and polished aluminium suitable to protect the external corners of coverings in low thickness. It can be used like connection profile between step tread and riser of stairs coated with ceramic and mosaic with low thickness. Its particular section and the availability in three different heights and finishes and special pieces such as internal and external corners, end caps and joints make **PROKERLAM LINE** a much sought-after profile that allows a workmanlike application even with low thickness coverings.

PROKERLAM LINE

ANODIZED, VARNISHED AND STONE LINE ALUMINIUM



ANODISED SILVER ALUMINIUM thermo packed
Bar lenght 2,7 lm - Pack 40 PCS - 108 lm

Article	H mm		
PKLLAA 045	4,5		
PKLLAA 06	6		

VARNISHED ALUMINIUM (White-Black) thermo packed
Bar lenght 2,7 lm - Pack 40 PCS - 108 lm

Article	H mm		
PKLLA 045-01	4,5		
PKLLA 045-11	4,5		
PKLLA 06-01	6		
PKLLA 06-11	6		




STONE LINE ALUMINIUM thermo packed
Bar lenght 2,7 lm - Pack 40 PCS - 108 lm

Article	H mm		
PKLLA 045-SL...	4,5		
PKLLA 06-SL...	6		


The code of the selected colour must be added to the article code.
E.g.: PKLLA 06-... (chosen colour stone cream) PKLLA 06-SL02.

COLOURS

ANODIZED		VARNISHED	
AA - Anodized Silver Alu.	01 - White Varnished Alu.	11 - Black Varnished Alu.	
STONE LINE			
SL02 - Stone cream	SL03 - Stone greywory	SL04 - Stone sand	
SL05 - Stone grey	SL08 - Stone antradark		



LAYING INSTRUCTIONS



1. Choose "PROKERLAM LINE" according to the desired finish.
2. Cut "PROKERLAM LINE" to the desired length and apply the adhesive on the support where the profile will be laid.
3. Press the anchoring flange of "PROKERLAM LINE" into the adhesive.
4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile.
5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.



PROSHELL D ALL is a profile in anodized and polished aluminum with a visible 45° sloping surface. The profile allows to connect the floor and wall coverings in ceramic and mosaic with low thickness. It is particularly suitable to ensure cleanliness and hygiene in every kind of environment where good resistance to mechanical and chemical stresses are required. Its particular section and availability in three different finishes, make **PROSHELL D ALL** a much sought after profile.

PROSHELL D ALL

ANODIZED SILVER, POLISHED CHROME AND GOLD ALUMINIUM




ANODIZED SILVER ALUMINIUM thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm
PSHDAA 045	4,5




POLISHED CHROME/GOLD ALUMINIUM thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm
PSHDBC 045	4,5
PSHDBO 045	4,5



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROSHELL D ALL" according to the desired finish.
2. Cut "PROSHELL D ALL" to the desired length and apply the adhesive on the support where the profile will be laid.
3. Press the anchoring flange of "PROSHELL D ALL" into the adhesive.
4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile.
5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.

COLOURS



PROSHELL R ALL is a cove-shaped profile in anodized and polished aluminum. The profile allows to connect the floor and wall coverings in ceramic and mosaic with low thickness. It is particularly suitable to ensure cleanliness and hygiene in every kind of environment where good resistance to mechanical and chemical stresses are required. Its particular section and availability in three different finishes, make **PROSHELL R ALL** a much sought after profile.

PROSHELL R ALL

ANODIZED SILVER, POLISHED CHROME AND GOLD ALUMINIUM




ANODIZED SILVER ALUMINIUM thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm
PSHRAA 045	4,5


POLISHED CHROME/GOLD ALUMINIUM thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm
PSHRBC 045	4,5
PSHRBO 045	4,5

COLOURS



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROSHELL R ALL" according to the desired finish.
2. Cut "PROSHELL R ALL" to the desired length and apply the adhesive on the support where the profile will be laid.
3. Press the anchoring flange of "PROSHELL R ALL" into the adhesive.
4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile.
5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.


* = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed

PROINTER KL ACC


STAINLESS STEEL AISI 304/1.4301-V2A

PROINTER KL ACC is a cove-shaped profile in stainless steel AISI 304/1.4301-V2A. The profile allows to connect the floor and wall coverings in ceramic and mosaic also with low thickness. It is particularly suitable to ensure cleanliness and hygiene in every kind of environment where good resistance to mechanical and chemical stresses are required. Its particular section makes **PROSHELL KL ALL** a much sought after profile.

PIKL... 15



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROINTER KL ACC" according to the desired finish. 2. Cut "PROINTER KL ACC" to the desired length. 3. Apply the silicone along the floor-wall connection. 4. Press the arrowhead of "PROINTER KL ACC" into the silicone evenly until it is completely adherent to the floor and wall.



POLISHED STAINLESS ST. AISI 304/1.4301-V2A with protective film
bar length 2,7 lm - pack. 40 Pcs - 108 lm - 8/10mm

Article	H mm
PIKLAC 15	15

BRUSHED STAINLESS ST. AISI 304/1.4301-V2A with protective film
bar length 2,7 lm - pack. 40 Pcs - 108 lm - 8/10mm

Article	H mm
PIKLACS 15	15

COLOURS



SANDED STAINLESS ST. AISI 304/1.4301-V2A with protective film
bar length 2,7 lm - pack. 40 Pcs - 108 lm - 8/10mm

Article	H mm
PIKLACSB 15	15

SUPER POLISHED ST. AISI 304/1.4301-V2A with protective film
bar length 2,7 lm - pack. 40 Pcs - 108 lm - 8/10mm

Article	H mm
PIKLACML 15	15

AVAILABLE MINIMUM QUANTITY 100 PCS




SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS

PROINTER KL ALL


POLISHED AND CHROMED BRASS AND ANODIZED AND POLISHED ALUMINIUM

PROSHELL KL ALL is a cove-shaped profile in polished and chromed brass and anodized and polished aluminium. The profile allows to connect the floor and wall coverings in ceramic and mosaic also with low thickness. It is particularly suitable to ensure cleanliness and hygiene in every kind of environment where good resistance to mechanical and chemical stresses are required. Its particular section and availability in five different finishes, make **PROSHELL KL ALL** a much sought after profile.

PIKL... 045



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROINTER KL ALL" according to the desired finish. 2. Cut "PROINTER KL ALL" to the desired length. 3. Apply the silicone along the floor-wall connection. 4. Press the arrowhead of "PROINTER KL ALL" into the silicone evenly until it is completely adherent to the floor and wall.



POLISHED / CHROMED BRASS thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm
PIKL0L 045	4,5
PIKL0C 045	4,5

CAPS - VARNISHED PLASTIC

Article	Pack. 2 Pcs	Pack. 10 Pcs
TPIKL .../...		



* End caps of the on demand profiles are also on demand.

COLOURS



POLISHED CHROME ALUMINIUM / GOLD thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm
PIKLBC 045	4,5
PIKLBO 045	4,5

ANODIZED SILVER ALUMINIUM thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm


Article	H mm
PIKLAA 045	4,5

CAPS - VARNISHED PLASTIC

Article	Pack. 2 Pcs	Pack. 10 Pcs
TPIKL .../...		



COLOURS



PROSTYLE KL 10 is a step protecting profile, technical and very elegant, used to keep the step made of thin ceramic tiles and kerlite/laminam non-skid and non-slip. Product in anodized aluminium with the angle portion crimped in order to increase its adhesion. Internal height 4.5 mm. It is compulsory in public buildings to comply with accident-prevention regulations.

PROSTYLE KL 10

ANODIZED SILVER ALUMINIUM



ANODIZED SILVER ALUMINIUM
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm
PSYKLAA 1045	4,5

COLOURS




AA - Anodized silver aluminium

CAPS - pack. 2 Pcs (1 R and 1 L)

Article	H mm
TPSYKLAA 1045/1	4,5

Articles not for sale singly

PSYKLAA 1045



1. Cut "PROSTYLE KL 10" to the desired length. 2. Lay the tiles on the step rise and apply the adhesive on the step tread where the profile will be laid. 3. Lay the profile on the step tread aligning it with the tiles of the step rise. 4. Apply the adhesive on the step tread and lay the tiles, aligning them with the profile. Remove immediately all the remains of adhesive from the surface of the profile. 5. Grout the joints between the tile and the profile, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



PROSTAIR KL 20 is a step protecting profile, technical and very elegant, used to keep the step made of thin ceramic tiles and kerlite/laminam non-skid and non-slip. Product in anodized aluminium with the upper portion crimped in order to increase its adhesion and a lower vertical tab created to cover the riser of the step. It is compulsory in public buildings to comply with accident-prevention regulations. Available height H 4.5 mm.


PROSTAIR KL 20

ANODIZED SILVER ALUMINIUM

ANODIZED SILVER ALUMINIUM
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm
PTRKLAA 2045	4,5


COLOURS



AA - Anodized silver aluminium




PTRKLAA 2045



1. Cut "PROSTAIR KL 20" to the desired length. 2. Lay the tiles on the step rise and apply the adhesive on the step tread where the profile will be laid. 3. Fill the cavities on back of the profile with adhesive and lay it on the step tread aligning it with the tiles of the step rise. 4. Apply the adhesive on the step tread and lay the tiles, aligning them with the profile. Remove immediately all the remains of adhesive from the surface of the profile. 5. Grout the joints between the tile and the profile, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS






An interpretation of:
Petronas Towers, César Pelli, KUALA LUMPUR (Malaysia), 1996






PROFILES FOR TERRACES




PROTERRACE DOUBLE DRIP

VARNISHED ALUMINIUM

PROTERRACE DOUBLE DRIP is an edging profile in varnished aluminium, designed to protect the edges of the tiles on terraces and balconies and to allow the downflow of water. The profile is provided with a flange that ensures the right fixing and an adhesive stripe, which protect the outflow holes to be closed by silicone. The double drip allows the drainage water to flow out in case of application with PRODES0 DRAIN drainage membrane. To reach a right connection between profile and the waterproofing system it's needed to use **PROBAND 150** with **PROBAND KOLL/AB**. The product is also available on request with a **SPECIAL SEASIDE PRE-TREATMENT** which increases its resistance to corrosion when installed at sea front environments.



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose PROTERRACE DOUBLE DRIP according to the tile thickness and desired colour. 2. Fix the external corners to the screed (at least 1 cm from it) with nails. 3. Fix the draining adhesive stripe in polyurethane on the vertical side of the profile. 4. Cut the PROTERRACE DOUBLE DRIP at desired length joining it to the corners using the linking elements and fix it with nails to the substrate. 5. Lay the desired waterproofing system. 6. Lay the tiles leaving at 5 mm between the tile and the profile. 7. Seal the space between tile and profile with **PROBAND FIX (P.186)**.

VARNISHED/COATED ALUMINIUM

bar length 2,7 lm - pack. 5 Pcs - 13,5 lm

Article	H mm		
⊙ PDD 10AL...	10		
⊙ PDD 125AL...	12,5		
⊙ PDD 175AL...	17,5		
⊙ PDD 205AL...	20,5		
⊙ PDD 225AL...	22,5		
⊙ PDD 30AL...	30		

Available in the colours: BF - GF - A - TF (EF - C - B - G - E - T on demand). The code of the selected colour must be added to the article code. E.g.: PDD 175AL... (white) PDD 175ALBF.

JOINTS - pack. 10 Pcs

Article	H mm		
⊙ GINPDD 10AL...	10		
⊙ GINPDD 125AL...	12,5		
⊙ GINPDD 175AL...	17,5		
⊙ GINPDD 205AL...	20,5		
⊙ GINPDD 225AL...	22,5		
⊙ GIPDD 30AL...	30		

EXTERNAL CORNERS - pack. 10 Pcs

Article	H mm		
⊙ AEPDD 10AL.../10	10		
⊙ AEPDD 125AL.../10	12,5		
⊙ AEPDD 175AL.../10	17,5		
⊙ AEPDD 205AL.../10	20,5		
⊙ AEPDD 225AL.../10	22,5		
⊙ AEPDD 30AL.../10	30		

INTERNAL CORNERS - pack. 10 Pcs

Article	H mm		
⊙ AIPDD 10AL.../10	10		
⊙ AIPDD 125AL.../10	12,5		
⊙ AIPDD 175AL.../10	17,5		
⊙ AIPDD 205AL.../10	20,5		
⊙ AIPDD 225AL.../10	22,5		
⊙ AIPDD 30AL.../10	30		

HOW TO REQUEST SEASIDE TREATMENT

When placing your order please add S to the article's number
Example: PDD 175ALGF (seaside) = **PDD 175ALGFS**

GINPDD ...AL...

AEPDD ...

AIPDD ...

EMBOSSED COLOURS

BF - White (9010)	GF - Grey (7038)	A - Anthracite grey (no RAL)	TF - Dark brown (8019)

COLOURS ON DEMAND




EMBOSSED		SEMIGLOSSY			
EF - Beige (1019)	C - Corten	B - White (9010)	G - Grey (7038)	E - Beige (1019)	T - Dark brown (8019)



PROTERRACE DRAIN DRIP is an edging profile in varnished aluminium, designed to protect the edges of the tiles on terraces and balconies and to allow the downflow of water. The profile is provided with a flange that ensures the right fixing and an adhesive stripe, which protect the outflow holes to be closed by silicone. To reach a right connection between profile and the waterproofing system it's needed to use **PROBAND 150** with **PROBAND KOLL/AB**. The product is also available on request with a **SPECIAL SEASIDE PRE-TREATMENT** which increases its resistance to corrosion when installed at sea front environments.

PROTERRACE DRAIN DRIP

VARNISHED/COATED ALUMINIUM
While stocks last.



VARNISHED/COATED ALUMINIUM
bar length 2,7 lm - pack. 5 Pcs - 13,5 lm

Article	H mm		
PFDPP 10AL...	10		
PFDPP 125AL...	12,5		
PFDPP 20AL...	20		

Available in the colours: BF - GF - A - TF (EF - C - B - G - E - T on demand). The code of the selected colour must be added to the article code. E.g.: PFDPP 10AL... (white) PFDPP 10ALBF.


END CAPS - Pack. 2 PCS

Article			
TPFDPP AL.../2			




EXTERNAL CORNERS - pack. 10 Pcs

Article			
AEPFDPP 10AL.../10			
AEPFDPP 125AL.../10			
AEPFDPP 20AL.../10			



INTERNAL CORNERS - pack. 10 Pcs

Article			
AIPFDPP 10AL.../10			
AIPFDPP 125AL.../10			
AIPFDPP 20AL.../10			



JOINTS - pack. 1 upper + 1 lower


Article			
GINFDPP 10AL .../1			
GINFDPP 125AL .../1			
GINFDPP 20AL .../1			



HOW TO REQUEST SEASIDE TREATMENT

When placing your order please add S to the article's number
Example: PFDPP 10ALGF (seaside) = PFDPP 10ALGFS

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose PROTERRACE DRAIN DRIP according to the tile thickness and desired colour.
2. Fix the external corners to the screed (at least 1 cm from it) with nails.
3. Fix the draining adhesive stripe in polyurethane on the vertical side of the profile.
4. Cut the PROTERRACE DRAIN FDP at desired length joining it to the corners using the linking elements and fix it with nails to the substrate.
5. Lay the desired waterproofing system.
6. Lay the tiles leaving at 5 mm between the tile and the profile.
7. Seal the space between tile and profile with **PROBAND FIX (P.186)**.

EMBOSSED COLOURS

BF - White (9010)	GF - Grey (7038)	A - Anthracite grey (no RAL)	TF - Dark brown (8019)

COLOURS ON DEMAND

EMBOSSED		SEMIGLOSSY			
EF - Beige (1019)	C - Corten	B - White (9010)	G - Grey (7038)	E - Beige (1019)	T - Dark brown (8019)




PROTERRACE DRAIN FDP


VARNISHED/COATED ALUMINIUM

PROTERRACE DRAIN FDP is an edging profile in varnished aluminium designed to protect the edges of the tiles laid on terraces and balconies and to allow a correct water discharge. The profile is equipped with a punched flange that ensures its fixing to the support. The profile is also provided with holes that allow the discharge of the water filtered between the profile and tiles. To reach a right connection between profile and the waterproofing system it's needed to use **PROBAND 150** with **PROBAND KOLL/AB**. The product is also available on request with a **SPECIAL SEASIDE PRE-TREATMENT** which increases its resistance to corrosion when installed at sea front environments.

PFDP 10AL...




EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose PROTERRACE DRAIN FDP according to the tile thickness and desired colour.
2. Fix the external corners to the screed with nails taking care to separate them at least 1 cm from it.
3. Cut "PROTERRACE DRAIN FDP" to the desired length. Lay the profile and fix it with nails. Connect it with the junctions.
4. Apply the desired waterproofing system.
5. Lay the tiles, leaving about 5 mm between tiles and profile.
6. Seal the space between tiles and profile with **PROBAND FIX (P.186)**.

HOW TO REQUEST SEASIDE TREATMENT

When placing your order please add S to the article's number
Example: PFDP 10ALGF (seaside) = **PFDP 10ALGFS**



VARNISHED/COATED ALUMINIUM
bar length **2,7 lm** - pack. **5 Pcs** - **13,5 lm**

Article	H mm
PFDP 10AL...	10
PFDP 125AL...	12,5

Available in the colours: BF - GF - A - TF (EF - C - B - G - T - E on demand)
The code of the selected colour must be added to the article code.
E.g.: PFDP 10 AL... (white) PFDP 10 ALB.

EMBOSSED COLOURS

BF - White (9010)	GF - Grey (7038)	A - Anthracite grey (no RAL)	TF - Dark brown (8019)
-------------------	------------------	------------------------------	------------------------

COLOURS ON DEMAND

EMBOSSED		SEMIGLOSSY	
EF - Beige (1019)	C - Corten	B - White (9010)	G - Grey (7038)
		E - Beige (1019)	T - Dark brown (8019)



EXTERNAL CORNERS - pack. **10 Pcs**

Article
AEPFDP 10AL.../10
AEPFDP 125AL.../10


INTERNAL CORNERS - pack. **10 Pcs**

Article
AIPFDP 10AL.../10
AIPFDP 125AL.../10

JOINTS - pack. **1 Pc upper + 1 Pc lower**

Article	H mm
GINFDP ...AL .../1	10/125

Choose the desired height and finish.
E.g.: 10 mm joint with finish A - GINFDP 10ALA/10



AEPFDP 10/125AL...


AIPFDP 10/125AL...




PROTERRACE ECO DRIP is an edging profile in aluminium designed to protect the front of the screed from water penetration and the edges of the tiles laid on terraces and balconies. The profile is equipped with a punched flange that ensures its fixing to the support. The front of the profile is equipped with a double drip to improve the push away of water from the wall. To reach a right connection between profile and the waterproofing system it's needed to use **PROBAND 150** with **PROBAND KOLL/AB**. The product is also available on request in **BENDABLE VERSION** and with a **SPECIAL SEASIDE PRE-TREATMENT** which increases its resistance to corrosion when installed at sea front environments.

PROTERRACE ECO DRIP


VARNISHED/COATED ALUMINIUM




VARNISHED/COATED ALUMINIUM bar length 2,7 lm - pack. 20 Pcs - 54 lm



EXTERNAL CORNER - pack 10 Pc



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROTERRACE ECO DRIP" according to the tile thickness.
 2. Cut "PROTERRACE ECO DRIP" to the desired length and fix it to the support with nails.
 3. Apply the desired waterproofing system, sealing the joint between profile and waterproofing.
 4. Lay the tiles, leaving about 5 mm between tiles and profile.
 5. Seal the space between tiles and profile using **PROBAND FIX (P.186)**.
- PROFILE BENDING:** 1) Cut the anchoring flange into sections and engrave the metal close to the vertical side 2) bend the profile with the help of a template;

HOW TO REQUEST SEASIDE TREATMENT

When placing your order please add S to the article's number
Example: PTEDP 10ALGF (seaside) = **PTEDP 10ALGFS**

Article	H mm		
PTEDP 10AL...	10		
PTEDP 125AL...	12,5		

Available in the colours: BF - GF - A - TF (EF - C - B - G - E - T on demand)
The code of the selected colour must be added to the article code.
E.g.: PTEDP 10AL... (gray) PTEDP 10GFAL.

JOINTS - pack. 2 / 10 Pcs

Article	pack. 2Pcs	pack. 10Pcs
GINEDP 10AL... /...		
GINEDP 125AL... /...		

EMBOSSED COLOURS


BF - White (9010)	GF - Grey (7038)	A - Anthracite grey (no RAL)	TF - Dark brown (8019)
-------------------	------------------	------------------------------	------------------------

Article	Pc	Pack
AEEDP 10AL.../10		
AEEDP 125AL.../10		

GINEDP 10/125ALGF



AEEDP 10/125ALGF



COLOURS ON DEMAND

SEMIGLOSSY			
B - White (9010)	G - Grey (7038)	E - Beige (1019)	T - Dark brown (8019)

EMBOSSED	
EF - Beige (1019)	C - Corten

PROSIDE WALK is a perimeter profile in varnished aluminium, available in grey and anthracite colour. It is designed to protect the edges of the tiles and the screed on pavements. The profile is equipped with a punched flange that ensures its fixing to the support. The flange is also provided with small holes that allow the momentary fixing of the profile with nails. To reach a right connection between profile and the waterproofing system it's needed to use **PROBAND 150** with **PROBAND KOLL/AB**. The product is also available on request in **BENDABLE VERSION** and with a **SPECIAL SEASIDE PRE-TREATMENT** which increases its resistance to corrosion when installed at sea front environments.

PROSIDE WALK

VARNISHED/COATED ALUMINIUM



VARNISHED EMBOSSED ALUMINIUM bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	h mm	H mm	L
PSDWK 10AL...	10	45	80
PSDWK 125AL...	12,5	45	80
PSDWK 15AL...	15	45	80
PSDWK 20AL...	20	45	80

EMBOSSED COLOURS

A - Anthracite grey (no RAL)	GF - Gray (7038)	TF - Dark brown (8019)
------------------------------	------------------	------------------------

EMBOSSED COLOURS ON DEMAND

BF - White (9010)	C - Corten	EF - Beige (1019)
-------------------	------------	-------------------



EXTERNAL CORNERS - pack. 10 Pcs


Article	h mm	H mm	L
AEPSDWK 10AL.../10	10	45	80
AEPSDWK 125AL.../10	12,5	45	80
AEPSDWK 15AL.../10	15	45	80
AEPSDWK 20AL.../10	20	45	80

JOINTS - pack. 10 Pcs


Article	H mm
GINSDWK ...AL.../10	10/125/15/20

Choose the desired height and finish.
E.g.: 10 mm joint with finish A - GINSDWK 10ALA/10


AEPSDWK external corner (welded)



GINSDWK joint



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose PROSIDE WALK according to the tile thickness and desired colour.
 2. Waterproof with **PROBAND 150** and **PROBAND KOLL** the front of the screed.
 3. Fix the external corners with nails.
 4. Cut PROSIDE WALK to the desired length and fix it with nails; connect it with the corners using the junction element.
 5. Lay the tiles, leaving about 5 mm between tiles and profile.
 6. Seal the space between tiles and profile with **PROBAND FIX (P.186)**.
- PROFILE BENDING:** 1) Cut the anchoring flange into sections and engrave the metal close to the vertical side 2) bend the profile with the help of a template;



HOW TO REQUEST SEASIDE TREATMENT

When placing your order please add S to the article's number
Example: PSDWK 10ALGF (seaside) = **PSDWK 10ALGFS**

PROTERRACE PCG

POLISHED STAINLESS STEEL AISI 304/1.4301-V2A

PROTERRACE PCG is an edging profile in polished stainless steel INOX AISI 304/1.4301-V2A designed to protect the edges of the tiles laid on terraces and balconies and to allow a correct water discharge. The profile is equipped with a punched flange that ensures its fixing to the support. The flange is also provided with small holes that allow the momentary fixing of the profile with nails. The availability of special pieces such as external corners and junctions make **PROTERRACE PCG** a much sought after and easy to lay profile. The product is also available on request in **BENDABLE VERSION**




POLISHED STAINLESS STEEL AISI 304/1.4301-V2A with protective film
bar length 2,7 lm - pack 5 Pcs - 13,5 lm (H 55 mm - 18,9 lm)

Article	h x H x L mm		
PCG10 8055AC	10 x 55 x 80		
PCG10 8075AC	10 x 75 x 80		
PCG10 8095AC	10 x 95 x 80		
PCG125 8055AC	12,5 x 55 x 80		
PCG125 8075AC	12,5 x 75 x 80		
PCG125 8095AC	12,5 x 95 x 80		

EXTERNAL CORNERS - pack 10 Pcs

Article		
AEPG10 55AC/75AC/95AC/10		
AEPG125 55AC/75AC/95AC/10		

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROTERRACE PCG" according to the tile thickness. 2. Fix the external corners to the screed with nails taking care to separate them at least 1 cm from it. 3. Cut "PROTERRACE PCG" to the desired length. Lay the profile and fix it with nails. Connect it with the corners using the junctions. 4. Apply the desired waterproofing system. 5. Lay the tiles, leaving about 5 mm between tiles and profile. 6. Seal the space between tiles and profile with **PROBAND FIX (P.186)**.

PROFILE BENDING: 1) Cut the anchoring flange into sections and engrave the metal close to the vertical side **2)** bend the profile with the help of a template;

JOINTS - pack 10 Pcs


Article		
GING10 55AC/75AC/95AC/10		
GING125 55AC/75AC/95AC/10		

* Corners and joints of the on demand profiles are also on demand


PROTERRACE PCG

VARNISHED/COATED ALUMINIUM

PROTERRACE PCG is an edging profile designed to protect the edges of the tiles laid on terraces and balconies and to allow a correct water discharge. The profile is equipped with a punched flange that ensures its fixing to the support and which is also provided with small holes that allow the momentary fixing of the profile with nails. The availability of special pieces such as external corners and junctions make **PROTERRACE PCG** a much sought after and easy to lay profile. To reach a right connection between profile and the waterproofing system it's needed to use **PROBAND 150** with **PROBAND KOLL/AB**. The product is also available on request with a **SPECIAL SEASIDE PRE-TREATMENT** which increases its resistance to corrosion when installed at sea front environments. The product is also available on request in **BENDABLE VERSION**



HOW TO REQUEST SEASIDE TREATMENT
When placing your order please add S to the article's number
Example: PCG10 8055ALGF (seaside) = **PCG10 8055ALGFS**



VARNISHED/COATED ALUMINIUM
bar length 2,7 lm - pack 5 Pcs - 13,5 lm (H 55 mm - 18,9 lm)

Article	h x H x L mm		
PCG10 8055AL...	10 x 55 x 80		
PCG10 8055ALG	10 x 55 x 80		
PCG10 8075AL...	10 x 75 x 80		
PCG10 8075ALG	10 x 75 x 80		
PCG10 8095AL...	10 x 95 x 80		
PCG10 8095ALG	10 x 95 x 80		
PCG125 8055AL...	12,5 x 55 x 80		
PCG125 8075AL...	12,5 x 75 x 80		
PCG125 8095AL...	12,5 x 95 x 80		


Available in the colours: BF - White (9010) GF - Grey (7038) A - Anthracite grey (no RAL) TF - Dark brown (8019)
The code of the selected colour must be added to the article code. E.g.: PCG10 8055AL... (white) PCG10 8055ALB.

EXTERNAL CORNERS - pack 10 Pcs

Article		
AEPG10 55AL.../75AL.../95AL.../10		
AEPG125 55AL.../75AL.../95AL.../10		

The code of the selected colour must be added to the article code. E.g.: AEPG10 55AL... (white) AEPG10 55ALB.

EXEMPLES OF LAYING (for laying instructions, see above)



EMBOSSED COLOURS

BF - White (9010)	GF - Grey (7038)	A - Anthracite grey (no RAL)	TF - Dark brown (8019)
-------------------	------------------	------------------------------	------------------------

COLOURS ON DEMAND

EMBOSSED	
EF - Beige (1019)	C - Corten

SEMIGLOSSY

B - White (9010)	G - Grey (7038)	E - Beige (1019)	T - Dark brown (8019)
------------------	-----------------	------------------	-----------------------

JOINTS - pack 10 Pcs

Article		
GING10 55AL.../75AL.../95AL.../10		
GING125 55AL.../75AL.../95AL.../10		

* Corners and joints of the on demand profiles are also on demand

News 2023

* = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed

PROTERRACE PC is a perimeter profile in polished stainless steel inox aisi 304/1.4301-V2A designed to protect the screed on terraces and balconies and to allow a correct water discharge. The profile is equipped with a punched flange that ensures its fixing to the support. The flange is also provided with small holes that allow the momentary fixing of the profile with nails. To reach a right connection between profile and the waterproofing system it's needed to use **PROBAND 150** with **PROBAND KOLL/AB**. The product is also available on request in **BENDABLE VERSION**.

PROTERRACE PC


POLISHED STAINLESS STEEL AISI 304/1.4301-V2A



POLISHED STAINLESS STEEL AISI 304/1.4301-V2A with protective film
bar length 2,7 lm - pack: 7 Pcs - 18,9 lm (H 75 mm - 13,5 lm - H 95 mm - 5,4 lm)


Article	L x H mm
PC 8055AC	80 x 55

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROTERRACE PC" according to the desired height. 2. Fix the external corners to the screed with nails taking care to separate them at least 1 cm from it. 3. Cut "PROTERRACE PC" to the desired length. Lay the profile and fix it with nails. Connect it with the corners using the junctions. 4. Apply the desired waterproofing system. 5. Lay the tiles. **PROFILE BENDING:** 1) Cut the anchoring flange into sections and engrave the metal close to the vertical side 2) bend the profile with the help of a template;

PC 8055AC



EXTERNAL CORNERS - pack. 10 Pcs


Article
AEPC 55AC 10

JOINTS - pack. 10 Pcs

Article
GINC 55AC 10

* Corners and joints of the on demand profiles are also on demand

AEPC external corner (welded)



GINC joints



PROTERRACE PC is a perimeter profile in varnished aluminium designed to protect the screed on terraces and balconies and to allow a correct water discharge. The profile is equipped with a punched flange that ensures its fixing to the support. The flange is also provided with small holes that allow the momentary fixing of the profile with nails. To reach a right connection between profile and the waterproofing system it's needed to use **PROBAND 150** with **PROBAND KOLL/AB**. The product is also available on request with a **SPECIAL SEASIDE PRE-TREATMENT** which increases its resistance to corrosion when installed at sea front environments. The product is also available on request in **BENDABLE VERSION**.

PROTERRACE PC

VARNISHED/COATED ALUMINIUM




VARNISHED/COATED ALUMINIUM - bar length 2,7 lm
pack. 7 Pcs - 18,9 lm (H 75 mm - 13,5 lm - H 95 mm - 5,4 lm)

Article	L x H mm
PC 8055AL...	80 x 55


The code of the selected colour must be added to the article code. E.g.: PC 8055AL... (white) PC 8055ALB.

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROTERRACE PC" according to the desired colour and height. 2. Fix the external corners to the screed with nails taking care to separate them at least 1 cm from it. 3. Cut "PROTERRACE PC" to the desired length. Lay the profile and fix it with nails. Connect it with the corners using the junctions. 4. Apply the desired waterproofing system. 5. Lay the tiles. **PROFILE BENDING:** 1) Cut the anchoring flange into sections and engrave the metal close to the vertical side 2) bend the profile with the help of a template;

PC 8055AL



SEMIGLOSSY COLOURS ON DEMAND

B - White (9010)	G - Grey (7038)	T - Dark brown (8019)
E - Beige (1019)		

EMBOSSED COLOURS ON DEMAND

BF - White (9010)	GF - Grey (7038)	A - Anthracite grey (no RAL)
EF - Beige (1019)	C - Corten	TF - Dark brown (8019)

EXTERNAL CORNERS - pack. 10 Pcs

Article
AEPC 55AL... 10

JOINTS - pack. 10 Pcs

Article
GINC 55AL... 10


The code of the selected colour must be added to the article code. E.g.: AEPC 55AL... (white) AEPC 55ALB.

* Corners and joints of the on demand profiles are also on demand

HOW TO REQUEST SEASIDE TREATMENT

When placing your order please add S to the article's number
Example: PC 8055ALGF (seaside) = **PC 8055ALGFS**

AEPC external corners (welded)




GINC joints





PROTERRACE UNDER EDGE L

VARNISHED ALUMINIUM

PROTERRACE UNDER EDGE L is a perimetric profile in aluminium designed to be installed under the edges of tiles or marbles laid on terraces and balconies, or can be installed as a terminal of lower edges of outdoor terraces with drip function and to ensure proper water outflow. Thanks to its ease of application and availability in different colors it is a highly appreciated profile.



EXAMPLES AND INSTALLATION INSTRUCTIONS




INSTALLATION UNDER TILES OR MARBLES:

1. Choose proterrace under edge l according to the desired colour. 2. Cut proterrace under edge l to the required size and fix it with nails to the substrate taking care to leave 2 mm between two adjacent bars. 3. Apply the desired waterproofing system. 4. Lay the flooring. 5. Fix the joints with proband fix.

INSTALLATION ON LOWER EDGES OF TERRACES AND BALCONIES:

1. Choose proterrace under edge l according to the desired colour. 2. Cut proterrace under edge l to the required size and secure it with proband fix and screws to the substrate taking care to leave 2 mm between two adjacent bars. 3. Fix the joints by gluing them with proband fix.



PROTERRACE UNDER EDGE L Varnished aluminium
Bar length 2.7 Lm - pack 5 pcs - 13.50 LM

Article	H mm
PTUEC...	15

CAPSULES

Varnished aluminium - pack 2 Pcs

Article
CPPTUE...S (left)
CPPTUE...D (right)



JOINTS

Varnished aluminium

Article
GINPTUE...

END CAPS

Varnished aluminium - pack 2 Pcs

Article
TPPTUE...S (left)
TPPTUE...D (right)

STANDARD COLOURS

BF - Embossed white (9010)	GF - Embossed grey (7038)	AN - Natural aluminium



GINPTUE...



CPPTUE...S



CPPTUE...D



TPPTUE...S



TPPTUE...D


GAMMA COLORI A RICHIESTA

GOFFRATI				SEMILUCIDI			
E - Beige (1019)	C - Corten	A - Anthracite grey (no RAL)	TF - Dark brown (8019)	B - White (9010)	G - Grey (7038)	E - Beige (1019)	T - Dark brown (8019)


PROTERRACE UNDER EDGE C

VARNISHED ALUMINIUM

PROTERRACE UNDER EDGE C is a perimetric profile in aluminium designed to be installed under the edges of tiles or marbles laid on terraces and balconies and to ensure proper water outflow. Thanks to its ease of application and availability in different colors it is a highly appreciated profile.




EXAMPLES AND INSTALLATION INSTRUCTIONS



INSTALLATION UNDER TILES OR MARBLES:

1. Choose proterrace under edge c according to the desired colour; 2. Cut proterrace under edge c to the required size; 3. Glue the profile to the structure with proband fix and secure it with screws, taking care to leave 2 mm between two adjacent bars; 4. Attach the joints with proband fix.



PROTERRACE UNDER EDGE C Varnished aluminium
Bar length 2.7 Lm - pack 5 pcs - 13.50 LM

Article	H mm
PTUEL...	15

CAPSULES

Varnished aluminium - pack 2 Pcs

Article
CPPTUE...S (left)
CPPTUE...D (right)



JOINTS

Varnished aluminium

Article
GINPTUE...

END CAPS

Varnished aluminium - pack 2 Pcs

Article
TPPTUE...S (left)
TPPTUE...D (right)

STANDARD COLOURS

BF - Embossed white (9010)	GF - Embossed grey (7038)	AN - Natural aluminium



GINPTUE...



CPPTUE...S



CPPTUE...D



TPPTUE...S



TPPTUE...D

GAMMA COLORI A RICHIESTA


GOFFRATI				SEMILUCIDI			
E - Beige (1019)	C - Corten	A - Anthracite grey (no RAL)	TF - Dark brown (8019)	B - White (9010)	G - Grey (7038)	E - Beige (1019)	T - Dark brown (8019)

PROSHOWER LATERAL AND VERTICAL DRAIN KIT are 2 central drain systems with lateral or vertical outflow equipped with a siphon, grate support, stainless steel grate, butyl double-sided ring for the fixing of the waterproof section, waterproof section and a protection cap with template function too that allows the correct positioning of the butyl ring and the waterproof section. LATERAL AND VERTICAL DRAIN KIT ensure a correct flow of rainwater.

PROSHOWER DRAIN KIT

LATERAL AND VERTICAL DRAINS

Article	Description	Pc/Pack.
PSHLDK	PROSHOWER DRAIN LATERAL KIT	1
PSHVDK	PROSHOWER DRAIN VERTICAL KIT	1



PROSHOWER DRAIN LATERAL KIT PSHLDK

PROSHOWER DRAIN VERTICAL KIT PSHVDK

AREA OF USE

- **Use** - Balconies, terraces, outdoor surfaces of any size, kitchens and showers.
- **Don't use** - In environments subject to heavy traffic and where washing with acidic and strong alkaline substances is foreseen.

WARNINGS

After the drain installation, apply the protective cap. Before applying the butyl double-sided adhesive ring on the flange of the drain, thoroughly clean the flange of any dirt residue that may compromise its adhesion. Apply the butyl double-sided adhesive ring and the waterproofing section during the application of the waterproofing system.

PROSHOWER DRAIN CENTRAL PRO is a 10x10 cm stainless steel AISI 316L / 1.4404 - V4A drain for the realisation of floor-level shower. This low thickness drain is equipped with a grid that can also be tiled for floor-level drains. PROSHOWER DRAIN CENTRAL PRO has excellent chemical resistance and is equipped with a 360° adjustable siphon.

PROSHOWER DRAIN CENTRAL PRO


LATERAL DRAIN

PROSHOWER DRAIN CENTRAL PRO - GRATE + POLYSTYRENE CHANNEL PROTECTION + PROFOIL SECTION + DUCT BODY + SIPHON

Article	Description	Pc/Pack.
PSHWCP	PROSHOWER DRAIN CENTRAL PRO	1

AREA OF USE

- **Use** - PROSHOWER BASE L PRO it can be used in any indoor and outdoor environment.
- **Don't use** - In environments where very aggressive substances are used and a high concentrated load is expected.



PRODRIP is a perimeter drain in ASA (Modified ABS) equipped with wall-floor junction. The junction is covered with non-woven polypropylene to ensure sealing with the used waterproofing system.

PRODRIP

PERIMETRAL DRAIN

PERIMETER DRAIN

pack. per pallet = 192


Article	Pcs/Pack.
PDRP	4


AREA OF USE

- **Use** - To realise perimeter drains on balconies, terraces and outside horizontal surfaces of any size.
- **Don't use** - With bituminous waterproofing and as vertical drain.

WARNINGS


Do not heat with direct flames and do not use adhesive with solvents. Consult the data sheet prior to application in the case of special applications, we recommend that you consult the technical department.





An interpretation of:
**Museum of the Future, Shaun Killa,
The Frame, Fernando Domis, DUBAI (United Arab Emirates), 2018**

MEMBRANE AND PANELS





PRODESO® DRAIN 5 SYSTEM

WEBSITE



Certified

- 12004 - Adhesion to the Substrate
- 12004 - Adhesion to the Tiles
- 12004 - Resistance to Substrate shear
- 12004 - Resistance to Tile shear
- ASTM C627-18 - Robinson Test with Screed
- ASTM C627-18 - Robinson Test with Plywood
- ANSI A118.12 - Uncoupling
- UNI EN 12667:2002 - Heat Resistance

Discover Prodeso® Drain 5!! The essential microventilation and desolidarization for a correct laying of large slabs inside.

PRODESO® DRAIN 5 is an uncoupling membrane that, thanks to its particular structure, guarantees a "micro ventilation" under the tiles that promotes a quick and uniform drying of the adhesive, especially in the case of large format tiles, and reduces the rise of triacetates and the appearance of efflorescence in joints. The membrane, with a total thickness of 5 mm, is composed of a high-density polyethylene sheet to which a polypropylene drainage

fabric is thermowelded. On the back, there is a polypropylene spunbond, thermowelded to the polyethylene sheet, which guarantees the anchoring of the membrane to the support and the vapour management. The uncoupling and vapour management features of PRODESO DRAIN 5 allow its installation even on cracked and not perfectly cured supports.


Functions



UNCOUPLING



VAPOUR MANAGEMENT



DRAINAGE



MICRO VENTILATION



HEATING DISTRIBUTION

PRODESO® DRAIN 5 MEMBRANE is a 3-layers uncoupling and draining membrane ideal for indoor environments.


PRODESO® DRAIN 5 SYSTEM



3 LAYERS MEMBRANE

PRODESO® DRAIN 5 MEMBRANE

Article	H Roll (m)	L Roll (m)	Thickness (mm)	Roll x Pallet			
PDES DR 201/E	1	20	5	6			



1 DRAINING POLYPROPYLENE FABRIC

2 POLYETHYLENE SHEET

3 POLYPROPYLENE FABRIC

PROMEMBRANE KOLL is a C2ES1 class cementitious adhesive, with high workability and prolonged adjustability, specially designed to bond all the membranes of the "PRODESO®" family, even overlapping and on floor heating systems and the PROFOIL membrane.

PROMEMBRANE KOLL

CEMENTITIOUS ADHESIVE

PROMEMBRANE KOLL

Article	Kg/Pack	Box/Pallet	kg/Pallet			
PRMKL	25	25	625			

Sold exclusively by the pallet.





PRODESO® DRAIN 8 SYSTEM

WEBSITE



PATENTED

PATENTED

10201800005884

Discover Prodeso® Drain 8!! The essential drainage and waterproofing function guaranteed by the most advanced system in the world.

PRODESO® DRAIN 8 is a draining, uncoupling and waterproofing patented membrane, with a total thickness of 8 mm, which can be installed even on not perfectly cured supports. The "air chamber" below the floor drains the water that has penetrated below it, it facilitates a fast drying of the adhesive and drastically reduces the rise of triacetates and the appearance of efflorescence.

The system, ideal for a correct laying on terraces and balconies even of large slabs, is completed with a band in polyethylene and elastic polypropylene and with a bicomponent waterproof adhesive. Quick and easy to install, the PRODESO® DRAIN 8 is very versatile and guarantees long life for outdoor flooring.

Functions




UNCOUPLING



WATERPROOFING



VAPOUR MANAGEMENT



DRAINAGE



MICRO VENTILATION

PRODESO® DRAIN 8 MEMBRANE is a waterproofing, uncoupling and draining membrane with 5 layers ideal for outdoor environments.


PRODESO® DRAIN 8 SYSTEM



5 LAYERS MEMBRANE

PRODESO® DRAIN 8 MEMBRANE

Article	H Roll (m)	L Roll (m)	Thickness (mm)	Roll x Pallet			
⊕ PDESDR 151/E	1	15	8	8			



- 1 DRAINING POLYPROPYLENE FABRIC
- 2 POLYETHYLENE SHEET
- 3 DRAINING POLYPROPYLENE FABRIC
- 4 POLYPROPYLENE FILM
- 5 POLYPROPYLENE FABRIC

PROBAND 150/250 is a waterproofing polyethylene tape with nonwoven polypropylene fabric on both side that guarantees high adhesion to the support.

PROBAND 250

ROLLS IN HDPE AND PP

PROBAND 250

Article	H Roll (mm)	L Roll (m)	Thickness (mm)	Roll x Pack			
⊕ PRBPE 2530	250	30	0,42	3			

For the indicative consumption of proband koll AB during the installation of the PROBAND, consult the technical data sheet of PROBAND 150/250



PROBAND KOLL AB is a bicomponent hydrophobic adhesive for the sealing of PROBAND 150/250 on PRODESO® MEMBRANE and PRODESO® HEAT/GRIP MEMBRANE.

PROBAND KOLL AB

BICOMPONENT HYDROPHOBIC ADHESIVE

PROBAND KOLL AB

Article	Kg/Pack	Pack/pallet	Kg/Pallet				
⊕ PRBKLAB	15	27	405				

For the indicative consumption of proband koll AB during the installation of the PROBAND, consult the technical data sheet of PROBAND 150/250



PROMEMBRANE KOLL is a C2E51 class cementitious adhesive, with high workability and prolonged adjustability, specially designed to bond all the membranes of the "PRODESO®" family, even overlapping and on floor heating systems and the PROFOIL membrane.

PROMEMBRANE KOLL

CEMENTITIOUS ADHESIVE

PROMEMBRANE KOLL

Article	Kg/Pack	Pack/Pallet	Kg/Pallet				
⊕ PRMKL	25	25	625				

Sold exclusively by the pallet.



Internal and external preformed corners in polyethylene provided on both side with nonwoven polypropylene fabric that guarantees its adhesion to the support.

PRE-WELDED CORNERS

PRE-WELDED CORNERS

Article	H mm	L mm	Pcs/Pack				
⊕ PRBI	60	120	10				
⊕ PRBE	60	120	10				



PRBE

PRBI



PRODESO® HEAT GRIP SYSTEM

INSTRUCTION VIDEO



PATENTED

PATENTED

UA2016A002209
 EP3225763 A1
 003067388
 2696795
 CN 107268933 A
 HK1238695
 CA 2,935,062
 US 9,726,383 B1
 US 10,502,434 B2
 US 10,859,274 B2
 US 10,215,423
 US D818,615S
 US D818,616S
 US D818,617S
 US D832,467S
 US D841,837S
 US D872,901S
 US D874,028S
 DESIGN PATENT
 Patent pending

A New evolution

with the goal of flexibility, innovation and energy efficiency

The system is composed of three elements: PRODESO® HEAT GRIP MEMBRANE, PRODESO® HEAT GRIP CABLE e PRODESO® HEAT GRIP THERMOSTAT KIT. The polyethylene membrane with uncoupling, waterproofing and vapour management features has a 8,5 mm thickness and a thermowelded non-woven fabric on the back side, which guarantees the adhesion to the substrate.

The new membrane structure allows a perfect fixing of the

heating cable and a crack-bridging ability 5 times more than the PRODESO® HEAT. The cables of last generation are composed of many resistances, each one 60 cm long, in a parallel circuit. If the cable is damaged, only the broken resistance stops working but not the whole cable. The thermostat of last generation interfaces with Android and Apple devices, that is why it is possible to adjust all settings and time schedule using an application with internet connection as remote control.

functions

- Only 8.5 mm thickness
- Higher crack-bridging ability
- Uncoupling
- Waterproofing

- Vapour management ducts
- Load distribution
- New constant power cable
- Remote controlled thermost




UNCOUPLING



WATERPROOFING



VAPOR AND MOISTURE MANAGEMENT



LOAD DISTRIBUTION

PRODESO® HEAT GRIP MEMBRANE is an uncoupling membrane, waterproofing in polyethylene, equipped with reliefs that allow the attachment of the electric heating cable.

PRODESO® HEAT GRIP SYSTEM

PRODESO® HEAT GRIP MEMBRANE

Article	H Roll (m)	L Roll (m)	Thickness (mm)	Roll/Pallet
PDESHG 131/E	1	13	8,5	6
PDESHG 451/E	1	4,5	8,5	15

it is a constant power electric heating cable to be embedded between the reliefs of PRODESO® HEAT GRIP MEMBRANE. The cable distance can be 6.2 or 9.3 cm

PRODESO® HEAT GRIP CABLE

PRODESO® HEAT GRIP CABLE

Article	Cable Length (m)	Heated surface on the WALL (6,2 cm)	Heated surface on the FLOOR (9,3 cm)	Total Power W
PDHGCB 20	19,80	1,19 m ²	2,00 m ²	250 W
PDHGCB 26	25,80	1,55 m ²	2,50 m ²	325 W
PDHGCB 31	30,80	1,83 m ²	3,00 m ²	385 W
PDHGCB 36	36,00	2,14 m ²	3,50 m ²	450 W
PDHGCB 40	40,20	2,38 m ²	4,00 m ²	500 W
PDHGCB 46	46,20	2,74 m ²	4,50 m ²	575 W
PDHGCB 52	52,20	3,10 m ²	5,00 m ²	650 W
PDHGCB 62	61,80	3,69 m ²	6,00 m ²	775 W
PDHGCB 72	72,00	4,29 m ²	7,00 m ²	900 W
PDHGCB 82	82,20	4,88 m ²	8,00 m ²	1025 W
PDHGCB 94	94,20	5,60 m ²	9,00 m ²	1175 W
PDHGCB 104	103,80	6,19 m ²	10,00 m ²	1300 W
PDHGCB 132	132,00	7,86 m ²	12,50 m ²	1650 W
PDHGCB 158	157,80	9,40 m ²	15,00 m ²	1975 W

PRODESO® HEAT GRIP CABLE - 450 M

Article	Diameter (mm)	Length ml	Power w/ml	Power supply V
PDHGCB450	6,5	450 M	12,5W	230 V

L 4,5m

L 13m



It is composed of a Wi-Fi digital thermostat, a flush-mounting box, corrugated pipe, two floor temperature sensors and clips to fix the cable.

PRODESO® HEAT GRIP THERMOSTAT

PRODESO® HEAT GRIP DIGITAL THERMOSTAT - TOUCH SCREEN - WI-FI

Article	PDHSTSMWT 230	PDSOT	PDSHI	PDHCF 202
PDHSTSMWT 230				

DIGITAL WIFI THERMOSTAT

Article	PDHSTSMWT 230
PDHSTSMWT 230	

PRODESO® HEAT GRIP SYSTEM OPTIONAL

ROLLER FOR CABLE INSTALLATION

Aluminum roller 15 cm long, facilitates and speeds up the insertion of the heating cables between the reliefs of the membranes PRODESO®HEAT e PRODESO® HEAT GRIP.

Article	L cm	Pc/Pack
PSC	15	1



PROECOFON

Roll of closed-cell polyethylene with adhesive used as edging between the wall and screed or where there are expansion joints - Pack. 2 Pcs

Article	Thick. x H mm	Lm/Roll
PEF 550A	5 X 50	25



PRODESO® HEAT GRIP CABLE KIT

Article	Lm shrink sheath	Cable Lugs Lm
PDHGCK110	1	10
PDHGCK550	5	50



PRODESO® HEAT GRIP POWER CABLE

Article	Lm/Roll
PDHGCBF	2,5



PRODESO® HEAT CABLE CLIP

Plastic Clip to hold heating cable on PRODESO® HEAT MEMBRANE (40 mm x 5 mm)

Article	Pcs/Pack
PCBLF	200





PRODESOS® HEAT SYSTEM

INSTRUCTION VIDEO



PATENTED



PATENTED

- 002748822
- EP 3,183,505 B1
- US 8,176,694 B2
- US 9,188,348 B2
- US 9,416,979 B2
- US 9,518,746 B2
- US 9,625,163 B2
- US 9,719,265 B2
- US 9,777,931 B2
- US 10,107,505 B2
- US 10,006,644 B2
- US 10,215,423 B2
- US 10,408,469 B2
- US 10,712,020 B2
- US 10,739,016 B2
- Patents Pending

A World of warmth and comfort in respect with the nature.

Progress Profiles innovative and patented PRODESOS® HEAT SYSTEM for electrical walls and floors heating ensures pleasant warm and comfortable environment with short laying times and at low cost. The system can be used on all kinds of substrate thanks to the membrane uncoupling and waterproofing properties. Temperature and operating times can be controlled from a latest generation thermostat that also guarantees significant savings in energy costs. The system

is quick and easy to install in all conditions and has an overall thickness of only 5.5 mm, far thinner than any alternative system. It is also maintenance free over time. This smart, responsible technology supports the growing demand for sustainable solutions and energy saving while also satisfying the needs of contemporary architecture and evolved home automation. A world of natural, warm wellbeing.

Functions




UNCOUPLING / CRACK ISOLATION



WATERPROOFING



VAPOR AND MOISTURE MANAGEMENT



LOAD DISTRIBUTION

PRODESO® HEAT MEMBRANE is an uncoupling membrane, waterproofing in polyethylene, equipped with reliefs that allow the attachment of the electric heating cable.

PRODESO® HEAT SYSTEM

PRODESO® HEAT MEMBRANE

Article	H Roll (m)	L Roll (m)	Thickness (mm)	Roll/Pallet
PDESH 151/E	1	15	5,5	6
PDESH 051/E	1	5	5,5	15

it is a constant power electric heating cable to be embedded between the reliefs of PRODESO® HEAT MEMBRANE. The cable distance can be 6.2 or 9.3 cm

PRODESO® HEAT CABLE

PRODESO® HEAT CABLE

Article	Cable Length (m)	Heated surface on the WALL (6,2 cm)	Heated surface on the FLOOR (9,3 cm)	Total Power W
PDHCB 12	12,07 ml	0,70 m ²	1,1 m ²	150
PDHCB 17	17,66 ml	1,00 m ²	1,6 m ²	225
PDHCB 23	23,77 ml	1,40 m ²	2,2 m ²	300
PDHCB 29	29,87 ml	1,80 m ²	2,7 m ²	375
PDHCB 35	35,97 ml	2,20 m ²	3,3 m ²	450
PDHCB 41	41,56 ml	2,50 m ²	3,8 m ²	525
PDHCB 47	47,67 ml	2,90 m ²	4,4 m ²	600
PDHCB 53	53,77 ml	3,30 m ²	5,0 m ²	675
PDHCB 59	59,87 ml	3,70 m ²	5,5 m ²	750
PDHCB 71	71,57 ml	4,40 m ²	6,6 m ²	900

PRODESO® HEAT CABLE - 450 M

Article	Diameter (mm)	Length ml	Power w/ml	Power supply V
PDHCB450	4,8	450 M	12,5W	230 V

L 4,5m

L 13m



It is composed by a digital or analogic programmable thermostat, flush-mounting box, corrugated pipe and two floor temperature sensors.

PRODESO® HEAT THERMOSTAT

PRODESO® HEAT GRIP DIGITAL THERMOSTAT - TOUCH SCREEN - WI-FI

Article	Image
PDHTSKT 230V	
PDHSTSMWT 230	
PDSOT	
PDSHI	
PDHCF 202	

DIGITAL WIFI THERMOSTAT

Article	Image
PDHTSMT 230	

PRODESO® HEAT THERMOSTAT KIT - ANALOGIC

Article	Image
PDHTSK 230V	
PDSOT	
PDSHI	
PDHCF 202	

ANALOGIC THERMOSTAT

Article	Image
PDHTSM 230	

PRODESO® HEAT GRIP SYSTEM OPTIONAL

ROLLER FOR CABLE INSTALLATION

Aluminum roller 15 cm long, facilitates and speeds up the insertion of the heating cables between the reliefs of the membranes PRODESO®HEAT e PRODESO® HEAT GRIP.

Article	L cm	Pc/Pack
PSC	15	1



PROCOFON

Roll of closed-cell polyethylene with adhesive used as edging between the wall and screed or where there are expansion joints - Pack. 2 Pcs

Article	Thick. x H mm	Lm/Roll
PEF 550A	5 X 50	25



Article	Lm shrink sheath	Cable Lugs Lm
PDHGCK110	1	10
PDHGCK550	5	50



PRODESO® HEAT GRIP POWER CABLE

Article	Lm/Roll
PDHGCBF	2,5



PRODESO® HEAT CABLE CLIP

Plastic Clip to hold heating cable on PRODESO® HEAT MEMBRANE (40 mm x 5 mm)

Article	/Pack
PCBLF	200



PRODESO® HEAT KIT SYSTEM

Floor and wall electric heating system kit, composed of 3 pieces: **PRODESO® HEAT MEMBRANE**, **PRODESO® HEAT CABLE** AND **PRODESO® HEAT THERMOSTAT KIT**. The polyethylene membrane, with its uncoupling, waterproofing and vapour management properties, has a thickness of just 5.5 mm.



PRODESO® HEAT KIT SYSTEM

Wall and floor electric heating system

Article	m ² membrane	Cable	Power tot W	Thermostat kit	Wall heated surface (with a cable distance of 6,2 cm)	Floor heated surface (with a cable distance of 9,3 cm)
PDESHK 4	3,2	PDHCB 23	300	1	1,40	2,20
PDESHK 7	5,6	PDHCB 41	520	1	2,50	3,80
PDESHK 10	8,0	PDHCB 59	750	1	3,70	5,50

heating cable PDHCB included in the kit

PRODESO® HEAT THERMOSTAT KIT: digital touch screen thermostat, 2 temperature sensors, flush mounting box, flexible corrugated pipe.



PRODESO HEAT MEMBRANE



PRODESO® HEAT CABLE



DIGITAL TOUCH



PRODESO® HEAT THERMOSTAT KIT




Uncoupling and waterproofing membrane in polypropylene with a thickness of 5.5 mm. The membrane is provided on top with pseudo-square reliefs which create channels for fixing the electric heating cable. On the back of the membrane there is a layer of adhesive which guarantees its fixing to the support, clean plywood, OSB, metal or old flooring.

PRODESO® HEAT STICK MEMBRANE

UNCOUPLING AND WATERPROOFING MEMBRANE

PRODESO® HEAT STICK MEMBRANE

Article	H roll (m)	L roll (m)	Thickness (mm)	Rolls/Pallet		
PDESHST 151/E	1	15	5,5	6		
PDESHST 051/E	1	5	5,5	15		



L 5m

L 15m



PRODESO® ECO / ECO STICK MEMBRANE is an uncoupling and waterproofing membrane in polyethylene with a thickness of 3.5 mm. The membrane is provided on top with dovetail square cavities and on bottom with a layer of adhesive which guarantees its fixing to the support, clean plywood, OSB, metal or old flooring. Thanks to its particular geometry PRODESO® ECO / ECO STICK MEMBRANE transfers loads directly to the support and guarantees the laying of any flooring and the waterproofing even in case of cracked and moisture-sensitive substrates. (*) available in the self-adhesive version PRODESO® ECO STICK for wood and ceramic substrates.

PRODESO® ECO / PRODESO® ECO STICK MEMBRANE

UNCOUPLING & WATERPROOFING MEMBRANE


PRODESO® ECO STICK MEMBRANE

Article	H roll (m)	L roll (m)	Thickness (mm)	Rolls/Pallet		
PDESECST 3530/EN	1	30	3,5	6		
PDESECST 3505/EN	1	5	3,5	30		*


PRODESO® ECO MEMBRANE

Article	H roll (m)	L roll (m)	Thickness (mm)	Rolls/Pallet		
PDESEC 3530/EN	1	30	3,5	6		
PDESEC 3505/EN	1	5	3,5	30		

PRODESO ECO STICK



PRODESO ECO




L 30m

L 30m



PRODESO ECO

PRODESO ECO STICK





PRODESOS[®] MEMBRANE SYSTEM




PATENTED




PATENTED
003368984

Uncoupling and waterproofing system, particularly good for problematic screeds substrates.


PRODESOS[®] MEMBRANE SYSTEM SECTION




1. Ceramic / Stone or Porcelain Tiles
2. Adhesive
3. PRODESOS[®]
4. Adhesive
5. Screed, Plywood, OSB etc.




UNCOUPLING




WATERPROOFING




UNCOUPLING



VAPOR AND MOISTURE MANAGEMENT



FLOOR HEATING DISTRIBUTION



SUPPORT/LOAD DISTRIBUTION

It is an uncoupling and waterproofing membrane for problematic substrates, balconies, terraces and horizontal surfaces of any size without expansion joints in the screed before the laying of ceramic and natural stone. **PRODESO®** ensures the laying of the flooring and the waterproofing of the substrate also in case of old tiles, on cracked and not perfectly cured substrates, and therefore with possible vapour pressure.

PRODESO® MEMBRANE

UNCOUPLING & WATERPROOFING
MEMBRANE

PRODESO® MEMBRANE

Article	H roll (m)	L roll (m)	Thickness (mm)	Rolls/Pallet
PDES 3530/EN	1	30	3,5	8
PDES 3505/EN	1	5	3,5	56

WHY USE PRODESO® MEMBRANE SYSTEM


Time Efficient: PRODESO® Membrane reduces drastically the installation times because from the installation of the membrane up to the laying of flooring you can work without interruption.

Flexible: it is suitable for every types of subfloor including very large surfaces both indoor and outdoor.

Safe: it is suitable for substrates with cracks as it does not transmit tension of the substrate to the tile coverings and vice versa. It is also suitable on substrates not perfectly cured since it allows the vapour management.

WARNINGS

Do not lay tiles with a size less than 5 x 5 cm. The technical and application details can be found in the **PRODESO® MEMBRANE SYSTEM** brochure. For other informations not described in the brochure **PRODESO® MEMBRANE SYSTEM**, refer to the technical department.



PROBAND 150/250 is a waterproofing polyethylene tape with nonwoven polypropylene fabric on both side that guarantees high adhesion to the support.

PROBAND 150/250

ROLLS IN HDPE AND PP

PROBAND 150/250

Article	H roll (m)	L roll (m)	Thickness (mm)	Rolls/Pallet
PRBPE 1507	150	7,5	0,42	16
PRBPE 1530	150	30	0,42	6
PRBPE 2530	250	30	0,42	3

For the indicative consumption of proband koll AB during the installation of the **PROBAND**, consult the technical data sheet of **PROBAND 150/250**



AREA OF USE

- **Use** - Terraces, balconies and outside surfaces of any dimension, bathrooms, showers, swimming pools and tanks. To realize waterproofing joints between floor and wall and along two adjacent rolls of **PROFOIL**, **PRODESO® MEMBRANE SYSTEM** and **PRODESO® HEAT/GRIP SYSTEM**
- **Don't use** - On bituminous coverings, over thermal-insulating layer and lightweight screed. With adhesives containing solvents.

WARNINGS

Store in a cool and dry place avoiding direct sunlight and sources of heat. Read the data sheet before applying; in case of special applications call the technical department

RECOMMENDED ADHESIVES FOR THE LAYING OF PRODESO® MEMBRANE (grey color)

<p>H40 NO LIMITS H40 REVOLUTION H40 EXTREME</p>	<p>SUPERFLEX K77 POWERFLEX K50 LITOSTONE K99</p>	<p>FLEXBOND C2S1 FLEXBOND LIGHT C2S1 WETBOND RAPID C2F</p>	<p>GRIGOKOLL TEX GRIGOKOLL MAX GRIGOKOLL VELOX</p>	<p>CERAM 255 STARFLEX CERAM 255 EASY S1 CERAM 270 MULTIFLOW</p>	<p>ULTRAGRES 440 ULTRAGRES FLEX ULTRAGRES FAST</p>	<p>PERICOL R-FLEX PERICOL EXTRA FLEX PERICOL FLEX</p>
<p>335 MAXI S 335 SUPER FLEX 325 RAPID FL</p>	<p>ARDEX X 78 ARDEX X 90 OUTDOOR ARDEX AF 495</p>	<p>MUREFLEX MFK 45 ADESIVO FBS 75 MAXIMO M 41</p>	<p>RT UNIVERSAL RT HI TECH RT RAPID FLEX</p>	<p>SEYFLEX S1 SEYULTRA T TIXOSEY</p>	<p>KRISTAL C2TE EXTRA C2S1</p>	<p>AZ 59 RAPID MAXI SPECIAL ONE</p>
<p>CERMIPLUS 2.0 CERMIPLUS XL FLEX 2.0</p>	<p>FORTEM MAXIM</p>	<p>BENFERFLEX+S1 BENFERFLEX C2 BENFERFLEX + FAST-S1</p>	<p>F.55 CERMONO PLUS F.55 CERFIX F.55 CERMONO RAPIDO</p>	<p>EXTRA 30 MAXI ADEFLEX GREEN S1 EXTRA 30 POWER</p>	<p>KERAFLEX EASY ULTRALITE S1 KERAFLEX MAXI S1</p>	

PREFORMED CORNERS

Internal and external preformed corners in polyethylene provided on both side with nonwoven polypropylene fabric that guarantees its adhesion to the support.



PRBE
EXTERNAL CORNER



PRBI
INTERNAL CORNER

PREFORMED CORNERS

Article	H mm	L mm	Pc/Pack		
PRBI	60	120	10		
PRBE	60	120	10		

Don't use - On bituminous coverings, over thermal-insulating layer and lightweight screed. With adhesives containing solvents. adhesive.

PROBAND BU

BUTYLE TAPE

PROBAND BU is an adhesive tape in butyle provided on one side with non-woven polypropylene that guarantees high adhesion. use for the Realization of perimeter junctions in case of bituminous coverings, PVC, wood, polycarbonate, glass, plastic and metal on balconies, terraces and external surfaces of any size.



PROBAND BU

Article	H Roll (mm)	L Roll (m)	Thickness (mm)	Rolls/Pack		
PRBBU 7515	75	15	1	8		

WARNINGS: Don't use - On dirty, incoherent and wet surfaces.

PROBAND KOLL

SINGLE-COMPONENT HYDROPHOBIC ADHESIVE

PROBAND KOLL is a single-component hygro-hardener adhesive for the sealing of PROBAND 150/250 on PRODESIO® MEMBRANE.



PROBAND KOLL

Article	Kg/Pack	Pack/Pallet	kg/Pallet		
PRBKL	6	100	600		

For the indicative consumption of proband koll during the installation of the PROBAND, consult the technical data sheet of PROBAND 150/250

AREA OF USE

- **Use** - For the sealing of the tape PROBAND 150/250 with PRODESIO® MEMBRANE and PRODESIO® HEAT/GRIP MEMBRANE on balconies, terraces, bathrooms, kitchens, saunas and external surfaces of any size.
- **Don't use** - On bituminous coverings, to glue tiles and to waterproof cement based support. Do not use outside with PRODESIO® HEAT/GRIP MEMBRANE

PROBAND KOLL AB

BICOMPONENT HYDROPHOBIC ADHESIVE

PROBAND KOLL AB is a bicomponent hydrophobic adhesive for the sealing of PROBAND 150/250 on PRODESIO® MEMBRANE and PRODESIO® HEAT/GRIP MEMBRANE.



PROBAND KOLL AB

Article	Kg/Pack	Pack/Pallet	kg/Pallet		
PRBKLAB	15	27	405		

For the indicative consumption of proband koll AB during the installation of the PROBAND, consult the technical data sheet of PROBAND 150/250

AREA OF USE

- **use** - Balconies, terraces, bathrooms, kitchens, saunas and external surfaces of any size.
- **Don't use** - as waterproofing sheet, to glue tiles and PRODESIO® family membranes, PROFOIL and PROFOIL PANEL.

PROMEMBRANE KOLL

CEMENTITIOUS ADHESIVE

PROMEMBRANE KOLL is a C2ES1 class cementitious adhesive, with high workability and prolonged adjustability, specially designed to bond all the membranes of the "PRODESIO®" family, even overlapping and on floor heating systems and the PROFOIL membrane.



PROMEMBRANE KOLL

Article	Kg/Pack	Pack/Pallet	kg/Pallet		
PRMKL	25	25	625		

Sold exclusively by the pallet.

WARNINGS: Do not use PROMEMBRANE KOLL for bonding natural or recomposed stone sensitive to moisture. Consult the technical data sheet before application; in case of particular applications, it's advisable to consult the technical department.

PROBAND FIX

MOISTURE-CURE SEALANT

PROBAND FIX is a moisture-cure sealant with high adhesion and elasticity. It guarantees the adhesion of PROBAND 150/250 with aluminium frames, plastic and metal and between adjacent sheets of PROFOIL. Don't use On bitumen membranes. To seal proband with PRODESIO®.

MOISTURE-CURE SEALANT
pack. of 12 cartridges - B (white) - G (grey)

Article	Cartridge lm		
PRBFXB	290		
PRBFXG	290		



GUN FOR MOISTURE-CURE SEALANT CARTRIDGE

Article	Pc/Pack
PRBFXGUN	1



MOISTURE-CURE SEALANT CARTRIDGE
pack. of 12 cartridges - B (white) - G (grey)

Articolo	Cartuccia ml		
PRBFXUB	600		
PRBFXUG	600		



It is a membrane in high density polyethylene. It is covered on top with a polypropylene spunbond and on the back with a non-woven fabric in polypropylene. Both of them are thermo-welded to the polyethylene sheet to guarantee the adhesion of the membrane with the adhesive. PRODESO® SOUND is an uncoupling and soundproof membrane, with a thickness of 2,3 mm, which does not require any expansion joints before tiling with ceramic or natural stone. PRODESO® SOUND guarantees the laying of any flooring and the soundproofing up to 17dB in any indoor environment, even in the case of problematic supports and old tiles.

PRODESO® SOUND

UNCOUPLING AND SOUNDPROOF MEMBRANE

PRODESO® SOUND MEMBRANE


Article	H roll (m)	L roll (m)	Thickness (mm)	Rolls/Pallet		
PDSND 30	1	20	2,3	12		

AREA OF USE

- **Use** - Uncoupling and soundproof membrane also for cracked screeds. It can be laid on cement and gypsum based screed, old ceramic, natural stone floorings, concrete and wood structure. Very resistant to saline solutions, acids and alkalis, alcohol and oils. In case of particular products, contact our technical department.
- **Don't use** - On lightweight screeds not suitable for the laying of flooring. Do not lay with adhesives containing solvents.

WARNINGS

For the laying of PRODESO® SOUND use a C2S1 cement based adhesive. Tile immediately after the membrane laying to avoid damages. If it is not possible to tile immediately, the membrane must be protected using running boards. Do not use PRODESO® SOUND on substrates subject to continuous rising moisture. For information not included in the Technical Details, please contact our technical department.



PROECOFON is a roll of closed-cell polyethylene used as edging between the wall and screed or where there are expansion joints. It should be used in all floor-laying work to ensure long life of the floor.

PROECOFON

EXPANDED POLYETHYLENE CLOSED - CELL WITH ADHESIVE



CLOSED-CELL EXPANDED POLYETHYLENE WITH ADHESIVE - (PEF 550A - Pack 2 Pcs)

Article	Thick. x H mm	lm/roll		
PEF 550A	5 X 50	25		
PEF 5100A	5 X 100	100		

Adhesive junction tape for the membrane PRODESO® SOUND

PRODESO® SOUND TAPE

PRODESO® SOUND TAPE - height 50 mm

Article	lm/roll	Pc/Pack	Pc/box		
PDSNDTP 550	50	6	36		



PROSHOWER LATERAL AND VERTICAL DRAIN KIT are 2 central drain systems with lateral or vertical outflow equipped with a siphon, grate support, stainless steel grate, butyl double-sided ring for the fixing of the waterproof section, waterproof section and a protection cap with template function too that allows the correct positioning of the butyl ring and the waterproof section. LATERAL AND VERTICAL DRAIN KIT ensure a correct flow of rainwater.

PROSHOWER DRAIN KIT

LATERAL AND VERTICAL DRAINS

Article	Description	Pc/Pack.	
PSHLDK	PROSHOWER DRAIN LATERAL KIT	1	
PSHVDK	PROSHOWER DRAIN VERTICAL KIT	1	

AREA OF USE

- **Use** - Balconies, terraces, outdoor surfaces of any size, kitchens and showers.
- **Don't use** - In environments subject to heavy traffic and where washing with acidic and strong alkaline substances is foreseen.

WARNINGS

After the drain installation, apply the protective cap. Before applying the butyl double-sided adhesive ring on the flange of the drain, thoroughly clean the flange of any dirt residue that may compromise its adhesion. Apply the butyl double-sided adhesive ring and the waterproofing section during the application of the waterproofing system.



PROSHOWER DRAIN
LATERAL KIT
PSHLDK



PROSHOWER DRAIN
VERTICAL KIT
PSHVDK

PRODRIP is a perimeter drain in ASA (Modified ABS) equipped with wall-floor junction. The junction is covered with non-woven polypropylene to ensure sealing with the used waterproofing system.

PRODRIP

SCARICO PERIMETRALE

PERIMETER DRAIN

pack. per pallet = 192


Article	Pcs/Pack.		
PDRP	4		

AREA OF USE

- **Use** - To realise perimeter drains on balconies, terraces and outside horizontal surfaces of any size.
- **Don't use** - With bituminous waterproofing and as vertical drain.

WARNINGS

Do not heat with direct flames and do not use adhesive with solvents. Consult the data sheet prior to application in the case of special applications, we recommend that you consult the technical department.



PROFOIL PROFOIL PRO

ROLLS IN HDPE AND PP

L 5m L 30m



PROFOIL



PROFOIL PRO



PROFOIL is a waterproofing polyethylene membrane with nonwoven polypropylene fabric on both side that guarantees high adhesion to the support.

PROFOIL PRO is a waterproofing elastic polyethylene membrane with nonwoven polypropylene fabric on both side that guarantees high adhesion to the support.

PROFOIL MEMBRANE

Article	H roll (m)	L roll (m)	Thickness (mm)	Rolls/Pallet			
PFLO 0430	1	30	0,42	40			
PFLO 0405	1	5	0,42	154			

PROFOIL PRO MEMBRANE

Article	H roll (m)	L roll (m)	Thickness (mm)	Rolls/Pallet			
PFLOPR 0430	1	30	0,42	40			



PROFOIL PASTE

WATERPROOFING ELASTIC MEMBRANE



PROFOIL PASTE is a ready to use thin-layer waterproofing elastic membrane with low emissions of volatile organic compounds.

WATERPROOFING ELASTIC MEMBRANE

Article	Kg./Bucket	Bucket/ Pallet				
PFLOPST 04	4	64				
PFLOPST 10	10	36				

WARNINGS

Don't use. For external application, on wet surfaces or substrates subject to moisture rising, in environments where water is always present, pools and tanks. Store in a cool and dry place avoiding direct sunlight and sources of heat. Read the data sheet before applying; in case of special applications please call the technical department.

PROBAND 150/250

ELASTIC ROLLS IN HDPE AND PP



PROBAND 150/250 is a waterproofing polyethylene tape with nonwoven polypropylene fabric on both side that guarantees high adhesion to the support.

PROBAND 150/250

Article	H Roll (mm)	L Roll (m)	Thickness (mm)	Roll/Pack			
PRBPE 1507	150	7,5	0,42	16			
PRBPE 1530	150	30	0,42	6			
PRBPE 2530	250	30	0,42	3			

PREFORMED CORNERS and PIPE COLLAR

Internal and external preformed corners and pipe collar in polyethylene provided on both side with nonwoven polypropylene fabric that guarantees its adhesion to the support. Use on Terraces, balconies and outside surfaces of any dimension, bathrooms, showers, swimming pools and tanks. To realize waterproofing joints between floor and wall and along two adjacent rolls of PROFOIL, PRODES® MEMBRANE SYSTEM and PRODES® HEAT/GRIP SYSTEM



EXTERNAL CORNER
PRBE



INTERNAL CORNER
PRBI



PIPE COLLAR
PRBT

PREFORMED CORNERS AND PIPE COLLAR IN HDPE AND PP

Thickness 0,42 mm


Articolo	H x L mm			
PRBI	60 x 120			
PRBE	60 x 120			
PRBT	125 x 125			

WARNINGS

Don't use - On bituminous coverings, over thermal-insulating layer and lightweight screed. With adhesives containing solvents. adhesive.

PRODRAIN 10

DRAINING MEMBRANE



PRODRAIN 10 is a drainage membrane composed by an high density polyethylene (HDPE) sheet provided with truncated cone reliefs. On the top of the reliefs a non-woven polypropylene fabric, in grey colour, permeable to water is thermowelded.

PRODRAIN 10 MEMBRANE

Article	H roll (m)	L roll (m)	Thickness (mm)	Rolls/Pallet			
PDRI 10	0,96	12,5	10	6			

AREAS OF USE

Use. Outside on concrete sloping suitably waterproofed such as terraces, balconies and pavements and in contact with waterproofed vertical structures such as foundation walls. Highly resistant to saline solutions, acid and alkaline, alcohol and oils. In case of special products consult the technical department.
Don't use. On concrete waterproofed without adequate slope to the drained water runoff. As soundproof and thermal-insulating layer.

PROFOIL PANEL are high density extruded polystyrene panels covered on both sides with a steam- and waterproofing membrane. The membrane is waterproofing and the adhesive to fix them reinforces the panels for a quick and inexpensive laying.

PROFOIL PANEL

HIGH DENSITY EXTRUDED POLYSTYRENE PANEL



PROFOIL PANEL 2700 mm - high density extruded polystyrene
915 mm x 2700 mm = 2,470 m²

Article	H mm	Pcs/pallet	Mq/pallet
PFLPAN1327	12,70	60	148,20
PFLPAN2527	25,00	30	74,10
PFLPAN5027	50,80	15	37,05

PROFOIL PANEL 1524 mm - high density extruded polystyrene
915 mm x 1524 mm = 1,394 m²

Article	H mm	Pcs/pallet	Mq/pallet
PFLPAN6	6,35	85	118,49

THICKNESS PROFOIL PANEL



PROFOIL AND PROBAND DOWELS, WASHERS, SCREWS

STAINLESS STEEL/ZINC-COATED METAL/GLASS FIBER NET



PROFOIL DOWELS - ZINC-COATED METAL - pack. 250 Pc

Article	L mm
TZPFP 110	100
TZPFP 140	140
TZPFP 170	170
TZPFP 200	200



PROFOIL DOWELS - STAINLESS STEEL - pack. 250 Pc

Article	L mm
TIPFP 110	110
TIPFP 140	140
TIPFP 170	170
TIPFP 200	200
TIPFP 250	250



PROFOIL WASHERS (ZINC-COATED METAL) - pack. 100 Pc

Article	Pcs/Pack.	ø mm
RFPP 36	100	35



PROFOIL SCREWS (ZINC-COATED METAL)

Article	Pcs/Pack.	L mm
VACFP 35	1000	35
VACFP 55	1000	45
VACFP 80	1000	80

PRO GOBOARD PANEL highdensity polyisocyanurate foam panel, covered on both sides with a fibre-glass reinforced cement-based waterproof coating to allow the laying of tiles. The panels, tested for a resistance long duration, are available in thickness of 6,25 / 12,5 / 25 and 50 mm, size of 92 x 152 cm and 122 x 244 cm and can be used on floors, false ceilings, walls, showers and ceilings.


PRO GOBOARD PANEL


HIGH DENSITY POLYISOCYANURATE FOAM PANEL

PRO GOBOARD PANEL - highdensity polyisocyanurate foam

Article	Description	Pcs/pallet	m ² /pallet	/m ²
PGOBOR06	PRO GOBOARD H 6,25 mm - 92 cm x 152 cm - 1,40 m ²	75	105	
PGOBOR125	PRO GOBOARD H 12,5 mm - 92 cm x 152 cm - 1,40 m ²	60	84	
PGOBOR25	PRO GOBOARD H 25 mm - 122 cm x 244 cm - 2,98 m ²	30	89,4	
PGOBOR50	PRO GOBOARD H 50 mm - 122 cm x 244 cm - 2,98 m ²	15	44,70	

PGOBOR...






An interpretation of:
Kaufmann "Fallingwater" House, Frank Ll. Wright, Pennsylvania (USA), 1939



SHOWER AND DRAINAGE SYSTEMS



PROSHOWER LINEAR KIT SYSTEM

PROSHOWER LINEAR KIT SYSTEM is an innovative solution, which combines functionality and design to answer to all requirements of the shower.



Article	Description	Pc/Pack.
PSHPANEK	PROSHOWER LINEAR KIT BASE	1

Article	Kit components	Pc/Pack.
PSHPAN...	PROSHOWER PANEL in moulded polystyrene 120x120 cm with glued Profoil	1
PRBFXB	PROBAND FIX white	2
PRBPE 1507	ROLL PROBAND 150 - 7,5 lm	1
PFLO 0405	PROFOIL ROLL - 5 lm	1
PIAA 40212	ALUMINUM PROFILES (screed leveling profile) length 120 cm	2
PRSPD 10	PVC TOWEL	1



PROSHOWER PANEL LINEAR
PSHPAN



PROFOIL
PFLO 0405



PROBAND 150
PRBPE 1507



PROBAND FIX
PRBFXB




PVC TOWEL
PRSPD 10





ALUMINUM PROFILES
PIAA 40212

Article	Description	Pc/Pack.
PSHPAN	Proshower panel in moulded polystyrene 120x120 cm with glued Profoil	1



Article	Description	Pc/Pack.
PSHPANXT 60120	PROSHOWER PANEL EXTENSION 120x60 cm for PROSHOWER PANEL LINEAR - Slope 2%	1
PSHPANXTL 60120	LATERAL PROSHOWER PANEL EXTENSION 60x120 cm for PROSHOWER PANEL LINEAR - Slope 2%	1

PROSHOWER PANEL EXTENSION
EXEMPLES OF LAYING



PROSHOWER BASE L is a channel body in stainless steel AISI 304/1.4301 - V2A steel for the realisation of floor-level shower. The body channel, with an overall height of 85 mm, is completed by 6 different grids in stainless steel. **PROSHOWER BASE L** undergoes electro-polishing and subsequent passivation, which guarantees excellent resistance in any environment. Its low thickness combined with the fully adjustable siphon, the modularity and the high number of grids make it a much sought-after solution.

PROSHOWER BASE L


SUPER POLISHED STAINLESS STEEL
AISI 304/1.4301-V2A



* L 30 cm

DUCT BODY MADE OF AISI 304 STAINLESS STEEL

Article	Description	Pc/Pack.
PSHWDL 30	PROSHOWER BASE L-ACC-L 30 x 8 cm	1
PSHWDL 70	PROSHOWER BASE L-ACC-L 70 x 8 cm	1
PSHWDL 80	PROSHOWER BASE L-ACC-L 80 x 8 cm	1
PSHWDL 90	PROSHOWER BASE L-ACC-L 90 x 8 cm	1
PSHWDL 100	PROSHOWER BASE L-ACC-L 100 x 8 cm	1
PSHWDL 120	PROSHOWER BASE L-ACC-L 120 x 8 cm	1



UPON REQUEST

PROSHOWER BASE L with vertical siphon complete of installed Profoil membrane (code ref. PSHWDVS...), Drain Ø 50 mm.

PROSHOWER BASE BASIC is a water collecting duct system in polypropylene for floor showers, available in several lengths and grids.


PROSHOWER BASE BASIC

GREY POLYPROPYLENE



GREY POLYPROPYLENE DUCT BODY

Article	Description	Pc/Pack.
PSHWBB 60	PROSHOWER BASE BASIC - 60 x 8 cm PP	1
PSHWBB 70	PROSHOWER BASE BASIC - 70 x 8 cm PP	1
PSHWBB 80	PROSHOWER BASE BASIC - 80 x 8 cm PP	1
PSHWBB 90	PROSHOWER BASE BASIC - 90 x 8 cm PP	1



UPON REQUEST


PROSHOWER BASE BASIC with vertical siphon complete of installed Profoil membrane (code ref. PSHWBBVS...), Drain Ø 50 mm.

PROFOIL SECTION

HDPE E PP GUAINE

PROFOIL SECTION AND DOUBLE SIDED TAPE 3 lm

Article	L	Pc/Pack.
PSHANT 30	30 cm	1
PSHANT 60	60 cm	1
PSHANT 70	70 cm	1
PSHANT 80	80 cm	1
PSHANT 90	90 cm	1
PSHANT 100	100 cm	1
PSHANT 120	120 cm	1



PROFOIL SECTION AND DOUBLE SIDED TAPE

PROSHOWER TOP

SUPER-POLISHED STAINLESS STEEL AISI 304 / 1.4301 - V2A

PROSHOWER TILE - tileable

PSHWT 30/60/70/80/90/100/120



PROSHOWER TILE - SUPER-POLISHED STAINLESS STEEL AISI 304 / 1.4301 - V2A - Pack. 1 Pc

Article	Lenght cm	Width cm	
PSHWT 30*	30	8	
PSHWT 60**	60	8	
PSHWT 70	70	8	
PSHWT 80	80	8	
PSHWT 90	90	8	
PSHWT 100*	100	8	
PSHWT 120*	120	8	

*PSHWT 30,100,120 Provided only combined with Proshower Base L.

**PSHWT 60 Provided only combined with Proshower Base Basic.

PROSHOWER LINE

PSHWL 60/70/80/90/100/120



PROSHOWER LINE - SUPER-POLISHED STAINLESS STEEL AISI 304 / 1.4301 - V2A - Pack. 1 Pc

Article	Lenght cm	Width cm	
PSHWL 60**	60	8	
PSHWL 70	70	8	
PSHWL 80	80	8	
PSHWL 90	90	8	
PSHWL 100*	100	8	
PSHWL 120*	120	8	

*PSHWL 100,120 Provided only combined with Proshower Base L.

**PSHWL 60 Provided only combined with Proshower Base Basic.

PROSHOWER DESIGN

PSHWD 30/60/70/80/90/100/120



PROSHOWER DESIGN - SUPER-POLISHED STAINLESS STEEL AISI 304 / 1.4301 - V2A - Pack. 1 Pc

Article	Lenght cm	Width cm	
PSHWD 30*	30	8	*
PSHWD 60**	60	8	
PSHWD 70	70	8	
PSHWD 80	80	8	
PSHWD 90	90	8	
PSHWD 100*	100	8	
PSHWD 120*	120	8	

*PSHWD 30,100,120 Provided only combined with Proshower Base L.

**PSHWD 60 Provided only combined with Proshower Base Basic.

PROSHOWER STRIPS

PSHWST 60/70/80/90/100/120



PROSHOWER STRIPS - SUPER-POLISHED STAINLESS STEEL AISI 304 / 1.4301 - V2A - Pack. 1 Pc

Article	Lenght cm	Width cm	
PSHWST 60**	60	8	*
PSHWST 70	70	8	*
PSHWST 80	80	8	*
PSHWST 90	90	8	*
PSHWST 100*	100	8	*
PSHWST 120*	120	8	*

*PSHWST 100,120 Provided only combined with Proshower Base L.

**PSHWST 60 Provided only combined with Proshower Base Basic.

PROSHOWER GRILL

PSHWGR 60/70/80/90/100/120



PROSHOWER GRILL - SUPER-POLISHED STAINLESS STEEL AISI 304 / 1.4301 - V2A - Pack. 1 Pc

Article	Lenght cm	Width cm	
PSHWGR 60**	60	8	*
PSHWGR 70	70	8	*
PSHWGR 80	80	8	*
PSHWGR 90	90	8	*
PSHWGR 100*	100	8	*
PSHWGR 120*	120	8	*

*PSHWGR 100,120 Provided only combined with Proshower Base L.

**PSHWGR 60 Provided only combined with Proshower Base Basic.

PROSHOWER SQUARE

PSHWSQ 60/70/80/90/100/120



PROSHOWER SQUARE - SUPER-POLISHED STAINLESS STEEL AISI 304 / 1.4301 - V2A - Pack. 1 Pc

Article	Lenght cm	Width cm	
PSHWSQ 60**	60	8	*
PSHWSQ 70	70	8	*
PSHWSQ 80	80	8	*
PSHWSQ 90	90	8	*
PSHWSQ 100*	100	8	*
PSHWSQ 120*	120	8	*

*PSHWSQ 100,120 Provided only combined with Proshower Base L.

**PSHWSQ 60 Provided only combined with Proshower Base Basic.

News 2023

* = Production on demand with minimum quantity of 10 pcs. Production delay 4/5 weeks. Price to be agreed




DRAIN REDUCTION

POLYPROPYLENE

Article	Description	Pc/Pack.
PSHWRD 5040	50 to 40 mm polypropylene drain reduction	1



REDUCTION







MODULAR ASSEMBLY KIT

Article	Description	Pc/Pack.
PSHWRD	Modular assembly kit to make drain ducts of any length	1



MODULAR ASSEMBLY KIT



PROSHOWER BASE L PRO

SUPER-POLISHED
STAINLESS STEEL AISI 316L / 1.4404 - V4A

PROSHOWER BASE L PRO is a stainless steel AISI 316L / 1.4404 - V4A drain for the realisation of floor-level and for wall shower drain. This drain is available in different lengths and equipped with different grids. The reduced thickness grid has excellent chemical resistance and is equipped with a 360° adjustable siphon.


PSHWP...



DUCT BODY MADE OF A STAINLESS STEEL AISI 316L / 1.4404 - V4A

Article	Description	Pc/Pack.
PSHWP 30	PROSHOWER BASE L PRO - L 30 x 5,5 cm	1
PSHWP 60	PROSHOWER BASE L PRO - L 60 x 5,5 cm	1
PSHWP 70	PROSHOWER BASE L PRO - L 70 x 5,5 cm	1
PSHWP 80	PROSHOWER BASE L PRO - L 80 x 5,5 cm	1
PSHWP 90	PROSHOWER BASE L PRO - L 90 x 5,5 cm	1
PSHWP 100	PROSHOWER BASE L PRO - L 100 x 5,5 cm	1

Article	Kit components	Pc/Pack.
PSHWPNN...	PROSHOWER BASE L PRO DUCT BODY	1
TASPRF...	PROFOIL SECTION	1
SPSHWPT...	POLYSTYRENE TEMPORARY CHANNEL PROTECTION	1



PROSHOWER BASE L PRO
DUCT BODY
PSHWPNN...



PROFOIL SECTION
TASPRF...




POLYSTYRENE TEMPORARY
CHANNEL PROTECTION
SPSHWPT...

PROSHOWER TOP PRO

SUPER-POLISHED STAINLESS STEEL AISI 316L / 1.4404 - V4A

PROSHOWER TILE/LINE PRO

PSHWPT 30/60/70/80/90/100



TILED SOLUTION

FLUSH FLOOR SOLUTION

PROSHOWER TILE/LINE PRO - SUPER-POLISHED STAINLESS STEEL AISI 316L/1.4404-V4A - Pack. 1 Pc

Article	Length cm	Width cm
PSHWPLT 30	30	5,5
PSHWPLT 60	60	5,5
PSHWPLT 70	70	5,5
PSHWPLT 80	80	5,5
PSHWPLT 90	90	5,5
PSHWPLT 100	100	5,5

Sold only in combination with Proshower Base L PRO

PROSHOWER DESIGN PRO

PSHWPD 30/60/70/80/90/100



PROSHOWER DESIGN PRO - - SUPER-POLISHED STAINLESS STEEL AISI 316L/1.4404-V4A - Pack. 1 Pc

Article	Length cm	Width cm
PSHWPD 30	30	5,5
PSHWPD 60	60	5,5
PSHWPD 70	70	5,5
PSHWPD 80	80	5,5
PSHWPD 90	90	5,5
PSHWPD 100	100	5,5

Sold only in combination with Proshower Base L PRO

PROSHOWER BASE L PRO is also equipped with a wall drain box made of AISI 316L / 1.4404 - V4A stainless steel which recessed into the wall, allows to realize wall drains without compromising the water flow and the ease of cleaning.


WALL DRAIN BOX

WALL DRAIN BOX STAINLESS STEEL AISI 316L/1.4404-V4A

Article	Description	Pc/Pack.
KBPSHWPAC 30	PROSHOWER BASE L PRO wall drain box 30 cm	1
KBPSHWPAC 60	PROSHOWER BASE L PRO wall drain box 60 cm	1
KBPSHWPAC 70	PROSHOWER BASE L PRO wall drain box 70 cm	1
KBPSHWPAC 80	PROSHOWER BASE L PRO wall drain box 80 cm	1
KBPSHWPAC 90	PROSHOWER BASE L PRO wall drain box 90 cm	1
KBPSHWPAC 100	PROSHOWER BASE L PRO wall drain box 100 cm	1





INSTALLATION SECTION OF THE WALL DRAIN PROSHOWER BASE L PRO



PROSHOWER PROFILE GLASS

SATINED STAINLESS STEEL AISI 304 / 1.4301 - V2A

PROSHOWER PROFILE GLASS Suitable profile for fixing glass slabs in case of floor level showers with a a slope of 2%. Due to its particular shape and finish in satin-finish stainless steel AISI 304 / 1.4301 - V2A, it covers and decorates the visible side of the screed.




SATINED STAINLESS STEEL AISI 304/1.4301-V2A - LEFT
degreased and passivated - thermo packed - Pack. 1 Pç


Article	H1 mm	H2 mm	L cm
PSHWPGACS 100SX	15	33	100
PSHWPGACS 150SX	15	43	150
PSHWPGACS 200SX	15	53	200

SATINED STAINLESS STEEL AISI 304/1.4301-V2A - RIGHT
degreased and passivated - thermo packed - Pack. 1 Pç

Article	H1 mm	H2 mm	L cm
PSHWPGACS 100DX	15	33	100 cm
PSHWPGACS 150DX	15	43	150 cm
PSHWPGACS 200DX	15	53	200 cm



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS






1. Choose "PROSHOWER PROFILE GLASS" according to the desired length.
2. Cut "PROSHOWER PROFILE GLASS" to the desired length and apply the adhesive on the support where the profile will be laid.
3. Press the anchoring flange of "PROJOLLY SQUARE" into the adhesive.
4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile.
5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.
6. Insert the sheet of glass and seal.

PROSHOWER PROFILE

SATINED STAINLESS STEEL AISI 304 / 1.4301 - V2A

PROSHOWER PROFILE is a profile for floor level showers in stainless steel for the protection of the floor edges and as decoration of the screed visible side. The profile has a 2% slope. Its specific shape makes it an easy to lay profile to be used with all kind of floor.




SATINED STAINLESS STEEL AISI 304/1.4301-V2A - RIGHT
degreased and passivated - thermo packed - Pack. 1 Pç

Article	H mm	H1 mm	H2 mm	L cm
PSHWPACS 1010DX	10	11	28	100
PSHWPACS 1015DX	10	11	38	150
PSHWPACS 1020DX	10	11	48	200
PSHWPACS 12510DX	12,5	13,5	30	100
PSHWPACS 12515DX	12,5	13,5	40	150
PSHWPACS 12520DX	12,5	13,5	50	200

SATINED STAINLESS STEEL AISI 304/1.4301-V2A - LEFT
degreased and passivated - thermo packed - Pack. 1 Pç

Article	H mm	H1 mm	H2 mm	L cm
PSHWPACS 1010SX	10	11	28	100
PSHWPACS 1015SX	10	11	38	150
PSHWPACS 1020SX	10	11	48	200
PSHWPACS 12510SX	12,5	13,5	30	100
PSHWPACS 12515SX	12,5	13,5	40	150
PSHWPACS 12520SX	12,5	13,5	50	200

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROSHOWER PROFILE" according to the desired length.
2. Cut "PROSHOWER PROFILE" to the desired length and apply the adhesive on the support where the profile will be laid.
3. Press the anchoring flange of "PROJOLLY SQUARE" into the adhesive.
4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile.
5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.
6. Insert the sheet of glass and seal.



PROSHOWER PROFILE FRONT is a satin-finish stainless steel AISI 304/1.4301-V2A profile. It is suitable to cover and decorate the visible part of wall in front of the shower tray in case of floor level showers with slope.

PROSHOWER PROFILE FRONT

SATINED STAINLESS STEEL AISI 304 / 1.4301 - V2A

SATINED STAINLESS STEEL AISI 304/1.4301-V2A
degreased and passivated - thermo packed - Pack. 1 Pc

Article	H mm	H1 mm	L cm
PSHWPFACS 101028	10	28	100
PSHWPFACS 101038	10	38	100
PSHWPFACS 101048	10	48	100
PSHWPFACS 101528	10	28	150
PSHWPFACS 101538	10	38	150
PSHWPFACS 101548	10	48	150
PSHWPFACS 1251028	12,5	28	100
PSHWPFACS 1251038	12,5	38	100
PSHWPFACS 1251048	12,5	48	100
PSHWPFACS 1251528	12,5	28	150
PSHWPFACS 1251538	12,5	38	150
PSHWPFACS 1251548	12,5	48	150




EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS




1. Choose "PROSHOWER PROFILE FRONT" according to the desired length.
2. Cut "PROSHOWER PROFILE FRONT" to the desired length and apply the adhesive on the support where the profile will be laid.
3. Press the anchoring flange of "PROJOLLY SQUARE" into the adhesive.
4. Lay the tiles, aligning them with the profile leaving a 2 mm joint.
5. Remove immediately all remains of adhesive from the surface of the profile.
6. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation.
7. Remove immediately all the remains of grout from the surface of the profile.
8. Insert the sheet of glass and seal.

PSHWPFACS 101028 PSHWPFACS 1251028 PSHWPFACS 101038
PSHWPFACS 101528 PSHWPFACS 1251528 PSHWPFACS 101538



PSHWPFACS 1251038 PSHWPFACS 101048 PSHWPFACS 1251048
PSHWPFACS 1251538 PSHWPFACS 101548 PSHWPFACS 1251548




PROSHOWER PROFILE WALL Profile in satin-finish stainless steel AISI 304 / 1.4301 - V2A. It is suitable to cover and decorate the visible part of wall beside the shower tray in case of floor level showers with a slope of 2%.

PROSHOWER PROFILE WALL

SATINED STAINLESS STEEL AISI 304 / 1.4301 - V2A

SATINED STAINLESS STEEL AISI 304/1.4301-V2A - RIGHT
degreased and passivated - thermo packed - Pack. 1 Pc

Article	H mm	H1 mm	H2 mm	L cm
PSHWPLACS 1010DX	10	10	28	100
PSHWPLACS 1015DX	10	10	38	150
PSHWPLACS 1020DX	10	10	48	200
PSHWPLACS 12510DX	12,5	10	28	100
PSHWPLACS 12515DX	12,5	10	38	150
PSHWPLACS 12520DX	12,5	10	48	200



SATINED STAINLESS STEEL AISI 304/1.4301-V2A - LEFT
degreased and passivated - thermo packed - Pack. 1 Pc


Article	H mm	H1 mm	H2 mm	L cm
PSHWPLACS 1010SX	10	10	28	100
PSHWPLACS 1015SX	10	10	38	150
PSHWPLACS 1020SX	10	10	48	200
PSHWPLACS 12510SX	12,5	10	28	100
PSHWPLACS 12515SX	12,5	10	38	150
PSHWPLACS 12520SX	12,5	10	48	200

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS




1. Choose "PROSHOWER PROFILE WALL" according to the desired length.
2. Cut "PROSHOWER PROFILE WALL" to the desired length and apply the adhesive on the support where the profile will be laid.
3. Press the anchoring flange of "PROJOLLY SQUARE" into the adhesive.
4. Lay the tiles, aligning them with the profile leaving a 2 mm joint.
5. Remove immediately all remains of adhesive from the surface of the profile.
6. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation.
7. Remove immediately all the remains of grout from the surface of the profile.
8. Insert the sheet of glass and seal.

PSHWPLACS ...SX




PSHWPLACS ...DX




PROLISTEL CHANNEL

STAINLESS STEEL AISI 304/1.4301-V2A

PLTCH... 08 - 10 - 11 - 12,5



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS




1. Choose "PROLISTEL CHANNEL" according to the visible surface and desired finish. 2. Cut "PROLISTEL CHANNEL" to the desired length and apply the adhesive on the surface where the profile will be laid. 3. Press "PROLISTEL CHANNEL" into the adhesive, aligning it with the tiles leaving a 2 mm. joint. Remove immediately all remains of adhesive from the surface of the profile. 4. Fill the joint between the profile and tiles with grout in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.

COLOURS



AC - Polished stainless steel AISI 304/1.4301-V2A
ACS - Satin finish stainless steel AISI 304/1.4301-V2A

PROLISTEL CHANNEL is a F-shaped strip in polished an satin-finish stainless steel AISI 304/1.4301-V2A suitable to decorate the wall coverings in ceramic tiles and natural stones. Its section allows the realization of a decorative joint which can also be used as a guide for the fixing of sheets of glass on floors and walls. Its particular section and the availability in two different finishes make PROLISTEL CHANNEL a much sought-after profile that allows an easy workmanlike application.



POLISHED STAINLESS STEEL AISI 304/1.4301-V2A
bar length 2,7 lm - pack. 1 Pc


Article	H mm	L mm
PLTCHAC 0812	8	12
PLTCHAC 1012	10	12
PLTCHAC 1112	11	12
PLTCHAC 12512	12,5	12

POLISHED STAINLESS STEEL AISI 304/1.4301-V2A
bar length 2,7 lm - pack. 1 Pc

Article	H mm	L mm
PLTCHAC 0808	8	08
PLTCHAC 1008	10	08
PLTCHAC 1108	11	08
PLTCHAC 12508	12,5	08

POLISHED STAINLESS STEEL AISI 304/1.4301-V2A
bar length 2,7 lm - pack. 1 Pc

Article	H mm	L mm
PLTCHAC 0810	8	10
PLTCHAC 1010	10	10
PLTCHAC 1110	11	10
PLTCHAC 12510	12,5	10



SATIN-FINISH STAINLESS STEEL AISI 304/1.4301-V2A
bar length 2,7 lm - pack. 1 Pc

Article	H mm	L mm
PLTCHACS 0812	8	12
PLTCHACS 1012	10	12
PLTCHACS 1112	11	12
PLTCHACS 12512	12,5	12

SATIN-FINISH STAINLESS STEEL AISI 304/1.4301-V2A
bar length 2,7 lm - pack. 1 Pc

Article	H mm	L mm
PLTCHACS 0808	8	08
PLTCHACS 1008	10	08
PLTCHACS 1108	11	08
PLTCHACS 12508	12,5	08


SATIN-FINISH STAINLESS STEEL AISI 304/1.4301-V2A
bar length 2,7 lm - pack. 1 Pc

Article	H mm	L mm
PLTCHACS 0810	8	10
PLTCHACS 1010	10	10
PLTCHACS 1110	11	10
PLTCHACS 12510	12,5	10


PROLISTEL CHANNEL

ANODIZED AND POLISHED ALUMINIUM

PLTCH... 08 - 10 - 11 - 12,5




EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROLISTEL CHANNEL" according to the visible surface and desired finish. 2. Cut "PROLISTEL CHANNEL" to the desired length and apply the adhesive on the surface where the profile will be laid. 3. Press "PROLISTEL CHANNEL" into the adhesive, aligning it with the tiles leaving a 2 mm. joint. Remove immediately all remains of adhesive from the surface of the profile. 4. Fill the joint between the profile and tiles with grout in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.

PROLISTEL CHANNEL is a F-shaped strip in anodized and polished aluminium suitable to decorate the wall coverings in ceramic tiles and natural stones. Its section allows the realization of a decorative joint which can also be used as a guide for the fixing of sheets of glass on floors and walls. Its particular section and the availability in two different finishes make PROLISTEL CHANNEL a much sought-after profile that allows an easy workmanlike application.



ANODIZED SILVER ALUMINIUM
bar length 2,7 lm - pack. 40 Pcs - 108 lm


Article	H mm
PLTCHAA 08	8
PLTCHAA 10	10
PLTCHAA 11	11
PLTCHAA 125	12,5



POLISHED CHROME ALUMINIUM
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm
PLTCHBC 08	8
PLTCHBC 10	10
PLTCHBC 11	11
PLTCHBC 125	12,5

COLOURS



AA - Anodized silver alum. BC - Polished chrome alum.

= News 2023

= Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed



PROSHOWER CENTRAL KIT SYSTEM

PROSHOWER CENTRAL KIT SYSTEM is an innovative solution, which combines functionality and design to answer to all requirements of the shower.



Article	Description	Pc/Pack.
PSHPANCEK	PROSHOWER CENTRAL KIT SYSTEM	1

Article	Kit components	Pc/Pack.
PSHPANC	PROSHOWER PANEL CENTRAL - moulded polystyrene 120 cm x 120 cm	1
PRBFXB	PROBAND FIX white	2
PRBPE 1507	PROBAND 150 - 7,5 lm	1
PFLO 0405	PROFOIL ROLL - 5 lm	1
PRSPD 10	PVC TOWEL	1
PSHLDK	PROSHOWER DRAIN LATERAL KIT	1



PROSHOWER PANEL CENTRAL
PSHPANC



PROFOIL
PFLO 0405



PROBAND 150
PRBPE 1507




PROBAND FIX
PRBFXB




PVC TOWEL
PRSPD 10

Article	Description	Pc/Pack.
PSHPANC	PROSHOWER PANEL CENTRAL - moulded polystyrene 120 cm x 120 cm	1



PROSHOWER PANEL CENTRAL
PSHPANC





PROSHOWER LATERAL DRAIN KIT are 2 central drain systems with lateral outflow equipped with a siphon, grate support, stainless steel grate, butyl double-sided ring for the fixing of the waterproof section, waterproof section and a protection cap with template function too that allows the correct positioning of the butyl ring and the waterproof section. LATERAL AND VERTICAL DRAIN KIT ensure a correct flow of rainwater.


PROSHOWER DRAIN KIT

LATERAL AND VERTICAL DRAINS

Article	Description	Pc/Pack.
PSHLDK	PROSHOWER DRAIN LATERAL KIT	1

AREA OF USE

- **Use** - PROSHOWER BASE L PRO it can be used in any indoor and outdoor environment.
- **Don't use** - In environments where very aggressive substances are used and a high concentrated load is expected.



PROSHOWER DRAIN CENTRAL PRO is a 10x10 cm stainless steel AISI 316L / 1.4404 – V4A drain for the realisation of floor-level shower. This low thickness drain is equipped with a grid that can also be tiled for floor-level drains. PROSHOWER DRAIN CENTRAL PRO has excellent chemical resistance and is equipped with a 360 ° adjustable siphon.

PROSHOWER DRAIN CENTRAL PRO

LATERAL DRAIN

PROSHOWER DRAIN CENTRAL PRO - GRATE + POLYSTYRENE CHANNEL PROTECTION + PROFOIL SECTION + DUCT BODY + SIPHON


Article	Description	Pc/Pack.
PSHWCP	PROSHOWER DRAIN CENTRAL PRO	1

AREA OF USE

- **Use** - Balconies, terraces, outdoor surfaces of any size, kitchens and showers.
- **Don't use** - In environments subject to heavy traffic and where washing with acidic and strong alkaline substances is foreseen.

WARNINGS


After the drain installation, apply the protective cap. Before applying the butyl double-sided adhesive ring on the flange of the drain, thoroughly clean the flange of any dirt residue that may compromise its adhesion. Apply the butyl double-sided adhesive ring and the waterproofing section during the application of the waterproofing system.



PROFOIL PANEL

HIGH DENSITY EXTRUDED
POLYSTYRENE PANEL

PROFOIL PANEL are high density extruded polystyrene panels covered on both sides with a steam- and waterproofing membrane. The membrane is waterproofing and the adhesive to fix them reinforces the panels for a quick and inexpensive laying.






PROFOIL PANEL 2700 mm - high density extruded polystyrene
915 mm x 2700 mm = 2,470 m²

Article	H mm	Pcs/pallet	Mq/pallet
PFLPAN1327	12,70	60	148,20
PFLPAN2527	25,00	30	74,10
PFLPAN5027	50,80	15	37,05

PROFOIL PANEL 1524 mm - high density extruded polystyrene
915 mm x 1524 mm = 1,394 m²

Article	H mm	Pcs/pallet	Mq/pallet
PFLPAN6	6,35	85	118,49

PROFOIL PANEL THICKNESS



PROFOIL AND PROBAND DOWELS, WASHERS, SCREWS

STAINLESS STEEL/ZINC-COATED METAL/GLASS FIBER NET



PROFOIL DOWELS - ZINC-COATED METAL - pack. 250 Pc

Article	L mm
TZPFP 110	110
TZPFP 140	140
TZPFP 170	170
TZPFP 200	200



PROFOIL DOWELS - STAINLESS STEEL - pack. 250 Pc

Article	L mm
TIPFP 110	110
TIPFP 140	140
TIPFP 170	170
TIPFP 200	200
TIPFP 250	250



PROFOIL PANEL SCREWS (ZINC-COATED METAL)

Article	Pcs/Pack.	L mm
VACFP 35	1000	35
VACFP 55	1000	45
VACFP 80	1000	80



PROFOIL PANEL WASHERS (ZINC-COATED METAL) - pack. 100 Pc

Article	Pcs/Pack.	ø mm
RFPP 36	100	35

PROFOIL PANEL NICHE are prefabricated built-in elements of PROFOIL PANEL to make indoor wall niches and support surfaces. The niches can be linked to the waterproofing systems PROFOIL and PROFOIL PANEL. The fixing of the shelf inside the niche is optional. The shelf, part of the, can be fixed at the needed height. It is available in 4 sizes.


PROFOIL PANEL NICHE

HIGH DENSITY EXTRUDED POLYSTYRENE


PROFOIL PANEL NICHE - WATERPROOFING NICHE

Article	Description	Pcs/Pack.
PFLPANICH 88	WATERPROOFING NICHE MADE OF PROFOIL PANEL of 12,5mm, Inside size of the niche 203,2 x 203,2 mm	1
PFLPANICH 1212	WATERPROOFING NICHE MADE OF PROFOIL PANEL of 12,5mm, Inside size of the niche 304,8 x 304,8 mm	1
PFLPANICH 821	WATERPROOFING NICHE MADE OF PROFOIL PANEL of 12,5mm, Inside size of the niche 203,2 x 533,4 mm	1
PFLPANICH 1221	WATERPROOFING NICHE MADE OF PROFOIL PANEL of 12,5mm, Inside size of the niche 304,8 x 533,4 mm	1


PFLPANICH 88





PFLPANICH 1212



PFLPANICH 821



PFLPANICH 1221



PROFOIL PROFOIL PRO

ROLLS IN HDPE AND PP

PROFOIL is a waterproofing polyethylene membrane with nonwoven polypropylene fabric on both side that guarantees high adhesion to the support.

PROFOIL PRO is a waterproofing elastic polyethylene membrane with nonwoven polypropylene fabric on both side that guarantees high adhesion to the support.

PROFOIL - ROLLS IN HDPE AND PP - Thickness 0,42 mm ROLLS IN HDPE AND PP - Thickness 0,42 mm

Article	Width roll H x L Im	total m ²	Rolls/pallet		
PFLO 0430	1 x 30	30	40		
PFLO 0405	1 x 5	5	154		

PROFOIL PRO - ELASTIC ROLLS IN HDPE AND PP - Thickness 0,42 mm PP


Article	Width roll H x L Im	total m ²	Rolls/pallet		
PFLOPR 0430	1 x 30	30	40		

AREAS OF USE

• **Use.** Waterproofing of substrates and vertical structures before the laying of ceramic in areas subject to occasional contact with water like bathrooms and kitchens, saunas and Turkish baths. **PROFOIL PRO** can also be used in environments with permanent contact with water like swimming pools and tanks. • **Don't use.** On bituminous coverings, over insulating panels and lightweight screed.

WARNINGS

Store in a cool and dry place avoiding direct sunlight and sources of heat. Read the data sheet before applying; in case of special applications please call the technical department.



WEBSITE



PROFOIL PASTE

WATERPROOFING ELASTIC MEMBRANE



WATERPROOFING ELASTIC MEMBRANE

Article	Kg/ Bucket	Bucket/ Pallet			
PFLOPST 04	4	64			
PFLOPST 10	10	36			

PROFOIL PASTE is a ready to use thin-layer waterproofing elastic membrane with low emissions of volatile organic compounds.

AREAS OF USE

• **Use.** Waterproofing for bathrooms, kitchens, showers, gypsum-based plasters, cement-based plaster and plasterboard walls. • **Don't use.** For external application, on wet surfaces or substrates subject to moisture rising, in environments where water is always present, pools and tanks.

WARNINGS

Store in a cool and dry place avoiding direct sunlight and sources of heat. Read the data sheet before applying; in case of special applications please call the technical department.

PROBAND 150/250

ELASTIC ROLLS IN HDPE AND PP




ROLLS IN HDPE AND PP - Thickness 0,42 mm

Article	Roll width H mm x L Im	Rolls/ Pack.			
PRBPE 1507	150 x 7,5	16			
PRBPE 1530	150 x 30	6			
PRBPE 2530	250 x 30	3			

CORNERS and PIPE COLLAR

HDPE E PP



PRBE

PRBI

PRBT

PREFORMED ELASTIC CORNERS AND PIPE COLLAR IN HDPE AND PP
Thickness 0,42 mm

Article	H x L mm			
PRBI	60 x 120			
PRBE	60 x 120			
PRBT	125 x 125			

PROBAND FIX

MOISTURE-CURE SEALANT



MOISTURE-CURE SEALANT

pack. of 12 cartridges - B (white) - G (grey)

Article	Cartridge Im		
PRBFXB	290		
PRBFXG	290		



PRBFXGUN

GUN FOR MOISTURE-CURE SEALANT CARTRIDGE

Article	Pc/Pack		
PRBFXGUN	1		



PRBFXU...

MOISTURE-CURE SEALANT CARTRIDGE

pack. of 12 cartridges - B (white) - G (grey)

Articolo	Cartridge Im		
PRBFXUB	600		
PRBFXUG	600		

PROSHELF are tileable shelves in stainless steel AISI 316/1.4404-V4A for the underile installation. Thanks of their perforated fixing flaps, they are easily installed on the wall during the laying of the ceramic coating. They are available in 2 shapes, triangular for the corner installation and rectangular. These shelves are suitable for the installation in Bathroom and kitchens.

PROSHELF

STAINLESS STEEL AISI 316/1.4404-V4A


PROSHELF - STAINLESS STEEL AISI 316/1.4404-V4A TRIANGULAR TILEABLE SHELF

Article	size	Pc/Pack.
PRSHLFTP24	170 mm x 240 mm	1
PRSHLFTP30	212 mm x 300 mm	1



PROSHELF - STAINLESS STEEL AISI 316/1.4404-V4A RECTANGULAR TILEABLE SHELF

Article	size	Pc/Pack.
PRSHLFRP40	150 mm x 400 mm	1
PRSHLFRP30	115 mm x 300 mm	1




PROSHELF - STAINLESS STEEL AISI 316/1.4404-V4A TRIANGULAR SHELF

Article	size	Pc/Pack.
PRSHLFTD24	170 mm x 240 mm	1
PRSHLFTD30	212 mm x 300 mm	1




PROSHELF - STAINLESS STEEL AISI 316/1.4404-V4A RECTANGULAR SHELF


Article	size	Pc/Pack.
PRSHLFRD40	150 mm x 400 mm	1
PRSHLFRD30	115 mm x 300 mm	1



EXAMPLES OF LAYING



1. Choose "PROSHELF" according to the desired shape and size.
2. apply the adhesive on the support where the shelf will be installed.
3. Press the anchoring flap into the adhesive;
4. Lay the tiles taking care to align them with the shelf. Immediately remove adhesive residues from the surface of the shelf.
5. Carefully seal the joints between the shelf and tiles with PROBAND FIX to avoid water stagnation. Remove any grout residue from the shelf surface.



PRO GOBOARD PANEL highdensity polyisocyanurate foam panel, covered on both sides with a fibre-glass reinforced cement-based waterproof coating to allow the laying of tiles. The panels, tested for a resistance long duration, are available in thickness of 6,25 / 12,5 / 25 and 50 mm, size of 92 x 152 cm and 122 x 244 cm and can be used on floors, false ceilings, walls, showers and ceilings.

PRO GOBOARD PANEL

HIGH DENSITY POLYISOCYANURATE FOAM PANEL

PRO GOBOARD PANEL - highdensity polyisocyanurate foam

Article	Description	Pcs/pallet	m ² /pallet
PGOBOR06	PRO GOBOARD H 6,25 mm - 92 cm x 152 cm - 1,40 m ²	75	105
PGOBOR125	PRO GOBOARD H 12,5 mm - 92 cm x 152 cm - 1,40 m ²	60	84
PGOBOR25	PRO GOBOARD H 25 mm - 122 cm x 244 cm - 2,98 m ²	30	89,4
PGOBOR50	PRO GOBOARD H 50 mm - 122 cm x 244 cm - 2,98 m ²	15	44,70

PGOBOR...



PROHEATER SYSTEM

PROHEATER is a wall porcelain stone tiled design heater that warms your bathroom with elegance and style


PROHEATER - WALL PORCELAIN STONE TILED HEATING SYSTEM

Article	Description
PHTST...	Proheater 60 x 152 cm

Available in various ceramic finishes. The code of the chosen color must be added to the article code.
Ex: PHTST... (chosen color 01 - Lincoln); PHTST01.

PROHEATER TOWEL RACK - Pack. 2 Pcs

Article	Description
PHTPSB	White varnished metal towel rack
PHTPSN	Black varnished metal towel rack




- CERAMIC
- ADHESIVE
- PRODESO HEAT GRIP CABLE
- PRODESO HEAT GRIP MEMBRANE
- ADHESIVE
- PROFOIL PANEL

PROHEATER WITH TOWEL RACK



CERAMIC COLOR RANGE





PATENTED





An interpretation of:
**Grande Arche De la Défense, J. Otto von Spreckelsen,
PARIS (France), 1989**

SKIRTING BOARDS





PROSKIRTING CHANNEL is the new innovative skirting designed with an integrated system for plasterboard walls, and devised to create a skirting flush to the wall with decorative inner grooves for a modern and contemporary touch.

PROSKIRTING CHANNEL

ANODIZED, BRUSHED, VARNISHED ALUMINIUM



SUPPORT/ PERFORATED BASE - ANODIZED SILVER ALUM.
thermo packed - bar length 2 lm - pack. 20 Pcs - 40 lm


Article	H mm
PKGCFAA 75	75

ORDER THE SUPPORT AND THE TOP YOU WISH


VISIBLE TOP - ANODIZED, BRUSHED, WHITE VARNISHED ALUM.
thermo packed bar length 2 lm - pack. 20 Pcs - 40 lm

Article	H mm
PKCHAA 55	55
PKCHBS 55	55
PKCHA 55-01	55

On demand may be realised in other finishes of the colour chart.
Contact our customer service for minimum quantity, timing and price.



EXAMPLES OF LAYING for instructions see the product below



EXTERNAL /INTERNAL CORNER - ANODIZED, BRUSHED, WHITE VARNISHED ALUM. - pack. 5 Pcs


Article	H mm
REPCHAA 55/5	55
REPCHBS 55/5	55
REPCHA 55-01/5	55

END CAPS - ANODIZED, BRUSHED, WHITE VARNISHED ALUM. - pack. 10 Pcs

Article	H mm
TPKCHAA 55/10	60
TPKCHBS 55/10	60
TPKCHA 55-01/10	60



COLOURS



PROSKIRTING FLAT is the new innovative skirting designed with an integrated system for plasterboard walls, and devised to create a skirting flush to the wall for a modern and contemporary touch.

PROSKIRTING FLAT

ANODIZED, BRUSHED, VARNISHED ALUMINIUM



SUPPORT/ PERFORATED BASE - ANODIZED SILVER ALUM.
thermo packed - bar length 2 lm - pack. 20 Pcs - 40 lm


Article	H mm
PKGCFAA 75	75

ORDER THE SUPPORT AND THE TOP YOU WISH


VISIBLE TOP - ANODIZED, BRUSHED, WHITE VARNISHED ALUM.
thermo packed - bar length 2 lm - pack. 20 Pcs - 40 lm

Article	H mm
PKFLAA 60	60
PKFLBS 60	60
PKFLA 60-01	60

On demand may be realised in other finishes of the colour chart.
Contact our customer service for minimum quantity, timing and price.



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



EXTERNAL / INTERNAL CORNER - ANODIZED, BRUSHED, WHITE VARNISHED ALUM. - pack. 5 Pcs


Article	H mm
REPFLAA 60/5	60
REPFLBS 60/5	60
REPFLA 60-01/5	60

END CAPS - ANODIZED, BRUSHED, WHITE VARNISHED ALUM. - pack. 10 Pcs

Article	H mm
TPKCHAA 55/10	60
TPKCHBS 55/10	60
TPKCHA 55-01/10	60



COLOURS




1. Fix the substrate/perforated base to the wall before laying the plasterboard, calculating all the heights and distances. 2. Lay the plasterboard aligning the lower part flush to the "PROSKIRTING CHANNEL" and/or FLAT. 3. Plaster and carry out the surface finishing on the plasterboard. 4. Choose the required Top "PROSKIRTING CHANNEL" and/or FLAT finish, cut and lay the profile fitting the lower part and then the upper part by pressing gently. **IMPORTANT:** Pay attention to the external edges of the aluminium Proskirting. They must be protected against agents such as adhesives and sealants and against grinding or scraping actions.

PROSKIRTING INS

ANODIZED SILVER ALUMINIUM

PROSKIRTING INS is the new innovative skirting designed with an integrated system for plasterboard walls, and devised to create a recessed skirting for a modern and minimalist design in line with the latest trends.

PKINSAA 60



ANODIZED SILVER ALUMINIUM thermo packed
bar length 2 lm - pack. 30 Pcs - 60 lm

Article	H x L mm
PKINSAA 60	60 X 15


ON DEMAND MAY BE REALISED IN OTHER FINISHES OF THE COLOUR CHART. CONTACT OUR CUSTOMER SERVICE FOR MINIMUM QUANTITY (MINIMUM QUANTITY ORDER OF 500 LM), TIMING AND PRICE.

COLOURS



AA - Anodized silver alum.

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Fix "PROSKIRTING INS" using screws (concealed part) and glue/silicone (exposed side), before laying the plasterboard, calculating all the heights and distance. 2. Lay the plasterboard aligning the lower part flush to the "PROSKIRTING INS". 3. Plaster and carry out the surface finishing on the plasterboard.

USE PROBAND FIX FOR FIXING THE PROFILE TO THE WALL




PROSKIRTING LINE

ANODIZED SILVER ALUMINIUM

PROSKIRTING LINE in the innovative skirting suitable for smoothed lime, marmorino, stucco, and Venetian coats on civil plaster or plasterboard.

PKLIAA 60



ANODIZED SILVER ALUMINIUM thermo packed
bar length 2 lm - pack. 40 Pcs - 80 lm

Article	H x L mm
PKLIAA 60	61 x 2,5


ON DEMAND MAY BE REALISED IN OTHER FINISHES OF THE COLOUR CHART. CONTACT OUR CUSTOMER SERVICE FOR MINIMUM QUANTITY (MINIMUM QUANTITY ORDER OF 500 LM), TIMING AND PRICE.

COLOURS



AA - Anodized silver alum.

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Fix the "PROSKIRTING LINE" using glue/silicone (exposed side), before making the required coat, calculating all the heights and distances. 2. Carry out the surface finishing aligning the lower part flush to the "PROSKIRTING LINE".

USE PROBAND FIX FOR FIXING THE PROFILE TO THE WALL



PROSKIRTING ISP is a joint, inspectional "cable duct" baseboard in aluminium, conceived and designed to hide and protect the passage of electric cables, the ones for computer, telephones and other plants as well, allowing an easy and quick access. The supports that are to be fixed on the wall consent accommodate different utility wires/cables as well. Aesthetically pleasant, it is recommended for various public and private environments: offices, schools, residences, commercial centers etc. Available in silver anodized aluminium (H: 100 mm) and in polished titanium and brushed titanium aluminium (H: 70 mm). In order to facilitate and to perfect the laying process, internal and external angles, plugs and junctions are recommended.

PROSKIRTING ISP

SILVER ANODIZED ALUMINIUM, TITANIUM
POLISHED AND BRUSHED ALUM. (H:70 MM)




SKIRTING ANODIZED SILVER ALUMINIUM
thermo packed - bar length 2 lm - pack. 25 Pcs - 50 lm

Article	H mm
PKISPA 70	70
PKISPA 100	100

PUNCHED SUPPORT
support length 2 cm - pack. 10 Pcs

Article	H mm
PKGS 55	55

ARTICLES NOT FOR SALE SINGLY



POWER SUPPLY BOX
SOCKET with FASTENING BASIS

Article
SPA 1820

SWITCH BOX
with BOX BASIS

Article
SI 1410

JUNCTION BOX
with FASTENING BASIS

Article
SD 1210


VERTICAL CABLE DUCT PROFILE
bar length 2,7 lm

Article
PSPV


It matches with CSPPK 80. Pag. 197.

LAYING INSTRUCTIONS

1. Choose "PROSKIRTING ISP" in the desired finish and height. 2. Fix the punched support to the wall with screws every 50 cm. 3. If expected, laying the low-voltage electric cables like web, computer, telephone and satellite TV. 4. Attach the profile to the support applying low pressure.



EXAMPLES OF LAYING



On demand may be realised in other finishes of the colour chart.
Contact our customer service for minimum quantity, timing and price.

SKIRTING POLISHED TITANIUM ALUMINIUM
thermo packed - bar length 2 lm - pack. 25 Pcs - 50 lm

Article	H mm
PKISPBT 70	70

SKIRTING POLISHED BRUSHED TITANIUM ALUMINIUM
thermo packed - bar length 2 lm - pack. 25 Pcs - 50 lm

Article	H mm
PKISPTS 70	70

UPON REQUEST AVAILABLE IN H 100mm (MINIMUM QUANTITY 200 lm)
Skirtings in polished brushed titanium aluminium match with capsules and joints in varnished PVC with polished titanium aluminium effect (see below).

COLOURS



CORNERS, END CAPS and JOINTS

VARNISHED PLASTIC (finishes anodized silver, polished titanium)

IN/EXTERNAL CORNER - VARNISHED PLASTIC anod. silver - pack. 5 Pcs

Article	H mm
PKIAGE .../5	70/100
PKIAGE .../5	70/100

JOINTS - VARNISHED PLASTIC anod. silver - pack. 10 Pcs

Article	H mm
PKIGIN .../10	70 / 100

END CAPS R / L - VARNISHED PLASTIC ANODIZED silver
pack. 10 Pcs (5 right and 5 left)

Article	H mm
PKITDSAA .../5	70 / 100

IN/EXTERNAL CORNER - VARNISHED PLASTIC polished titanium - pack. 5 Pcs

Article	H mm
PKIAGIBT 70/5	70
PKIAGEBT 70/5	70

JOINTS - VARNISHED PLASTIC polished titanium - pack. 10 Pcs

Article	H mm
PKIGINBT 70/10	70

END CAPS R / L - VARNISHED PLASTIC poli. titanium - pack. 10 Pcs (5 right and 5 left)

Article	H mm
PKITDSBT 70/5	70

Available on demand aluminium prewelded internal and external flush corners. Price to be agreed. Production delay 4/5 weeks.



PKIAGE.. 70 / 100
external corner



PKIAGI.. 70 / 100
internal corner



PKIGIN.. 70 / 100
joint



PKITDS.. 70 / 100/5
end caps




* = Production on demand with minimum quantity of 100 Pcs. Production delay 4/5 weeks. Price to be agreed


PROSKIRTING LIST 40

ANODISED, BRUSHED, VARNISHED ALUMINIUM

PROSKIRTING LIST is a skirting/baseboard profile in different finishes anodized, polished, brushed, varnished aluminium, 40 mm high and 10 mm wide which can be fixed directly to the wall with adhesive (PKLT .. 40A non-inspectable version) or with aluminum supports (inspectable version PKLT .. 40). The aluminum supports, 20 mm long, are fixed with plugs to the wall, every about 50 cm. PROSKIRTING LIST 40 in aluminum is suitable in any indoor environment.



LAYING EXAMPLE



LAYING INSTRUCTIONS

1. Choose "PROSKIRTING LIST" in the desired finish and height. 2. Fix the punched support to the wall with screws every 50 cm. 3. If expected, laying the low-voltage electric cables like web, computer, telephone and satellite TV. 4. Attach the profile to the support applying low pressure.



PROSKIRTING LIST 40 - ANODISED SILVER ALUMINIUM thermo packed - bar length 2 ml - pack. 20 PCS - 40 ml

Article	H mm
PKLTAA 40	40
PKLTAA 40A	40

"A" at the end of the product code = Item with adhesive

PROSKIRTING LIST 40 - VARNISHED ALUMINIUM WHITE thermo packed - bar length 2 ml - pack. 20 PCS - 40 ml

Article	H mm
PKLTA 40-01	40
PKLTA 40-01A	40

"A" at the end of the product code = Item with adhesive

COLOURS

01 - Aluminium varnished white	AA - Anodised silver aluminium	BS - Brushed silver aluminium



PROSKIRTING LIST 40 - BRUSHED SILVER ALUMINIUM thermo packed - bar length 2 ml - pack. 20 PCS - 40 ml

Article	H mm
PKLTBS 40	40
PKLTBS 40A	40

"A" at the end of the product code = Item with adhesive

PUNCHED SUPPORT - Natural aluminium - bar length 2 cm - pack. 10 PCS

Article	H mm
PKGS 37	37

COLOURS ON DEMAND 100 PCS / 200 LM

010 - Varnished aluminium matt white	BT - Polished titanium aluminium	TS - Brushed titanium aluminium
RS - Brushed copper aluminium		

INTERNAL and EXTERNAL CORNERS, END CAPS

ANODISED, BRUSHED AND VARNISHED ALUMINIUM

Internal / external corners
REPFLT... 40



End caps
TPKLT... 40



INTERNAL / EXTERNAL CORNER - ANODISED SILVER ALUMINIUM
pack. 5 PCS

Article	H mm
REPFLTAA 40/5	40

INTERNAL / EXTERNAL CORNER - BRUSHED SILVER ALUMINIUM
pack. 5 PCS

Article	H mm
REPFLTBS 40/5	40

INTERNAL / EXTERNAL CORNER - VARNISHED ALUMINIUM WHITE
pack. 5 PCS

Article	H mm
REPFLTA 40-01/5	40

END CAPS - ALL ANODISED SILVER ALUMINIUM
pack. 4/10 PCS

Article	H mm
TPKLTAA 40/...	40

END CAPS - BRUSHED SILVER ALUMINIUM
pack. 4/10 PCS

Article	H mm
TPKLTBS 40/...	40

END CAPS - VARNISHED ALUMINIUM WHITE
pack. 4/10 PCS

Article	H mm
TPKLTAA 40-01/...	40

Choose the desired packaging.
E.g.: TPKLTA... 40/4 (pack. 4 Pcs)
TPKLTAA... 40/10 (pack. 10 Pcs)



PROSKIRTING LIST is a skirting/baseboard profile in different finishes anodised, polished, brusched, varnished aluminium, 80 mm high and 10 mm wide which can be fixed directly to the wall with adhesive (PKLT .. 80A non-inspectable version) or with aluminum supports (inspectable version PKLT .. 80). The aluminum supports, 20 mm long, are fixed with plugs to the wall, every about 50 cm. PROSKIRTING LIST 80 in aluminum is suitable in any indoor environment.

PROSKIRTING LIST 80

ANODISED, BRUSHED, VARNISHED ALUMINIUM



PROSKIRTING LIST 80 - ANODISED SILVER ALUMINIUM thermo packed - bar lenght 2 ml - pack. 20 PCS - 40 ml

Article	H mm
PKLTAA 80	80
PKLTAA 80A	80


"A" at the end of the product code = Item with adhesive

PROSKIRTING LIST 80 - VARNISHED ALUMINIUM WHITE thermo packed - bar lenght 2 ml - pack. 20 PCS - 40 ml


Article	H mm
PKLTA 80-01	80
PKLTA 80-01A	80

"A" at the end of the product code = Item with adhesive

COLOURS



COLOURS ON DEMAND 100 PCS / 200 LM



PROSKIRTING LIST 80 - BRUSHED SILVER ALUMINIUM thermo packed - bar lenght 2 ml - pack. 20 PCS - 40 ml



Article	H mm
PKLTBS 80	80
PKLTBS 80A	80

"A" at the end of the product code = Item with adhesive

PUNCHED SUPPORT - Natural aluminium - bar lenght 2 cm - pack. 10 PCS

Article	H mm
PKGS 55	55

EXAMPLE FOR THE LAYING



ISTRUZIONI TECNICHE DI POSA

1. Choose "PROSKIRTING LIST" in the desired finish and height. 2. Fix the punched support to the wall with screws every 50 cm. 3. If expected, laying the low-voltage electric cables like web, computer, telephone and satellite TV. 4. Attach the profile to the support applying low pressure.

INTERNAL and EXTERNAL CORNERS, END CAPS

ANODISED, BRUSHED AND VARNISHED ALUMINIUM

INTERNAL / EXTERNAL CORNER - ANODISED SILVER ALUMINIUM pack. 5 PCS

Article	H mm
REPCLTAA 80/5	80

INTERNAL / EXTERNAL CORNER - BRUSHED SILVER ALUMINIUM pack. 5 PCS

Article	H mm
REPCLTBS 80/5	80

INTERNAL / EXTERNAL CORNER - VARNISHED ALUMINIUM WHITE pack. 5 PCS

Article	H mm
REPCLTA 80-01/5	80

END CAPS - ALL. ANODISED SILVER ALUMINIUM pack. 4/10 PCS

Article	H mm
TPKLTA 80/...	80

END CAPS - BRUSHED SILVER ALUMINIUM pack. 4/10 PCS

Article	H mm
TPKLTS 80/...	80

END CAPS - VARNISHED ALUMINIUM WHITE pack. 4/10 PCS

Article	H mm
TPKLTA 80-01/...	80

Choose the desired packaging.
E.g.: TPKLTA... 80/4 (pack. 4 Pcs)
TPKLTA... 80/10 (pack. 10 Pcs)

End caps
TPKLT... 80



Internal / external
corners
REPCLT... 80



* = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed



PROSKIRTING LED is an innovative patented baseboard called "cable duct" in anodized aluminium, with illumination led system incorporated. Conceived and designed to illuminate the passage zone such as corridors and house and office entrances as well. It generates soft and indirect light. Moreover, it solves many other problems such as the laying of the baseboard itself, the passage of the electric cables, the ones for PC, telephone and other plants as well. **PROSKIRTING LED** has been designed with double function and utility: 1- **PROSKIRTING LED** complete PKLEDAA 80 is an inspectional joint baseboard composed of PKGS 66 support for fixing it with screws on the wall and the **PROSKIRTING LED** PKLEDAA 80 at sight profile. 2- **PROSKIRTING LED** PKLEDAA 80 is a at sight baseboard profile to be fixed directly with silicone/ adhesive. It is not an inspectional one like **PROSKIRTING LED** complete, and is available also in auto adhesive version (PKLEDAA 80A).

PROSKIRTING LED

ANODIZED SILVER ALUMINIUM WITH LED AND POWER SUPPLY BOX



SKIRTING BOARD IN ANOD. SILVER ALU. WITHOUT ADHESIVE. ADAPTOR LED, LED & FLAT NOT INCLUDED (indicate the article) thermo packed - bar length 2 lm - pack. 10 Pcs - 20 lm

Article	H mm
PKLEDAA 80	80

SKIRTING BOARD IN ANOD. SILVER ALUM. WITH ADHESIVE, ADAPTOR LED, LED & FLAT NOT INCLUDED (indicate the article) thermo packed - bar length 2 lm - pack. 10 Pcs - 20 lm

Article	H mm
PKLEDAA 80A	80

Please, specify in your order the code of the FLAT you choose : matt or gloss. Eg.: PKLEDAA 80 + PKGPAL



POLYCARBONATE FLAT - bar length 2 lm


Article
PKGPAL
PKGPIAO

ADHESIVE FLEXIBLE LED COIL

length 5 lm - pack. 1 ROLL

Article
LEDN
LEDF
LEDC

"N" at the end of the product code = neutral light
 "F" at the end of the product code = cold light
 "C" at the end of the product code = hot light



POWER SUPPLY BOX
 SOCKET with FASTENING BASIS

Article
SPA 1820

LED POWER SUPPLY 75W - 12V

Article
ALL 7512



CABLE RACEWAY/ SUPPORT- COEXTRUDED PVC
 bar length 2 lm - pack. 20 Pcs - 40 lm

Article	H mm
CSPPK 80	70

PUNCHED SUPPORT - NATURAL ALUMINIUM
 support length 2 cm - pack. 10 Pcs

Article	H mm
PKGS 66	66


ARTICLES NOT FOR SALE SINGLY



COLOURS



On demand may be realised in other finishes of the colour chart. Contact our customer service for minimum quantity, timing and price.



SWITCH BOX
 with BOX BASIS

Article
SI 1410


JUNCTION BOX
 with FASTENING BASIS

Article
SD 1210


VERTICAL CABLE DUCT PROFILE
 bar length 2,7 lm

Article
PSPV

It matches with CSPPK 80.



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Fix the support on the wall putting the screws and plugs every 50 cm (recommended). Make a test with "PROSKIRTING LED" in order to value the height and the correct position of supports.
2. Fix in the chosen spaces the socket/ power supply box basis, switch box basis and, eventually, the junction box.
3. Connect 220V supply to power/ transformer unit, and afterwards, connect the "PROSKIRTING LED" bar next to power unit.
4. Connect the pre-applied led bars inside the "PROSKIRTING LED" with the supplied cables/ wires in continuous way.
5. The power supply unit guarantees about 15 lm of led illumination, beyond that distance it is necessary to add another power supply box/socket.

When fixing without support, clean the surface carefully so that it's dry and with no grass trace, apply the silicone on the knurled sides of the profile and lay down correctly, pressing uniformly and with no hammering. For the application of "PROSKIRTING LED" with adhesive, we recommend the temperature not below 15°.

CORNERS, END CAPS and JOINTS

VARNISHED PLASTIC SILVER FINISH




PKAGI 80 internal corner



PKAGI 80 external corner



PKGIN 80 joint



PKTDSAA 80/5 end caps

IN/EXTERNAL CORNER - VARNISHED PLASTIC (SILVER FIN.)
 pack. 5 Pcs

Article	H x L mm
PKAGI 80/5	80 X 40
PKAGE 80/5	80 X 40

JOINTS - VARNISHED PLASTIC (SILVER FIN.) - pack. 10 Pcs

Article	H mm
PKGIN 80/10	80

END CAPS R / L - VARNISHED PLASTIC (SILVER FIN.)
 pack. 10 Pcs (5 right and 5 left)

Article	H mm
PKTDSAA 80/5	80



* = Production on demand with minimum quantity of 100 Pcs. Production delay 4/5 weeks. Price to be agreed



PROSKIRTING GILED is an innovative profile in silver anodized aluminum and polished chrome, with 80 and 100 mm height, with a rigid vinyl resin TOP PROFILE, with a 17,5mm exposed surface, available in 9 different marmorised finishes, provided with an integrated LED lighting system generating a soft and indirect light. **PROSKIRTING GILED** can be used instead of the classic skirting board or rotated 180 degrees and installed along the ceiling edges, allowing to cover up to 15mm wide joints. The reflection of the LED light by the aluminum surface of the profile creates a modern atmosphere. **PROSKIRTING GILED** is equipped with all the trim pieces available such as inside and outside corner, joints, end caps and power supply box. *Conceived and designed by the designer Gilberto Toneguzzi.*

PROSKIRTING GILED

ANODIZED ALUMINIUM
POLISHED ALUMINIUM



SKIRTING H 80 mm IN ANOD. SILVER, POLI. CHROME ALUM.
TOP PROFILE NOT INCLUDED (indicate the article)
thermo packed - bar length 2 lm - pack. 20 Pcs - 40 lm

Article	H mm		
PKGLEDAA 80	80		
PKGLEDBC 80	80		
PKGLEDAA 80A	80		
PKGLEDBC 80A	80		
PKGLEDAA 80F	80		
PKGLEDBC 80F	80		

"F" at the end of the product code = Punched Item

USE PROBAND FIX FOR FIXING THE PROFILE TO THE WALL




TOP PROFILE IN PVC - bar length 2 lm

Article	
TOPPKGL...	

In the order specify the chosen colour of the TOP PROFILE.
E.g. TOPPKGL... (colour gold) TOPPKGLMBO.


Specify the chosen colour of the PVC TOP PROFILE (see below).

PVC TOP PROFILE COLOURS



On demand may be realised in other finishes of the colour chart. Contact our customer service for minimum quantity, timing and price.

SKIRTING COLOURS



SKIRTING H 100 mm IN ANOD. SILVER, POLI. CHROME ALUM.
TOP PROFILE NOT INCLUDED (indicate the article)
thermo packed - bar length 2 lm - pack. 20 Pcs - 40 lm

Article	H mm		
PKGLEDAA 100	100		
PKGLEDBC 100	100		
PKGLEDAA 100A	100		
PKGLEDBC 100A	100		
PKGLEDAA 100F	100		
PKGLEDBC 100F	100		

"A" at the end of the product code = Item with adhesive
"F" at the end of the product code = Punched Item

ADHESIVE FLEXIBLE LED COIL

length 5 lm - pack. 1 ROLL

Article			
LEDN			
LEDF			
LEDC			


"N" at the end of the product code = neutral light
"F" at the end of the product code = cold light
"C" at the end of the product code = hot light

LED ADAPTOR AC/DC 75W - 12V (15 lm)
LED ADAPTOR AC/DC 25W - 12V (5 lm)

Article	
ALL 7512	
ALL 2512	

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS

1. Choose "PROSKIRTING GILED" depending on the desired finish and fixing system; 2. If you are installing the version with adhesive: clean the surface on which the profile is to be laid, ensuring that it is dry. Remove the protective film and place the profile, applying adequate pressure on it. If you are installing the punched version, drill the surface on which the profile is to be laid using a drill with 5mm diameter and insert the 5x 25mm screws. Screw the profile; 3. Connect the 12/24 V adaptor; 4. Fix the LED light to the inclined side of the aluminum profile or to the vinyl resin support and install electrical wiring; 5. Apply the rigid vinyl resin insert to the aluminum profile.



CORNERS, END CAPS and JOINTS

VARNISHED PLASTIC

FLUSH CORNERS - varnished plastic

IN/EXTERNAL CORNER - FLUSH CORNERS

VARNISHED PLASTIC ANOD. SILVER, POLI. CHROME - pack. 5 Pcs

Article	H x L mm		
REPKGLEDAA 80/5	80 x 10		
RIPKGLEDAA 80/5	80 x 10		
REPKGLEDBC 80/5	80 x 10		*
RIPKGLEDBC 80/5	80 x 10		*

FLUSH JOINT - VARNISHED PLASTIC ANOD. SILVER, POLI. CHROME
pack. 5 Pcs

Article	H mm		
GIPKGLEDAA 80/5	80		
GIPKGLEDBC 80/5	80		*

FLUSH END CAPS R / L - VARNISHED PLASTIC ANOD. SILVER, POLI. CHROME - pack. 6 Pcs (3 right and 3 left)

Article	H mm		
TPKGLEDAA 80/3	80		
TPKGLEDBC 80/3	80		*

FLUSH CORNERS - varnished plastic

IN/EXTERNAL CORNER - FLUSH CORNERS

VARNISHED PLASTIC ANOD. SILVER, POLI. CHROME - pack. 5 Pcs

Article	H x L mm		
REPKGLEDAA 100/5	100 x 10		
RIPKGLEDAA 100/5	100 x 10		
REPKGLEDBC 100/5	100 x 10		*
RIPKGLEDBC 100/5	100 x 10		*

FLUSH JOINT - VARNISHED PLASTIC ANOD. SILVER, POLI. CHROME
pack. 5 Pcs

Article	H mm		
GIPKGLEDAA 100/5	100		
GIPKGLEDBC 100/5	100		*

FLUSH END CAPS R / L - VARNISHED PLASTIC ANOD. SILVER, POLI. CHROME - pack. 6 Pcs (3 right and 3 left)

Article	H mm		
TPKGLEDAA 100/3	100		
TPKGLEDBC 100/3	100		*

INTERNAL CORNER
RIPKGLED... 80/100



JOINT
GIPKGLED... 80/100



EXTERNAL CORNER
REPKGLED... 80/100



END CAPS
TPKGLED... 80/100




* = Production on demand with minimum quantity of 100 Pcs. Production delay 4/5 weeks. Price to be agreed

PROSKIRTING

ANODIZED SILVER ALUMINIUM

PROSKIRTING is an innovative patented "cable channel" skirting in anodized aluminium. Studied and designed to resolve various problems related to the installation of skirting and to the laying of electrical, computer and telephone cables and other service systems. **PROSKIRTING** has been designed to offer a dual function: 1- **PROSKIRTING** complete PKAA 80 is a snap-on inspectable skirting consisting of a support PKGS 66 to be screwed to the wall and the visible profile **PROSKIRTING** PKAA 80. 2- **PROSKIRTING** PKAA 80 is the visible skirting profile to be fixed directly with silicone/adhesive. It is not inspectable like **PROSKIRTING** complete; it is also available in a self-adhesive version (PKAA 80A).



ONLY SKIRTING (for sale singly) - ANODIZED SILVER ALUMINIUM thermo packed - bar length 2 lm - pack. 10 Pcs - 20 lm

Article	H mm
PKAA 80	80
PKAA 80A	80

"A" at the end of the product code = Item with adhesive

USE PROBAND FIX FOR FIXING THE PROFILE TO THE WALL



- Advantages:** profile to be glued. Aesthetically superior thanks to the HI-TECH design with rounded shell-shape top and bottom edges that are easy to clean. PROSKIRTING is made in anodized aluminium with silver finish; the anodizing layer is approx. 15/20 micron. Recommended for indoor and outdoor use thanks to its good anti-oxidation properties.
- Single visible skirting profile, which may be inspectable or fixed.
 - Minimum stock investment with just 2 products for three functions.
 - Easy to install and clean.
 - Patented innovative HI-TECH design.
 - Inside-outside corners-end caps and joints varnished in the same finish as the profile.
 - The PROSKIRTING profile is antistatic and stops electromagnetic and electrostatic discharge.




CABLE RACEWAY/ SUPPORT- COEXTRUDED PVC bar length 2 lm - pack. 20 Pcs - 40 lm

Article	H mm
CSPPK 80	80


PUNCHED SUPPORT - NATURAL ALUMINIUM support length 2 cm - pack. 10 Pcs

Article	H mm
PKGS 66	66


ARTICLES NOT FOR SALE SINGLY



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the system with or without support
 2. Fix the support to the wall with screws and screw anchors at 50 cm intervals (recommended)
 3. When laying without support, thoroughly clean the surface ensuring that it is grease-free and dry, apply the silicone on the knurled sides of the profiles and lay correctly by applying pressure evenly over the whole profile without using a hammer.
 4. For the "PROSKIRTING" with adhesive, application is recommended at a temperature of at least 15°.
- Always use the inside/outside corner linking elements and end caps for impeccable, faultless laying.




POWER SUPPLY BOX
SOCKET with FASTENING BASIS

Article	H mm
SPA 1820	1820

SWITCH BOX
with BOX BASIS

Article	H mm
SI 1410	1410



JUNCTION BOX
with FASTENING BASIS


Article	H mm
SD 1210	1210

VERTICAL CABLE DUCT PROFILE
bar length 2,7 lm

Article	H mm
PSPV	1410

It matches with CSPPK 80

COLOURS



CORNERS, END CAPS and JOINTS

VARNISHED PLASTIC SILVER FINISH.



PKAGI 80
internal corner



PKAGE 80
external corner



PKGIN 80
JOINT



PKTDSAA 80/5
end caps

IN/EXTERNAL CORNER - VARNISHED PLASTIC (silver finish.)
pack. 5 Pcs

Article	H x L mm
PKAGI 80/5	80 x 40
PKAGE 80/5	80 x 40

JOINTS - VARNISHED PLASTIC (silver finish.) - pack. 10 Pcs

Article	H mm
PKGIN 80/10	80

END CAPS R / L - VARNISHED PLASTIC (silver finish.)

pack. 10 Pcs (5 right and 5 left)

Article	H mm
PKTDSAA 80/5	80



PROSKIRTING 40 is an anodized silver aluminium skirting profile, with a height of 40 mm. It can be fixed directly to the wall with adhesive (non-inspectionable adhesive version PKAA 40A) or to a support (inspectionable version PKAA 40) in punched aluminium, pieces 20 mm long to be fixed to the wall with screws, every about 50 cm.

PROSKIRTING 40

ANODIZED SILVER ALUMINIUM



SKIRTING - SILVER ANODIZED ALUMINIUM thermo packed
bar length 2 lm - pack. 20 Pcs - 40 lm

Article	H mm
PKAA 40	40
PKAA 40A	40

"A" at the end of the product code = Item with adhesive
PUNCHED SUPPORT - NATURAL ALUMINIUM


support length 2 cm - pack. 10 Pcs

Article	H mm	It matches with PKAA 40
PKGS 37	37	

COLOURS



AA - Anodized silver alum.



CORNERS, END CAPS and JOINTS

VARNISHED PLASTIC (SILVER FINISH)

IN/EXTERNAL CORNERS - VARNISHED PLASTIC (silver finish.)
pack. 5 Pcs

Article	H mm
PKAGI 40/5	40
PKAGE 40/5	40

JOINTS - VARNISHED PLASTIC (silver finish.) - pack. 10 Pcs

Article	H mm
PKGIN 40/10	40

END CAPS R / L - VARNISHED PLASTIC (silver finish.) - pack. 10 Pcs (5 right and 5 left)

Article	H mm
PKTDSAA 40/5	40



PROSKIRTING SHELL is an innovative aluminum skirting board, with 70mm height, in silver anodized finish. The skirting board can be fixed to the wall with silicone or screwed to 20mm long aluminum punched flanges, that have to be fastened to the wall at 50cm distance from each other. It allows to cover up to 25mm high perimeter edges. Moreover the version with punched flanges allows the housing of low tension electrical cables, such as internet, phone, TV and satellite cables and can be easily inspected. The optional completing pieces, such as inside/ outside corners, linking elements and end caps make **PROSKIRTING SHELL** easy to install and guarantee a practical and elegant end result.

PROSKIRTING SHELL

ANODIZED SILVER ALUMINIUM



SKIRTING - ANODIZED SILVER ALUMINIUM thermo packed
bar length 2 lm - pack. 25 Pcs - 50 lm


Article	H mm
PKSHAA 70	70
PKSHAA 70A	70

"A" at the end of the product code = Item with adhesive

USE PROBAND FIX FOR FIXING THE PROFILE TO THE WALL



COLOURS




AA - Anodized silver alum.



PUNCHED SUPPORT - NATURAL ALUMINIUM
support length 2 cm - pack. 10 Pcs


Article	H mm
PKGS 55	55

ARTICLES NOT FOR SALE SINGLY



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS

1. Choose the right version of "PROSKIRTING SHELL" depending on the desired fixing solution; 2. If you want to build low tension electrical cables (e.g. internet, phone, TV and satellite cables) into the profile, fasten the punched flanges to the wall using dowels at 50cm distance from each other; 3. Install electrical wiring and fasten "PROSKIRTING SHELL" to the flanges; 4. If you are installing the version with adhesive, first clean and the surface where the profile will be installed, then apply the silicone once the surface is dry. Remove the protective film and lay the profile, applying adequate pressure on it.



CORNERS, END CAPS and JOINTS

VARNISHED PLASTIC (SILVER FINISH)

EDGE COVER CORNERS

IN/EXTERNAL CORNER - EDGE COVER
VARNISHED PLASTIC (silver finish.) - pack. 5 Pcs

Article	H x L mm
RIPKSHAA 70/5	70 x 20
REPKSHAA 70/5	70 x 20

JOINT - EDGE COVER - VARNISHED PLASTIC (silver finish.)
pack. 5 Pcs

Article	H mm
GIPKSHAA 70/5	70

END CAPS R / L - EDGE COVER
VARNISHED PLASTIC (silver finish.) - pack. 6 Pcs (3 right and 3 left)

Article	H mm
TPKSHAA 70/3	70

EXTERNAL CORNER REPKSHAA 70 INTERNAL CORNER RIPKSHAA 70 JOINT GIPKSHAA 70 END CAPS TPKSHAA 70








SKIRTING 40

POLISHED AND BRUSHED
STAINLESS STEEL AISI 304/1.4301-V2A

SKIRTING 40 made in stainless steel AISI 304/1.4301-V2A in height 40 mm. Available with or without adhesive. Superior aesthetic quality, extremely strong and easy to lay, it is ideal for all public and private environments that require high standards of hygiene and image. Used increasingly more often in contrast combinations with wood, carpeted floors, etc. for an unmistakable hi-tech effect. In order to facilitate and to perfect the laying process, internal and external angles, plugs and junctions are recommended.



POLISHED STAINLESS STEEL AISI 304/1.4301-V2A
with protective film - bar length 2 lm - pack. 25 Pcs - 50 lm

Article	H mm		
BTAC 40A	40		
BTAC 40	40		

"A" at the end of the product code = Item with adhesive



BRUSHED STAINLESS STEEL AISI 304/1.4301-V2A
with protective film - bar length 2 lm - pack. 25 Pcs - 50 lm

Article	H mm		
BTACS 40A	40		
BTACS 40	40		

"A" at the end of the product code = Item with adhesive

EXAMPLES OF LAYING



SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS

LAYING INSTRUCTIONS

1. Choose the "SKIRTING 40" also choose with or without adhesive.
2. Cut the profile to the required length, taking care to calculate the width of the inside-outside corner joints. 3. For the self-adhesive version, the surface must be smooth, grease-free and not porous. It is not recommended for plaster and mortar surfaces (version without adhesive is better, using fast-setting acrylic silicone which is suitable for fixing aluminium to mortar - plaster, etc.). 4. Use the corner linking elements-joints and right and left end caps to facilitate laying.

COLOURS



USE PROBAND FIX FOR FIXING THE PROFILE TO THE WALL



CORNERS, END CAPS AND JOINTS

STEEL and VARNISHED METAL

EDGE COVER VARNISHED METAL



RIZCT... 40/...
Internal corner



REZCT... 40/...
external corner




GIZCT... 40/...
joint



TPZCT... 40/...
end caps

PRE-WELDED



RI... 40/...
internal corner



RE... 40/...
external corner

VARNISHED METAL - EDGE COVER CORNERS - articles not for sale singly

INTERNAL/EXTERNAL CORNER - EDGE COVER VARNISHED METAL POLISHED STEEL EFFECT

Article	HxL mm	pack. 2Pcs	pack. 5Pcs
RIZCTAC 40/...	40 x 20		
REZCTAC 40/...	40 x 20		

JOINT - EDGE COVER

VARNISHED METAL POLISHED STEEL EFFECT

Article	HxL mm	pack. 2Pcs	pack. 5Pcs
GIZCTAC 40/...	40		

Choose the desired packaging.

E.g.: RIZCTAC 40/2 (pack. 2 Pcs) - RIZCTAC 40/5 (pack. 5 Pcs)

END CAPS R / L - EDGE COVER - VARNISHED METAL POLISHED STEEL EFFECT - pack. 4Pcs (2 R + 2 L) / 10Pcs (5 R + 5 L)

Article	H mm	pack. 4Pcs	pack. 10Pcs
TPZCTAC 40/...	40		

Choose the desired packaging.

E.g.: TPCCTAC 40/2 (pack. 4 Pcs: 2 right + 2 left)
TPCCTAC 40/5 (pack. 10 Pcs: 5 right + 5 left)

INTERNAL/EXTERNAL CORNER - EDGE COVER VARNISHED METAL BRUSHED STAINLESS ST. EFFECT

Article	HxL mm	pack. 2Pcs	pack. 5Pcs
RIZCTACS 40/...	40 x 20		
REZCTACS 40/...	40 x 20		

JOINT - EDGE COVER

VARNISHED METAL BRUSHED STAINLESS ST. EFFECT

Article	H mm	pack. 2Pcs	pack. 5Pcs
GIZCTACS 40/...	40		

Choose the desired packaging.

E.g.: RIZCTACS 40/2 (pack. 2 Pcs) - RIZCTACS 40/5 (pack. 5 Pcs)

END CAPS R / L - EDGE COVER - VARNISHED METAL BRUSHED STAINLESS ST. EFFECT - pack. 4Pcs (2 R + 2 L) / 10Pcs (5 R + 5 L)

Article	H mm	pack. 4Pcs	pack. 10Pcs
TPZCTACS 40/...	40		

Choose the desired packaging.

E.g.: TPCCTACS 40/2 (pack. 4 Pcs: 2 right + 2 left)
TPCCTACS 40/5 (pack. 10 Pcs: 5 right + 5 left)

STEEL AISI 304/1.4301-V2A - FLUSH CORNERS - articles not for sale singly

INTERNAL/EXTERNAL CORNER FLUSH PRE-WELDED - POLISHED STEEL EFFECT

Article	HxL mm	pack. 2Pcs	pack. 5Pcs
RIAC 40/...	40 x 50		
REAC 40/...	40 x 50		

Choose the desired packaging.

E.g.: RIAC 40/2 (pack. 2 Pcs) - RIAC 40/5 (pack. 5 Pcs)

INTERNAL/EXTERNAL CORNER FLUSH PRE-WELDED - BRUSHED STAINLESS STEEL

Article	HxL mm	pack. 2Pcs	pack. 5Pcs
RIACS 40/...	40 x 50		
REACS 40/...	40 x 50		


Choose the desired packaging.

E.g.: RIACS 40/2 (pack. 2 Pcs) - RIACS 40/5 (pack. 5 Pcs)

SKIRTING 40 made in anodized, polished and brushed aluminium in height 40 mm. Available with or without adhesive. Superior aesthetic quality and easy to lay, it is ideal for all public and private environments. Can be used with all types of flooring. In order to facilitate and to perfect the laying process, internal and external angles, plugs and junctions are recommended. Please contact the technical department for informations concerning the skirting bending radius.

SKIRTING 40

ANODIZED, POLISHED, VARNISHED and BRUSHED ALUMINIUM



ANODIZED SILVER ALUMINIUM thermo packed
bar length 2 lm - pack. 40 Pcs - 80 lm

Article	H mm		
BTAA 40A	40		
BTAA 40	40		

"A" at the end of the product code = Item with adhesive

POLISHED TITANIUM ALUMINIUM thermo packed
bar length 2 lm - pack. 40 Pcs - 80 lm

Article	H mm		
BTBT 40A	40		
BTBT 40	40		

"A" at the end of the product code = Item with adhesive

VARNISHED SEMIGLOSSY AND MATT WHITE ALUMINIUM thermo packed - bar length 2 lm - pack. 40 Pcs - 80 lm

Article	H mm		
BTA 40-01A	40		
BTA 40-01	40		
BTA 40-01OA	40		
BTA 40-01O	40		

"A" at the end of the product code = Item with adhesive

BRUSHED ALUMINIUM (silver-copper-titanium) thermo packed - bar length 2 lm - pack. 40 Pcs - 80 lm

Article	H mm		
BTBS 40A	40		
BTBS 40	40		
BTRS 40A	40		
BTRS 40	40		
BTTS 40A	40		
BTTS 40	40		


"A" at the end of the product code = Item with adhesive

STONE LINE ALUMINIUM thermo packed - bar length 2 lm - pack. 40 Pcs - 80 lm

Article	H mm		
BTA 40-SL01A	40		
BTA 40-SL01	40		
BTA 40-SL08A	40		
BTA 40-SL08	40		
BTA 40-SL12A	40		
BTA 40-SL12	40		

"A" at the end of the product code = Item with adhesive

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the "SKIRTING 40" also choose with or without adhesive.
2. Cut the profile to the required length, taking care to calculate the width of the inside-outside corner joints.
3. For the self-adhesive version, the surface must be smooth, grease-free and not porous. It is not recommended for plaster and mortar surfaces (version without adhesive is better, using fast-setting acrylic silicone which is suitable for fixing aluminium to mortar - plaster, etc.).
4. Use the corner linking elements-joints and right and left end caps to facilitate laying.

(There aren't combinations for the finish alu. RS)

On demand may be realised in other finishes of the colour chart. Contact our customer service for minimum quantity, timing and price.

USE PROBAND FIX FOR FIXING THE PROFILE TO THE WALL



COLOURS

ANODIZED		POLISHED		BRUSHED		
					ON DEMAND	
AA - Anodized silver alum.	BT - Polished titanium alum.	BS - Brushed silver alum.	RS - Brushed copper alum.	TS - Brushed titanium alum.		
SEMIGLOSSY		MATT		STONE LINE		
					ON DEMAND	
01 - White varnished alum. (9016)	01O - White varnished alum. (9016)	SL01 - Stone white	SL08 - Stone antradarck	SL12 - Stone black		

CORNERS, END CAPS AND JOINTS

VARNISHED METAL and VARNISHED PLASTIC

* Corners, end caps and joints of the on demand profiles are also on demand

INTERNAL/EXTERNAL CORNER - EDGE COVER - VARNISHED METAL, ANODIZED, POLISHED STONE LINE - H 40 MM - L 20 MM

Article	pack. 2Pcs	pack. 5Pcs
RIZCTAA 40/...		
REZCTAA 40/...		
RIZCTBT/BS/TS/RS 40/...		
REZCTBT/BS/TS/RS 40/...		
RIZCT01/01O 40/...		
REZCT01/01O 40/...		
RIZCTA 40-SL.../...		
REZCTA 40-SL.../...		

Choose the desired packaging.
E.g.: RIZCTAA 40/2 (pack. 2 Pcs) - RIZCTAA 40/5 (pack. 5Pcs)

JOINT - EDGE COVER VARNISHED METAL ANODIZED, POLISHED, STONE LINE

Article	H mm		
GIZCTAA 40/...	40		
GIZCTBT/BS/TS/RS 40/...	40		
GIZCT01/01O 40/...	40		
GIZCTA 40-SL.../...	40		

END CAPS R / L - EDGE COVER - VARNISHED METAL ANODIZED, POLISHED, STONE LINE - pack. 4Pcs (2 R + 2 L) / 10Pcs (5 R + 5 L)

Article	H mm		
TPZCTAA 40/...	40		
TPZCTBT/BS/TS/RS 40/...	40		
TPZCT01/01O 40/...	40		
TPZCTA 40-SL.../...	40		

INTERNAL/EXTERNAL CORNER - EDGE COVER VARNISHED PLASTIC ANODIZED SILVER, POLISHED AND TITANIUM

Article	HxL mm	pack. 2Pcs	pack. 5Pcs
RICTAA 40/...	40 x 20		
RECTAA 40/...	40 x 20		
RICTBT 40/...	40 x 20		
RECTBT 40/...	40 x 20		

Choose the desired packaging.
E.g.: RICTAA 40/2 (pack. 2 Pcs) - RICTAA 40/5 (pack. 5 Pcs)

Available on demand aluminium prewelded internal and external flush corners. Finishing: 01 - 01O - AA - BT - BS - RS - TS. Price to be agreed. Production delay 4/5 weeks.

JOINT - EDGE COVER VARNISHED PLASTIC ANODIZED SILVER, POLISHED AND TITANIUM

Article	H mm		
GICTAA 40/...	40		
GICTBT 40/...	40		

END CAPS R / L - EDGE COVER - VARNISHED PLASTIC ANODIZED SILVER, POLISHED AND TITANIUM - pack. 4Pcs (2 R + 2 L) / 10Pcs (5 R + 5 L)

Article	H mm		
TPCTAA 40/...	40		
TPCTBT 40/...	40		

Choose the desired packaging.
E.g.: TPCTAA 40/2 (pack. 4 Pcs: 2 right + 2 left)



** = Production on demand with minimum quantity of 80 Pcs. Production delay 4/5 weeks. Price to be agreed

* = Production on demand with minimum quantity of 100 Pcs. Production delay 4/5 weeks. Price to be agreed


News 2023

SKIRTING 60


POLISHED and Brushed
STAINLESS STEEL AISI 304/1.4301-V2A

SKIRTING 60 made in stainless steel AISI 304/1.4301-V2A in height 60 mm. Available with or without adhesive. Superior aesthetic quality, extremely strong and easy to lay, it is ideal for all public and private environments that require high standards of hygiene and image. Used increasingly more often in contrast combinations with wood, carpeted floors, etc. for an unmistakable hi-tech effect. In order to facilitate and to perfect the laying process, internal and external angles, plugs and junctions are recommended.

BTAC/S 60/60A



EXAMPLES OF LAYING



POLISHED STAINLESS STEEL AISI 304/1.4301-V2
with protective film - bar length 2 lm - pack. 25 Pcs - 50 lm

Article	H mm		
BTAC 60A	60		
BTAC 60	60		

"A" at the end of the product code = Item with adhesive



Brushed STAINLESS STEEL AISI 304/1.4301-V2A
with protective film - bar length 2 lm - pack. 25 Pcs - 50 lm

Article	H mm		
BTACS 60A	60		
BTACS 60	60		

"A" at the end of the product code = Item with adhesive

SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS

LAYING INSTRUCTIONS

1. Choose the "SKIRTING 60" also choose with or without adhesive. 2. Cut the profile to the required length, taking care to calculate the width of the inside-outside corner joints. 3. For the self-adhesive version, the surface must be smooth, grease-free and not porous. It is not recommended for plaster and mortar surfaces (version without adhesive is better, using fast-setting acrylic silicone which is suitable for fixing aluminium to mortar - plaster, etc.). 4. Use the corner linking elements-joints and right and left end caps to facilitate laying.

COLOURS



USE PROBAND FIX FOR FIXING THE PROFILE TO THE WALL



CORNERS, END CAPS AND JOINTS

STEEL and VARNISHED METAL

EDGE COVER VARNISHED METAL



RIZCT... 60/...
internal corner



REZCT... 60/...
external corner



GIZCT... 60/...
joint




TPZCT... 60/...
end caps

PRE-WELDED



RI... 60/...
internal corner



RE... 60/...
external corner

VARNISHED METAL - EDGE COVER CORNERS - articles not for sale singly

INTERNAL/EXTERNAL CORNER - EDGE COVER VARNISHED METAL POLISHED STEEL EFFECT

Article	HxL mm	pack. 2Pcs	pack. 5Pcs
RIZCTAC 60/...	60 x 20		
REZCTAC 60/...	60 x 20		

JOINT - EDGE COVER VARNISHED METAL POLISHED STEEL EFFECT

Article	H mm	pack. 2Pcs	pack. 5Pcs
GIZCTAC 60/...	60		

Choose the desired packaging.

E.g.: RIZCTAC 60/2 (pack. 2 Pcs) - RIZCTAC 60/5 (pack. 5 Pcs)

END CAPS R / L - EDGE COVER - VARNISHED METAL POLISHED STEEL EFFECT - pack. 4Pcs (2 R + 2 L) / 10Pcs (5 R + 5 L)

Article	H mm	pack. 4Pcs	pack. 10Pcs
TPZCTAC 60/...	60		

Choose the desired packaging.

E.g.: TPCCTAC 60/2 (pack. 4 Pcs: 2 right + 2 left)
TPCCTAC 60/5 (pack. 10 Pcs: 5 right + 5 left)

INTERNAL/EXTERNAL CORNER - EDGE COVER VARNISHED METAL BRUSHED STAINLESS ST. EFFECT

Article	HxL mm	pack. 2Pcs	pack. 5Pcs
RIZCTACS 60/...	60 x 20		
REZCTACS 60/...	60 x 20		

JOINT - EDGE COVER VARNISHED METAL BRUSHED STAINLESS ST. EFFECT

Article	H mm	pack. 2Pcs	pack. 5Pcs
GIZCTACS 60/...	60		

Choose the desired packaging.

E.g.: RIZCTACS 60/2 (pack. 2 Pcs) - RIZCTACS 60/5 (pack. 5 Pcs)

END CAPS R / L - EDGE COVER - VARNISHED METAL BRUSHED STAINLESS ST. EFFECT - pack. 4Pcs (2 R + 2 L) / 10Pcs (5 R + 5 L)

Article	H mm	pack. 4Pcs	pack. 10Pcs
TPZCTACS 60/...	60		

Choose the desired packaging.

E.g.: TPCCTACS 60/2 (pack. 4 Pcs: 2 right + 2 left)
TPCCTACS 60/5 (pack. 10 Pcs: 5 right + 5 left)

STEEL AISI 304/1.4301-V2A - FLUSH CORNERS - articles not for sale singly

INTERNAL/EXTERNAL CORNER FLUSH PRE-WELDED - POLISHED STEEL EFFECT

Article	HxL mm	pack. 2Pcs	pack. 5Pcs
RIAC 60/...	60 x 50		
REAC 60/...	60 x 50		

Choose the desired packaging.

E.g.: RIAC 60/2 (pack. 2 Pcs) - RIAC 60/5 (pack. 5 Pcs)

INTERNAL/EXTERNAL CORNER FLUSH PRE-WELDED - BRUSHED STAINLESS STEEL

Article	HxL mm	pack. 2Pcs	pack. 5Pcs
RIACS 60/...	60 x 50		
REACS 60/...	60 x 50		

Choose the desired packaging.

E.g.: RIACS 60/2 (pack. 2 Pcs) - RIACS 60/5 (pack. 5 Pcs)

SKIRTING 60 made in anodized, polished and brushed aluminium in height 60 mm. Available with or without adhesive. Superior aesthetic quality and easy to lay, it is ideal for all public and private environments. Can be used with all types of flooring. In order to facilitate and to perfect the laying process, internal and external angles, plugs and junctions are recommended. Please contact the technical department for informations concerning the skirting bending radius.

SKIRTING 60

ANODIZED, POLISHED, VARNISHED and BRUSHED ALUMINIUM



ANODIZED SILVER ALUMINIUM thermo packed
bar length 2 lm - pack. 40 Pcs - 80 lm

Article	H mm
BTAA 60A	60
BTAA 60	60

*"A" at the end of the product code = Item with adhesive

POLISHED TITANIUM ALUMINIUM thermo packed
bar length 2 lm - pack. 40 Pcs - 80 lm

Article	H mm
BTBT 60A	60
BTBT 60	60

*"A" at the end of the product code = Item with adhesive

VARNISHED SEMIGLOSSY AND MATT WHITE ALUMINIUM thermo packed - bar length 2 lm - pack. 40 Pcs - 80 lm

Article	H mm
BTA 60-01A	60
BTA 60-01	60
BTA 60-01OA	60
BTA 60-01O	60

*"A" at the end of the product code = Item with adhesive



BRUSHED ALUMINIUM (silver-copper-titanium) thermo packed - bar length 2 lm - pack. 40 Pcs - 80 lm

Article	H mm
BTBS 60A	60
BTBS 60	60
BTRS 60A	60
BTRS 60	60
BTTS 60A	60
BTTS 60	60


*"A" at the end of the product code = Item with adhesive

STONE LINE ALUMINIUM thermo packed - bar length 2 lm - pack. 40 Pcs - 80 lm

Article	H mm
BTA 60-SL01A	60
BTA 60-SL01	60
BTA 60-SL08A	60
BTA 60-SL08	60
BTA 60-SL12A	60
BTA 60-SL12	60

*"A" at the end of the product code = Item with adhesive

BT... 60/60A



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



USE PROBAND FIX FOR FIXING THE PROFILE TO THE WALL

COLOURS

ANODIZED	POLISHED	BRUSHED		SEMIGLOSSY	MATT	STONE LINE			
					On demand	On demand	On demand	On demand	
AA - Anodized silver alum.	BT - Polished titanium alum.	BS - Brushed silver alum.	RS - Brushed copper alum.	TS - Brushed titanium alum.	01 - White varnished alum. (9016)	010 - White varnished alum. (9016)	SL01 - Stone white	SL08 - Stone antradrak	SL12 - Stone black

CORNERS, END CAPS AND JOINTS

VARNISHED METAL and VARNISHED PLASTIC

* Corners, end caps and joints of the on demand profiles are also on demand

INTERNAL/EXTERNAL CORNER - EDGE COVER - VARNISHED METAL ANODIZED, POLISHED, STONE LINE - H 60 X L 20

Article
RIZCTAA 60/...
REZCTAA 60/...
RIZCTBT/BS/TS/RS 60/...
REZCTBT/BS/TS/RS 60/...
RIZCT01/010 60/...
REZCT01/010 60/...
RIZCTA 60-SL.../...
REZCTA 60-SL.../...

Choose the desired packaging.
E.g.: RIZCTAA 60/2 (pack. 2 Pcs) - RIZCTAA 60/5 (pack. 5 Pcs)

JOINT - EDGE COVER VARNISHED METAL ANODIZED, POLISHED, STONE LINE

Article	H mm
GIZCTAA 60/...	60
GIZCTBT/BS/TS/RS 60/...	60
GIZCT01/010 60/...	60
GIZCTA 60-SL.../...	60

END CAPS R / L - EDGE COVER - VARNISHED METAL ANODIZED, POLISHED, STONE LINE - pack. 4Pcs (2 R + 2 L) / 10Pcs (5 R + 5 L)

Article	H mm
TPZCTAA 60/...	60
TPZCTBT/BS/TS/RS 60/...	60
TPZCT01/010 60/...	60
TPZCTA 60-SL.../...	60

Choose the desired packaging.
E.g.: TPCCTAA 60/2 (pack. 4 Pcs: 2 right + 2 left)

INTERNAL/EXTERNAL CORNER - EDGE COVER VARNISHED PLASTIC ANODIZED SILVER, POLISHED AND TITANIUM

Article	HxL mm
RICTAA 60/...	60 x 20
RECTAA 60/...	60 x 20
RICTBT 60/...	60 x 20
RECBT 60/...	60 x 20

JOINT - EDGE COVER VARNISHED PLASTIC ANODIZED SILVER, POLISHED AND TITANIUM

Article	H mm
GICTAA 60/...	60
GICBT 60/...	60

END CAPS R / L - EDGE COVER - VARNISHED PLASTIC ANODIZED SILVER, POLISHED AND TITANIUM - pack. 4Pcs (2 R + 2 L) / 10Pcs (5 R + 5 L)

Article	H mm
TPCTAA 60/...	60
TPCTBT 60/...	60

INTERNAL/EXTERNAL CORNER - FLUSH VARNISHED PLASTIC ANODIZED SILVER, POLISHED AND TITANIUM

Article	HxL mm
RIBAA 60/...	60 x 25
REBAA 60/...	60 x 25
RIBBT 60/...	60 x 25
REBBT 60/...	60 x 25

JOINT - FLUSH VARNISHED PLASTIC ANODIZED SILVER, POLISHED AND TITANIUM

Article	H mm
GIBAA 60/...	60
GIBBT 60/...	60

END CAPS R / L - FLUSH - VARNISHED PLASTIC ANODIZED SILVER, POLISHED AND TITANIUM - pack. 4Pcs (2 R + 2 L) / 10Pcs (5 R + 5 L)

Article	H mm
TPBAA 60/...	60
TPBBT 60/...	60


Available on demand aluminium prewelded internal and external flush corners. Finishing: 01 - 010 - AA - BT - BS - RS - TS. Price to be agreed. Production delay 4/5 weeks.



RIZCT... 60/... internal corner
REZCT... 60/... external corner
GIZCT... 60/... joint
TPZCT... 60/... end caps



RICT... 60/... internal corner
RECT... 60/... external corner
GICT... 60/... joint
TPCT... 60/... end caps



RIB... 60/... internal corner
REB... 60/... external corner
GIB... 60/... joint
TPB... 60/... end caps

*** = Production on demand with minimum quantity of 80 Pcs. Production delay 4/5 weeks. Price to be agreed


* = Production on demand with minimum quantity of 100 Pcs. Production delay 4/5 weeks. Price to be agreed

= News 2023


SKIRTING 80

POLISHED AND BRUSHED
STAINLESS STEEL AISI 304/1.4301-V2A

SKIRTING 80 made in stainless steel AISI 304/1.4301-V2A in height 80 mm. Available with or without adhesive. Superior aesthetic quality, extremely strong and easy to lay, it is ideal for all public and private environments that require high standards of hygiene and image. Used increasingly more often in contrast combinations with wood, carpeted floors, etc. for an unmistakable hi-tech effect. In order to facilitate and to perfect the laying process, internal and external angles, plugs and junctions are recommended.



EXAMPLES OF LAYING



POLISHED STAINLESS STEEL AISI 304/1.4301-V2
with protective film - bar length 2 lm - pack. 25 Pcs - 50 lm

Article	H mm		
BTAC 80A	80		
BTAC 80	80		

"A" at the end of the product code = Item with adhesive



Brushed STAINLESS STEEL AISI 304/1.4301-V2A
with protective film - bar length 2 lm - pack. 25 Pcs - 50 lm

Article	H mm		
BTACS 80A	80		
BTACS 80	80		

"A" at the end of the product code = Item with adhesive

SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS

LAYING INSTRUCTIONS

1. Choose the "SKIRTING 80" also choose with or without adhesive. 2. Cut the profile to the required length, taking care to calculate the width of the inside-outside corner joints. 3. For the self-adhesive version, the surface must be smooth, grease-free and not porous. It is not recommended for plaster and mortar surfaces (version without adhesive is better, using fast-setting acrylic silicone which is suitable for fixing aluminium to mortar - plaster, etc.). 4. Use the corner linking elements-joints and right and left end caps to facilitate laying.

COLOURS

	
AC - Polished stainless steel AISI 304/1.4301-V2A	ACS - Brushed stainless steel AISI 304/1.4301-V2A

USE PROBAND FIX FOR FIXING THE PROFILE TO THE WALL



CORNERS, END CAPS AND JOINTS

STEEL and VARNISHED METAL

EDGE COVER VARNISHED METAL



VARNISHED METAL - EDGE COVER CORNERS - articles not for sale singly

INTERNAL/EXTERNAL CORNER - EDGE COVER VARNISHED METAL POLISHED STEEL EFFECT

Article	HxL mm	pack. 2Pcs	pack. 5Pcs
RIZCTAC 80/...	80 x 20		
REZCTAC 80/...	80 x 20		

JOINT - EDGE COVER VARNISHED METAL POLISHED STEEL EFFECT

Article	H mm	pack. 2Pcs	pack. 5Pcs
GIZCTAC 80	80		

Choose the desired packaging.
E.g.: RIZCTAC 80/2 (pack. 2 Pcs) - RIZCTAC 80/5 (pack. 5 Pcs)

END CAPS R / L - EDGE COVER - VARNISHED METAL POLISHED STEEL EFFECT - pack. 4Pcs (2 R+2 L) / 10Pcs (5 R+5 L)

Article	H mm	pack. 4Pcs	pack. 10Pcs
TPZCTAC 80/...	80		

Choose the desired packaging.
E.g.: TPCCTAC 80/2 (pack. 4 Pcs: 2 right + 2 left)
TPCCTAC 80/5 (pack. 10 Pcs: 5 right + 5 left)

INTERNAL/EXTERNAL CORNER - EDGE COVER VARNISHED METAL BRUSHED STAINLESS ST. EFFECT

Article	HxL mm	pack. 2Pcs	pack. 5Pcs
RIZCTACS 80/...	80 x 20		
REZCTACS 80/...	80 x 20		

JOINT - EDGE COVER VARNISHED METAL BRUSHED STAINLESS ST. EFFECT

Article	H mm	pack. 2Pcs	pack. 5Pcs
GIZCTACS 80/...	80		


Choose the desired packaging.
E.g.: RIZCTACS 80/2 (pack. 2 Pcs) - RIZCTACS 80/5 (pack. 5 Pcs)

END CAPS R / L - EDGE COVER - VARNISHED METAL BRUSHED STAINLESS ST. EFFECT - pack. 4Pcs (2 R+2 L) / 10Pcs (5 R+5 L)

Article	H mm	pack. 4Pcs	pack. 10Pcs
TPZCTACS 80/...	80		

Choose the desired packaging.
E.g.: TPCCTACS 80/2 (pack. 4 Pcs: 2 right + 2 left)
TPCCTACS 80/5 (pack. 10 Pcs: 5 right + 5 left)

PRE-WELDED



STEEL AISI 304/1.4301-V2A - FLUSH CORNERS - articles not for sale singly

INTERNAL/EXTERNAL CORNER FLUSH PRE-WELDED - POLISHED STEEL EFFECT

Article	HxL mm	pack. 2Pcs	pack. 5Pcs
RIAC 80/...	80 x 50		
REAC 80/...	80 x 50		

Choose the desired packaging.
E.g.: RIAC 80/2 (pack. 2 Pcs) - RIAC 80/5 (pack. 5 Pcs)

INTERNAL/EXTERNAL CORNER FLUSH PRE-WELDED - BRUSHED STAINLESS STEEL

Article	HxL mm	pack. 2Pcs	pack. 5Pcs
RIACS 80/...	80 x 50		
REACS 80/...	80 x 50		

Choose the desired packaging.
E.g.: RIACS 80/2 (pack. 2 Pcs) - RIACS 80/5 (pack. 5 Pcs)

SKIRTING 80 made in anodized, polished and brushed aluminium in height 80 mm. Available with or without adhesive. Superior aesthetic quality and easy to lay, it is ideal for all public and private environments. Can be used with all types of flooring. In order to facilitate and to perfect the laying process, internal and external angles, plugs and junctions are recommended.

Please contact the technical department for informations concerning the skirting bending radius.

SKIRTING 80

ANODIZED, POLISHED, VARNISHED and BRUSHED ALUMINIUM



ANODIZED SILVER ALUMINIUM thermo packed

bar length 2 lm - pack. 25 Pcs - 50 lm

Article	H mm
BTAA 80A	80
BTAA 80	80

POLISHED TITANIUM ALUMINIUM thermo packed

bar length 2 lm - pack. 25 Pcs - 50 lm

Article	H mm
BTBT 80A	80
BTBT 80	80

VARNISHED SEMIGLOSSY AND MATT WHITE ALUMINIUM

thermo packed - bar length 2 lm - pack. 25 Pcs - 50 lm

Article	H mm
BTA 80-01A	80
BTA 80-01	80
BTA 80-01OA	80
BTA 80-01O	80



BRUSHED ALUMINIUM (silver-copper-titanium)

thermo packed - bar length 2 lm - pack. 25 Pcs - 50 lm


Article	H mm
BTBS 80A	80
BTBS 80	80
BTRS 80A	80
BTRS 80	80
BTTS 80A	80
BTTS 80	80

STONE LINE ALUMINIUM


thermo packed - bar length 2 lm - pack. 40 Pcs - 80 lm

Article	H mm
BTA 80-SL01A	80
BTA 80-SL01	80
BTA 80-SL08A	80
BTA 80-SL08	80
BTA 80-SL12A	80
BTA 80-SL12	80

BT... 80/80A



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



USE PROBAND FIX FOR FIXING THE PROFILE TO THE WALL

COLOURS

ANODIZED	POLISHED	BRUSHED		SEMIGLOSSY	MATT	STONE LINE		On demand	
AA - Anodized silver alum.	BT - Polished titanium alum.	BS - Brushed silver alum.	RS - Brushed copper alum.	TS - Brushed titanium alum.	O1 - White varnished alum. (9016)	O10 - White varnished alum. (9016)	SLO1 - Stone white	SL08 - Stone antradrak	SL12 - Stone black

CORNERS, END CAPS AND JOINTS

VARNISHED METAL and VARNISHED PLASTIC

* Corners, end caps and joints of the on demand profiles are also on demand

INTERNAL/EXTERNAL CORNER - EDGE COVER - VARNISHED METAL ANODIZED, POLISHED, STONE LINE - H 80 X L 20

Article
RIZCTAA 80/...
REZCTAA 80/...
RIZCTBT/BS/TS/RS 80/...
REZCTBT/BS/TS/RS 80/...
RIZCT01/010 80/...
REZCT01/010 80/...
RIZCTA 80-SL.../...
REZCTA 80-SL.../...

Choose the desired packaging.
E.g.: RIZCTAA 80/2 (pack. 2 Pcs) - RIZCTAA 80/5 (pack. 5 Pcs)

JOINT - EDGE COVER VARNISHED METAL ANODIZED, POLISHED, STONE LINE

Article	H mm
GIZCTAA 80/...	80
GIZCTBT/BS/TS/RS 80/...	80
GIZCT01/010 80/...	80
GIZCTA 80-SL.../...	80

END CAPS R / L - EDGE COVER - VARNISHED METAL ANODIZED, POLISHED, STONE LINE - pack. 4Pcs (2 R + 2 L) / 10Pcs (5 R + 5 L)

Article	H mm
TPZCTAA 80/...	80
TPZCTBT/BS/TS/RS 80/...	80
TPZCT01/010 80/...	80
TPZCTA 80-SL.../...	80

Choose the desired packaging.
E.g.: TPCCTAA 80/2 (pack. 4 Pcs: 2 right + 2 left)

INTERNAL/EXTERNAL CORNER - EDGE COVER VARNISHED PLASTIC ANODIZED SILVER, POLISHED AND TITANIUM

Article	HxL mm
RICTAA 80/...	80 x 20
RECTAA 80/...	80 x 20
RICTBT 80/...	80 x 20
RECTBT 80/...	80 x 20

INTERNAL/EXTERNAL CORNER - FLUSH VARNISHED PLASTIC ANODIZED SILVER, POLISHED AND TITANIUM

Article	HxL mm
RIBAA 80/...	80 x 25
REBAA 80/...	80 x 25
RIBBT 80/...	80 x 25
REBBT 80/...	80 x 25

JOINT - EDGE COVER VARNISHED PLASTIC ANODIZED SILVER, POLISHED AND TITANIUM

Article	H mm
GICTAA 80/...	80
GICBT 80/...	80

JOINT - FLUSH VARNISHED PLASTIC ANODIZED SILVER, POLISHED AND TITANIUM

Article	H mm
GIBAA 80/...	80
GIBBT 80/...	80

END CAPS R / L - EDGE COVER - VARNISHED PLASTIC ANODIZED SILVER, POLISHED AND TITANIUM - pack. 4Pcs (2 R + 2 L) / 10Pcs (5 R + 5 L)

Article	H mm
TPCTAA 80/...	80
TPCTBT 80/...	80

END CAPS R / L - FLUSH - VARNISHED PLASTIC ANODIZED SILVER, POLISHED AND TITANIUM - pack. 4Pcs (2 R + 2 L) / 10Pcs (5 R + 5 L)

Article	H mm
TPBAA 80/...	80
TPBBT 80/...	80

Available on demand aluminium prewelded internal and external flush corners. Finishing: O1 - O10 - AA - BT - BS - RS - TS. Price to be agreed. Production delay 4/5 weeks.


METAL EDGE COVER



PLASTIC EDGE COVER



PLASTIC FLUSH



*** = Production on demand with minimum quantity of 80 Pcs. Production delay 4/5 weeks. Price to be agreed


* = Production on demand with minimum quantity of 100 Pcs. Production delay 4/5 weeks. Price to be agreed

News 2023


SKIRTING 100 SKIRTING 150

POLISHED AND BRUSHED
STAINLESS STEEL AISI 304/1.4301-V2A

SKIRTING 100 and **SKIRTING 150** made in stainless steel AISI 304/1.4301-V2A in height 100 and 150 mm. Available with or without adhesive. Superior aesthetic quality, extremely strong and easy to lay, it is ideal for all public and private environments that require high standards of hygiene and image. Used increasingly more often in contrast combinations with wood, carpeted floors, etc. for an unmistakable hi-tech effect. In order to facilitate and to perfect the laying process, internal and external angles, plugs and junctions are recommended.



EXAMPLES OF LAYING



POLISHED STAINLESS STEEL AISI 304/1.4301-V2
with protective film - bar length 2 lm - pack. 20 Pcs - 40 lm

Article	H mm		
BTAC 100A	100		
BTAC 100	100		

Brushed STAINLESS STEEL AISI 304/1.4301-V2A
with protective film - bar length 2 lm - pack. 20 Pcs - 40 lm

Article	H mm		
BTACS 100A	100		
BTACS 100	100		

"A" at the end of the product code = Item with adhesive

SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS

LAYING INSTRUCTIONS

1. Choose the "SKIRTING 100 -150" also choose with or without adhesive. 2. Cut the profile to the required length, taking care to calculate the width of the inside-outside corner joints. 3. For the self-adhesive version, the surface must be smooth, grease-free and not porous. It is not recommended for plaster and mortar surfaces (version without adhesive is better, using fast-setting acrylic silicone which is suitable for fixing aluminium to mortar - plaster, etc.). 4. Use the corner linking elements-joints and right and left end caps to facilitate laying.



POLISHED STAINLESS STEEL AISI 304/1.4301-V2
with protective film - bar length 2 lm - pack. 20 Pcs - 40 lm

Article	H mm		
BTAC 150A	150		
BTAC 150	150		

Brushed STAINLESS STEEL AISI 304/1.4301-V2A
with protective film - bar length 2 lm - pack. 20 Pcs - 40 lm

Article	H mm		
BTACS 150A	150		
BTACS 150	150		

"A" at the end of the product code = Item with adhesive

USE PROBAND FIX FOR FIXING THE PROFILE TO THE WALL



COLOURS



CORNERS, END CAPS AND JOINTS

STEEL and VARNISHED METAL

EDGE COVER VARNISHED METAL




RIZCT... 100
internal corner



REZCT... 100
external corner



GIZCT... 100
joint



TPZCT... 100/3
end caps

STEEL PRE-WELDED

RI... 100 / 150
internal corner



RE... 100 / 150
external corner



VARNISHED METAL - EDGE COVER CORNERS H100 - articles not for sale singly

INTERNAL/EXTERNAL CORNER - EDGE COVER VARNISHED METAL POLISHED STEEL EFFECT

Article	HxL mm	pack. 2Pcs	pack. 5Pcs
RIZCTAC 100/...	100 x 20		
REZCTAC 100/...	100 x 20		

JOINT - EDGE COVER

VARNISHED METAL POLISHED STEEL EFFECT

Article	H mm	pack. 2Pcs	pack. 5Pcs
GIZCTAC 100/...	100		

Choose the desired packaging.

E.g.: RIZCTAC 100/2 (pack. 2 Pcs) - RIZCTAC 100/5 (pack. 5 Pcs)

END CAPS R / L - EDGE COVER - VARNISHED METAL POLISHED STEEL EFFECT - pack. 4Pcs (2 R + 2 L) / 10Pcs (5 R + 5 L)

Article	H mm	pack. 4Pcs	pack. 10Pcs
TPZCTAC 100/...	100		

Choose the desired packaging.

E.g.: TPZCTAC 100/2 (pack. 4 Pcs: 2 right + 2 left)
TPZCTAC 100/5 (pack. 10 Pcs: 5 right + 5 left)

STEEL AISI 304/1.4301-V2A - FLUSH CORNERS H100

articles not for sale singly

INTERNAL/EXTERNAL CORNER - FLUSH PRE-WELDED POLISHED-BRUSHED STAINLESS STEEL EFFECT

Article	HxL mm	pack. 2Pcs	pack. 5Pcs
RIAC 100/...	100 x 50		
REAC 100/...	100 x 50		
RIACS 100/...	100 x 50		
REACS 100/...	100 x 50		

Choose the desired packaging.

E.g.: RIAC 100/2 (pack. 2 Pcs) - RIAC 100/5 (pack. 5 Pcs)

INTERNAL/EXTERNAL CORNER - EDGE COVER VARNISHED METAL BRUSHED STAINLESS ST. EFFECT

Article	HxL mm	pack. 2Pcs	pack. 5Pcs
RIZCTACS 100/...	100 x 20		
REZCTACS 100/...	100 x 20		

JOINT - EDGE COVER

VARNISHED METAL BRUSHED STAINLESS ST. EFFECT

Article	H mm	pack. 2Pcs	pack. 5Pcs
GIZCTACS 100/...	100		

Choose the desired packaging.

E.g.: RIZCTACS 100/2 (pack. 2 Pcs) - RIZCTACS 100/5 (pack. 5 Pcs)

END CAPS R / L - EDGE COVER - VARNISHED METAL BRUSHED STAINLESS ST. EFFECT - pack. 4Pcs (2 R + 2 L) / 10Pcs (5 R + 5 L)

Article	H mm	pack. 4Pcs	pack. 10Pcs
TPZCTACS 100/...	100		

Choose the desired packaging.

E.g.: TPZCTACS 100/2 (pack. 4 Pcs: 2 right + 2 left)
TPZCTACS 100/5 (pack. 10 Pcs: 5 right + 5 left)

STEEL AISI 304/1.4301-V2A - FLUSH CORNERS H150

articles not for sale singly

INTERNAL/EXTERNAL CORNER - FLUSH PRE-WELDED POLISHED-BRUSHED STAINLESS STEEL EFFECT

Article	HxL mm	pack. 2Pcs	pack. 5Pcs
RIAC 150/...	150 x 50		
REAC 150/...	150 x 50		
RIACS 150/...	150 x 50		
REACS 150/...	150 x 50		

Choose the desired packaging.

E.g.: RIACS 150/2 (pack. 2 Pcs) - RIACS 150/5 (pack. 5 Pcs)

SKIRTING 100 made in anodized, polished and brushed aluminium in height 100 mm. Available with or without adhesive. Superior aesthetic quality and easy to lay, it is ideal for all public and private environments. Can be used with all types of flooring.

In order to facilitate and to perfect the laying process, internal and external angles, plugs and junctions are recommended.

Please contact the technical department for informations concerning the skirting bending radius.

SKIRTING 100

ANODIZED, POLISHED, VARNISHED and BRUSHED ALUMINIUM



ANODIZED SILVER ALUMINIUM thermo packed
bar length 2 lm - pack. 20 Pcs - 40 lm

Article	H mm		
BTAA 100A	100		
BTAA 100	100		

POLISHED TITANIUM ALUMINIUM thermo packed
bar length 2 lm - pack. 20 Pcs - 40 lm

Article	H mm		
BTBT 100A	100		
BTBT 100	100		

VARNISHED SEMIGLOSSY AND MATT WHITE ALUMINIUM thermo packed - bar length 2 lm - pack. 20 Pcs - 40 lm

Article	H mm		
BTA 100-01A	100		
BTA 100-01	100		
BTA 100-010A	100		
BTA 100-010	100		




BRUSHED ALUMINIUM (silver-copper-titanium) thermo packed - bar length 2 lm - pack. 20 Pcs - 40 lm

Article	H mm		
BTBS 100A	100		
BTBS 100	100		
BTRS 100A	100		
BTRS 100	100		
BTTS 100A	100		
BTTS 100	100		

STONE LINE ALUMINIUM thermo packed - bar length 2 lm - pack. 40 Pcs - 80 lm

Article	H mm		
⊕ BTA 100-SL01A	100		
⊕ BTA 100-SL01	100		
⊕ BTA 100-SL08A	100		
⊕ BTA 100-SL08	100		**
⊕ BTA 100-SL12A	100		**
⊕ BTA 100-SL12	100		**



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



USE PROBAND FIX FOR FIXING THE PROFILE TO THE WALL

COLOURS

ANODIZED	POLISHED	BRUSHED	SEMIGLOSSY	MATT	STONE LINE
AA - Anodized silver alum.	BT - Polished titanium alum.	BS - Brushed silver alum.	RS - Brushed copper alum.	TS - Brushed titanium alum.	01 - White varnished alum. (9016)
					010 - White varnished alum. (9016)
					SLO1 - Stone white
					SL08 - Stone antradrak
					SL12 - Stone black

CORNERS, END CAPS AND JOINTS

VARNISHED METAL and VARNISHED PLASTIC

* Corners, end caps and joints of the on demand profiles are also on demand

INTERNAL/EXTERNAL CORNER - EDGE COVER - VARNISHED METAL, ANODIZED, POLISHED STONE LINE - H 100 MM - L 20 MM

Article	pack. 2Pcs	pack. 5Pcs
RIZCTAA 100/...		
REZCTAA 100/...		
RIZCTBT/BS/TS/RS 100/...		
REZCTBT/BS/TS/RS 100/...		
RIZCT01/010 100/...		
REZCT01/010 100/...		
⊕ RIZCTA 100-SL.../...		
⊕ REZCTA 100-SL.../...		


Choose the desired packaging.
E.g.: RIZCTAA 100/2 (pack. 2 Pcs) - RIZCTAA 100/5 (pack. 5Pcs)

JOINT - EDGE COVER VARNISHED METAL ANODIZED, POLISHED, STONE LINE

Article	H mm		
GIZCTAA 100/...	100		
GIZCTBT/BS/TS/RS 100/...	100		
GIZCT01/010 100/...	100		
⊕ GIZCTA 100-SL.../...	100		

END CAPS R / L - EDGE COVER - VARNISHED METAL ANODIZED, POLISHED, STONE LINE - pack. 4Pcs (2 R + 2 L) / 10Pcs (5 R + 5 L)

Article	H mm		
TPZCTAA 100/...	100		
TPZCTBT/BS/TS/RS 100/...	100		
TPZCT01/010 100/...	100		
⊕ TPZCTA 100-SL.../...	100		



INTERNAL/EXTERNAL CORNER - EDGE COVER VARNISHED PLASTIC ANODIZED SILVER, POLISHED AND TITANIUM

Article	HxL mm	pack. 2Pcs	pack. 5Pcs
RICTAA 100/...	100 x 20		
RECTAA 100/...	100 x 20		
RICTBT 100/...	100 x 20		
RECTBT 100/...	100 x 20		

Choose the desired packaging.
E.g.: RICTAA 100/2 (pack. 2 Pcs) - RICTAA 100/5 (pack. 5 Pcs)

Available on demand aluminium prewelded internal and external flush corners. Finishing: 01 - 010 - AA - BT - BS - RS - TS. Price to be agreed. Production delay 4/5 weeks.

JOINT - EDGE COVER VARNISHED PLASTIC ANODIZED SILVER, POLISHED AND TITANIUM

Article	H mm		
GICTAA 100/...	100		
GICTBT 100/...	100		

END CAPS R / L - EDGE COVER - VARNISHED PLASTIC ANODIZED SILVER, POLISHED AND TITANIUM - pack. 4Pcs (2 R + 2 L) / 10Pcs (5 R + 5 L)

Article	H mm		
TPCTAA 100/...	100		
TPCTBT 100/...	100		

Choose the desired packaging.
E.g.: TPCTAA 100/2 (pack. 4 Pcs: 2 right + 2 left)



** = Production on demand with minimum quantity of 80 Pcs. Production delay 4/5 weeks. Price to be agreed



* = Production on demand with minimum quantity of 100 Pcs. Production delay 4/5 weeks. Price to be agreed

⊕ = News 2023

PROMULTISKIRT SQUARE

FOAMED VINYL RESIN

PROMULTISKIRT SQUARE is an expanded vinyl resin profile covered with a vinyl resin film available in white, black, silver and wood finishes. The profile has a good resistance to chemical agents and can be secured to the wall with plastic supports fixed with screws or silicone. The skirting height is 100 mm, it can be cut to 80 and 60 mm heights thanks to the pre-incisions on the back. **PROMULTISKIRT SQUARE** in expanded vinyl resin coated with vinyl resin film is suitable for any indoor environment.



FOAMED VINYL RESIN (wood finishes - black - white and silver)
bar length **2,4 lm** - pack. **20 Pcs - 48 lm**

Article	H mm
BTEPR... 108614/S	100/80/60

Available in the finishes: 29W - 30W - 34W - B - N - AA.
The code of the selected colour must be added to the article code.
E.g.: BTEPR...108614/S (chosen finish Havana oak) BTEPR34W 108614/S

SUPPORT / FIXING CLIP - PLASTIC
pack. **100 Pcs**

Article	H mm
BTEPRS 18	16,5

Order the SUPPORT and choose the SKIRTING in the desired finish.

USE PROBAND FIX FOR FIXING THE PROFILE TO THE WALL



COLOURS

(For a precise assessment of colours request the wood finishes sample range)

29W - White oak	30W - Grey oak	34W - Havana oak	B - White	N - Black	AA - Silver

On request it is possible to realize other finishes of the color range: minimum order 400 pcs. Production delay 4/5 weeks. Price to be agreed. For sample finishes, contact the sales office for minimum quantities, timing and costs.

LAYING INSTRUCTIONS

1. Choose "PROMULTISKIRT SQUARE" according to the chosen colour. **2.** Cut "PROMULTISKIRT SQUARE" to the required length. **3.** if necessary cut "PROMULTISKIRT SQUARE" to the required height. *** 4.** Carefully clean the substrate on which the profile will be placed from oil, grease and dirt residues in general.

Laying with adhesive only:

5a. With dry surface apply the Proband Fix. **6a.** Press the profile against the wall with the correct pressure.

Laying with adhesive and support:

5b. Fix the plastic supports to the wall every 50mm with screws. **6b.** Apply Proband Fix only to the back upper part of the skirting board. **7b.** Fix the profile to the supports and press it against the wall with correct pressure.

*CUT INSTRUCTIONS




Option 1A: Cut to have the height 80 mm.
Cut along the first pre-incision on the back of the skirting;



Option 1B: Cut to have the height 60 mm.
Cut along the second pre-incision on the back of the skirting;




2. Cut the skirting on the front side at the cut previously made on the back;



3. Remove the excess part.


EXAMPLE OF LAYING



CORNERS, END CAPS AND JOINTS

FOAMED VINYL RESIN

INTERNAL CORNER KIT



KIT BTEPR ... 108614/SI

EXTERNAL CORNER KIT



KIT BTEPR ...108614/SE

IN/EXTERNAL CORNERS and END CAPS KIT
(wood finishes - black - white and silver)

Article	H mm
KBTEPR...108614/SI	100/80/60
KBTEPR...108614/SE	100/80/60

Available in the finishes: 29W - 30W - 34W - B - N - AA.
The code of the selected colour must be added to the article code.
E.g.: KBTEPR...108614/S (chosen finish Havana oak) KBTEPR34W 108614/S

PROMULTISKIRT ROUND is an expanded vinyl resin profile covered with a vinyl resin film available in white, black, silver and wood finishes. The profile has a good resistance to chemical agents and can be secured to the wall with plastic supports fixed with screws or silicone. The skirting height is 100 mm, it can be cut to 80 and 60 mm heights thanks to the pre-incisions on the back. PROMULTISKIRT ROUND in expanded vinyl resin coated with vinyl resin film is suitable for any indoor environment.

PROMULTISKIRT ROUND

FOAMED VINYL RESIN

PATENTED



FOAMED VINYL RESIN (wood finishes - black - white and silver)
bar length 2,4 lm - pack: 20 Pcs - 48 lm

SUPPORT / FIXING CLIP - PLASTIC
pack: 100 Pcs

Article	H mm
BTEPR... 108614/R	100/80/60

Article	H mm
BTEPRS 18	16,5

Available in the finishes: 29W - 30W - 34W - B - N - AA.
The code of the selected colour must be added to the article code.
E.g.: BTEPR... 108614/R (chosen finish Havana oak) BTEPR34W 108614/R

Order the SUPPORT and choose the SKIRTING in the desired finish.

USE PROBAND FIX FOR FIXING THE PROFILE TO THE WALL



COLOURS

(For a precise assessment of colours request the wood finishes sample range)



On request it is possible to realize other finishes of the color range: minimum order 400 pcs. Production delay 4/5 weeks. Price to be agreed. For sample finishes, contact the sales office for minimum quantities, timing and costs.

LAYING INSTRUCTIONS: IT ROUND" according to the chosen colour. **2.** Cut "PROMULTISKIRT ROUND" to the required length. **3.** if necessary cut "PROMULTISKIRT ROUND" to the required height. * **4.** Carefully clean the substrate on which the profile will be placed from oil, grease and dirt residues in general.

Laying with adhesive only:

5a. With dry surface apply the Proband Fix. **6a.** Press the profile against the wall with the correct pressure.

Laying with adhesive and support:

5b. Fix the plastic supports to the wall every 50mm with screws. **6b.** Apply Proband Fix only to the back upper part of the skirting board.

7b. Fix the profile to the supports and press it against the wall with correct pressure.



Option 1A: Cut to have the height 80 mm.
Cut along the first pre-incision on the back of the skirting;



Option 1B: Cut to have the height 60 mm.
Cut along the second pre-incision on the back of the skirting;




2. Cut the skirting on the front side at the cut previously made on the back;




3. Remove the excess part.

BTEPR... 108614/R

BTEPRS 18/100



EXAPLE OF LAYING



CORNERS, END CAPS AND JOINTS

FOAMED VINYL RESIN

IN/EXTERNAL CORNERS and END CAPS KIT
(wood finishes - black - white and silver)

Available in the finishes: 29W - 30W - 34W - B - N - AA.
The code of the selected colour must be added to the article code.
E.g.: KBTEPR...108614/S (chosen finish Havana oak) KBTEPR34W 108614/S

Article	H mm
KBTEPR...108614/RI	100/80/60
KBTEPR...108614/RE	100/80/60

INTERNAL CORNER KIT



KIT BTEPR ...108614/RI

EXTERNAL CORNER KIT




KIT BTEPR ...108614/RE

SKIRTING 7016

FOAMED VINYL RESIN

SKIRTING 7016 is a vinyl resin foam profile with a height of 70 mm. available wooden finishes and finishes in solid colour that could be matched with the PROINSERT SYSTEM's profiles. The profile, suitable like skirting for floating and glued wood floor, laminate and LVT, could be laid with suitable adhesive, nails, screws or using the pre-punched support fixed to the wall with screws every 57 cm. Its special section, that allows to cover a 16 mm perimetral joint, and wide range of finishes make it a very requested, elegant and economic skirting profile.



FOAMED VINYL RESIN (wood finishes - black - white and silver)
Length = 2,5 m - Pack 20 pcs - 50 lm

Article	H mm
BTEPR... 7016	70



SUPPORT / FIXING CLIP - PLASTIC
support Length 5 cm

Article	H mm
BTEPRS 385	37,5

Order the SUPPORT and choose the SKIRTING in the desired finish.

USE PROBAND FIX FOR FIXING THE PROFILE TO THE WALL



IN/EXTERNAL CORNERS and END CAPS KIT
(wood finishes - black - white and silver)


Article	H mm
KIT BTEPR ...7016I	70
KIT BTEPR ...7016E	70



KIT BTEPR...7016I
INTERNAL CORNER KIT



KIT BTEPR...7016E
EXTERNAL CORNER KIT



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS


1. Choose "Skirting 7016" in the desired finish.
2. Fix the pre-punched support to the wall with screws every 50 cm.
3. Attach the profile to the support applying low pressure.
4. Alternatively fix the profile using a suitable fast adhesive, nails or screws

COLOURS

(For a precise assessment of colours request the wood finishes sample range)

04W - Dark oak	05W - Light oak	13W - Teak Indonesia	18W - Light Zerbano	21W - Powder Oak	25W - Bleached fir	29W - White oak	30W - Gray oak	31W - Victoria oak	33W - Sawed oak
34W - Havana oak	35W - Edimburgo oak	36W - American oak	37W - Carvi oak	38W - Queens oak	39W - Grey elm	41W - Ice oak	42W - Grace oak	45W - Morocco oak	46W - Black decap
53W	54W	55W	B - White	N - Black	AA - Silver				

On request it is possible to realize other finishes of the color range: minimum order 400 pcs. Production delay 4/5 weeks. Price to be agreed. For sample finishes, contact the sales office for minimum quantities, timing and costs.



SKIRTING 7011 is a vinyl resin foam profile with a height of 70 mm x 10,5 mm, available in wooden finishes and finishes standard colours that could be matched with the PROINSERT SYSTEM's profiles. Suitable as Basebord for floating and glued wood floor, laminate and LVT, could be laid with suitable adhesive, or else with nails .

SKIRTING 7011

FOAMED VINYL RESIN



FOAMED VINYL RESIN (wood finishes - black - white and silver)
Length = 2,5 m - Pack 20 pcs - 50 lm

Article	H mm
BTEPR... 7011	70



IN/EXTERNAL CORNERS and END CAPS KIT
(wood finishes - black - white and silver)

Article	H mm
KIT BTEPR ...7011I	70
KIT BTEPR ...7011E	70

INTERNAL CORNER KIT


EXTERNAL CORNER KIT



KIT BTEPR...7011I


KIT BTEPR...7011E

USE PROBAND FIX FOR FIXING THE PROFILE TO THE WALL




COLOURS

(For a precise assessment of colours request the wood finishes sample range)



On request it is possible to realize other finishes of the color range: minimum order 400 pcs. Production delay 4/5 weeks. Price to be agreed. For sample finishes, contact the sales office for minimum quantities, timing and costs.

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the "Skirting 7011" in the required the colour.
2. Lay the "Skirting 7011" using quick-setting suitable adhesive for gluing flexible PVC onto mortar-plaster-accessorised walls, etc. or fix with nails.

SKIRTING 40 is a vinyl resin foam profile with a height of 40 mm x 10 mm, available in wooden finishes and finishes standard colours that could be matched with the PROINSERT SYSTEM's profiles. Suitable as Basebord for floating and glued wood floor, laminate and LVT, could be laid with suitable adhesive, or else with nails .

SKIRTING 40

FOAMED VINYL RESIN



FOAMED VINYL RESIN (wood finishes - black - white and silver)
Length = 2,4 m - Pack. 20 PC - 48 ml

Article	H mm
BTEPR... 4010	40

Available in the finishes: 29W - 30W - 34W - B - N - AA.
The code of the selected colour must be added to the article code.
E.g.: BTEPR... 4010 (chosen finish Havana oak) BTEPR34W 4010

USE PROBAND FIX FOR FIXING THE PROFILE TO THE WALL



IN/EXTERNAL CORNERS and END CAPS KIT
(wood finishes - black - white and silver)

Article	H mm
KIT BTEPR ...4010I	40
KIT BTEPR ...4010E	40

INTERNAL CORNER KIT


EXTERNAL CORNER KIT




KIT BTEPR...4010I

KIT BTEPR...4010E

BTEPR... 4010



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the "Skirting 40" in the required the colour.
2. Lay the "Skirting 40" using quick-setting suitable adhesive for gluing flexible PVC onto mortar-plaster-accessorised walls, etc. or fix with nails.

On request it is possible to realize other finishes of the color range: minimum order 400 pcs. Production delay 4/5 weeks. Price to be agreed. For sample finishes, contact the sales office for minimum quantities, timing and costs.

COLOURS


(For a precise assessment of colours request the wood finishes sample range)



SKIRTING 60 SKIRTING 120

NON-TOXIC FLEXIBLE VINYL RESIN
IN 6 COLOURS

PVC FLEXIBLE SKIRTING 60/120 height 60 mm and 120 mm, is a very strong profile ideal for easily achieving special, attractive, superior finishes. Installation recommended with glue or silicone. Easy to install, the shaped edges ensure perfect adhesion to the surface. The projecting rounded flange covers the terminal expansion joint.



ATTENTION: IN ORDER TO USE, LAY AND FIX PROPERLY THIS PRODUCT PLEASE LOOK AT OUR WEBSITE OR APP LAYING / FIXING VIDEO FOR CORRECT INSTALLATION.



NON-TOXIC FLEXIBLE VINYL RESIN
rolls length 50 lm

Article	H mm		
BTPV... 60	60		
BTPV... 120	120		

Available in the colours: B - GC - GS - T - M - N.
The code of the selected colour must be added to the article code.
E.g.: BTPV... 60 (chosen finish light gray) BTPVGC 60.

NON-TOXIC FLEXIBLE VINYL RESIN - ADHESIVE
rolls length 50 lm


Article	H mm		
BTPV... 60A	60		
BTPV... 120A	120		

Available in the colours: B - GC - GS - T - M - N.
The code of the selected colour must be added to the article code.
E.g.: BTPV... 60 (chosen finish light gray) BTPVGC 60.

COLOURS

B - White	GC - Light gray	GS - Dark gray	T - Dark brown	M - Brown	N - Black

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the "SKIRTING 60 - 120" of the required height 60/120mm and choose the colour. 2. Lay the "SKIRTING 60 - 120" using an adhesive suitable for gluing flexible PVC onto mortar, plaster, accessorised walls, etc. or fix with screws/nails.


As regards the items with adhesive, the adhesive roll is sold separately (50 lm for H:60), (50 lm for H:120)

SKIRTING 62F


FLEXIBLE VINYL RESIN
IN 6 COLOURS

SKIRTING 62F is a new 62 mm skirting board made of non-toxic, flexible vinyl resin. This profile is very resistant and particularly suited for providing highly aesthetic perimeter skirting of excellent quality at reasonable prices. It differs from the BTPV... 60 skirting board in that it is provided with a bottom flange that allows it to be placed perpendicularly (90°) to the wall/lining and welded to PVC floors. In addition, the horizontal flange covers the floor's perimeter expansion joint. We recommend applying the skirting using glue/adhesive/Bostik/mastic. Alternatively, you can choose the self-adhesive version for quick, effortless installation.

BTPF... 62 / BTPF... 62A



EXAMPLES OF LAYING



LAYING INSTRUCTIONS

1. Choose the colour of the "SKIRTING 62F" board, indicating whether you want it with or without a self-adhesive backing. 2. Cut the "SKIRTING 62F" to length, taking into account the width of the internal and external connections. 3. Self-adhesive skirting is recommended only for surfaces that are perfectly smooth, non-oily and non-porous. On plaster and mortar surfaces, use a non-adhesive version and apply the skirting using quick-setting acrylic silicone suitable for gluing aluminium to mortar, plaster, etc.

ATTENTION: IN ORDER TO USE, LAY AND FIX PROPERLY THIS PRODUCT PLEASE LOOK AT OUR WEBSITE OR APP LAYING / FIXING VIDEO FOR CORRECT INSTALLATION



FLEXIBLE VINYL RESIN

rolls length 50 lm with or without adhesive

Article	H mm		
BTPF... 62	62		

Available in the colours: B - GC - GS - T - M - N.
The code of the selected colour must be added to the article code.
E.g.: BTPF...62 (chosen finish light gray) BTPFGC 62.

FLEXIBLE VINYL RESIN

rolls length 50 lm with or without adhesive

Article	H mm		
BTPF... 62A	62		

Available in the colours: B - GC - GS - T - M - N.
The code of the selected colour must be added to the article code.
E.g.: BTPF...62 (chosen finish light gray) BTPFGC 62.

As regards the items with adhesive, the adhesive roll is sold separately (50 lm)


COLOURS

B - White	GC - Light gray	GS - Dark gray
T - Dark brown	M - Brown	N - Black

SKIRTING in PVC foam height 70 mm in 4 semi-matt colours and 8 wood finishes to be matched with the PROINSERT SYSTEM profiles for floating laminated wood floors and traditional parquet floors. Laying is done by gluing (acetic silicone - acrylic-mastic) or using screws or nails. Attractive, strong, hardwearing and economic, it is easy to lay and ideal for many public premises (hospitals, schools, gymnasiums, rest homes and creative areas) and private environments.

SKIRTING

EXPANDED VINYL RESIN



EXPANDED RIGID VINYL RESIN (black - light and dark grey - white)
bar length 2 lm - pack. 60 Pcs - 120 lm

Article	H mm
BTPR... 70	70

EXPANDED RIGID VINYL RESIN (8 wood finishes)
bar length 2 lm - pack. 60 Pcs - 120 lm

Article	H mm
BTPR... 70	70

Available in the wood finishes: B - GC - GS - N - 04W - 05W - 06W - 07W - 08W - 09W - 10W - M.
The code of the selected colour must be added to the article code. E.g.: BTPR... 70 (chosen colour black) BTPRN 70.


USE PROBAND FIX FOR FIXING THE PROFILE TO THE WALL




COLOURS

B - White	GC - Light grey	GS - Dark grey	N - Black	04W - Dark beech	05W - Light oak (strip)
06W - Dark oak (walnut)	07W - Light cherry (strip)	08W - Dark cherry (board)	09W - Red walnut (merbau-apple-walnut)	10W - Wengé (panga panga-wengé)	M - Mogano

The shade of the wooden finish in rigid expanded vinyl resin/PVC results slightly different from the film usually applied on the profiles in aluminium.



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the "SKIRTING" in the required colour. 2. Lay the "SKIRTING" using quick-setting acrylic silicone, mastic or bostik, suitable for gluing flexible PVC onto mortar-plaster-accessorised walls, etc. or fix with screws/nails.

ANGLE BAR produced in expanded PVC in 4 semi-matt colours and 8 wood finishes used to protect angles. Laying is done by gluing (acetic silicone - acrylic-mastic) or using screws or nails. Attractive, strong, hardwearing and economic, it is easy to lay and ideal for many public premises (hospitals, schools, gymnasiums, rest homes and creative areas) and private environments.

ANGLE BAR

EXPANDED VINYL RESIN



EXPANDED RIGID VINYL RESIN (black - light and dark grey - white)
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	L x H mm
AGE... 25	25 x 25

EXPANDED RIGID VINYL RESIN (8 wood finishes)
bar length 2,7 lm - pack. 40 Pcs - 108 lm


Article	L x H mm
AGE... 25	25 x 25

Available in the wood finishes: B - GC - GS - 11 - 04W - 05W - 06W - 07W - 08W - 09W - 10W - M.
The code of the selected colour must be added to the article code. E.g.: AGE... 25 (chosen finish black) AGE11 25.


USE PROBAND FIX FOR FIXING THE PROFILE TO THE WALL



The shade of the wooden finish in rigid expanded vinyl resin/PVC results slightly different from the film usually applied on the profiles in aluminium.



EXAMPLES OF LAYING




PROSEAL WOOD


EXPANDED PVC
2 WOOD FINISHING AND 4 MATCHING COLOURS

transition profiles

PSAW... 20



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROSEAL WOOD" color and/or wood finish required.
2. The laying must be carried out using fast fixing acrylic silicone, mastic, bostik suitable for gluing PVC with mortar - plaster - wall units etc., or fix using screws/nails.

PROSEAL WOOD is a new inner connector square suitable for creating a concave skirting for wood / rolled-melamine floating wood / ceramic / marble tiles to reduce the floor /covering detachment. The particular material used allows to resist to the main chemical agents ant to small breakages. **PROSEAL WOOD's** dimensions allow the necessary expansion of the outer joint. Ideal for public (schools, rest homes, recreational area) and private places. In expanded PVC , in 2 wood finishes 4 in matching colours to combine with various wood finishes. Easy to lay with fixing silicone.



EXPANDED PVC - 2 WOOD FINISHING

bar length 2,5 lm - pack. 40 Pcs - 100 lm

Article	L x H mm
PSAW... 20	21 x 21

Available in the wood finishes: 05W - 10W , and colours: B - GC - GS - N.
The code of the selected colour must be added to the article code. E.g.: PSAW...20 (chosen finish black) PSAWN 20.



EXPANDED PVC - 4 COLOURS

bar length 2,5 lm - pack. 40 Pcs - 100 lm

Article	L x H mm
PSAW... 20	21 x 21



USE PROBAND FIX FOR FIXING THE PROFILE TO THE WALL

COLOURS

B - White	GC - Light gray	GS - Dark gray	N - Black	05W - Light oak (strip)	10W - Wengé (panga panga-wengé)


The shade of the wooden finish in rigid expanded vinyl resin/PVC results slightly different from the film usually applied on the profiles in aluminium.

PROANGLE WOOD


EXPANDED PVC
2 WOOD FINISHING AND 4 MATCHING COLOURS

transition profiles

PGAW... 15



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROANGLE WOOD" color and/or wood finish required.
2. The laying must be carried out using fast fixing acrylic silicone, mastic, bostik, suitable for glueing PVC with mortar-plaster-wall units etc., or fix using screws/nails.

PROANGLE WOOD is a new inner connector square suitable for creating a convex skirting for wood / rolled-melamine floating wood / ceramic / marble floor to reduce the floor /covering detachment. The particular material used allows to resist to the main chemical agents and to small breakages. **PROANGLE WOOD's** dimensions allow the necessary expansion of the outer joint. Ideal for public (schools, rest homes, recreational area) and private places. In expanded PVC , in 2 wood finishes 4 in matching colors to combine with various wood finishes. Easy to lay with fixing silicone.



EXPANDED PVC - 2 WOOD FINISHING

bar length 2,5 lm - pack. 40 Pcs - 100 lm

Article	L x H mm
PGAW... 15	15 x 15

Available in the wood finishes: 05W - 10W , and colours: - GC - GS - N.
The code of the selected colour must be added to the article code. E.g.: PGAW...15 (chosen finish black) PGAWN 15.



EXPANDED PVC - 4 COLOURS

bar length 2,5 lm - pack. 40 Pcs - 100 lm

Article	L x H mm
PGAW... 15	15 x 15

USE PROBAND FIX FOR FIXING THE PROFILE TO THE WALL



COLOURS

B - White	GC - Light gray	GS - Dark gray	N - Black	05W - Light oak (strip)	10W - Wengé (panga panga-wengé)

The shade of the wooden finish in rigid expanded vinyl resin/PVC results slightly different from the film usually applied on the profiles in aluminium.

SKIRTING COVECAP is a series of flexible co-extruded non-toxic vinyl profiles. **SKIRTING COVECAP** is a **SKIRTING/ SKIRTING** with capping seal used to provide an elegant and functional solution to finish the top of resilient floor covering where it has been covered up to the wall, support floor covering at a wall point and protects the exposed edges. The visible portion of the profiles is rounded and available in white - light grey - dark grey - dark brown - brown and black.

SKIRTING COVECAP

NON-TOXIC FLEXIBLE CO-EXTRUDED VINYL RESIN



NON-TOXIC FLEXIBLE CO-EXTRUDED VINYL RESIN - bar length 2,50 lm
Pack H 60 mm / 40 Pcs - H 80 mm / 30 Pcs - H 100 mm / 20 Pcs

Article	H mm	Pcs/Pack.			
BTVCC... 60	60	40			
BTVCC... 80	80	30			
BTVCC... 100	100	20			

Available in the colours: B - GC - GS - T - M - N.



The code of the selected colour must be added to the article code. E.g.: BTVCC... 60 (chosen colour white) BTVCCB 60.

Adhesive version: add the letter A after the article. As regards the items with adhesive, the adhesive roll is sold separately.

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS

1. Select the "SKIRTING COVECAP" of the desired color and height. 2. Using a utility knife cut the "SKIRTING COVECAP" to the desired length. 3. Apply the proper adhesive or glue/mastic and install the profile

ATTENTION: THE INSTALLATION OF THIS PROFILES IS RECOMMENDED FOR AN EXPERT INSTALLER OF VINYL FLOORINGS




COLOURS - FLEXIBLE PART

B - White	GC - Light gray	GS - Dark gray	T - Dark brown	M - Brown	N - Black

PROCAP S is a non-toxic co-extruded flexible vinyl resin profile that in combination with PROSEAL FLEX allows a correct application and finishing of vinyl flooring and carpet along the wall-floor joint. The visible surface of the profile is available in white, light gray, dark gray, dark brown, brown and black. Its ease of application makes it a very practical profile for the finishing of vinyl and carpet flooring

PROCAP S

NON-TOXIC CO-EXTRUDED FLEXIBLE VINYL RESIN



PROCAP S - NON-TOXIC FLEXIBLE CO-EXTRUDED VINYL RESIN
bar length 2,50 - pack. 20 Pcs - 50 lm

Article	H x L mm			
PRCPS...	31 x 5,3			



Available in the colours: B - GC - GS - T - M - N.

The code of the selected colour must be added to the article code. E.g.: PRCPL... (chosen colour white) PRCPLB


PROSEAL FLEX - FLEXIBLE BLACK NON-TOXIC VYNIL RESIN

bar length 2,5 lm - pack. 40 Pcs - 100 lm

Article	L X H mm			
PSF 15-11	15x15			
PSF 20-11	20x20			
PSF 25-11	25x25			




EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROCAP S" according to height and desired colour. 2. Cut "PROCAP S" to the right length. 3. Apply a suitable adhesive and lay the profile. 4. Lay the desired resilient flooring.



COLOURS

PLAIN PRCPS & EMBOSSED PRCL		
B - White	GC - Light gray	GS - Dark gray
T - Dark brown	M - Brown	N - Black



An interpretation of:
Bosjes Chapel, Steyn Studio, CAPE TOWN (South Africa), 2016

PROFILES FOR LAMINATE, PARQUET
AND CARPETED FLOORS



WOODEN/LVT

COLOURS
STANDARD AND ON DEMAND

For a precise assessment of colours request the wooden finishes sample range.
For sample finishes, contact the sales office for minimum quantities, timing and costs.

WOOD COLOURS

wooden finishes	Promutifix	SOL 40P Zero Curve Terminal Pin	Terminal	Style Stair	Style Stair L	LVT	Prowalk	SOL 30	Procover wood	Profixer line	7016	7011	Multiskirting round/square	Skirting 40
04W	*	●	*	*	●	*	*	*	*	●	●	*	*	*
05W	●	●	●	●	●	●	*	●	●	●	●	*	*	*
06W	*	*	*	*	*	*	*	*	*	*	*	*	*	*
07W	●	●	*	●	*	*	*	*	*	●	*	●	*	*
08W	*	*	*	*	*	*	*	*	*	*	*	*	*	*
09W	●	●	●	●	*	●	*	●	*	●	*	●	*	*
10W	*	*	*	*	*	*	*	*	*	*	*	*	*	*
11W	*	*	*	*	*	*	*	*	●	*	*	*	*	*
13W	*	●	*	*	●	●	*	●	*	●	●	*	*	*
18W	●	●	●	●	●	●	*	●	*	●	●	●	*	*
21W	●	●	●	●	●	●	*	●	*	●	●	●	*	*
25W	*	●	*	*	●	●	*	●	*	●	●	*	●	●
28W	*	*	*	*	*	*	*	*	●	*	*	*	*	*
29W	●	●	●	●	●	●	*	●	●	●	●	●	●	●
30W	●	●	●	●	●	●	*	*	●	●	●	●	●	●
31W	●	●	●	●	●	●	*	*	*	●	●	●	*	*
32W	●	●	*	●	●	*	*	*	*	●	●	●	*	*
33W	*	●	*	*	●	●	*	*	*	●	●	*	*	*
34W	●	●	●	●	●	●	*	*	*	●	●	●	●	●
35W	●	●	*	●	●	*	*	*	*	●	●	●	*	*
36W	*	●	*	*	●	●	*	*	*	●	●	*	*	*
37W	●	●	●	●	●	●	*	*	*	●	●	●	*	*
38W	*	●	*	*	●	●	*	*	*	●	●	*	*	*
39W	*	●	*	*	●	●	*	*	*	●	●	*	*	*
40W	*	*	*	*	*	*	*	*	*	*	*	●	*	*
41W	●	●	●	●	●	●	*	*	*	●	●	●	*	*
42W	●	●	●	●	●	●	*	*	*	●	●	●	*	*
43W	*	*	*	*	*	●	*	*	*	*	*	●	*	*
44W	●	●	●	●	●	●	*	*	*	●	●	●	*	*
45W	*	●	*	*	●	●	*	*	*	●	●	*	*	*
46W	●	●	●	●	*	●	*	*	*	●	*	●	*	*
47W	*	*	*	*	*	●	*	*	*	*	*	●	*	*
48W	●	●	*	●	*	●	*	*	*	●	*	●	*	*
49W	●	●	*	●	*	●	*	*	*	●	*	●	*	*
50W	*	*	*	*	*	*	*	*	*	*	*	*	*	*
51W	*	*	*	*	*	*	*	*	*	*	*	*	*	*
52W	*	*	*	*	*	*	*	*	*	*	*	*	*	*
53W	*	●	*	*	●	*	*	*	*	●	●	*	*	*
54W	*	●	*	*	●	*	*	*	*	●	●	*	*	*
55W	*	●	*	*	●	*	*	*	*	●	●	*	*	*
56W	*	*	*	*	*	*	*	*	*	*	*	*	*	*
57W	*	*	*	*	*	*	*	*	*	*	*	*	*	*
58W	*	*	*	*	*	*	*	*	*	*	*	*	*	*

wooden finishes	Promutifix	SOL 40P Zero Curve Terminal Pin	Terminal	Style Stair	Style Stair L	LVT	Prowalk	SOL 30	Procover wood	Profixer line	7016	7011	Multiskirting round/square	Skirting 40
59W	*	*	*	*	*	*	*	*	*	*	*	*	*	*
60W	*	*	*	*	*	*	*	*	*	*	*	*	*	*
61W	*	*	*	*	*	*	*	*	*	*	*	*	*	*
62W	*	*	*	*	*	*	*	*	*	*	*	*	*	*
63W	*	*	*	*	*	*	*	*	*	*	*	*	*	*
64W	*	*	*	*	*	*	*	*	*	*	*	*	*	*
65W	●	●	*	●	*	*	*	*	*	●	*	●	*	*
66W	*	*	*	*	*	*	*	*	*	*	*	*	*	*
67W	*	*	*	*	*	*	*	*	*	*	*	*	*	*
68W	*	*	*	*	*	*	*	*	*	*	*	*	*	*
69W	*	*	*	*	*	*	*	*	*	*	*	*	*	*
70W	*	*	*	*	*	*	*	*	*	*	*	*	*	*
71W	*	*	*	*	*	*	*	*	*	*	*	*	*	*
72W	*	*	*	*	*	*	*	*	*	*	*	*	*	*
73W	●	●	*	●	*	*	*	*	*	●	*	●	*	*
74W	*	*	*	*	*	*	*	*	*	*	*	*	*	*
75W	●	●	*	●	*	*	*	*	*	●	*	●	*	*
76W	*	*	*	*	*	*	*	*	*	*	*	*	*	*
77W	*	*	*	*	*	*	*	*	*	*	*	*	*	*
78W	*	*	*	*	*	*	*	*	*	*	*	*	*	*
79W	*	*	*	*	*	*	*	*	*	*	*	*	*	*
80W	*	*	*	*	*	*	*	*	*	*	*	*	*	*
81W	*	*	*	*	*	*	*	*	*	*	*	*	*	*
82W	*	*	*	*	*	*	*	*	*	*	*	*	*	*
83W	*	*	*	*	*	*	*	*	*	*	*	*	*	*
84W	*	*	*	*	*	*	*	*	*	*	*	*	*	*
85W	*	*	*	*	*	*	*	*	*	*	*	*	*	*
86W	*	*	*	*	*	*	*	*	*	*	*	*	*	*
87W	*	*	*	*	*	*	*	*	*	*	*	*	*	*
88W	*	*	*	*	*	*	*	*	*	*	*	*	*	*
89W	*	*	*	*	*	*	*	*	*	*	*	*	*	*
90W	*	*	*	*	*	*	*	*	*	*	*	*	*	*
91W	*	*	*	*	*	*	*	*	*	*	*	*	*	*
93W	●	*	*	*	*	●	*	*	*	*	*	*	*	*
94W	*	*	*	*	*	*	*	*	*	*	*	*	*	*
95W	*	*	*	*	*	*	*	*	*	*	*	*	*	*
97W	*	*	*	*	*	*	*	*	*	*	*	*	*	*
AA	X	X	X	X	X	X	X	X	*	*	●	●	●	●
B	X	X	X	X	X	X	X	X	X	X	●	●	●	●
N	X	X	X	X	X	X	X	X	X	X	●	*	●	●

● = Available finishes X = Not available finishes
* = minimum order 200 pcs. Production delay 4/5 weeks. Price to be agreed.

WOODEN/LVT

COLOURS
STANDARD AND ON DEMAND

For a precise assessment of colours request the wooden finishes sample range.
For sample finishes, contact the sales office for minimum quantities, timing and costs.

WOOD COLOURS

04W - Dark beech	05W - Light oak (strip)	06W - Dark oak (Walnut)	07W - Light cherry (strip)	08W - Dark cherry (board)	09W - Red walnut	10W - Wengè	11W - Decapè bleached	13W - Indonesian teak
18W - Light zerbano	21W - Oak powder	25W - Bleached fir	28W - Aspen oak	29W - White oak	30W - Grey oak	31W - Victoria oak	32W - Pink oak	33W - Sawed oak
34W - Havana oak	35W - Edinburgh oak	36W - American oak	37W - Carvi oak	38W - Queens oak	39W - Grey elm	40W - Brown oak	41W - Ice oak	42W - Grace oak
43W - Manhattan oak	44W - Honey oak	45W - Marocco oak	46W - Black decapè	47W - Black oak	48W - Cork oak	49W - Sand oak	50W	51W
52W	53W	54W	55W	56W	57W	58W	59W	60W
61W	62W	63W	64W	65W - Tripoli	66W	67W	68W	69W
70W	71W	72W	73W - Bangkok	74W	75W - Liotard	76W	77W	78W
79W	80W	80W	82W	83W	84W	85W	86W	87W
88W	89W	90W	93W - New white	94W	95W	97W		

EXTRUDED EXPANDED PVC COLOURS

B - White	GC - Light grey	GS - Dark grey	N - Black
04W - Dark beech	05W - Light Oak	06W - Dark Oak	07W - Light cherry
08W - Dark cherry	09W - Red Walnut	10W - Wengè	M - Mahogany

Extruded Expanded PVC	Proseal wood	Proangle wood	Skirting	Angle bar
B (White)	●	●	●	●
GC (Light Grey)	●	●	●	●
GS (Dark Grey)	●	●	●	●
N (Black)	●	●	●	●
04W (Dark Beech)	X	X	●	●
05W (Light Oak)	●	●	●	●
06W (Dark Oak)	X	X	●	●
07W (Light cherry)	X	X	●	●
08W (Dark cherry)	X	X	●	●
09W (Red Walnut)	X	X	●	●
10W (Wengè)	●	●	●	●
M (Mahogany)	X	X	●	●

ANODIZED COLOURS

AO - Anod. gold aluminium	AA - Anod. silver aluminium	AB - Anod. bronze aluminium	AT - Anod. titanium aluminium
CH - Anod. champagne alum.	SB - Anod. sand aluminium		

Anodized Aluminium Colours	Promultifix	SOL 40P Zero Curve Terminal Pin	Terminal	Style Stair	Style Stair L	LVT	Prowalk	Prostep ins	SOL 30	Profixer line	Proscrow
AO (anod. gold)	●	●	●	●	●	●	●	●	●	●	●
AA (anod. silver)	●	●	●	●	●	●	●	X	*	●	*
AB (anod. bronze)	●	●	●	●	●	●	●	X	*	●	*
AT (anod. titanium)	*	*	*	*	*	*	*	X	*	*	*
CH (anod. champagne)	*	*	*	*	*	*	*	X	*	*	*
SB (anod. sand)	*	*	*	*	*	*	*	X	*	*	*

● = Available finishes

X = Not available finishes

* = minimum order 200 pcs. Production delay 4/5 weeks. Price to be agreed.

PROMULTIFIX SYSTEM®

INSTRUCTIONS FOR LAYING



PROGRESS PROFILES® has filed an innovative patent PROMULTIFIX SYSTEM® in respect of a wide range of aluminum profiles covered with very strong films in wooden finishes, plus anodized finishes.

The PROMULTIFIX SYSTEM® system is a multipurpose profile for finishing laminate, melamine-coated, parquet and wood floating floors.

FIXING: it can be fixed with adhesive, nylon anchors, glue, flatten down base and screws.

STANDARD Wooden FINISHES: Light oak (strip), Light cherry (strip), Red walnut (merbau-apple-walnut), Light zerbano, Oak powder, White oak, Grey oak, Victoria oak, Pink oak, Havana oak, Edinburgh oak, Carvi oak, Ice oak, Grace oak, Honey oak, Black decapè, Cork oak, Sand oak, Tripoli, Bangkok, Liotard, New white.

STANDARD ALUMINUM FINISHES: anodized Silver, Gold and Bronze.

ANODIZED COLOURS




* ANODIZED COLOURS ON DEMAND




WOODEN COLOURS

(For a precise assessment of colours request the wooden finishes sample range)



* WOODEN COLOURS ON DEMAND




On request it is possible to realize other finishes of the color range: minimum order 200 pcs. Production delay 4/5 weeks. Price to be agreed. For sample finishes, contact the sales office for minimum quantities, timing and costs.

PROMULTIFIX SYSTEM

PROMULTIFIX SYSTEM is composed of an aluminium profile with adhesive, with a lengthwise groove in form of dovetail, where nylon anchors can be inserted, or a punched aluminium flatten down base for an easy and invisible fixing.

NYLON SCREW ANCHORS



PERIMETRIC SUPPORTS



FLATTEN DOWN BASE



LEGNO / LVT


It is a system composed of a special TOP with adhesive, with a visible surface of 44.7 mm, anodized aluminium or covered with wooden film. The aluminium TOP can be fixed to the floor in different ways: with adhesive, with nylon anchors, support with removable spacers, flatten down base.

PROMULTIFIX SYSTEM


ALUMINIUM PROFILES
FIXING KIT




PMPFX... 42090AS / 42A



PMPFX... 42090AS / 42A



PMPFX... 42090AS / 42A + PMFIXBSAN 23



TOP IN ANOD. ALUMINIUM with adhesive (6 finishes of which 3 on demand) n.3 KIT (15 screws, 12 perimeter pins, 6 joints) thermo packed - bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	L mm
PMPFX... 42A	44,7

TOP IN ANOD. ALUMINIUM with adhesive (6 finishes of which 3 on demand) + n.1 KIT (5 screws, 4 perimeter pins, 2 joints) thermo packed - bar length 0,90 lm - 15 Pcs

Article	L mm
PMPFX... 42090AS	44,7

TOP IN ALUM. COVERED with adhesive (80 wooden finishes of which 59 on demand) + n.3 KIT (15 screws, 12 perimeter pins, 6 joints) thermo packed - bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	L mm
PMPFX... 42A	44,7

TOP IN ALUM. COVERED with adhesive (80 wooden finishes of which 59 on demand) + n.1 KIT (5 screws, 4 perimeter pins, 2 joints) thermo packed - bar length 0,90 lm - 15 Pcs


Article	L mm
PMPFX... 42090AS	44,7

Available in the colours: AO - AA - AB (AT, CH and SB on demand with a minimum quantity order of 200 pcs) and in the wooden finishes: 05W - 07W - 09W - 18W - 21W - 29W - 30W - 31W - 32W - 34W - 35W - 37W - 41W - 42W - 44W - 46W - 48W - 49W - 65W - 73W - 75W - 93W. The code of the selected colour must be added to the article code. E.g.: PMPFX... 42A(chosen finish anod. gold) PMPFXAO 42A.

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS

1. Choose the profile of the required finish, if necessary cut the TOP in the required length.
2. Clean, remove the grease and dry the substrate: the temperature should be at least of 15° C.
- Fixing with biadhesive tape:**
3. Remove the paper protection from the adhesive and lay the TOP with a vertical pressure without moving the profile.
- Fixing with screw anchors:**
3. Drill the substrate with a 6 mm bit, 5 holes per linear meter. 4. Remove the paper protection from the adhesive. 5. Insert the screw anchors in the profile dovetail groove. 6. Beat with a rubber/pvc hammer to insert the screw anchors into the holes.
- Fixing of the aluminium flatten down base:**
3. Cut the flatten down base to the requested length. 4. Remove the paper protection from the adhesive. 5. insert the base into the profile groove dovetail, then fix or glue the base to the floor. 6. Make a uniform pressure on the profile with the hands or a rubber hammer.
- Perimetric laying:**
3. Remove the paper protection from the adhesive. 4. Cut the perimetric pins according to the thickness of the floor. 5. Insert the perimetric pins into the profile groove dovetail using 4 supports per linear meter. 6. Fix the profil making a uniform pressure on the profile with the hands, but do not move the profile.

One fixing kit is composed of: 5 screws, 4 perimetric pins, 2 joints




SCREWS AND SCREW ANCHORS, TAP-DOWN BASE

NICKEL - PLATED FLATHEAD SCREWS + SCREW ANCHORS

pack. 1.000 Pcs


Article	Ø mm	L mm
VINIPT 325	3	25



PROFIXER TAP-DOWN BASE - ALUM. PUNCHED/PERFORED

bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H mm
PMFIXBSAN 23	23






PROGRESS® PROFILES has filed an innovative patent PROINSERT SYSTEM in respect of a wide range of aluminum profiles covered with very strong films in 77 wooden finishes are available, plus 6 anodized finishes.

The **PROINSERT SYSTEM** system comprises a complete set of profiles for finishing laminate, melamine-coated, parquet and wood floating floors.

INTERCHANGEABLE INSERTS in 7 heights: (H 07, 09, 11, 13, 15, 17 and 19 mm). **PROFILES COVERED** with film: resistant to wear and UV rays (classe AC1). **TWO VERSATILE VERSIONS OF BASES:** available for fixing with glue or screws.


INSTRUCTIONS FOR LAYING:




1) Choose between the two types of aluminum base.



2) Fix and/or glue the base to the floor.



3) Lay the floor correctly leaving between 3 and 10 mm gap for the natural expansion of the wood.



4) Choose the vinyl resin insert according to the clear height and thickness of the floor.



5) Keep the profile with the groove for insertion facing upwards and slot in the insert from the top downwards (if it does not slide easily, lubricate with water, silicone spray or vegetable oil).



6) Place the profile over the "U" shaped channel.



7) With the help of a wooden tapping block, apply pressure evenly over the whole length of the profile using a hammer. If tapping is done correctly, a "click" will be heard when the profile slots into place.

THESE PROFILES ARE APPLIED TO CREATE:

- Threshold covers and expansion joints (SOL 30, SOL 40P and SOL 50)
- Transition joints for differences in level and floors in differing materials and thickness (ZERO CURVE)
- Perimeter joints or terminal expansion pieces (TERMINAL PIN)
- Corner joints and step nosings (serie STYLE STAIR)

SOL 30, SOL 40P AND SOL 50



ZERO CURVE



TERMINAL PIN



STYLE STAIR / STYLE STAIR L



PROFIXER LINE SYSTEM

The **PROFIXER LINE SYSTEM** comprises an assortment of profiles in aluminum with a longitudinal dovetail groove/channel into which the anchors or the tap-down punched/perforated aluminum profile may be inserted for easy and invisible fixing.

NYLON SCREW ANCHORS



TAP-DOWN BASE



SOL 40P range comprises a large assortment of universal jointing profiles in aluminium covered with film that is highly resistant to pedestrian traffic, wear, UV rays and commonly used floor cleaning products. Thanks to the insert in rigid PVC (non-conducting) between the base and the top, the new **SOL 40P** stops and eliminates electrostatic charges and magnetic fields and whatever else may be transmitted between two floors (e.g.: heated floors). available in wooden finishes, plus anodized finishes. Any insert of height H 7, 9, 11, 13, 15, 17 and 19 mm may be used with either the punched/perforated base for screwing or for gluing. Covering width 40 mm.

SOL 40P

TOP IN WOODEN OR ANODIZED FINISHES
+ PIN INSERT + ALUMINIUM BASE



ALUM. TOP + PIN INSERT + ALUM. BASE 45 PUNCHED/PERFORED
(6 anod. alum. finishes of which 3 on demand) thermo packed
bar length 2,7 lm - pack. 20 Pcs - 54 lm (PIN 17, 19 - 40,5 lm)

Article	H mm
PISPC... 407 (PIN 07)	7 / 10
PISPC... 409 (PIN 09)	9 / 12
PISPC... 4011 (PIN 11)	11 / 14
PISPC... 4013 (PIN 13)	13 / 16
PISPC... 4015 (PIN 15)	15 / 18
PISPC... 4017 (PIN 17)	17 / 20
PISPC... 4019 (PIN 19)	19 / 22

COMPLETE

ALUM. TOP + PIN INSERT + ALUM. BASE 45 PUNCHED/PERFORED
(6 anod. alum. finishes of which 3 on demand) thermo packed
length 0,90 lm - 15 Pcs (PIN 13, 15, 17, 19 - 10 Pcs)



Article	H mm
PISPC... 4079S (PIN 07)	7 / 10
PISPC... 4099S (PIN 09)	9 / 12
PISPC... 40119S (PIN 11)	11 / 14
PISPC... 40139S (PIN 13)	13 / 16
PISPC... 40159S (PIN 15)	15 / 18
PISPC... 40179S (PIN 17)	17 / 20
PISPC... 40199S (PIN 19)	19 / 22



ALUM. TOP COVERED + PIN INSERT + ALUM. BASE 45 PUNCHED/PERFORED
(80 wooden finishes of which 49 on demand) thermo packed
bar length 2,7 lm - pack. 20 Pcs - 54 lm (PIN 17, 19 - 40,5 lm)

Article	H mm
PISPC... 407 (PIN 07)	7 / 10
PISPC... 409 (PIN 09)	9 / 12
PISPC... 4011 (PIN 11)	11 / 14
PISPC... 4013 (PIN 13)	13 / 16
PISPC... 4015 (PIN 15)	15 / 18
PISPC... 4017 (PIN 17)	17 / 20
PISPC... 4019 (PIN 19)	19 / 22

COMPLETE

ALUM. TOP COVERED + PIN INSERT + ALUM. BASE 45 PUNCHED/PERFORED
(80 wooden finishes of which 49 on demand) thermo packed
length 0,90 lm - 15 Pcs (PIN 13, 15, 17, 19 - 10 PCS)




Article	H mm
PISPC... 4079S (PIN 07)	7 / 10
PISPC... 4099S (PIN 09)	9 / 12
PISPC... 40119S (PIN 11)	11 / 14
PISPC... 40139S (PIN 13)	13 / 16
PISPC... 40159S (PIN 15)	15 / 18
PISPC... 40179S (PIN 17)	17 / 20
PISPC... 40199S (PIN 19)	19 / 22


Available in the finishes: AO - AA - AB (AT, CH and SB available on demand with a minimum quantity order of 200 pcs) and in the wooden finishes: 04W - 05W - 07W - 09W - 13W - 18W - 21W - 25W - 29W - 30W - 31W - 32W - 33W - 34W - 35W - 36W - 37W - 38W - 39W - 41W - 42W - 44W - 45W - 46W - 48W - 49W - 53W - 54W - 55W - 65W - 65W - 73W - 75W.

The code of the selected colour must be added to the article code. E.g.: PISPC... 4079S (chosen finish anod. gold) PISPCAO 4079S.


ANODIZED COLOURS



* ANODIZED COLOURS ON DEMAND



WOODEN COLOURS



* WOODEN COLOURS ON DEMAND




On request it is possible to realize other finishes of the color range: minimum order 200 pcs. Production delay 4/5 weeks. Price to be agreed. For sample finishes, contact the sales office for minimum quantities, timing and costs.

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Fix and/or glue the base to the floor. 2. Lay the floor leaving from 3 to 10 mm between the floor and the insert. 3. Choose the desired profile, if necessary cut TOP, PIN and BASE at the needed length and then insert the PIN in the TOP in the specific "dovetail" seat. The position the profile above the U-shaped snap-in seat of the base. 4. With the aid of a board, hammer the TOP to the desired fitting level.




* = Production on demand with minimum quantity of 200 pcs. Production delay 4/5 weeks. Price to be agreed

ZERO CURVE

TOP IN WOODEN FINISHES
AND ANODIZED FINISHES
+ PIN INSERT + ALUMINIUM BASE

The **ZERO CURVE** range comprises a large assortment of terminal transition profiles for joining floors at different levels and with different thickness varying from 7 to 20 mm. wooden finishes are available, plus anodized finishes. There is a profile (top) and an insert (pin) for each height, while the base (punched or perforated) allows fixing by screwing or gluing.



ALUM. TOP + PIN INSERT + ALUM. BASE 45 PUNCHED/PERFORATED
(6 anod. alum. finishes of which 3 on demand) thermo packed
bar length 2,7 lm - pack. 20 Pcs - 54 lm - (PIN 15, 17 - 40,5 lm) (PIN 19 - 27 lm)

Article	H mm
PINZC... 07 (top PINZ... 07 + PIN 07)	7 / 9
PINZC... 11 (top PINZ... 07 + PIN 11)	10 / 12
PINZC... 13 (top PINZ... 09 + PIN 13)	13 / 14
PINZC... 15 (top PINZ... 13 + PIN 15)	14 / 15
PINZC... 17 (top PINZ... 13 + PIN 17)	16 / 17
PINZC... 19 (top PINZ... 15+ PIN 19)	18 / 20

COMPLETE

ALUM. TOP + PIN INSERT + ALUM. BASE 45 PUNCHED/PERFORATED
(6 anod. alum. finishes of which 3 on demand) thermo packed
L. 0,90 lm - 15 Pcs (PIN 13, 15, 17, 19 - 10 Pcs)



Article	H mm
PINZC... 07S (top PINZ... 07 + PIN 07)	7 / 9
PINZC... 11S (top PINZ... 07 + PIN 11)	10 / 12
PINZC... 13S (top PINZ... 09 + PIN 13)	13 / 14
PINZC... 15S (top PINZ... 13 + PIN 15)	14 / 15
PINZC... 17S (top PINZ... 13 + PIN 17)	16 / 17
PINZC... 19S (top PINZ... 15+ PIN 19)	18 / 20

ALUM. TOP COVERED + PIN INSERT + ALUM. BASE 45 PUNCHED/PERFORATED
(80 wooden finishes of which 49 on demand) thermo packed
bar length 2,7 lm - pack. 20 Pcs - 54 lm - (PIN 15, 17 - 40,5 lm) (PIN 19 - 27 lm)

Article	H mm
PINZC... 07 (top PINZ... 07 + PIN 07)	7 / 9
PINZC... 11 (top PINZ... 07 + PIN 11)	10 / 12
PINZC... 13 (top PINZ... 09 + PIN 13)	13 / 14
PINZC... 15 (top PINZ... 13 + PIN 15)	14 / 15
PINZC... 17 (top PINZ... 13 + PIN 17)	16 / 17
PINZC... 19 (top PINZ... 15+ PIN 19)	18 / 20

COMPLETE

ALUM. TOP COVERED + PIN INSERT + ALUM. BASE 45 PUNCHED/PERFORATED
(80 wooden finishes of which 49 on demand) thermo packed
L. 0,90 lm - 15 Pcs (PIN 13, 15, 17, 19 - 10 Pcs)




Article	H mm
PINZC... 07S (top PINZ... 07 + PIN 07)	7 / 9
PINZC... 11S (top PINZ... 07 + PIN 11)	10 / 12
PINZC... 13S (top PINZ... 09 + PIN 13)	13 / 14
PINZC... 15S (top PINZ... 13 + PIN 15)	14 / 15
PINZC... 17S (top PINZ... 13 + PIN 17)	16 / 17
PINZC... 19S (top PINZ... 15+ PIN 19)	18 / 20


Available in the finishes: AO - AA - AB (AT, CH and SB available on demand with a minimum quantity order of 200 pcs) and in the wooden finishes: 04W - 05W - 07W - 09W - 13W - 18W - 21W - 25W - 29W - 30W - 31W - 32W - 33W - 34W - 35W - 36W - 37W - 38W - 39W - 41W - 42W - 44W - 45W - 46W - 48W - 49W - 53W - 54W - 55W - 65W - 73W - 75W.

The code of the selected colour must be added to the article code. E.g.: PINZC... 07S (chosen finish anod. gold) PINZCAO 07S.


ANODIZED COLOURS




* ANODIZED COLOURS ON DEMAND



WOODEN COLOURS



* WOODEN COLOURS ON DEMAND



On request it is possible to realize other finishes of the color range: minimum order 200 pcs. Production delay 4/5 weeks. Price to be agreed. For sample finishes, contact the sales office for minimum quantities, timing and costs.

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS




1. Fix and/or glue the base to the floor. 2. Lay the floor leaving from 3 to 10 mm between the floor and the insert. 3. Choose the desired profile, if necessary cut TOP, PIN and BASE at the needed length and then insert the PIN in the TOP in the specific "dovetail" seat. The position the profile above the U-shaped snap-in seat of the base. 4. With the aid of a board, hammer the TOP to the desired fitting level.



TERMINAL PIN

TOP IN WOODEN FINISHES
AND ANODIZED FINISHES
+ PIN INSERT + ALUMINIUM BASE

The **TERMINAL PIN** series consists in a wide range of terminal/ outer joint squares ideal to realize the connection and junction with floors in laminate or melamine and/or wood/parquet rolled floor. The **TERMINAL PIN** allows the floor underneath to expand for more than 5 / 10 mm. It prevents from the use of the skirting -board and covers perfectly any kind of floor with a minimum thickness of 7 mm and a maximum of 22 mm. It delimitates the floor in proximity of walls, coverings, windows, doors, sliding doors, doormats buss etc.



ALUM. TOP + PIN INSERT + ALUM. BASE 40 PUNCHED/PERFORATED
(6 anod. alum. finishes of which 3 on demand) thermo packed
bar length 2,7 lm - pack. 20 Pcs - 54 lm (PIN 11, 15, 17 - 40,5 lm) (PIN 19 - 27 lm)

Article	H mm		
PINTPC... 07 (PIN 07)	7 / 10		
PINTPC... 09 (PIN 09)	9 / 11		
PINTPC... 11 (PIN 11)	10 / 13		
PINTPC... 13 (PIN 13)	12 / 16		
PINTPC... 15 (PIN 15)	15 / 18		
PINTPC... 17 (PIN 17)	17 / 20		
PINTPC... 19 (PIN 19)	19 / 22		

COMPLETE

ALUM. TOP + PIN INSERT + ALUM. BASE 40 PUNCHED/PERFORATED
(6 anod. alum. finishes of which 3 on demand) thermo packed
L. 0,90 lm - 15 Pcs (PIN 13, 15, 17, 19 - 10 Pcs)



Article	H mm		
PINTPC... 07S (PIN 07)	7 / 10		
PINTPC... 09S (PIN 09)	9 / 11		
PINTPC... 11S (PIN 11)	10 / 13		
PINTPC... 13S (PIN 13)	12 / 16		
PINTPC... 15S (PIN 15)	15 / 18		
PINTPC... 17S (PIN 17)	17 / 20		
PINTPC... 19S (PIN 19)	19 / 22		

ALUM. TOP COVERED + PIN INSERT + ALUM. BASE 40 PUNCHED/PERFORATED
(80 wooden finishes of which 49 on demand) thermo packed
bar length 2,7 lm - pack. 20 Pcs - 54 lm (PIN 11, 15, 17 - 40,5 lm) (PIN 19 - 27 lm)

Article	H mm		
PINTPC... 07 (PIN 07)	7 / 10		
PINTPC... 09 (PIN 09)	9 / 11		
PINTPC... 11 (PIN 11)	10 / 13		
PINTPC... 13 (PIN 13)	12 / 16		
PINTPC... 15 (PIN 15)	15 / 18		
PINTPC... 17 (PIN 17)	17 / 20		
PINTPC... 19 (PIN 19)	19 / 22		

COMPLETE


ALUM. TOP COVERED + PIN INSERT + ALUM. BASE 40 PUNCHED/PERFORATED
(80 wooden finishes of which 49 on demand) thermo packed
L. 0,90 lm - 15 Pcs (PIN 13, 15, 17, 19 - 10 Pcs)




Article	H mm		
PINTPC... 07S (PIN 07)			
PINTPC... 09S (PIN 09)			
PINTPC... 11S (PIN 11)			
PINTPC... 13S (PIN 13)			
PINTPC... 15S (PIN 15)			
PINTPC... 17S (PIN 17)			
PINTPC... 19S (PIN 19)			

Available in the finishes: AO - AA - AB (AT, CH and SB available on demand with a minimum quantity order of 200 pcs) and in the wooden finishes: 04W - 05W - 07W - 09W - 13W - 18W - 21W - 25W - 29W - 30W - 31W - 32W - 33W - 34W - 35W - 36W - 37W - 38W - 39W - 41W - 42W - 44W - 45W - 46W - 48W - 49W - 53W - 54W - 55W - 65W - 73W - 75W.
The code of the selected colour must be added to the article code. E.g.: PINTPC... 07S (chosen finish anod. gold) PINTPCAO 07S.


ANODIZED COLOURS




*ANODIZED COLOURS ON DEMAND



WOODEN COLOURS



* WOODEN COLOURS ON DEMAND



On request it is possible to realize other finishes of the color range: minimum order 200 pcs. Production delay 4/5 weeks. Price to be agreed. For sample finishes, contact the sales office for minimum quantities, timing and costs.

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Fix PINBFTL 40 base at the outer edge/wall.
2. Align the laminate/melamine/wood floor, ensuring that approx. 3/10mm gap is left on each side to accommodate the natural expansion between the floor and the base.
3. Choose the desired profile, if necessary cut TOP, PIN and BASE at the needed length and then insert the PIN in the TOP in the specific "dovetail" seat. The position the profile above the U-shaped snap-in seat of the base.
4. With the aid of a board, hammer the TOP to the desired fitting level.

The **TERMINAL** range comprises a large assortment of perimeter joint or edging profiles in aluminium covered in wooden finishes are available, plus anodized finishes. They are used in various laying situations. Ideal as an edging profile for wood parquet, laminate and melamine-coated floors. They finish the floor where it joins to abutting surfaces, windows, glazed areas, doors, terraces and may also be used for joining two floors: wood/tiles, wood/ carpeting.

TERMINAL

ALUMINIUM COVERED WOODEN FINISHES AND ANODIZED FINISHES



ANODIZED ALUMINIUM (6 anod. alum. finishes of which 3 on demand)
thermo packed - bar length 2,7 lm - pack. 40 Pcs - 108 lm
(H 11 - H 13 - H 15 mm - 80 lm)

Article	H mm
PINT... 07	7
PINT... 09	9
PINT... 11	11
PINT... 13	13
PINT... 15	15

Available in the finishes: AO - AA - AB (AT, CH and SB available on demand with a minimum quantity order of 100 pcs) and in the wooden finishes: 05W-08W-10W-29W-30W-31W-34W-37W-41W-42W.
The code of the selected colour must be added to the article code. E.g.: PINT... 07 (chosen finish anod. gold) PINTAO 07.

ANODIZED ALUM. (6 anod. alum. finishes of which 3 on demand)
thermo packed
bar length 0,90 lm - 20 Pcs - BLISTER PACKS

Article	H mm
PINT... 07S	7 / 8
PINT... 09S	9 / 10
PINT... 11S	11 / 12
PINT... 15S	15 / 16


Available in the finishes: AO - AA - AB (AT, CH and SB available on demand with a minimum quantity order of 100 pcs) and in the wooden finishes: 05W-08W-10W-29W-30W-31W-34W-37W-41W-42W.
The code of the selected colour must be added to the article code. E.g.: PINT... 07S (chosen finish anod. gold) PINTAO 07S.

ALUMINIUM COVERED (80 wooden finishes of which 70 on demand)
thermo packed - bar length 2,7 lm - pack. 20 Pcs - 54 lm
(H 11 - H 15 mm - 80 lm)

Article	H mm
PINT... 09	9
PINT... 11	11
PINT... 15	15

ALUMINIUM COVERED (80 wooden finishes of which 70 on demand)
thermo packed
bar length 0,90 lm - 20 Pcs - BLISTER PACKS

Article	H mm
PINT... 09S	9 / 10
PINT... 11S	11 / 12
PINT... 15S	15 / 16




EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS




1. Choose the **TERMINAL** according to the required height and finish and fix with screws and screw anchors or with glue/silicone; the profile must be placed next to the abutting surface e.g. wall, glazing, etc. 2. Align the laminate/melamine/wood floor, ensuring that a large enough gap is left to accommodate the natural expansion between the floor and the profile (approx. 3/10mm on one side).


ANODIZED COLOURS



* ANODIZED COLOURS ON DEMAND



WOODEN COLOURS




* WOODEN COLOURS ON DEMAND



STYLE STAIR

TOP IN WOODEN FINISHES
and ANODIZED FINISHES
+ PIN INSERT + ALUMINIUM BASE

The **STYLE STAIR** range comprises a large assortment of aluminium step nosing profiles for the edges of steps in wood, parquet, laminate or melamine with thickness varying from 7 to 20 mm. Wooden finishes are available, plus anodized finishes. Select the most suitable profile for the thickness of the floor. There is a profile (top) and an insert (pin) for each height, while the base (punched or perforated) allows fixing by screwing or gluing.



ALUM. TOP + PIN INSERT + ALUM. BASE 40 PUNCHED/PERFORATED (6 anod. alum. finishes of which 3 on demand) thermo packed bar length 2,7 lm - pack. 20 Pcs - 54 lm (H 14 - H 16 - H 18 mm - 40,5 lm)

Article	H mm		
PINYC... 07 (PIN 07)	7 / 9		
PINYC... 09 (PIN 09)	10 / 12		
PINYC... 11 (PIN 11)	13 / 14		
PINYC... 13 (PIN 13)	14 / 15		
PINYC... 15 (PIN 15)	16 / 17		
PINYC... 17 (PIN 17)	18 / 20		

COMPLETE




ALUM. TOP COVERED + PIN INSERT + ALUM. BASE 40 PUNCHED/PERFORATED (80 wooden finishes of which 60 on demand) thermo packed bar length 2,7 lm - pack. 20 Pcs - 54 lm (H 14 - H 16 - H 18 mm - 40,5 lm)

Article	H mm		
PINYC... 07 (PIN 07)	7 / 9		
PINYC... 09 (PIN 09)	10 / 12		
PINYC... 11 (PIN 11)	13 / 14		
PINYC... 13 (PIN 13)	14 / 15		
PINYC... 15 (PIN 15)	16 / 17		
PINYC... 17 (PIN 17)	18 / 20		

COMPLETE

Available in the finishes: AO - AA - AB (AT, CH and SB available on demand with a minimum quantity order of 200 pcs) and in the wooden finishes: 05W - 07W - 09W - 18W - 21W - 29W - 30W - 31W - 32W - 34W - 35W - 37W - 41W - 42W - 44W - 46W - 48W - 49W - 65W - 73W - 75W. The code of the selected colour must be added to the article code. E.g.: PINYC... 07 (chosen finish anod. gold) PINYCAO 07.

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS




TOP IN ANODIZED FINISHES

TOP IN WOODEN FINISHES

1. Fix the base exactly over the stair riser.
2. Align the laminate/melamine/wood floor, ensuring that approx. 3/10mm gap is left on one side to accommodate the natural expansion between the floor and the base.
3. Choose the desired profile, if necessary cut TOP, PIN and BASE at the needed length and then insert the PIN in the TOP in the specific "dovetail" seat. The position the profile above the U-shaped snap-in seat of the base.
4. With the aid of a board, hammer the TOP to the desired fitting level.

ANODIZED COLOURS



* ANODIZED COLOURS ON DEMAND



WOODEN COLOURS



* WOODEN COLOURS ON DEMAND



On request it is possible to realize other finishes of the color range: minimum order 200 pcs. Production delay 4/5 weeks. Price to be agreed. For sample finishes, contact the sales office for minimum quantities, timing and costs.

STYLE STAIR L comprises a large range of aluminium stair nosing protecting profiles for step in timber, parquet, laminate or melamine material with thickness varying from 7 to 20 mm. wooden finishes are available, plus anodized finishes. The profiles are made with 3 pcs. A natural aluminium base to screw or glue to the pavement, a PIN in non-toxic rigid to insert in the TOP, then a TOP should be selected most suitable for the floor.

STYLE STAIR L

TOP IN WOODEN FINISHES
AND ANODIZED FINISHES
+ PIN INSERT + ALUMINIUM BASE



ALUM. TOP + PIN INSERT + ALUM. BASE 40 PUNCHED/PERFORATED
(6 anod. alum. finishes of which 3 on demand) thermo packed
bar length 2,7 lm - pack. 20 Pcs - 54 lm (H 14 - H 16 - H 18 mm - 40,5 lm)


Article	H mm
PINYLC... 07 (PIN 07)	7 / 9
PINYLC... 09 (PIN 09)	10 / 12
PINYLC... 11 (PIN 11)	13 / 14
PINYLC... 13 (PIN 13)	14 / 15
PINYLC... 15 (PIN 15)	16 / 17
PINYLC... 17 (PIN 17)	18 / 20

COMPLETE


Available in the finishes: AO - AA - AB (AT, CH and SB available on demand with a minimum quantity order of 200 pcs) and in the wooden finishes: 04W - 05W - 13W - 18W - 21W - 25W - 29W - 30W - 31W - 32W - 33W - 34W - 35W - 36W - 37W - 38W - 39W - 41W - 42W - 44W - 45W - 58W - 54W - 55W.

The code of the selected colour must be added to the article code. E.g.: PINYLC... 07 (chosen finish anod. gold) PINYLCAO 07.

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS









TOP IN ANODIZED FINISHES



TOP IN WOODEN FINISHES


1. Fix the base exactly over the stair riser. 2. Align the laminate/melamine/wood floor, ensuring that approx. 3/10mm gap is left on one side to accommodate the natural expansion between the floor and the base. 3. Choose the desired profile, if necessary cut TOP, PIN and BASE at the needed length and then insert the PIN in the TOP in the specific "dovetail" seat. The position the profile above the U-shaped snap-in seat of the base. 4. With the aid of a board, hammer the TOP to the desired fitting level.



transition profiles

COMPLETE

ANODIZED COLOURS




* ANODIZED COLOURS ON DEMAND



WOODEN COLOURS



* WOODEN COLOURS ON DEMAND



On request it is possible to realize other finishes of the color range: minimum order 200 pcs. Production delay 4/5 weeks. Price to be agreed. For sample finishes, contact the sales office for minimum quantities, timing and costs.

* = Production on demand with minimum quantity of 200 pcs. Production delay 4/5 weeks. Price to be agreed



UNIVERSAL, CONNECTION AND PERIMETER JOINTS



SOL 30P (Page 244)



ZERO CURVE (Page 244)



TERMINAL PIN (Page 244)

CONNECTION JOINTS



**PROINTER KL
ACC / ALL** (Page 30-32)



**PROSHELL D
ALL** (Page 159)



**PROSHELL R
ALL** (Page 159)



PROLEVALL 305
(Page 80)



PROLINOLEUM
(Page 85)



PROFLOOR 24
(Page 85)



**PROSLIDER KL
ALL** (Page 86)



**PROCOVER
1045 ALL** (Page 86)

STAIR NOSINGS PROFILES



PROSTYLE KL 10 (Page 161)




PROSTAIR KL 20 (Page 161)

LVT PROFILES - SOL 30P

AWOODEN FINISHES and ANODIZED FINISHES

SOL 30P, ZERO CURVE AND TERMINAL PIN are profile which serve as expansion joints, junction and as perimetrical expansion joint between different floors in vinyl. The profiles are composed of a **BASE** in PVC to fix to the support and of three **TOP**. The choice of the **TOP** depend on the desired application. Their particular section, together with the wide range of finishes available and the ease of installation, make them a much-sought profiles, that could be easily matched with every type of floor in vinyl.



INSTRUCTIONS FOR LAYING METHODS

1. Choose SOL P / ZERO CURVE / TERMINAL PIN according to the desired finish. 2. Cut the BASE in vinyl resin/PVC to the desired length and fix it with adhesive or dowels to the support. 3. Lay the floor in vinyl, leaving a 5 mm joint between the vertical walls of the base in vinyl resin/PVC and the floor. 4. Cut the desired TOP in aluminium to the desired length. 5. Place a small wooden board on the TOP in aluminium and hammer equally in order to facilitate the insertion of the TOP into the pvc base.



ALUMINIUM TOP 6 anod. finishes (3 on demand) + **BASE** (vinyl resin/PVC) -thermo packed - bar length **2,7 lm** - pack. **20 Pcs - 54 lm**

Article	L mm
PISPC... 3046	30

The code of the selected colour must be added to the article code. E.g.: PISPC... 3046 (chosen finish anod. gold) PISPCAO 3046.

ALUMINIUM TOP 80 wooden finishes (56 on demand) + **BASE** (vinyl resin/PVC) -thermo packed - bar length **2,7 lm** - pack. **20 Pcs - 54 lm**

Article	L mm
PISPC... 3046	30


The code of the selected colour must be added to the article code. E.g.: PISPC... 3046 (chosen finish anod. gold) PISPCAO 3046.

ALUMINIUM TOP (anod. silver) + **BASE** (vinyl resin/PVC) -thermo packed - bar length **2,7 lm** - pack. **20 Pcs - 54 lm**

Article	L mm
PISPCAA 4046	40

LVT PROFILES - ZERO CURVE

WOODEN FINISHES and ANODIZED FINISHES



ALUMINIUM TOP (anod. silver) + **BASE** (vinyl resin/PVC) -thermo packed - bar length **2,7 lm** - pack. **20 Pcs - 54 lm**

Article	L mm
PINZCAA 3246	32

ALUMINIUM TOP 6 anod. finishes (3 on demand) + **BASE** (vinyl resin/PVC) -thermo packed - bar length **2,7 lm** - pack. **20 Pcs - 54 lm**

Article	L mm
PINZC... 2646	26

The code of the selected colour must be added to the article code. E.g.: PINZC... 2646 (chosen finish anod. gold) PINZCAO 2646.


ALUMINIUM TOP 80 wooden finishes (56 on demand) + **BASE** (vinyl resin/PVC) -thermo packed - bar length **2,7 lm** - pack. **20 Pcs - 54 lm**

Article	L mm
PINZC... 2646	26

The code of the selected colour must be added to the article code. E.g.: PINZC... 2646 (chosen finish anod. gold) PINZCAO 2646.

LVT PROFILES - TERMINAL PIN

WOODEN FINISHES and ANODIZED FINISHES



ALUMINIUM TOP (anod. silver) + **BASE** (vinyl resin/PVC) -thermo packed - bar length **2,7 lm** - pack. **20 Pcs - 54 lm**

Article	L mm
PINTPCAA 2546	25

ALUMINIUM TOP 6 anod. finishes (3 on demand) + **BASE** (vinyl resin/PVC) -thermo packed - bar length **2,7 lm** - pack. **20 Pcs - 54 lm**

Article	L mm
PINTPC... 1946	19

The code of the selected colour must be added to the article code. E.g.: PINTPC... 1946 (chosen finish anod. gold) PINTPCAO 1946.

ALUMINIUM TOP 80 wooden finishes (56 on demand) + **BASE** (vinyl resin/PVC) -thermo packed - bar length **2,7 lm** - pack. **20 Pcs - 54 lm**

Article	L mm
PINTPC... 1946	19

The code of the selected colour must be added to the article code. E.g.: PINTPC... 1946 (chosen finish anod. gold) PINTPCAO 1946.

COLOURS

(For a precise assessment of colours request the wooden finishes sample range)


ANODIZED									
ON DEMAND - MINIMUM QUANTITY 200 PCS									
AO - Anod. gold aluminium	AA - Anod. silver aluminium	AB - Anod. bronze aluminium	AT - Anod. titanium aluminium	CH - Anod. champagne alum.	SB - Anod. sand aluminium				
05W - Light oak (strip)	09W - Red walnut (merbau-apple-walnut)	13W - Indonesian teak	18W - Light zerbano	21W - Oak powder	25W - Bleached fir	29W - White oak	30W - Grey oak	31W - Victoria oak	
33W - Sawed oak	34W - Havana oak	36W - American oak	37W - Canvi oak	38W - Queens oak	39W - Grey elm	41W - Ice oak	42W - Grace oak	43W - Manhattan oak	
44W - Honey oak	45W - Morocco oak	46W - Black decape	47W - Black oak	48W - Cork oak	49W - Sand oak	93W - New white			

On request it is possible to realize other finishes of the color range: minimum order 200 pcs. Production delay 4/5 weeks. Price to be agreed. For sample finishes, contact the sales office for minimum quantities, timing and costs.

PROWALK 2510 & 2520 are new stair-nosing profiles for existing stairways. Designed to protect and restore stair steps made of wood, laminate, ceramic, etc. Made with anodized aluminium and wooden finishes. Available in self-adhesive or perforated versions. Sizes available: 2.7 m lengths and 0.9 m & 1.35 m Self-Pack.

PROWALK 2510 & 2520

ANODIZED ALUMINIUM AND WOODEN FINISHES
PUNCHED OR SELF ADHESIVE



stair nosing profiles

ANODIZED ALUMINIUM with adhesive thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	L x H mm		
PWK... 2510A	24 x 10		
PWK... 2520A	24 x 20		

ANODIZED ALUMINIUM with adhesive thermo packed - bar length 0,90 lm - pack. 20 Pcs



Article	L x H mm		
PWK... 25109AS	24 x 10		
PWK... 25209AS	24 x 20		

ANODIZED ALUMINIUM punched thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	L x H mm		
PWK... 2510F	24 x 10		
PWK... 2520F	24 x 20		

ANOD. ALUM. PUNCHED with screws and screw anchors thermo packed - bar length 0,90 lm - pack. 20 Pcs



Article	L x H mm		
PWK... 25109FS	24 x 10		
PWK... 25209FS	24 x 20		

ANOD. ALUM. PUNCHED with screws and screw anchors thermo packed - bar length 1,35 lm - pack. 20 Pcs



Article	L x H mm		
PWK... 251013FS	24 x 10		


Available in the colours: AO - AA - AB (AT, CH and SB available on demand with a minimum quantity order of 200 pcs). The code of the selected colour must be added to the article code. E.g.: PWK... 2510A (chosen finish anod. silver) PWKAA 2510A.

ALUMINIUM WOOD FINISH with adhesive thermo packed - bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	L x H mm		
PWK... 2510A	24 x 10		
PWK... 2520A	24 x 20		

Available on demand in the colours: 04W - 05W - 07W - 09W - 13W - 18W - 21W - 25W - 29W - 30W - 31W - 32W - 33W - 34W - 35W - 36W - 37W - 38W - 39W - 41W - 42W - 44W - 45W - 46W - 48W - 49W - 53W - 54W - 55W - 65W - 73W - 75W with a minimum quantity order of x pcs. The code of the selected colour must be added to the article code. E.g.: PWK... 2510A (chosen finish dark beech) PWK04 2510A.



EXAMPLES OF LAYING



PROSTEP INS is a step cover profile in silver anodized aluminium ideal for protecting and laying laminated wood / floating melaminic and parquets. Available in two heights 10.5 and 16.

PROSTEP INS

ANODIZED SILVER ALUMINIUM




stair nosing profiles

ANODIZED SILVER ALUMINIUM thermo packed
bar length 2,7 lm - pack. 40 Pcs - 108 lm


Article	H mm		
PTSAA 105	10,2		
PTSAA 16	15,9		

COLOURS



AA - Anod. silver aluminium

EXAMPLES OF LAYING




* = Production on demand with minimum quantity of 200 pcs. Production delay 4/5 weeks. Price to be agreed.

SOL 30 SELF-ADHESIVE


ALUMINIUM COVERED WITH PROTECTIVE FILM
IN WOODEN FINISHES

SOL 30 self-adhesive is a joint/threshold cover profile in aluminum covered with film wooden finishes, which is highly resistant to pedestrian traffic, wear, UV rays and commonly used floor cleaning products. Easy to lay and to match with any wood finish; the surface has an open pore embossed finish. Recommended for covering joints between floors in laminate, wood, ceramic tiles, etc.

threshold - joint-cover profiles



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the adhesive "SOL 30" in the required finish. 2. Cut the profile to the required length and clean, degrease and dry the surface, checking that the temperature for application is at least 15°. 3. Remove the protective paper from the adhesive and lay the profile correctly applying a uniform vertical pressure by hand without moving the profile and without using iron/steel hammers.



ALUMINIUM COVERED 80 wooden finishes (71 on demand) with ADHESIVE thermo packed - length 30 mm - bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	L mm
PINS...30A	30

Available in the wooden finishes: 04W - 05W - 07W - 08W - 09W - 10W - 11W - 28W - 29W - 30W.

The code of the selected colour must be added to the article code. E.g.: PINS... 30A (chosen finish dark beech) PINZ04W 30A.



ALUMINIUM COVERED 80 wooden finishes (71 on demand) with ADHESIVE - thermo packed - bar length 0,90 lm - 20 Pcs


Article	L mm
PINS...309AS	30

ZERO CURVE SELF-ADHESIVE


ALUMINIUM COVERED WITH WOODEN FINISHES
AND ANODIZED ALUMINIUM

ZERO CURVE self-adhesive is a transition profile in anodised aluminum and aluminum covered with film in wooden finishes, which is highly resistant to pedestrian traffic, wear, UV rays and commonly used floor cleaning products. Easy to lay and to match with any wood finish; the surface has an open pore embossed finish. Recommended for covering joints between floors in laminate, wood, ceramic tiles, etc.

transition profiles



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the "ZERO CURVE" with adhesive with the required finish. 2. Cut the profile to the required length and clean, degrease and dry the surface, checking that the temperature for application is at least 15°. 3. Remove the protective paper from the adhesive and lay the profile correctly applying a uniform vertical pressure by hand without moving the profile and without using an iron/steel hammer.



ALUMINIUM COVERED 80 wooden finishes (49 on demand) with ADHESIVE thermo packed - length 40 mm - bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	L mm
PINZ...07A	40
PINZAA 07A	40

Available in the finish: AA - 04W - 05W - 07W - 09W - 13W - 18W - 21W - 25W - 29W - 30W - 31W - 32W - 33W - 34W - 35W - 36W - 37W - 38W - 39W - 41W - 42W - 44W - 45W - 46W - 48W - 49W - 53W - 54W - 55W - 65W - 73W - 75W.

The code of the selected colour must be added to the article code. E.g.: PINZ... 07A (chosen finish dark beech) PINZ04W 07A.



ALUMINIUM COVERED 80 wooden finishes (49 on demand) with ADHESIVE thermo packed - bar length 0,90 lm - 20 Pcs

Article	L mm
PINZ...079AS	40

COLOURS

ANODIZED



AA - Anod. silver aluminium

04W - Dark beech	05W - Light oak (strip)	07W - Light cherry (strip)	09W - Red walnut (merbau-apple-walnut)	13W - Indonesian teak	18W - Light zerbano	21W - Oak powder	25W - Bleached fir	29W - White oak
30W - Grey oak	31W - Victoria oak	32W - Pink oak	33W - Sawed oak	34W - Havana oak	35W - Edinburgh oak	36W - American oak	37W - Carvi oak	38W - Queens oak
39W - Grey elm	41W - Ice oak	42W - Grace oak	44W - Honey oak	45W - Marocco oak	46W - Black decape'	48W - Cork oak	49W - Sand oak	53W
54W	55W	65W - Tripoli	73W - Bangkok	75W - Liotard				

On request it is possible to realize other finishes of the color range: minimum order 200 pcs. Production delay 4/5 weeks. Price to be agreed. For sample finishes, contact the sales office for minimum quantities, timing and costs.

(For a precise assessment of colours request the wooden finishes sample range)

SOL 40P self-adhesive is a joint/threshold cover profile in aluminum covered with film in wooden finishes, which is highly resistant to pedestrian traffic, wear, UV rays and commonly used floor cleaning products. Easy to lay and to match with any wood finish; the surface has an open pore embossed finish. Recommended for covering joints between floors in laminate, wood, ceramic tiles, etc.



SILVER ANODIZED ALUMINUM with ADHESIVE thermo packed - length 40 mm - bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	L mm
PNSPAA 40 PA	40

ALUMINIUM COVERED 80 wooden finishes (49 on demand) with ADHESIVE thermo packed - length 40 mm - bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	L mm
PNSP.. 40 PA	40

Available in the colours: 04W - 05W - 07W - 09W - 13W - 18W - 21W - 25W - 29W - 30W - 31W - 32W - 33W - 34W - 35W - 36W - 37W - 38W - 39W - 41W - 42W - 44W - 45W - 46W - 48W - 49W - 53W - 54W - 55W - 65W - 73W - 75W.
The code of the selected colour must be added to the article code. E.g.: PNSP... 40 PA (chosen finish dark beech) PNSP04W 40 PA.

SILVER ANODIZED ALUMINUM with ADHESIVE thermo packed - bar length 90 cm - pack. 20 Pcs

Article	L mm
PNSPAA 409 PAS	40

ALUMINIUM COVERED 80 wooden finishes (49 on demand) with ADHESIVE - thermo packed - bar length 0,90 lm - 20 Pcs

Article	L mm
PNSP.. 409 PAS	40

ALUMINIUM COVERED 80 wooden finishes (49 on demand) with ADHESIVE - thermo packed - bar length 1 lm - 20 Pcs


Article	L mm
PNSPAA 4010 PAS	40

SILVER ANODIZED ALUMINUM with ADHESIVE - thermo packed - bar length 1 lm - 20 Pcs


Article	L mm
PNSP.. 4010 PAS	40

SOL 40P SELF-ADHESIVE

ALUMINIUM COVERED WOODEN FINISHES



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the adhesive "SOL 40" in the required finish. 2. Cut the profile to the required length and clean, degrease and dry the surface, checking that the temperature for application is at least 15°. 3. Remove the protective paper from the adhesive and lay the profile correctly applying a uniform vertical pressure by hand without moving the profile and without using iron/steel hammers.

threshold - joint-cover profiles


PROCOVER WOOD is a joint-cover profile in aluminum covered with a very strong film available in wooden finishes. It is applied at the end of laying two adjoining floors with the same height, having left a 6 - 24 mm gap between the two floors set in a thin bed of adhesive. It protects the outside edges of the floor/covering. It is easy to lay and attractive. The design of the profile with lower vertical arrowhead part allows excellent anchorage with the silicone/adhesive.



ALUMINIUM COVERED 80 wooden finishes (76 on demand) thermo packed - bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	L x H mm
PCRA... 149	14 x 9
PCRA... 269	26 x 9

COLOURS




On request it is possible to realize other finishes of the color range: minimum order 200 pcs. Production delay 4/5 weeks. Price to be agreed. For sample finishes, contact the sales office for minimum quantities, timing and costs.




Available in the wooden finishes: 05W - 11W - 28W - 29W - 30W.
The code of the selected colour must be added to the article code.
Es.: PCRA.. 149 (chosen finish light oak) PCRA04W 149.

PROCOVER WOOD

ALUMINIUM COVERED WITH PROTECTIVE FILM IN WOODEN FINISHES



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the "PROCOVER" with the width suitable for the gap between the two floors to be joined, taking into consideration 2/3 mm - 2/32" - 1/8" side lap. 2. Fill the gap with single-pack silicone or with the adhesive used for laying the floor. 3. Bury the profile into the adhesive, making sure that both side laps of the profile rest on the coverings to be joined.

threshold - joint-cover profiles

PROCOVER INSERT

VINYL RESIN / BLACK RUBBER


Vinyl resin/rubber profile "U-form" for inserting PROCOVER with PINBFT 45 or PINBFT 40 Proinsert System base.

VINYL RESIN / RUBBER
length 2,7 lm and/or in rolls

Article
PCPCR

PROINSERT BASE 45 and BASE 40 - ALUM. PUNCHED/PERFORED
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H mm
PINBFT 45	45
PINBFT 40	40






PROFIXER LINE SYSTEM

ZERO CURVE INSERTS + NYLON ANCHORS + BASE
WOODEN FINISHES AND ANODIZED FINISHES

The **PROFIXER LINE SYSTEM** comprises an assortment of profiles in aluminium with a longitudinal dovetail groove/channel into which the anchors or the tap-down punched/perforated aluminium profile may be inserted for easy and invisible fixing.

The profiles are covered with wooden finishes that are highly resistant to pedestrian traffic, wear, UV rays and commonly used floor cleaning products. Plus anodized finishes. The **PROFIXER LINE SYSTEM** profiles are recommended for floors up to 22.5 mm thick.



ANODIZED ALUMINIUM (6 anod. alum. finishes of which 3 on demand)
thermo packed - bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	L mm	H mm
PINZ... 07	40	7 - 13
PINZ... 13	47	15 - 17

Available in the finishes: AO - AA - AB (AT, CH and SB available on demand with a minimum quantity order of 100 pcs) and in the wooden finishes: 04W - 05W - 07W - 09W - 13W - 18W - 21W - 25W - 29W - 30W - 31W - 32W - 33W - 34W - 35W - 36W - 37W - 38W - 39W - 41W - 42W - 44W - 45W - 46W - 48W - 49W - 53W - 54W - 55W - 65W - 73W - 75W.

The code of the selected colour must be added to the article code. E.g.: PINZ... 07 (chosen finish anod. gold) PINZAO 07.

ALUMINIUM COVERED (80 wooden finishes of which 49 on demand)
thermo packed - bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	L mm	H mm
PINZ... 07	40	7 - 13
PINZ... 13	47	15 - 17

ANODIZED ALUMINIUM (6 anod. alum. finishes of which 3 on demand)
thermo packed - bar length 0,90 lm - 20 Pcs
with 5 anchors

Article	L mm	H mm
PINZ... 07S	40	7 - 13
PINZ... 13S	47	15 - 17


Available in the finishes: AO - AA - AB (AT, CH and SB available on demand with a minimum quantity order of 100 pcs) and in the wooden finishes: 04W - 05W - 07W - 09W - 13W - 18W - 21W - 25W - 29W - 30W - 31W - 32W - 33W - 34W - 35W - 36W - 37W - 38W - 39W - 41W - 42W - 44W - 45W - 46W - 48W - 49W - 53W - 54W - 55W - 65W - 73W - 75W.

The code of the selected colour must be added to the article code. E.g.: PINZ... 07 (chosen finish anod. gold) PINZAO 07.

ALUMINIUM COVERED (80 wooden finishes of which 49 on demand)
thermo packed - bar length 0,90 lm - 20 Pcs
with 5 anchors

Article	L mm	H mm
PINZ... 07S	40	7 - 13
PINZ... 13S	47	15 - 17

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



- Choose the PROFIXER LINE SYSTEM profile in the required type and finish.
- Cut the profile to the required length.
- For the version with screw anchors:** make 5 drill holes per linear metre on the floor using a Ø 7mm drill, insert the anchors into the relative groove/channel of the profile and with the help of a rubber/plastic hammer, tap evenly over the surface until the anchor slots into the hole.
- For the version with tap-down aluminium base:** first insert the base into the groove/channel of the "TOP" profile and then fix or glue the base to the floor; alternatively first fix or glue the base to the floor and then insert the 'profile'.
- Close the profile, applying uniform pressure, either manually or with the help of a rubber hammer.

COLOURS

(For a precise assessment of colours request the wooden finishes sample range)

ANODIZED								
ON DEMAND - MINIMUM QUANTITY 200 PCS								
AO - Anod. gold aluminium	AA - Anod. silver aluminium	AB - Anod. bronze aluminium	AT - Anod. titanium aluminium	CH - Anod. champagne alum.	SB - Anod. sand aluminium			
04W - Dark beech	05W - Light oak (strip)	07W - Light cherry (strip)	09W - Red walnut (merbau-apple-walnut)	13W - Indonesian teak	18W - Light zerbano	21W - Oak powder	25W - Bleached fir	29W - White oak
30W - Grey oak	31W - Victoria oak	32W - Pink oak	33W - Sawn oak	34W - Havana oak	35W - Edinburgh oak	36W - American oak	37W - Carvi oak	38W - Queens oak
39W - Grey elm	41W - Ice oak	42W - Grace oak	44W - Honey oak	45W - Morocco oak	46W - Black decapè'	48W - Cork oak	49W - Sand oak	53W
54W	55W	65W - Tripoli	73W - Bangkok	75W - Liotard				


On request it is possible to realize other finishes of the color range: minimum order 200 pcs. Production delay 4/5 weeks. Price to be agreed. For sample finishes, contact the sales office for minimum quantities, timing and costs.

NYLON 36 SCREW ANCHORS AND TAP-DOWN BASE

SCREW ANCHORS 36 - H 36 mm - pack. 20 Pcs
for SOL 30-40-50 and ZERO CURVE 07-15


Article	H mm
TAS 36	36

minimum order 5 pcs.



PROFIXER TAP-DOWN BASE - ALUM. PUNCHED/PERFORED
for SOL 30-40-50 and ZERO CURVE 07-15
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H mm
PMFIXBSAN 23	23




The **PROFIXER LINE SYSTEM** comprises an assortment of profiles in aluminium with a longitudinal dovetail groove/channel into which the anchors or the tap-down punched/perforated aluminium profile may be inserted for easy and invisible fixing.

The profiles are covered with wooden finishes that are highly resistant to pedestrian traffic, wear, UV rays and commonly used floor cleaning products. Plus six anodized finishes (3 available on demand). The **PROFIXER LINE SYSTEM** profiles are recommended for floors up to 22.5 mm thick.


PROFIXER LINE SYSTEM

INSERTS SOL 30 - SOL 40P - SOL 50
+ NYLON ANCHORS + BASE



ANODIZED ALUMINIUM (6 anod. alum. finishes of which 3 on demand)
thermo packed - bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	L mm		
PINS... 30	30		
PNSP... 40P	40		


ANODIZED ALUM. (6 anod. alum. finishes of which 3 on demand)
thermo packed - bar length 0,90 lm - 20 Pcs with 5 anchors 

Article	L mm		
PINS... 309S	30		

Available in the colours: AO - AA - AB (AT, CH and SB on demand with a minimum quantity order of 200 pcs)

ALUMINIUM COVERED (80 wooden finishes of which 71 on demand)
thermo packed - bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	L mm		
PINS... 30	30		

ALUM. COVERED (80 wooden finishes of which 71 on demand)
thermo packed - bar length 0,90 lm - 20 Pcs with 5 anchors 

Article	L mm		
PINS... 309S	30		

Available in the wooden finishes: 04W - 05W - 07W - 08W - 09W - 10W - 11W - 28W - 29W - 30W.
The code of the selected colour must be added to the article code.
E.g.: PINS...30 (chosen finish dark beech) PINS04W 30.




ALUMINIUM COVERED (80 wooden finishes of which 49 on demand)
thermo packed - bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	L mm		
PNSP... 40 P	40		

Available in the colours: 04W - 05W - 07W - 09W - 13W - 18W - 21W - 25W - 29W - 30W - 31W - 32W - 33W - 34W - 35W - 36W - 37W - 38W - 39W - 41W - 42W - 44W - 45W - 46W - 48W - 49W - 53W - 54W - 55W - 65W - 73W - 75W.
The code of the selected colour must be added to the article code.
E.g.: PINS... 30 (chosen finish anod. gold) PINSAO 30.

ANODIZED SILVER ALUMINIUM
thermo packed - bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	L mm		
PINSAA 50	50		




NYLON 36 SCREW ANCHORS AND TAP-DOWN BASE

SCREW ANCHORS 36 - H 36 mm - pack. 20 Pcs
for SOL 30-40-50 and ZERO CURVE 07-15


Article	H mm		
TAS 36	36		

minimum order 5 pcs.




PROFIXER TAP-DOWN BASE - ALUM. PUNCHED/PERFORATED
for SOL 30-40-50 and ZERO CURVE 07-15
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H mm		
PMFIXBSAN 23	23		



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the PROFIXER LINE SYSTEM profile in the required type and finish. 2. Cut the profile to the required length.

For the version with screw anchors:

3. Make 5 drill holes per linear metre on the floor using a Ø 7mm drill, insert the anchors into the relative groove/channel of the profile and with the help of a rubber/plastic hammer, tap evenly over the surface until the anchor slots into the hole.


For the version with tap-down aluminium base:

3. First insert the base into the groove/channel of the "TOP" profile and then fix or glue the base to the floor; alternatively first fix or glue the base to the floor and then insert the profile. 4. Close the profile, applying uniform pressure, either manually or with the help of a rubber hammer.

PROSCREW 34

ANODIZED SILVER, GOLD, BRONZE, SAND AND CHAMPAGNE ALUMINIUM

universal joints with screw



BASE + TOP IN ANODIZED SILVER, GOLD, BRONZE, SAND AND CHAMPAGNE ALUMINIUM + SCREWS AND SCREW ANCHORS thermo packed - bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	L mm		
PSWCAA 34	34		
PSWCAO 34	34		
PSWCSB 34	34		
PSWCAB 34	34		
PSWCCH 34	34		


To order the following items (top and base), see page 259

TOP IN ANODIZED SILVER, GOLD, BRONZE, SAND AND CHAMPAGNE ALUMINIUM thermo packed
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	L mm		
PSWAA 34	34		
PSWAO 34	34		*
PSWSB 34	34		*
PSWAB 34	34		*
PSWCH 34	34		*

BASE IN NATURAL ALUMINIUM thermo packed - bar length 2,7 lm - pack. 20 Pcs - 54 lm


Article	L mm		
PSWBAN 07F	22,6		



PROSCREW 44

ANODIZED SILVER, GOLD, BRONZE, SAND AND CHAMPAGNE ALUMINIUM

universal joints with screw



BASE + TOP IN ANODIZED SILVER, GOLD, BRONZE, SAND AND CHAMPAGNE ALUMINIUM + SCREWS AND SCREW ANCHORS thermo packed - bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	L mm		
PSWCAA 44	44		
PSWCAO 44	44		
PSWCSB 44	44		
PSWCAB 44	44		
PSWCCH 44	44		


To order the following items (top and base), see page 259

TOP IN ANODIZED SILVER, GOLD, BRONZE, SAND AND CHAMPAGNE ALUMINIUM thermo packed
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	L mm		
PSWAA 44	44		
PSWAO 44	44		
PSWSB 44	44		
PSWAB 44	44		
PSWCH 44	44		

BASE IN NATURAL ALUMINIUM thermo packed - bar length 2,7 lm - pack. 20 Pcs - 54 lm



Article	L mm		
PSWBAN 07F	22,6		



PROSCREW 33

ANODIZED SILVER, GOLD, BRONZE, SAND AND CHAMPAGNE ALUMINIUM

universal joints with screw



BASE + TOP IN ANODIZED SILVER, GOLD, BRONZE, SAND AND CHAMPAGNE ALUMINIUM + SCREWS AND SCREW ANCHORS thermo packed - bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	L mm		
PSWCAA 33	33		
PSWCAO 33	33		
PSWCSB 33	33		
PSWCAB 33	33		
PSWCCH 33	33		*


To order the following items (top and base), see page 259

TOP IN ANODIZED SILVER, GOLD, BRONZE, SAND AND CHAMPAGNE ALUMINIUM thermo packed
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	L mm		
PSWAA 33	33		
PSWAO 33	33		
PSWSB 33	33		
PSWAB 33	33		*
PSWCH 33	33		*

BASE IN NATURAL ALUMINIUM thermo packed - bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	L mm		
PSWBAN 07F	22,6		



COLOURS

ANODIZED
AA - Anod. silver alum.

ON DEMAND (minimum quantity 100 pcs)

ANODIZED			
AO - Anod. gold alum.	AB - Anod. bronze alum.	CH - Anod. champagne alum.	SB - Anod. sand alum.

* = Production on demand with minimum quantity of 200 pcs. Production delay 4/5 weeks. Price to be agreed.



TOP IN ANODIZED SILVER, GOLD, BRONZE, SAND AND CHAMPAGNE ALUMINIUM thermo packed
bar length 2,7 lm - pack. 20 Pcs - 54 lm


Article	L mm		
PSWAA 50	50		
PSWAO 50	50		
PSWSB 50	50		
PSWAB 50	50		
PSWCH 50	50		

BASE + TOP IN ANODIZED SILVER, GOLD, BRONZE, SAND AND CHAMPAGNE ALUMINIUM + SCREWS AND SCREW ANCHORS thermo packed - bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	L mm		
PSWCAA 50	50		
PSWCAO 50	50		
PSWCSB 50	50		
PSWCAB 50	50		
PSWCCH 50	50		


BASE IN NATURAL ALUMINIUM thermo packed - bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	L mm		
PSWBAN 07F	22,6		



PROSCREW 50

ANODIZED SILVER, GOLD, BRONZE, SAND AND CHAMPAGNE ALUMINIUM



universal joints with screw

To order the following items (top and base), see page 259

COLOURS



ON DEMAND (minimum quantity 100 pcs)



SCREWS to fix all perforated versions

NICKEL PLATED


WHITE NICKEL-PLATED FLATHEAD SCREW UNI 7688 3X10
pack. 14 Pcs

Article	Ø mm	H mm	
VIZBP 310	05	10	


WHITE NICKEL-PLATED FLATHEAD SCREW UNI 7688 3X16
pack. 14 Pcs

Article	Ø mm	H mm	
VIZBP 316	05	16	

VIZBP 310



VIZBP 316




KIT PROSCREW


KIT PROSCREW

Article	
KIT PROSCREW	KIT consists of 14 screws VIZBP 310, 14 screws VIZBP 316, 15 screws + screw anchors VINPT 325

KIT PROSCREW



EXAMPLES OF LAYING





* = Production on demand with minimum quantity of 200 pcs. Production delay 4/5 weeks. Price to be agreed.

PROMULTISKIRT SQUARE

FOAMED VINYL RESIN

PROMULTISKIRT SQUARE is an expanded vinyl resin profile covered with a vinyl resin film available in white, black, silver and wood finishes. The profile has a good resistance to chemical agents and can be secured to the wall with plastic supports fixed with screws or silicone. The skirting height is 100 mm, it can be cut to 80 and 60 mm heights thanks to the pre-incisions on the back. **PROMULTISKIRT SQUARE** in expanded vinyl resin coated with vinyl resin film is suitable for any indoor environment.



FOAMED VINYL RESIN (wood finishes - black - white and silver)
bar length **2,4 lm** - pack. **20 Pcs - 48 lm**

Article	L mm	H mm
BTEPR... 108614/S	100/80/60	

Available in the finishes: 29W - 30W - 34W - B - N - AA.
The code of the selected colour must be added to the article code.
E.g.: BTEPR...108614/S (chosen finish Havana oak) BTEPR34W 108614/S

SUPPORT / FIXING CLIP - PLASTIC
pack. **100 Pcs**

Article	H mm
BTEPRS 18	16,5

Order the **SUPPORT** and choose the **SKIRTING** in the desired finish.

USE PROBAND FIX FOR FIXING THE PROFILE TO THE WALL



COLOURS

29W - White oak	30W - Grey oak	34W - Havana oak	B - White	N - Black	AA - Silver

On request it is possible to realize other finishes of the color range: minimum order 400 pcs. Production delay 4/5 weeks.
Price to be agreed. For sample finishes, contact the sales office for minimum quantities, timing and costs.

LAYING INSTRUCTIONS

1. Choose "PROMULTISKIRT SQUARE" according to the chosen colour. **2.** Cut "PROMULTISKIRT SQUARE" to the required length. **3.** if necessary cut "PROMULTISKIRT SQUARE" to the required height. *** 4.** Carefully clean the substrate on which the profile will be placed from oil, grease and dirt residues in general.

Laying with adhesive only:

5a. With dry surface apply the Proband Fix. **6a.** Press the profile against the wall with the correct pressure.

Laying with adhesive and support:

5b. Fix the plastic supports to the wall every 50mm with screws. **6b.** Apply Proband Fix only to the back upper part of the skirting board. **7b.** Fix the profile to the supports and press it against the wall with correct pressure.

*CUT INSTRUCTIONS



Option 1A: Cut to have the height 80 mm.
Cut along the first pre-incision on the back of the skirting;



Option 1B: Cut to have the height 60 mm.
Cut along the second pre-incision on the back of the skirting;




2. Cut the skirting on the front side at the cut previously made on the back;



3. Remove the excess part.


EXAMPLE OF LAYING



CORNERS, END CAPS AND JOINTS

FOAMED VINYL RESIN

INTERNAL CORNER KIT



KIT BTEPR ... 108614/SI

EXTERNAL CORNER KIT



KIT BTEPR ...108614/SE

IN/EXTERNAL CORNERS and END CAPS KIT
(wood finishes - black - white and silver)

Article	H mm
KBTEPR...108614/SI	100/80/60
KBTEPR...108614/SE	100/80/60

Available in the finishes: 29W - 30W - 34W - B - N - AA.
The code of the selected colour must be added to the article code.
E.g.: KBTEPR...108614/S (chosen finish Havana oak) KBTEPR34W 108614/S

PROMULTISKIRT ROUND is an expanded vinyl resin profile covered with a vinyl resin film available in white, black, silver and wood finishes. The profile has a good resistance to chemical agents and can be secured to the wall with plastic supports fixed with screws or silicone. The skirting height is 100 mm, it can be cut to 80 and 60 mm heights thanks to the pre-incisions on the back. PROMULTISKIRT ROUND in expanded vinyl resin coated with vinyl resin film is suitable for any indoor environment.

PROMULTISKIRT ROUND

FOAMED VINYL RESIN

PATENTED



FOAMED VINYL RESIN (wood finishes - black - white and silver)
bar length 2,4 lm - pack: 20 Pcs - 48 lm

SUPPORT / FIXING CLIP - PLASTIC
pack: 100 Pcs

Article	L mm
BTEPR... 108614/R	100/80/60

Article	H mm
BTEPRS 18	16,5

Available in the finishes: 29W - 30W - 34W - B - N - AA.
The code of the selected colour must be added to the article code.
E.g.: BTEPR... 108614/R (chosen finish Havana oak) BTEPR34W 108614/R

Order the SUPPORT and choose the SKIRTING in the desired finish.

USE PROBAND FIX FOR FIXING THE PROFILE TO THE WALL



COLOURS

(For a precise assessment of colours request the wood finishes sample range)



On request it is possible to realize other finishes of the color range: minimum order 400 pcs. Production delay 4/5 weeks. Price to be agreed. For sample finishes, contact the sales office for minimum quantities, timing and costs.

LAYING INSTRUCTIONS

1. Choose "PROMULTISKIRT ROUND" according to the chosen colour. 2. Cut "PROMULTISKIRT ROUND" to the required length. 3. if necessary cut "PROMULTISKIRT ROUND" to the required height. * 4. Carefully clean the substrate on which the profile will be placed from oil, grease and dirt residues in general.

Laying with adhesive only:

5a. . With dry surface apply the Proband Fix. 6a. Press the profile against the wall with the correct pressure.

Laying with adhesive and support:

5b. Fix the plastic supports to the wall every 50mm with screws. 6b. Apply Proband Fix only to the back upper part of the skirting board.

7b. Fix the profile to the supports and press it against the wall with correct pressure.



Option 1A: Cut to have the height 80 mm.
Cut along the first pre-incision on the back of the skirting;



Option 1B: Cut to have the height 60 mm.
Cut along the second pre-incision on the back of the skirting;




2. Cut the skirting on the front side at the cut previously made on the back;




3. Remove the excess part.

BTEPR... 108614/R

BTEPRS 18/100



EXAPLE OF LAYING



CORNERS, END CAPS AND JOINTS


FOAMED VINYL RESIN

IN/EXTERNAL CORNERS and END CAPS KIT
(wood finishes - black - white and silver)

Available in the finishes: 29W - 30W - 34W - B - N - AA.
The code of the selected colour must be added to the article code.
E.g.: KBTEPR...108614/S (chosen finish Havana oak) KBTEPR34W 108614/S


Article	H mm
KBTEPR...108614/RI	100/80/60
KBTEPR...108614/RE	100/80/60

INTERNAL CORNER KIT



KIT BTEPR ...108614/RI

EXTERNAL CORNER KIT




KIT BTEPR ...108614/RE

SKIRTING 7016

FOAMED VINYL RESIN

SKIRTING 7016 is a vinyl resin foam profile with a height of 70 mm. available wooden finishes and finishes in solid colour that could be matched with the PROINSERT SYSTEM's profiles. The profile, suitable like skirting for floating and glued wood floor, laminate and LVT, could be laid with suitable adhesive, nails, screws or using the pre-punched support fixed to the wall with screws every 57 cm. Its special section, that allows to cover a 16 mm perimetral joint, and wide range of finishes make it a very requested, elegant and economic skirting profile.



FOAMED VINYL RESIN (wood finishes - black - white and silver)
Length = 2,5 m - Pack 20 pcs - 50 lm

Article	L mm
BTEPR... 7016	70



SUPPORT / FIXING CLIP - PLASTIC
support Length 5 cm

Article	H mm
BTEPRS 385	37,5

USE PROBAND FIX FOR FIXING THE PROFILE TO THE WALL



Order the SUPPORT and choose the SKIRTING in the desired finish.



IN/EXTERNAL CORNERS and END CAPS KIT
(wood finishes - black - white and silver)

Article	H mm
KIT BTEPR ...7016I	70
KIT BTEPR ...7016E	70

INTERNAL CORNER KIT



EXTERNAL CORNER KIT



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS


1. Choose "Skirting 7016" in the desired finish.
2. Fix the pre-punched support to the wall with screws every 50 cm.
3. Attach the profile to the support applying low pressure.
4. Alternatively fix the profile using a suitable fast adhesive, nails or screws

COLOURS

(For a precise assessment of colours request the wood finishes sample range)

04W - Dark oak	05W - Light oak	13W - Teak Indonesia	18W - Light Zerbano	21W - Powder Oak	25W - Bleached fir	29W - White oak	30W - Gray oak	31W - Victoria oak	33W - Sawed oak
34W - Havana oak	35W - Edimburgo oak	36W - American oak	37W - Carvi oak	38W - Queens oak	39W - Grey elm	41W - Ice oak	42W - Grace oak	45W - Morocco oak	46W - Black decap
53W	54W	55W	B - White	N - Black	AA - Silver				

On request it is possible to realize other finishes of the color range: minimum order 400 pcs. Production delay 4/5 weeks. Price to be agreed. For sample finishes, contact the sales office for minimum quantities, timing and costs.



SKIRTING 7011 is a vinyl resin foam profile with a height of 70 mm x 10,5 mm, available in wooden finishes and finishes standard colours that could be matched with the PROINSERT SYSTEM's profiles. Suitable as Basebord for floating and glued wood floor, laminate and LVT, could be laid with suitable adhesive, or else with nails .

SKIRTING 7011

FOAMED VINYL RESIN



FOAMED VINYL RESIN (wood finishes - black - white and silver)
Length = 2,5 m - Pack 20 pcs - 50 lm

Article	H mm
BTEPR... 7011	70



IN/EXTERNAL CORNERS and END CAPS KIT
(wood finishes - black - white and silver)

Article	H mm
KIT BTEPR ...7011I	70
KIT BTEPR ...7011E	70

INTERNAL CORNER KIT

EXTERNAL CORNER KIT



KIT BTEPR...7011I

KIT BTEPR...7011E

USE PROBAND FIX FOR FIXING THE PROFILE TO THE WALL




COLOURS


(For a precise assessment of colours request the wood finishes sample range)

05W - Light oak	07W - Light cherry	09W - Red walnut	18W - Light Zebano	21W - Powder Oak	29W - White oak	30W - Grey oak	31W - Victoria oak	32W - Pink oak	34W - Havana oak
35W - Edimburgo oak	37W - Carvi oak	40W - Brown oak	41W - Ice oak	42W - Grace oak	43W - Manhattan oak	44W - Honey oak	46W - Black decapie	47W - Black oak	48W - Cork oak
49W - Sand oak	65W - Tripoli	73W - Bangkok	75W - Liotard	B - White	N - Black	AA - Silver			

On request it is possible to realize other finishes of the color range: minimum order 400 pcs. Production delay 4/5 weeks. Price to be agreed. For sample finishes, contact the sales office for minimum quantities, timing and costs.



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the "Skirting 7011" in the required the colour. 2. Lay the "Skirting 7011" using quick-setting suitable adhesive for gluing flexible PVC onto mortar-plaster-accessorised walls, etc. or fix with nails.

SKIRTING 40 is a vinyl resin foam profile with a height of 40 mm x 10 mm, available in wooden finishes and finishes standard colours that could be matched with the PROINSERT SYSTEM's profiles. Suitable as Basebord for floating and glued wood floor, laminate and LVT, could be laid with suitable adhesive, or else with nails .

SKIRTING 40

FOAMED VINYL RESIN



FOAMED VINYL RESIN (wood finishes - black - white and silver)
Length = 2,4 m - Pack. 20 PCS - 48 Lm

Article	H mm
BTEPR... 4010	40

Available in the finishes: 29W - 30W - 34W - B - N - AA.
The code of the selected colour must be added to the article code.
E.g.: BTEPR... 4010 (chosen finish Havana oak) BTEPR34W 4010

USE PROBAND FIX FOR FIXING THE PROFILE TO THE WALL



COLOURS

(For a precise assessment of colours request the wood finishes sample range)

29W - White oak	30W - Grey oak	34W - Havana oak	B - White	N - Black	AA - Silver
-----------------	----------------	------------------	-----------	-----------	-------------

On request it is possible to realize other finishes of the color range: minimum order 400 pcs. Production delay 4/5 weeks. Price to be agreed. For sample finishes, contact the sales office for minimum quantities, timing and costs.

IN/EXTERNAL CORNERS and END CAPS KIT
(wood finishes - black - white and silver)

Article	H mm
KIT BTEPR ...4010I	40
KIT BTEPR ...4010E	40

KIT BTEPR...4010I


KIT BTEPR...4010E

INTERNAL CORNER KIT


EXTERNAL CORNER KIT



BTEPR... 4010



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS




1. Choose the "Skirting 40" in the required the colour. 2. Lay the "Skirting 40" using quick-setting suitable adhesive for gluing flexible PVC onto mortar-plaster-accessorised walls, etc. or fix with nails.


PROSEAL WOOD

EXPANDED PVC
2 WOOD FINISHING AND 4 MATCHING COLOURS

PSAW... 20



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROSEAL WOOD" color and/or wood finish required.
2. The laying must be carried out using fast fixing acrylic silicone, mastic, bostik suitable for gluing PVC with mortar - plaster - wall units etc., or fix using screws/nails.

PROSEAL WOOD is a new inner connector square suitable for creating a concave skirting for wood / rolled-melamine floating wood / ceramic / marble tiles to reduce the floor /covering detachment. The particular material used allows to resist to the main chemical agents ant to small breakages. **PROSEAL WOOD's** dimensions allow the necessary expansion of the outer joint. Ideal for public (schools, rest homes, recreational area) and private places. In expanded PVC , in 2 wood finishes 4 in matching colours to combine with various wood finishes. Easy to lay with fixing silicone.



EXPANDED PVC - 2 WOOD FINISHING
bar length 2,5 lm - pack. 40 Pcs - 100 lm

Article	L mm
PSAW... 20	21 x 21

Available in the wood finishes: 05W - 10W , and colours: B - GC - GS - N.
The code of the selected colour must be added to the article code. E.g.: PSAW...20 (chosen finish black) PSAWN 20.



EXPANDED PVC - 4 COLOURS
bar length 2,5 lm - pack. 40 Pcs - 100 lm

Article	L mm
PSAW... 20	21 x 21

USE PROBAND FIX FOR FIXING THE PROFILE TO THE WALL



COLOURS


B - White	GC - Light gray	GS - Dark gray	N - Black	05W - Light oak (strip)	10W - Wengé (panga panga-wengé)

The shade of the wooden finish in rigid expanded vinyl resin/PVC results slightly different from the film usually applied on the profiles in aluminium.

PROANGLE WOOD

EXPANDED PVC
2 WOOD FINISHING AND 4 MATCHING COLOURS

PGAW... 15



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROANGLE WOOD" color and/or wood finish required.
2. The laying must be carried out using fast fixing acrylic silicone, mastic, bostik, suitable for gluing PVC with mortar-plaster-wall units etc., or fix using screws/nails.

PROANGLE WOOD is a new inner connector square suitable for creating a convex skirting for wood / rolled-melamine floating wood / ceramic / marble floor to reduce the floor /covering detachment. The particular material used allows to resist to the main chemical agents and to small breakages. **PROANGLE WOOD's** dimensions allow the necessary expansion of the outer joint. Ideal for public (schools, rest homes, recreational area) and private places. In expanded PVC , in 2 wood finishes 4 in matching colors to combine with various wood finishes. Easy to lay with fixing silicone.



EXPANDED PVC - 2 WOOD FINISHING
bar length 2,5 lm - pack. 40 Pcs - 100 lm

Article	L mm
PGAW... 15	15 x 15

Available in the wood finishes: 05W - 10W, and colours: - GC - GS - N.
The code of the selected colour must be added to the article code. E.g.: PGAW...15 (chosen finish black) PGAWN 15.



EXPANDED PVC - 4 COLOURS
bar length 2,5 lm - pack. 40 Pcs - 100 lm

Article	L mm
PGAW... 15	15 x 15

USE PROBAND FIX FOR FIXING THE PROFILE TO THE WALL



COLOURS

B - White	GC - Light gray	GS - Dark gray	N - Black	05W - Light oak (strip)	10W - Wengé (panga panga-wengé)

The shade of the wooden finish in rigid expanded vinyl resin/PVC results slightly different from the film usually applied on the profiles in aluminium.

SKIRTING in PVC foam height 70 mm in 12 finishes: 4 in semi-matt black-grey-white and 8 wooden finishes to be matched with the PROINSERT SYSTEM profiles for floating laminated wood floors and traditional parquet floors. Laying is done by gluing (acetic silicone - acrylic - mastic) or using screws or nails. Attractive, strong, hardwearing and economic, it is easy to lay and ideal for many public premises (hospitals, schools, gymnasiums, rest homes and creative areas) and private environments. Easy to match with many wood species.

SKIRTING

EXPANDED VINYL RESIN



EXPANDED RIGID VINYL RESIN (black - light and dark grey - white)
bar length 2 lm - pack. 60 Pcs - 120 lm

Article	H mm		
BTPR... 70	70		

EXPANDED RIGID VINYL RESIN (8 wooden finishes)
bar length 2 lm - pack. 60 Pcs - 120 lm

Article	H mm		
BTPR... 70	70		

Available in the colours: B - GC - GS - N - 04W - 05W - 06W - 07W - 08W - 09W - 10W - M.
The code of the selected colour must be added to the article code. E.g.: BTPR... 70 (chosen colour black) BTPRN 70.

COLOURS

B - White	GC - Light grey	GS - Dark grey	N - Black	04W - Dark beech	05W - Light oak (strip)
06W - Dark oak (Walnut)	07W - Light cherry (strip)	08W - Dark cherry (board)	09W - Red walnut (Merbau-Apple-Walnut)	10W - Wengè (Panga-Panga - Wengè)	M - Mahogany

The shade of the wooden finish in rigid expanded vinyl resin/pvc results slightly different from the film usually applied on the profiles in aluminum.

ANGLE BAR produced in expanded PVC in 12 finishes: 4 colours in semi-matt, black-grey-white and 8 wooden finishes used to protect angles. Laying is done by gluing (acetic silicone - acrylic - mastic) or using screws or nails. Attractive, strong, hardwearing and economic, it is easy to lay and ideal for many public premises (hospitals, schools, gymnasiums, rest homes and creative areas) and private environments. Easy to match with many wood species.



EXPANDED RIGID VINYL RESIN (black - light and dark grey - white)
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	L x H mm		
AGE... 25	25 x 25		

Available in the colours: B - GC - GS - N - 04W - 05W - 06W - 07W - 08W - 09W - 10W - M.
The code of the selected colour must be added to the article code. E.g.: AGE... 25 (chosen colour black) AGEN 25.

The shade of the wooden finish in rigid expanded vinyl resin/pvc results slightly different from the film usually applied on the profiles in aluminum.




EXPANDED RIGID VINYL RESIN (8 wooden finishes)
bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	L x H mm		
AGE... 25	25 x 25		

ANGLE BAR

EXPANDED VINYL RESIN

USE PROBAND FIX FOR FIXING THE PROFILE TO THE WALL



USE PROBAND FIX FOR FIXING THE PROFILE TO THE WALL

LVT PROFILES - SOL 30P

ALUMINIUM ANODIZED FINISHES AND WOODEN FINISHES

ALUMINIUM TOP 80 wooden fin. "...W" (56 on demand), 6 anodized fin. (3 on demand) thermo packed - bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	L mm		
PNSP... 3046	30		
PNSP...W 3046	30		

Available in the anodized finishes: AO - AA - AB (AT, CH and SB on demand) with a minimum quantity order of 200 pcs) 05W - 09W - 13W - 18W - 21W - 25W - 29W - 30W - 31W - 33W - 34W - 36W - 37W - 38W - 39W - 41W - 42W - 43W - 44W - 45W - 46W - 47W - 48W - 49W. The code of the selected colour must be added to the article code. E.g.: PNSP... 3046 (chosen finish anod. gold) PNSPAO 3046.

ALUMINIUM TOP (anod. silver) thermo packed - bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	L mm		
PNSPAA 4046	40		



BASE (vinyl resin/PVC) - bar length 2,7 lm

Article	L mm		
PINBFT 3646	36		



LVT PROFILES - ZERO CURVE

ALUMINIUM ANODIZED FINISHES AND WOODEN FINISHES

ALUMINIUM TOP 80 wooden fin. "...W" (56 on demand), 6 anodized fin. (3 on demand) thermo packed - bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	L mm		
PINZ... 2646	26		
PINZ...W 2646	26		

ALUMINIUM TOP (anod. silver) thermo packed - bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	L mm		
PINZAA 3246	32		



BASE (vinyl resin/PVC) - bar length 2,7 lm

Article	L mm		
PINBFT 2346	23		



LVT PROFILES - TERMINAL PIN

ALUMINIUM ANODIZED FINISHES AND WOODEN FINISHES

ALUMINIUM TOP 80 wooden fin. "...W" (56 on demand), 6 anodized fin. (3 on demand) thermo packed - bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	L mm		
PINTP... 1946	19		
PINTP...W 194	19		

ALUMINIUM TOP (anod. silver) thermo packed - bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	L mm		
PINTPAA 2546	25		



BASE (vinyl resin/PVC) - bar length 2,7 lm

Article	L mm		
PINBFT 2346	23		




SOL 30 (only top)

WOODEN-FINISHES AND ANODIZED FINISHES

joints

PINS... 30



ANODIZED ALUMINIUM (6 anod. alum. finishes of which 3 on demand)
thermo packed - bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	L mm		
PINS... 30	30		

Available in the anodized finishes: AO - AA - AB (AT, CH and SB available on demand with a minimum quantity order of 200 pcs), 04W - 05W - 07W - 09W - 13W - 18W - 21W - 25W - 29W - 30W.

The code of the selected colour must be added to the article code. E.g.: PINS... 30 (chosen finish anod. gold) PINSAO 30.

ALUMINIUM COVERED (80 wooden finishes f which 71 on demand)
thermo packed - bar length 2,7 lm - pack. 40 Pcs - 108 lm


Article	L mm		
PINS... 30	30		

TERMINAL PIN (only top)

WOODEN-FINISHES AND ANODIZED FINISHES

terminal
outherprofiles

PINTP... 10



ANODIZED ALUMINIUM (6 anod. alum. finishes of which 3 on demand)
thermo packed - bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	L mm		
PINTP... 10	10		

Available in the colours: AO - AA - AB (AT, CH and SB on demand with a minimum quantity order of 200 pcs) 04W - 05W - 07W - 09W - 13W - 18W - 21W - 25W - 29W - 30W - 31W - 32W - 33W - 34W - 35W - 36W - 37W - 38W - 39W - 41W - 42W - 44W - 45W - 46W - 48W - 49W - 53W - 54W - 55W - 65W - 73W - 75W.

The code of the selected colour must be added to the article code. E.g.: PINTP... 10 (chosen finish anod. gold) PINTPAO 10.

ALUMINIUM COVERED (80 wooden finishes f which 49 on demand)
thermo packed - bar length 2,7 lm - pack. 40 Pcs - 108 lm


Article	L mm		
PINTP...	10		

ZERO CURVE 07-09-13-15 (only top)

WOODEN-FINISHES AND ANODIZED FINISHES

transition
profiles


PINZ... 07




PINZ... 09



PINZ... 13



PINZ... 15



ANODIZED ALUMINIUM (6 anod. alum. finishes of which 3 on demand)
thermo packed - bar length 2,7 lm
pack 20 Pcs - 54 lm (H 7 - H 9 mm - 108 lm)

Article	H mm		
PINZ... 07	7 / 11		
PINZ... 09	11 / 14		
PINZ... 13	15 / 17		
PINZ... 15	19 / 22		

Available in the anodized finishes: AO - AA - AB (AT, CH and SB on demand with a minimum quantity order of 200 pcs) 04W - 05W - 07W - 09W - 13W - 18W - 21W - 25W - 29W - 30W - 31W - 32W - 33W - 34W - 35W - 36W - 37W - 38W - 39W - 41W - 42W - 44W - 45W - 46W - 48W - 49W - 53W - 54W - 55W - 65W - 73W - 75W.

The code of the selected colour must be added to the article code. E.g.: PINZ... 07 (chosen finish anod. gold) PINZAO 07.

ALUMINIUM COVERED (80 wooden finishes f which 49 on demand)
thermo packed - bar length 2,7 lm
pack 20 Pcs - 54 lm (H 7 - H 9 mm - 108 lm)


Article	H mm		
PINZ... 07	7 / 11		
PINZ... 09	11 / 14		
PINZ... 13	15 / 19		
PINZ... 15	19 / 22		

STYLE STAIR (only top)

WOODEN-FINISHES AND ANODIZED FINISHES

stair nosing
profiles

PINY...



ANODIZED ALUMINIUM (6 anod. alum. finishes of which 3 on demand)
thermo packed - bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	L x H mm		
PINY...	27,5 x 25		

Available in the colours: AO - AA - AB (AT, CH and SB on demand with a minimum quantity order of 200 pcs) 05W - 07W - 09W - 18W - 21W - 29W - 30W - 31W - 32W - 34W - 35W - 37W - 41W - 42W - 44W - 46W - 48W - 49W - 65W - 73W - 75W.

The code of the selected colour must be added to the article code. E.g.: PINY... (chosen finish anod. gold) PINYAO.

ALUMINIUM COVERED (80 wooden finishes f which 60 on demand)
thermo packed - bar length 2,7 lm - pack. 10 Pcs - 27 lm


Article	L x H mm		
PINY...	27,5 x 25		

STYLE STAIR L (only top)

WOODEN-FINISHES AND ANODIZED FINISHES

stair nosing
profiles

PINYL...



ANODIZED ALUMINIUM (6 anod. alum. finishes of which 3 on demand)
thermo packed - bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	L x H mm		
PINYL...	45 x 23,8		

Available in the colours: AO - AA - AB (AT, CH and SB on demand with a minimum quantity order of 200 pcs) 04W - 05W - 13W - 18W - 21W - 25W - 29W - 30W - 31W - 32W - 33W - 34W - 35W - 36W - 37W - 38W - 39W - 41W - 42W - 44W - 45W - 53W - 54W - 55W

The code of the selected colour must be added to the article code. E.g.: PINYL... (chosen finish anod. gold) PINYAO.

ALUMINIUM COVERED (80 wooden finishes f which 57 on demand)
thermo packed - bar length 2,7 lm - pack. 10 Pcs - 27 lm


Article	L x H mm		
PINYL...	45 x 23,8		

SOL 40 P (only top)

WOODEN-FINISHES AND ANODIZED FINISHES

joints

PNSP... 40P



ANODIZED ALUMINIUM (6 anod. alum. finishes of which 3 on demand)
thermo packed - bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	L x H mm		
PNSP... 40P	40		

Available in the colours: AO - AA - AB (AT, CH and SB on demand with a minimum quantity order of 200 pcs) 04W - 05W - 07W - 09W - 13W - 18W - 21W - 25W - 29W - 30W - 31W - 32W - 33W - 34W - 35W - 36W - 37W - 38W - 39W - 41W - 42W - 44W - 45W - 46W - 48W - 49W - 53W - 54W - 55W - 65W - 73W - 75W.

The code of the selected colour must be added to the article code. E.g.: PNSP... 40P (chosen finish anod. gold) PNSPAO 40P.

ALUMINIUM COVERED (80 wooden finishes f which 49 on demand)
thermo packed - bar length 2,7 lm - pack. 10 Pcs - 27 lm

Article	L x H mm		
PNSP... 40P	40		


INTERCHANGEABLE INSERT

RIGID IMPACT-RESISTANT
NO-TOXIC VINYL RESIN

RIGID IMPACT-RESISTANT NO-TOXIC VINYL RESIN
bar length 2,7 LM - pack. 20 Pcs - 54 LM

Article	H mm		
PIN 07	7		
PIN 09	9		
PIN 11	11		
PIN 13	13		
PIN 15	15		
PIN 17	17		
PIN 19	19		

FOR SOL 40 P AND TERMINAL PIN




RIGID IMPACT-RESISTANT NO-TOXIC VINYL RESIN
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H mm		
PIN 09	9		
PIN 11	11		
PIN 13	13		
PIN 15	15		
PIN 17	17		
PIN 19	19		


FOR ZERO CURVE, STYLE STAIR

For a correct assembly, see the drawings of the complete products in the previous pages


PIN 07




PIN 09




PIN 11




PIN 13




PIN 15



PIN 17



PIN 19



PROINSERT BASE 45 AND BASE 40


NATURAL ALUMINIUM




ALUM. PUNCHED/PERFORED FOR SOL 30-40-50 AND ZERO CURVE
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	width mm		
PINBFT 45	45		
PINBFT 40	40		

PINBFT 45



PINBFT 40



SCREWS and SCREW ANCHORS to fix all perforated version


NICKEL-PLATED


NICKEL - PLATED FLATHEAD SCREWS + SCREW ANCHORS
pack. 1.000 Pcs

Article	Ø mm	length mm	
VINIPT 325	03	25	

BRASS - PLATED FLATHEAD SCREWS + SCREW ANCHORS
pack. 1.000 Pcs

Article	Ø mm	length mm	
VIOPT 325	03	25	





An interpretation of:
The Gherkin, Norman Foster, LONDON (England), 2004




PROFILES & SYSTEMS

DO IT YOUR SELF PROFILES



CORNER EQUAL SIDES

POLISHED STAINLESS STEEL 1.4016



POLISHED STAINLESS STEEL 1.4016 with protective film
thick 1 mm - bar length 2 lm - pack. 10 Pcs - 20 lm

Article	L x H mm		
AGAC 201C	20 x 20		
AGAC 301C	30 x 30		


On demand are available 1 lm bars.

COLOURS



CORNER EQUAL SIDES

POLISHED BRASS




POLISHED BRASS with protective film
thick 1 mm - bar length 2 lm - pack. 10 Pcs - 20 lm

Article	L x H mm		
AGOL 201C	20 x 20		*
AGOL 301C	30 x 30		*


On demand are available 1 lm bars.

COLOURS



CORNER EQUAL SIDES

ANODIZED GOLD AND SILVER, POLISHED CHROME AND WHITE VARNISHED ALUMINIUM



ANODIZED GOLD and SILVER ALUMINIUM thermo packed
bar length 2 lm - pack. 10 Pcs - 20 lm

Article	L x H mm		
AG... 101C	10 x 10		
AG... 151C	15 x 15		
AG... 201C	20 x 20		
AG... 251C	25 x 25		
AG... 301C	30 x 30		
AG... 401C	40 x 40		

Available in the finishes: AO - AA.
The code of the selected colour must be added to the article code.
E.g.: AG... 101C (chosen finish anodized gold) AGAO 101C.

POLISHED CHROME ALUMINIUM thermo packed
bar length 2 lm - pack. 10 Pcs - 20 lm


Article	L x H mm		
AGBC 101C	10 x 10		
AGBC 151C	15 x 15		
AGBC 201C	20 x 20		
AGBC 251C	25 x 25		
AGBC 301C	30 x 30		
AGBC 401C	40 x 40		

WHITE VARNISHED ALUMINIUM thermo packed
bar length 2 lm - pack. 10 Pcs - 20 lm

Article	L x H mm		
AGB 101C	10 x 10		
AGB 151C	15 x 15		
AGB 201C	20 x 20		
AGB 251C	25 x 25		
AGB 301C	30 x 30		
AGB 401C	40 x 40		


On demand are available 1 lm bars.

COLOURS



CORNER EQUAL SIDES

NON - TOXIC VINYL RESIN



NON - TOXIC VINYL RESIN

bar length 2 lm - pack. 10 Pcs - 20 lm

Article	L x H mm		
AGP10...C	10 x 10		
AGP15...C	15 x 15		
AGP20...C	20 x 20		
AGP25...C	25 x 25		

Available in the colours: B-N.




The code of the selected colour must be added to the article code.
E.g.: AGP10...C (colour white) AGP10BC.

On demand are available 1 lm bars.

COLOURS


B - White	N - Black

AGP10...C



CORNER "L-FORM"

ANODIZED GOLD AND SILVER, POLISHED CHROME AND WHITE VARNISHED ALUMINIUM



ANODIZED GOLD AND SILVER ALUMINIUM thermo packed

bar length 2 lm - pack. 10 Pcs - 20 lm

Article	L x H mm		
AL... 1510C	15 x 10		
AL... 1020C	20 x 10		
AL... 3015C	30 x 15		

Available in the finishes: AO - AA.

The code of the selected colour must be added to the article code.
E.g.: AL... 1510C (chosen finish anodized gold) ALAO1510C.

POLISHED CHROME ALUMINIUM thermo packed

bar length 2 lm - pack. 10 Pcs - 20 lm

Article	L x H mm		
ALBC 1510C	15 x 10		
ALBC 1020C	20 x 10		
ALBC 3015C	30 x 15		


WHITE VARNISHED ALUMINIUM thermo packed

bar length 2 lm - pack. 10 Pcs - 20 lm


Article	L x H mm		
ALB 1510C	15 x 10		
ALB 3015C	30 x 15		

On demand are available 1 lm bars.


AL... 1510C



AL... 1020C



AL... 3015C



COLOURS

AO - Anodized gold alum.	AA - Anodized silver alum.	BC - Polished chrome alum.
B - White varnished alum.		

CORNER "L-FORM"

NON - TOXIC VINYL RESIN



NON TOXIC VINYL RESIN

bar length 2 lm - pack. 10 Pcs - 20 lm

Article	L x H mm		
ALP20...C	20 x 10		
ALP25...C	25 x 20		
ALP30...C	30 x 20		
ALP40...C	40 x 10		

Available in the colours: B-N.



The code of the selected colour must be added to the article code.
E.g.: ALP20...C (colour white) ALP20BC.

On demand are available 1 lm bars.

COLOURS

B - White	N - Black


ALP20...C




CANAL "U FORM"

ANODIZED GOLD AND SILVER, POLISHED CHROME AND WHITE VARNISHED ALUMINIUM


CU... 081C




CU... 101C



CU... 151C



CU... 201C



ANODIZED GOLD AND SILVER ALUMINIUM thermo packed
bar length 2 lm - pack. 10 Pcs - 20 lm

Article	L x H mm		
CU... 081C	8 x 8		
CU... 101C	10 x 10		
CU... 151C	10 x 15		
CU... 201C	10 x 20		

Available in the finishes: AO - AA.
The code of the selected colour must be added to the article code.
E.g.: CU... 101C (chosen finish anodized gold) CUAO 101C.

POLISHED CHROME ALUMINIUM thermo packed
bar length 2 lm - pack. 10 Pcs - 20 lm

Article	L x H mm		
CUBC 081C	8 x 8		
CUBC 101C	10 x 10		
CUBC 151C	10 x 15		


WHITE VARNISHED ALUMINIUM thermo packed
bar length 2 lm - pack. 10 Pcs - 20 lm

Article	L x H mm		
CUB 081C	8 x 8		
CUB 101C	10 x 10		
CUB 151C	10 x 15		
CUB 201C	10 x 20		*

On demand are available 1 lm bars.




COLOURS




CANAL DOUBLE "U FORM"

ANODIZED GOLD AND SILVER, POLISHED CHROME AND WHITE VARNISHED ALUMINIUM


CW... 167C




CW... 161C



CW... 201C



CW... 208C



ANODIZED GOLD AND SILVER ALUMINIUM thermo packed
bar length 2 lm - pack. 10 Pcs - 20 lm

Article	L x H mm		
CW... 167C	16 x 7		
CW... 161C	16 x 12		
CW... 201C	20 x 10		
CW... 208C	20 x 18		

Available in the finishes: AO - AA.
The code of the selected colour must be added to the article code.
E.g.: CW... 167C (chosen finish anodized gold) CWAO 167C.

POLISHED CHROME ALUMINIUM thermo packed
bar length 2 lm - pack. 10 Pcs - 20 lm

Article	L x H mm		
CWBC 167C	16 x 7		
CWBC 161C	16 x 12		
CWBC 201C	20 x 10		
CWBC 208C	20 x 18		


WHITE VARNISHED ALUMINIUM thermo packed
bar length 2 lm - pack. 10 Pcs - 20 lm


Article	L x H mm		
CWB 161C	16 x 12		*
CWB 208C	20 x 18		*

On demand are available 1 lm bars.



COLOURS





ANODIZED GOLD AND SILVER ALUMINIUM thermo packed

bar length 2 lm - pack. 10 Pcs - 20 lm

Article	L mm		
PI... 102C	10		
PI... 122C	12		
PI... 152C	15		
PI... 202C	20		
PI... 252C	25		
PI... 302C	30		
PI... 402C	40		

Available in the finishes: AO - AA.
The code of the selected colour must be added to the article code.
E.g.: PI... 122C (chosen finish anodized gold) PIAO 122C.

POLISHED CHROME ALUMINIUM thermo packed

bar length 2 lm - pack. 10 Pcs - 20 lm

Article	L mm		
PIBC 102C	10		
PIBC 122C	12		
PIBC 152C	15		
PIBC 202C	20		
PIBC 252C	25		
PIBC 302C	30		
PIBC 402C	40		


WHITE VARNISHED ALUMINIUM thermo packed

bar length 2 lm - pack. 10 Pcs - 20 lm


Article	L mm		
PIB 102C	10		
PIB 152C	15		
PIB 202C	20		
PIB 252C	25		
PIB 302C	30		
PIB 402C	40		

On demand are available 1 lm bars.


PI... 102C




PI... 122C




PI... 152C



PI... 202C



PI... 252C



PI... 302C



PI... 402C



COLOURS



NATURAL BRASS thermo packed

bar length 2,7 lm - pack. 10 Pcs - 20 lm


Article	L mm	€/lm	€/Pc
PION 102C	10		
PION 202C	20		

POLISHED BRASS thermo packed


bar length 2,7 lm - pack. 10 Pcs - 20 lm

Article	L mm	€/lm	€/Pc
PIOL 102C	10		
PIOL 202C	20		

PI... 102C scale 1:1



PI... 202C scale 1:1




BRUSHED BRASS thermo packed

bar length 2,7 lm - pack. 20 Pcs - 20 lm


Article	L mm	€/lm	€/Pc
PIOS 102C	10		
PIOS 202C	20		

COLOURS



EMPTY ROUND TUBE

ANODIZED GOLD AND SILVER ALUMINIUM
POLISHED CHROME ALUMINIUM



ANODIZED GOLD AND SILVER ALUMINIUM thermo packed
thick 1 mm - bar length 2 lm - pack. 10 Pcs - 20 lm

Article	Ø mm ext.		
TV... 061C	6		
TV... 081C	8		
TV... 101C	10		
TV... 121C	12		
TV... 161C	16		
TV... 181C	18		
TV... 201C	20		
TV... 241C	24		

Available in the finishes: AO - AA.
The code of the selected colour must be added to the article code.
E.g.: TV... 122C (chosen finish anodized gold) TVAO 122C.

POLISHED CHROME ALUMINIUM thermo packed
thick 1 mm - bar length 2 lm - pack. 10 Pcs - 20 lm

Article	Ø mm ext.		
TVBC 081C	8		*
TVBC 101C	10		*
TVBC 121C	12		*
TVBC 161C	16		*
TVBC 181C	18		*
TVBC 201C	20		*
TVBC 241C	24		*




COLOURS



On demand are available 1 lm bars.

FULL ROUND TUBE

ANODIZED GOLD AND SILVER ALUMINIUM
POLISHED CHROME ALUMINIUM



ANODIZED GOLD AND SILVER ALUMINIUM thermo packed
bar length 2 lm - pack. 10 Pcs - 20 lm

Article	Ø mm ext.		
TP... 06C	6		*
TP... 08C	8		
TP... 10C	10		

Available in the finishes: AO - AA.
The code of the selected colour must be added to the article code.
E.g.: TP... 122C (chosen finish anodized gold) TPAO 122C.

POLISHED CHROME ALUMINIUM thermo packed
bar length 2 lm - pack. 10 Pcs - 20 lm

Article	Ø mm ext.		
TPBC 06C	6		*
TPBC 08C	8		*
TPBC 10C	10		*

On demand are available 1 lm bars.



COLOURS



FULL SQUARE TUBE

ANODIZED GOLD AND SILVER ALUMINIUM

ANODIZED GOLD AND SILVER ALUMINIUM thermo packed
bar length 2 lm - pack. 10 Pcs - 20 lm

Article	L x H mm		
TQP... 08C	8 x 8		
TQP... 10C	10 x 10		

Available in the finishes: AO - AA. The code of the selected colour must be added to the article code. E.g.: TQP... 08C (chosen finish anodized gold) TQPAO 08C.

On demand are available 1 lm bars.




COLOURS



* = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed

EMPTY SQUARE TUBE

ANODIZED GOLD AND SILVER ALUMINIUM
POLISHED CHROME ALUMINIUM





ANODIZED GOLD AND SILVER ALUMINIUM thermo packed
bar length 2 lm - pack. 10 Pcs - 20 lm

Article	L x H mm		
TQV... 10C	10 x 10		
TQV... 15C	15 x 15		
TQV... 20C	20 x 20		


Available in the finishes: AO - AA.
The code of the selected colour must be added to the article code.
E.g.: TQV... 10C (chosen finish anodized gold) TQVAO 10C.

POLISHED CHROME ALUMINIUM thermo packed
bar length 2 lm - pack. 10 Pcs - 20 lm

Article	L x H mm		
TQVBC 10C	10 x 10		
TQVBC 15C	15 x 15		
TQVBC 20C	20 x 20		



COLOURS




AO - Anodized gold alum. AA - Anodized silver alum. BC - Polished chrome alum.

On demand are available 1 lm bars.

EMPTY RECTANGULAR TUBE

ANODIZED GOLD AND SILVER, POLISHED CHROME
AND WHITE VARNISHED ALUMINIUM



ANODIZED GOLD AND SILVER ALUMINIUM thermo packed
bar length 2 lm - pack. 10 Pcs - 20 lm

Article	L x H mm		
TR... 2010C	20 x 10		
TR... 3015C	30 x 15		



Available in the finishes: AO - AA.
The code of the selected colour must be added to the article code.
E.g.: TR... 2010C (chosen finish anodized gold) TRA0 2010C.

POLISHED CHROME ALUMINIUM thermo packed
bar length 2 lm - pack. 10 Pcs - 20 lm

Article	L x H mm		
TRBC 2010C	20 x 10		
TRBC 3015C	30 x 15		

WHITE VARNISHED ALUMINIUM thermo packed
bar length 2 lm - pack. 10 Pcs - 20 lm


Article	L x H mm		
TRB 2010C	20 x 10		



On demand are available 1 lm bars.

CURVE PROFILE

ANODIZED GOLD AND SILVER, POLISHED CHROME
AND WHITE VARNISHED ALUMINIUM





ANODIZED GOLD AND SILVER ALUMINIUM thermo packed
thick 1 mm - bar length 2 lm - pack. 10 Pcs - 20 lm

Article	L mm		
UG... 181C	18		
UG... 221C	22		
UG... 251C	25		


Available in the finishes: AO - AA.
The code of the selected colour must be added to the article code.
E.g.: UG... 181C (chosen finish anodized gold) UGAO 181C.

POLISHED CHROME ALUMINIUM thermo packed
thick 1 mm - bar length 2 lm - pack. 10 Pcs - 20 lm

Article	L mm		
UGBC 181C	18		
UGBC 221C	22		
UGBC 251C	25		



COLOURS



AO - Anodized gold alum. AA - Anodized silver alum. BC - Polished chrome alum.



B - White varnished alum.

WHITE VARNISHED ALUMINIUM thermo packed
thick 1 mm - bar length 2 lm - pack. 10 Pcs - 20 lm


Article	L mm		
UGB 181C	18		

On demand are available 1 lm bars.


PROFILE "T FORM"

ANODIZED GOLD AND SILVER ALUMINIUM
POLISHED CHROME ALUMINIUM

T... 1515C



T... 2525C



ANODIZED GOLD AND SILVER ALUMINIUM thermo packed
thick 1 mm - bar length 2 lm - pack. 10 Pcs - 20 lm


Article	L x H mm		
T... 1515C	15 x 15		
T... 2525C	25 x 25		

Available in the finishes: AO - AA.
The code of the selected colour must be added to the article code.
E.g.: T... 1515C (chosen finish anodized gold) TAO 1515C.


POLISHED CHROME ALUMINIUM thermo packed
thick 1 mm - bar length 2 lm - pack. 10 Pcs - 20 lm

Article	L x H mm		
TBC 1515C	15 x 15		
TBC 2525C	25 x 25		

On demand are available 1 lm bars.




COLOURS




CURTAINBALANCE

ANODIZED SILVER AND WHITE VARNISHED ALUMINIUM

CTAA 304C
CTB 304C



CTAA 404C
CTB 404C



ANODIZED SILVER ALUMINIUM thermo packed
thick 4 mm - bar length 2 lm - pack. 10 Pcs - 20 lm

Article	L mm		
CTAA 304C	30		
CTAA 404C	40		*

WHITE VARNISHED ALUMINIUM thermo packed
thick 4 mm - bar length 2 lm - pack. 10 Pcs - 20 lm

Article	L mm		
CTB 304C	30		*
CTB 404C	40		*

On demand are available 1 lm bars.



COLOURS



PIF 153
PIF 203
PIF 253
PIF 403




FLAT IRON

thick 3 mm - bar length 2 lm - pack. 10 Pcs - 20 lm

Article	L mm		
PIF 153	15		
PIF 203	20		
PIF 253	25		
PIF 403	40		

items not for sell individually.

AGF 203
AGF 303
AGF 403




CORNER EQUAL SIDES IRON

thick 3 mm - bar length 2 lm - pack. 10 Pcs - 20 lm

Article	L x H mm		
AGF 203	20 x 20		
AGF 303	30 x 30		
AGF 403	40 x 40		

items not for sell individually.

ALF 3020
ALF 4020




CORNER "L-FORM" IRON

thick 2 mm - bar length 2 lm - pack. 10 Pcs - 20 lm

Article	L x H mm		
ALF 3020	30 x 20		*
ALF 4020	40 x 20		*

items not for sell individually.

TVF 12
TVF 16
TVF 20
TVF 25




EMPTY ROUND TUBE IRON

bar length 2 lm - pack. 10 Pcs - 20 lm

Article	Ø mm ext.		
TVF 12	12		*
TVF 16	16		*
TVF 20	20		*
TVF 25	25		*

items not for sell individually.

TPF 10
TPF 12




FULL ROUND TUBE IRON

bar length 2 lm - pack. 10 Pcs - 20 lm

Article	Ø mm ext.		
TPF 10	10		*
TPF 12	12		*

items not for sell individually.

TQPF 08
TQPF 10
TQPF 12
TQPF 14




FULL SQUARE TUBE IRON

bar length 2 lm - pack. 10 Pcs - 20 lm

Article	L x H mm		
TQPF 08	8 x 8		*
TQPF 10	10 x 10		*
TQPF 12	12 x 12		*
TQPF 14	14 x 14		*

items not for sell individually.

TQVF 20
TQVF 25
TQVF 30
TQVF 40




EMPTY SQUARE TUBE IRON

bar length 2 lm - pack. 10 Pcs - 20 lm

Article	L x H mm		
TQVF 20	20 x 20		*
TQVF 25	25 x 25		*
TQVF 30	30 x 30		
TQVF 40	40 x 40		*

items not for sell individually.

TRF 3020
TRF 4020




EMPTY RECTANGULAR TUBE IRON

bar length 2 lm - pack. 10 Pcs - 20 lm

Article	L x H mm		
TRF 3020	30 x 20		
TRF 4020	40 x 20		

items not for sell individually.

TF 20




PROFILE "T-FORM" IRON

bar length 2 lm - pack. 10 Pcs - 20 lm

Article	L x H mm		
TF 20	20 x 20		*

items not for sell individually.

CUF 1515
CUF 3020



CANAL "U FORM" IRON


bar length 2 lm - pack. 10 Pcs - 20 lm

Article	L x H mm		
CUF 1515	15 x 15		*
CUF 3020	30 x 20		*


items not for sell individually.



An interpretation of:
One World Trade Center, David Childs , NEW YORK CITY (USA), 2014



PRODUCTS FOR LAYING



TRANSPARENCY FOR A PERFECT LAYING.

LAYING
INSTRUCTIONS



PATENTED

Completely visible joint

H ≥ 50 mm

H ≥ 50 mm


The only one with 2 elements

Save 3 pieces on intersections

PATENTED

- 1407796
- 1424326
- 2.790.556
- EP 2573296 B1
- EP 2952652 B1
- EP 3511484 B1
- US 8.635.815 B2
- US 9.328.522 B2
- US 10.760.284
- 2019000015848
- 202018000000069410
- Patents Pending

GRESS®
PROBAND



Kicking the clip in the direction of the joint.

ADVANTAGES

- 1 Simple and quick to lay with **only 2 elements: leveler & cap**. No need for expensive hand tools.
- 2 The only worldwide leveling system with multiple size levelers (2,3 and 5 mm). Built in spacers are available to accommodate "+" intersections as well as "T" joints **with a single leveler saving up to 3 pieces per joint**.
- 3 The only System with only two elements (**leveler & cap**) capable of leveling 3 to 20 mm floors and wall coverings with 1/2/3/5 mm available joints, and from 20 to 40 mm with 8 mm joint. Simply flip the cap over to work with various thicknesses.
- 4 It guarantees a minimum joint of 1 mm, maximum 5 mm.
- 5 Vertical compression reduces movement and widening of joints.
- 6 The thin base of the leveler allows for easy placement without mortar accumulation.
- 7 The shaped hole in the middle of the cross and T-shaped levelers allow a perfect control of the tiles lining up. Moreover the holes on their base enable a perfect anchoring between adhesive and tile.

Proleveling System

DESCRIPTION

Proleveling System is a revolutionary and innovative leveling system when laying medium and large materials with a thickness between 3 and 40 mm.

The patented system is made of 2 elements:

- A leveling base (1-2-3-5 mm size) with spaced notches that allow spacing/separating/ joining floors of any type and material in a way that is: linear, cross and half cross with joints to be chosen between 1mm, 2 mm, 3 mm and 5 mm.
- The threaded stem is attached perpendicularly to the base in a way that allows for easy adjustment with turns of the cap during installation. Removal of the cap and Stem after the materials are set is made easy with strategically placed breakage points that release with either increased pressure by turning the cap or by kicking the cap in the direction of the joint.

One cap fits all threaded stems and can be reused an infinite amount of times for big cost savings.

The new PPLS (patented) system assists in the reduction or elimination of ledging and lippage in the installation of various types of materials that are applied to floors or walls with mortar including: Large Format Tile, Natural Stone, Thin Profile Tile and many others.


LAYING SYSTEM

- Choose the desired type of Leveler (spacers) based on the requested joints and joining:
 - 1 mm Linear, Cross and Half Cross Version
 - 2 mm Linear, Cross and Half Cross Version
 - 3 mm Linear, Cross and Half Cross Version
 - 5 mm Linear, Cross and Half Cross Version
- Apply the thinset or mortar on a level base with the proper notched trowel as called out in the setting materials manufacturer's installation instructions.
- During the application of the tile or other materials, position the base of the chosen Leveler under the edge of the tile at the appropriate joint location and continue laying in sequence.
- Attach the cap to the threaded stem by rotating it clockwise. Level the joint by rotating the cap using the minimum amount of pressure needed.
- Once the setting materials have become solid and the floor or wall is ready for grout: kick the cap in the direction of the joint to detach connection points between base and stem.

Remover: Fixed on a drill allows to remove levelers from caps.



By turning the cap it is possible to level a thickness of up to 40 mm with an 8 mm joint.




T-shaped leveler installation.



Linear leveler installation.



Proleveling System



LINEAR LEVELER PROLEVELING SYSTEM

Article	thick mm	Pcs/Pack.		Pcs/box
PRSL 1	1	100		4000
PRSL 2	2	100		4000
PRSL 3	3	100		4000
PRSL 5	5	100		4000

"T" LEVELER PROLEVELING SYSTEM

Article	thick mm	Pcs/Pack.		Pcs/box
PRST 1	1	100		3000
PRST 2	2	100		3000
PRST 3	3	100		3000
PRST 5	5	100		3000

CROSS LEVELER PROLEVELING SYSTEM

Article	thick mm	Pcs/Pack.		Pcs/box
PRSC 1	1	100		3000
PRSC 2	2	100		3000
PRSC 3	3	100		3000
PRSC 5	5	100		3000

PROLEVELING SYSTEM REMOVER FOR LEVELER

Article	Pcs/Pack.		Pcs/box
PRSSV	50		1300



PRSSV

ROTATING POMMEL CAP FOR LEVELER PROLEVELING SYSTEM

Article	Pcs/Pack.		Pcs/box
PRSTT	50		1000
PRST	50		1000

PROTECTION CAP FOR PROLEVELING SYSTEM


Article	Pcs/Pack.		Pcs/box
PRSPC	50		3000




It protects the marble and natural stones surface from scratches that could be provoked by the cap during the floor levelling.

Tiles cm x cm	30 X 30	40 X 40	45 X 45	50 X 50	60 X 60	80 X 80	90 X 90	120 X 120
U. / MQ (Type of leveler)*	11 (only +)	6 (only +)	5 (only +)	4 (only +)	3 (only +)	5 (2+, 3L)	5 (2+, 3L)	3 (1+, 2L)

* + = cross leveler, L = linear leveler, T = "T" shape leveler



(30x30)
(40x40)
(45x45)
(50x50)
(60x60)




(80x80)
(90x90)
(120x120)

Tiles cm x cm	30 X 60	40 X 80	45 X 90	120 X 30	100 X 50	120 X 60
U. / MQ (Type of leveler)*	6 (only +)	6 (3+, 3L)	6 (3+, 3L)	6 (3+, 3L)	4 (2+, 2L)	4 (2+, 2L)

* + = cross leveler, L = linear leveler, T = "T" shape leveler




(30x60)



(40x80)
(45x90)
(120x30)
(120x50)
(120x60)




Tilest cm x cm	10 X 100	12 X 100	15 X 100	20 X 100	10 X 120	12 X 120	15 X 120	20 X 120	10 X 80	12 X 80	15 X 80	20 X 80	40 x 80	45 x 90	100 x 50	120 x 60
U. / MQ (Type of leveler)*	20 (only T)	17 (only T)	14 (only T)	10 (only T)	17 (only T)	14 (only T)	11 (only T)	9 (only T)	25 (only T)	21 (only T)	17 (only T)	13 (only T)	6 (only T)	5 (only T)	4 (only T)	4 (only T)

* + = cross leveler, L = linear leveler, T = "T" shape leveler



(10x100)
(12x100)
(15x100)
(20x100)
(10x120)
(12x120)
(15x120)
(20x120)
(10x80)
(12x80)
(15x80)
(20x80)
(40x80)
(45x90)
(100x50)
(120x60)

Proleveling Wedge System



ADVANTAGES



Complies with the legislation:
Thanks to the join of the stems directly on the base, after the removal there are no components between the joints;



Ergonomic wedge:
The concave part of the wedge allows greater ease in insertion;



Easier to insert:
Improved base with the new eye shape that ensures better and more effective insertion under the tile;

PROLEVELING WEDGE SYSTEM

Leveling system for tiles composed of 3 elements: wedge, leveler and plier. The levelers are available for grout lines of 1/1.5/2 and 3 mm and are suitable for tiles with thickness from 3 to 12 mm and from 12 to 20 mm. The wedge, with a length of 90 mm and a width of 22 mm, is inserted during the laying inside the leveler and thanks to the plier we get a complete flatness between adjacent tiles. When the adhesive is hardened, kick the wedges and the protruding part of the levelers along the grout line.

Levelers H 3-12 mm



Levelers H 12-20 mm



Wedge - PRLW



LEVELING WEDGE

Article	Pcs/pack			
PRLW	100			

TRACTION PLIER for PROLEVELING WEDGE SYSTEM

Article	Pcs/pack	
PRLWP	1	


PROLEVELING WEDGE SYSTEM - LINEAR LEVELERS

Article	h. mm	Thick. mm	Pcs/pack	Pcs/Box		
PRLW 1	3-12	1	200	3000		
PRLW 15	3-12	1,5	200	3000		
PRLW 2	3-12	2	200	3000		
PRLW 3	3-12	3	200	3000		
PRLW 120	12-20	1,5	100	2500		
PRLW 220	12-20	2	100	2500		

INDICATIVE CONSUMPTIONS FOR A SURFACE OF 10 M²

X cm	10	15	20	25	30	40	45	50	55	60	75	80	90	100	120	150	180	200	Y cm
10	1980																		
15	1317	876																	
20	495	328	490																
25	396	263	391	312															
30	660	438	488	389	431														
35	495	328	365	291	322	240													
40	440	292	324	258	285	213	189												
45	396	263	291	232	256	191	169	152											
50	360	239	264	211	232	173	154	138	125										
55	330	219	242	193	212	158	141	126	114	105									
75	396	263	258	206	212	158	140	126	114	104	99								
80	371	246	241	192	198	148	131	117	107	97	93	87							
90	330	219	214	171	176	131	116	104	94	86	82	77	68						
100	297	197	192	153	157	117	104	93	84	77	73	68	61	54					
120	330	219	200	160	157	117	104	93	84	77	71	66	59	52	49				
150	330	219	192	153	146	109	96	86	78	71	64	60	53	47	44	38			
180	330	219	186	149	139	103	91	82	74	68	60	56	49	44	40	34	31		
200	347	230	192	153	140	104	92	83	75	68	59	55	49	44	39	33	30	28	

Ex: 120 X 50 cm = 93 Pz X 10 m²





MULTISPACER Removable and reusable spacer for joints of tiled floors and walls. Its little tabs and open shape allows various uses with a perfect joint and view of the junctions among tiles during the laying.

MULTISPACER

PATENTED



MULTISPACER

Article	Thick. mm	Pcs/pack	Pcs/Box
MSP 1	1	100	2500
MSP 2	2	100	2500
MSP 3	3	100	2500
MSP 5	5	100	2500




The **CROSS-SHAPED** and **T-SHAPED SPACERS** are perforated, weatherproof and made in top quality material with choice of colour. They are used to provide regular gaps in floors and coverings and thanks to the anti-floating perforations remain in the correct laying position. Available in every required thickness 1 - 2 - 3 - 4 - 5 - 7 - 10 mm. Levelling wedges are also available for compensating differences in level that emerge during laying. The **Y-SHAPED SPACERS** have to be used to separate hexagonal tiles in floors and walls. Available in thickness 2 and 3 mm.

SPACERS LEVELLING WEDGES

PERFORATED SPACERS CROSS-SHAPED boxes with bags of 250 Pcs each

Article	Thick. mm	Pcs/Box
RC 1	1	20.000
RC 2	2	15.000
RC 3	3	15.000
RC 4	4	15.000
RC 5	5	15.000
RC 7	7	10.000
RC 10	10	5.000




PERFORATED SPACERS T-SHAPED boxes with bags of 250 Pcs each

Article	Thick. mm	Pcs/Box
RT 1	1	20.000
RT 2	2	15.000
RT 3	3	15.000
RT 4	4	15.000
RT 5	5	15.000
RT 7	7	10.000
RT 10	10	5.000




Y-SHAPED SPACERS FOR HEXAGONAL TILES boxes with bags of 250 Pcs each

Article	Thick. mm	Pcs/Box
RY 2	2	10.000
RY 3	3	10.000



LEVELLING WEDGES boxes with bags of 500 Pcs

Article	Thick. mm	Pcs/Box
PCU 5	0 - 5	10.000



SPACERS / SQ.M

TILE FORMAT cm x cm	60 x 60	60 x 30	40 x 40	40 x 30	40 x 20	33 x 33	30 x 30	30 x 20	25 x 25	20 x 20	15 x 15	13 x 26	13 x 13	10 x 20	10 x 10
CROSS-SHAPED SPACERS No. / Sq.m	3	6	7	9	12	9	11	17	16	25	44	30	60	50	100
T-SHAPED SPACERS No. / Sq.m	6	12	14	18	24	18	22	34	32	50	88	60	120	100	200

Y-SHAPED SPACERS

2 spacers for each tile multiplied by the amount of tiles per square meter

PROSUPPORT TUBE SYSTEM

ADJUSTABLE AND MODULAR SUPPORTS SYSTEM FOR OUTDOOR FLOATING FLOORS

PROSUPPORT TUBE SYSTEM is an adjustable and modular supports system for outdoor floating floors from the height of 29 mm to 1000 mm. The system is composed of 1 base, 2 screws, 1 flange, 2 heads and several pvc pipes to obtain the requested height. Both heads, according to the screw, can be fix or self-levelling.

PATENTED

PROSUPPORT TUBE SYSTEM KIT HEIGHTS

FULL KIT - Pack. 40 Pcs. - Items not for sale individually. Minimum order one pack.

A: SUPPORT'S HEIGHT WITH SELF-LEVELLING INSTALLATION
B: SUPPORT'S HEIGHT WITH FIX SIDE INSTALLATION
T: THICKNESS OF THE SPACER FLAP



 T: 4 / 2 mm A: 34 / 54 mm B: 29 / 49 mm	 T: 4 / 2 mm A: 54 / 74 mm B: 49 / 69 mm	 T: 4 / 2 mm A: 74 / 94 mm B: 69 / 89 mm	 T: 4 / 2 mm A: 94 / 114 mm B: 89 / 109 mm
FULL KIT CODE PST3454/4 T = 4 mm PST3454/2 T = 2 mm €/Pc. €/Pack.	FULL KIT CODE PST5474/4 T = 4 mm PST5474/2 T = 2 mm €/Pc. €/Pack.	FULL KIT CODE PST7494/4 T = 4 mm PST7494/2 T = 2 mm €/Pc. €/Pack.	FULL KIT CODE PST94114/4 T = 4 mm PST94114/2 T = 2 mm €/Pc. €/Pack.
 T: 4 / 2 mm A: 114 / 134 mm B: 109 / 129 mm	 T: 4 / 2 mm A: 134 / 154 mm B: 129 / 149 mm	 T: 4 / 2 mm A: 154 / 174 mm B: 149 / 169 mm	 T: 4 / 2 mm A: 174 / 194 mm B: 169 / 189 mm
FULL KIT CODE PST114134/4 T = 4 mm PST114134/2 T = 2 mm €/Pc. €/Pack.	FULL KIT CODE PST134154/4 T = 4 mm PST134154/2 T = 2 mm €/Pc. €/Pack.	FULL KIT CODE PST154174/4 T = 4 mm PST154174/2 T = 2 mm €/Pc. €/Pack.	FULL KIT CODE PST174194/4 T = 4 mm PST174194/2 T = 2 mm €/Pc. €/Pack.
 T: 4 / 2 mm A: 194 / 214 mm B: 189 / 209 mm			
FULL KIT CODE PST194214/4 T = 4 mm PST194214/2 T = 2 mm €/Pc. €/Pack.			


HEIGHTS GREATER THAN 209 mm

H (mm) SELF-LEVELLING HEAD (A)	H (mm) FIX HEAD (B)	Choose the kit according to the desired tile joint (T)		PIPE	FLANGE
		PST3454/4 T = 4 mm	PST3454/2 T = 2 mm		PSTGH 02
214/234	209/229			+ PSTT 175	
234/254	229/249			+ PSTT 195	
254/274	249/269			+ PSTT 215	
274/294	269/289			+ PSTT 235	
294/314	289/309			+ PSTT 255	
314/334	309/329			+ PSTT 275	
334/354	329/349			+ PSTT 295	
354/374	349/369			+ PSTT 315	
374/394	369/389			+ PSTT 335	
394/414	389/409			+ PSTT 355	
414/434	409/429			+ PSTT 375	
434/454	429/449			+ PSTT 395	
454/474	449/469			+ PSTT 415	
474/494	469/489			+ PSTT 435	
494/514	489/509			+ PSTT 455	




SELF-LEVELLING HEAD MODE

Self-levelling head mode
Max height 1000 mm with max slope of 5%.



FIXED HEAD MODE

Fixed head mode
Max height 1000 mm




PROSUPPORT TUBE SYSTEM COMPONENTS

BASE +SCREW 20/40 mm
polypropylene - pack. 40 Pcs. (PSTK 0202) - pack. 20 Pcs. (PSTK 0204)

Article	Thickness (mm)	kit / pack.
PSTK 0202	20	40
PSTK 0204	40	20

Items not for sale individually. Minimum order one pack.



PSTK 0202

BASE +
SCREW 20 mm



PSTK 0204

BASE +
SCREW 40 mm


HEAD with removable flaps 2/4 mm
polypropylene - pack. 40 Pcs.

Article	flap Thk (mm)	kit/pack.
PSTH 02	2	40
PSTH 04	4	40


Items not for sale individually. Minimum order one pack.



PSTH 02 / PSTH 04



FLAP THICKNESS 2 mm - PSTH 02



FLAP THICKNESS 4 mm - PSTH 04

FLANGE 40 mm
polypropylene - pack. 40 pcs

Article	H (mm)	Pc/pack.
PSTGH 02	40	40

Connection nut with a lower side of 110 mm inner diameter, where the pipe of different heights should be inserted, and one side with thread where the regulation screws should be inserted.
Items not for sale individually. Minimum order one pack.



PSTGH 02

ANTI-NOISE AND ANTI-SLIP DISK
rubber - H 1,5 mm - Ø 150 - pack. 120 pcs

Article	H / Ø mm	Pc/pack.
PSTG	H 1,5 - Ø150	120

The non-slip rubber disk to be used with the heads of PROSUPPORT TUBE SYSTEM reduces noises till 25 dB.
Items not for sale individually. Minimum order one pack.



PSTG

PRE-CUT EXTENSION PIPE - outer diameter Ø110 mm Thickness 4 mm - polyethylene polypropylene - pack. 40 Pcs.

Article	H (mm)	Pc/pack.
PSTT 35	35	40
PSTT 55	55	40
PSTT 75	75	40
PSTT 95	95	40
PSTT 115	115	40
PSTT 135	135	40
PSTT 155	155	40

Items not for sale individually. Minimum order one pack.



PSTT...

FULL LENGHT EXTENSION PIPE - outer diameter Ø110 mm Thickness 4 mm - polyethylene or polypropylene - pallet 43 Pcs.

Article	H (ml)	ml/pallet.
PSTT 2700	2,7	116

Items not for sale individually. Minimum order one pallet.

UPON REQUEST IT IS POSSIBLE TO HAVE HEIGHTS TILL 1000 MM USING PIPES FROM 155 TILL 955. For information and installation instructions ask for the technical data sheet. Price to be agreed. Production delay 4/5 weeks.


PSTT 2700



270 cm

PERIMETER SPACER

Perimeter spacer of stainless steel AISI 316L / 1.4404 - V4A for laying outdoor floating floors. The profile makes a 5 mm wide perimeter gap, for the outflow of rainwater; moreover, thanks to the rounded fin with which is provided, it does not damage the waterproofing sheath. The slit width of 0.5 cm and the length of 18 cm ensure a perfect anchorage of the spacer with the heads of the Prosupport System.



PERIMETER SPACER PROSUPPORT SYSTEM
Stainless steel AISI 316L / 1.4404 - V4A - pack. 40 Pcs



Article		
DPP		

PROSUPPORT TUBE SYSTEM OPTIONAL

ADJUSTING KEY (only for head PSTH 04)

Article		
PSTAK		



ADJUSTABLE SPACER TABS 4 mm
polypropylene - Pack 80 pcs

Article	L x H mm	Pcs/pack	
PSTJ	80 x 20	80	

Spacer tabs 80 mm long to be fixed on the self-levelling head, which allow the fixing of wooden, WPC and aluminium joists of max width 80 mm.



Items not for sale individually. Minimum order one pack.

FIXING CLIP FOR TILES - WIND-PROOF
Pack 40 pairs

Article	L x H mm	pairs/pack	
PSTWP	20 x 60	40	

Fastening clip to fix the tiles and block the floor in case of strong wind. The clips must be inserted inside the cross joint or along the perimeter of the floor.



Items not for sale individually. Minimum order one pack.

RUBBER DISK for laying on bituminous roof membrane
H 2 mm - Pack. 100 Pcs (box 100 pcs)

Article	H (mm)	
LVGG 02	2	

Rubber disc, 2 mm thick, to be applied under the support (SQG 15) to protect the bituminous membrane.



SPACER FOR APPLICATION ON GRAVEL
Pack. 100 Pcs (box 100 pcs)

Article		
DILV		



Transparent plastic 4 mm cross spacer for laying on gravel or irregular surfaces.



PROSUPPORT PROFILE T & N is a profile for the protection and finishing of the external edge of raised floors in ceramic, wood and composite materials. The vertical section of the profiles features a specially designed fins that create a dovetail cladding system. This dovetail cladding system allows for the adhesive used to fix the covering to also mechanically bond to the profiles. The profile is also available with a decorative edge of 2 cm height (PROSUPPORT PROFILE T).

PROSUPPORT PROFILE T & N

VARNISHED ALUMINIUM
NATURAL ALUMINIUM



PROSUPPORT PROFILE T - VARNISHED ALUMINIUM
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	L x H mm	h mm		
PSPRPT 20AL...	177,7x81,5	60		

COLOURS (EMBOSSSED)



PROSUPPORT PROFILE N - NATURAL ALUMINIUM
bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H mm	L		
PSPRP 15560AL	60	156,5		

COLOURS



*** ON DEMAND (EMBOSSSED)**



LAYING INSTRUCTIONS


1. Choose "PROSUPPORT PROFILE" desired model.
2. Cut "PROSUPPORT PROFILE" to the desired length and put on the supports and aligning.
3. Lay the floor by adjusting the height of the supports until completely leveling.
4. Cut the tiles of the correct size to close the perimeters of the floating floor.
5. Fix on the vertical surface of the profile the tiles using a suitable adhesive.

PROSUPPORT SYSTEM A&B Perimeter profile to protect and finish the outer edge of raised floors of different types, ceramic, wood, stone etc. The **PROSUPPORT PROFILE A** consists in an "L"-shaped horizontal flat base to insert and anchor above the **PROSUPPORT** Self-leveling head and a vertical visible part to insert in the vertical "L"-shaped element (as indicated in the drawing).

Use: Perimeter profile to protect and finish the outer edge of raised floors of different types, ceramic, wood, marble etc. The **PROSUPPORT PROFILE** consists in an "L"-shaped horizontal flat base to insert and anchor above the **PROSUPPORT** Self-leveling head and a vertical visible part to insert in the vertical "L"-shaped element (as indicated in the drawing)

PROSUPPORT PROFILE A & B

VARNISHED ALUMINIUM,
NATURAL ALUMINIUM



PUNCHED AND PERFORATED PROSUPPORT A
NATURAL ALUMINIUM - length 2,7 lm - pack. 20 Pcs

Article	L x H		
BPPSAN 15015	150 X 15		
BPPSAN 15020	150 X 20		
BPPSAN 15025	150 X 25		


COLOURS




TOP PROFILE PROSUPPORT B - VARNISHED ALUMINIUM
length 2,7 lm Pack 10 Pcs (PFPSAL...1060 Pack 20 Pcs)

Article	H1		
PFPSAL... 1060	60		
PFPSAL... 1080	80		
PFPSAL... 10100	100		

COLOURS (EMBOSSSED)




PROSUPPORT A




PROSUPPORT B

PFPSAL... 1060 PFPSAL... 1080 PFPSAL... 10100



*** ON DEMAND (EMBOSSSED)**




* = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed

PRORAIL SYSTEM

PRORAIL SYSTEM SYSTEM is a modular system composed of aluminium joists to lay floating floors of any size, to create steady and modular substructures together with PROSUPPORT TUBE and PROSUPPORT SLIM. The system consists of two aluminium joists, PRORAIL and PRORAIL RET, one fastening ring PRORAIL RING, two cross spacers with removable flaps PRORAIL SPACER and one anti-noise and anti-slip rubber PRORAIL RUBBER

PRORAIL
PSTRAN 53



PRORAIL - SHAPED JOIST
aluminium - Pack 10 Pcs - Bar length 2,7 Lm

Article	L x H (mm)	Pc/Pack		
PSTRAN 53	50 X 30	10		




PRORAIL RUBBER
Roll length 110 Lm

Article	L roll ml			
PSTRI	110			



PRORAIL RET
PSTRAN 5030



PRORAIL RET - SMOOTH JOIST
aluminium - Pack 10 Pcs - Bar length 2,7 ML

Article	L x H (mm)	Pc/Pack		
PSTRAN 5030	50 X 30	10		




PRORAIL RING - JOIST FASTENING RING
polypropylene - Pack 40 Pcs

Article	Ø mm	Pc/Pack		
PSTRR	135	40		




PRORAIL SYSTEM LAYING PATTERN

- Material required for 1 qm of the below pattern:
- 3 pcs **PROSUPPORT TUBE/PROSUPPORT TUBE SLIM**
 - 3 pcs fastening rings **PRORAIL RING**
 - 2.7 lm **PRORAIL** joist
 - 4 lm **PRORAIL RUBBER**



TECHICAL LAYING INSTRUCTIONS

1. Choose the support **PROSUPPORT TUBE** or **PROSUPPORT SLIM** of the required height;
2. Set the fastening ring **PRORAIL RING** on the supports;
3. Set the joist **PRORAIL (*)** or the joist **PRORAIL RET** on the ring;
4. Insert the rubber **PRORAIL RUBBER** inside the grooves of the joist **PRORAIL**;
5. Set the cross spacers **PRORAIL SPACER** following the laying pattern; (*) It is possible to fix the joist **PRORAIL** on the supports fixing it into the spacer flaps, see picture hereunder.



PRORAIL SPACER
PSTRS 02



PRORAIL SPACER
PSTRS 04

PRORAIL SPACER - CROSS SPACER with removable flaps
polypropylene - Pack 100 Pcs

Article	thickness (mm)	Pc/Pack		
PSTRS 02	2	100		
PSTRS 04	4	100		



ANTI-ROTATION CLIP - Pack 40 Pcs

Article	Pc/Pack			
PSTCAR	40			

FIXING WITH PRORAIL JOIST:

Prosupport tube/slim + Prorail + Prorail spacer + Prorail rubber



FIXING WITH RING AND PRORAIL JOIST:

Prosupport tube/slim + Prorail ring + Prorail + Prorail spacer + Prorail rubber



FIXING WITH RING AND PRORAIL RET SMOOTH JOIST :

Prosupport tube/slim + Prorail ring + Prorail ret



PATENTED



PROSUPPORT
TUBE

PRORAIL RING

PRORAIL

PRODRAIN 10
(OPTIONAL)

PRORAIL
SPACER

PRORAIL
RUBBER

PROSUPPORT SLIM SYSTEM

PROSUPPORT SLIM is a modular system to make outdoor floating floors from 10 to 40 mm height, it is composed of two bases of 10 mm height, levellers of 10 mm thickness and anti-noise and anti-slip disks. Thanks its modularity the system allows to make, from a height of 10 mm, all heights with 2 mm interval using the levellers.



BASE WITH FLAPS
PSTSB 02 - 2 mm



BASE WITH FLAPS
PSTSB 04 - 4 mm



LEVELLER
PSTSL 02 - 2 mm



ANTI-NOISE AND ANTI-SLIP DISK
PSTSG

BASE with flaps 2/4 mm
polypropylene - Pack 120 Pc.



Article	Thickness (mm)	Pcs/pack		
PSTSB 02	2	120		
PSTSB 04	4	120		

LEVELLER
Polystyrene - Pack 120 Pc.




Article	Thickness (mm)	Pcs/pack		
PSTSL 02	2	120		

ANTI-NOISE AND ANTI-SLIP DISK
rubber - pack. 120 pcs

Article	H/Ø mm	Pcs/pack		
PSTSG	H 1,5 - Ø 150	120		



ACHIEVABLE HEIGHTS WITH PROSUPPORT SLIM SYSTEM



TO OBTAIN MORE THAN 30 mm HEIGHTS USE THE PROSUPPORT TUBE SYSTEM WITH WHICH IT'S POSSIBLE TO OBTAIN HEIGHTS FROM 29 mm UP TO A MAXIMUM OF 1000 mm.



SUPPORT and **LEVELLER** are suitable for the realization of outdoor floating floors. The support, in polyethylene, has a height of 15 mm. The rubber leveler, with a thickness of 3 mm, can be applied on the supports up to a maximum of 2. **SUPPORT** and **LEVELLER** are suitable for outdoor areas, terraces, pool edges and pedestrian crossings.

SUPPORT AND LEVELLER

POLYETHYLENE

SQUARES SUPPORT

boxes of 350 Pcs

Article	Thick. mm
SQG 15	15

ITEMS NOT FOR SALE INDIVIDUALLY.



SUPPORT

SQUARES LEVELLER

boxes of 100 Pcs

Article	Thick. mm
LQG 03	3


ITEMS NOT FOR SALE INDIVIDUALLY.




LEVELER



SQG 15




LQG 03



LAYING INSTRUCTIONS

1. Lay the supports on the waterproofing membrane. 2. To reach the desired height or compensate different heights, if necessary, place 1 or 2 rubber levelers on the support. 3. Lay the floating flooring.

MAGNET KIT



MAGNET KIT - 4 magnets and 4 plates
for ceramic inspection panel - packs of **10 kits**

Article	
KMD	

SCISSORS FOR PVC PROFILES



SCISSORS
for cutting PVC profiles

Article	
FTPP	

PROECOFON

EXPANDED POLYETHYLENE CLOSED - CELL WITH ADHESIVE



PROECOFON is a roll of closed-cell polyethylene used as edging between the wall and screed or where there are expansion joints. It should be used in all floor-laying work to ensure long life of the floor.

CLOSED-CELL EXPANDED POLYETHYLENE

Article	Thick. x H mm	lm/roll		
PEF 550A	5 X 50	25		
PEFPU 510A	5 X 10	2,7		
PEF 5100A	5 X 100	100		

For perimeter areas and joints.
PEFPU 510A for Prot Terrace Drain Drip
PEF 550A - sold exclusively in packs of **2 pcs**

EXEMPLE OF LAYING



PROBAND FIX

MONOCOMPONENT WATERPROOF SEALANT



SEALANT MONOCOMPONENT WATERPROOF

Pack of **12** cartridges

Article	Cartridge lm		
PRBFXB	290		
PRBFXG	290		

DISPENSING GUN FOR SEALANT CARTRIDGES

Article	Pc/Pack		
PRBFXGUN	1		

SEALANT MONOCOMPONENT WATERPROOF CARTRIDGE

Pack of **12** cartridges

Article	Cartridge lm		
PRBFXUB	600		
PRBFXUG	600		

COLOURS

B - White	G - Grey

Technical data:

Appearance:	white or gray thixotropic paste
Temperature range for application:	+ 5 °C / + 40 °C
Temperature range:	- 40 °C / + 90 °C
Curing:	≈ 2 mm / 24 h
Commissioning:	≈ 7 days

Suggestions for the installation:

In general cementitious support must be free from dust, oil and grease, dry and free from any visible moisture, free of loose or imperfectly anchored parts such as residual traces of cement, lime and paint, which must be totally removed. In case of contact with eyes, rinse immediately with water and seek medical advice. Avoid contact with skin and keep out of reach of children.

• Use

Balconies, terraces, bathrooms, kitchens, saunas, swimming pools and exterior surfaces of any size.

• Don't use

On bitumen membranes.
To seal proband with PRODESO®.

PROPOLISH

WHITE CREAM - BASED SURFACTANTS SUITABLE FOR CLEANING

White cream - based surfactants, amines and inert powder, suitable for cleaning, degreasing and polishing of stainless steel surfaces and opaque/matt brass. The product, ready to use, does not contain acids and alkalis and do not leave marks after use. It does not emit harmful substances



Article	Pack. g.	Pcs/Pack		
PRLISH	250	6		

PROCARE CLEAN

CLEANING SPRAY

Cleaning spray ready to use suitable for cleaning of stainless steel, brass and aluminum profiles, from residual surface oxide and limestone. The product deposit a protective film that prevents the deposit of limestone and soap residues. Its periodic use allows to obtain bright and cleaner surfaces for long period. Suitable also for glasses, mirrors and bathroom fittings.



Article	Pack. lm	Pcs/Pack.		
PRCLEAN	750	6		

TROWEL in steel foil 3x3, support in polished aluminium with electro welded fixing. Rubber grip fixed with an anti-rotation system. Particularly suitable for the laying of the waterproofing system PROFOIL.


TROWEL

STEEL

TROWEL STEINLESS STEEL

Box 6 Pcs

Article	Tooth	Dimensions mm	Pcs/Box
PFTT33	3X3	280X120	6



TROWEL in steel foil 5x7, support in polished aluminium with electro welded fixing. Rubber grip fixed with an anti-rotation system. Particularly suitable for the laying of the waterproofing and uncoupling systems PRODESO® and PRODESO® HEAT & PRODESO® HEAT GRIP.


TROWEL

STEEL

TROWEL STEINLESS STEEL

Box 6 Pcs

Article	Tooth	Dimensions mm	Pcs/Box
PFTT57	5X7	280X121	6



TROWEL in steel foil 10x10, support in polished aluminium with electro welded fixing. Rubber grip fixed with an anti-rotation system. Particularly suitable for the laying of tiles above the waterproofing and uncoupling systems PRODESO® and PRODESO® HEAT & PRODESO® HEAT GRIP.


TROWEL

STEEL

TROWEL STEINLESS STEEL

Box 6 Pcs

Article	Tooth	Dimensions mm	Pcs/Box
PFTT1010	10X10	280X122	6




TROWEL in PVC size 10x10 cm, resistant to solvents, with a triangular teeth of interaxle spacing of 5 mm, 4 mm and 3 mm. To be used for the application of adhesives PROBAND FIX.

TROWEL

PVC

TROWEL

Article	Dimensions mm
PRSPD 10	100x100



ROLLER in nylon, 40 cm long, fixed to a varnished metal or stainless steel 304 frame, suitable for pressing the PRODESO®, PRODESO® HEAT & PRODESO® HEAT GRIP and PROFOIL. The roller is equipped with an extendable grip, length-adjustable and with an L base that allows to load 1 bag of adhesive to obtain the correct and homogenous pressing of the membranes. A tripod allows to keep the roll in the right position while loading the bag.

ROLLER

VARNISHED STEEL OR STAINLESS STEEL

ROLLER IN STAINLESS STEEL

L 40 cm

Article	L mm	Finish
PSM	400	varnished
PSMAC	400	steel





An interpretation of:
Premier Tower, Elenberg Fraser, MELBOURNE (Australia)


BUILDING SYSTEMS



SNAP-ON STRAND SHEATH

GREY RIGID PVC

The **SNAP-ON PVC STRAND SHEATH** serves to cover/neutralise the reinforcement strands inside the prestressed beams; the sheath cancels out the stress that the strands transmit to the beam, thereby permitting the positive to be changed to left-handed moments. Available in various diameters and lengths.




GREY RIGID PVC

bar length **3 lm** - pack. **50 Pcs** - 150 lm


Article	Ø inches	Ø mm		
R 110	3 x 3"	8		
R 111	3 / 8"	12		
R 112	1 / 2"	15		
R 113	0' 6"	19		

R 110/ 111: 15.000 lm / pallets
R 112/113: 10.800 lm / pallets

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS




Laying is extremely simple by just positioning the sheath so that the "V" shaped flanges are facing the prestressed reinforcement strands that are already in situ and gently pressing until the sheath snaps on.



SNAP-ON STRAND TUBE

GREY RIGID PVC



GREY RIGID PVC

bar length **3 lm** - pack. **50 Pcs** - 150 lm


Article	Ø inches	Ø mm		
R 114	3/8"	12		
R 115	1/2"	15		
R 116	0/6"	19		

R 114/ 115: 15.000 lm / pallets
R 116: 12.000 lm / pallets

COLOURS



G - Grey




LAYING INSTRUCTIONS

Laying is very simple; just insert the casing over the strands before they are tensioned.

FINNED DISTANCE TUBE

GREY RIGID PVC



GREY RIGID PVC

bar length **2 lm** - pack. **50 Pcs** - 100 lm

Article	Ø mm		
TDA 09	9		
TDA 12	12		

TDA 09: 15.000 lm / pallets
TDA 12: 10.000 lm / pallets

COLOURS



G - Grey



LAYING INSTRUCTIONS

Laying is very simple:
1. Just insert the iron rod into the finned tube before closing the reinforcement panel.
2. Upon removing the reinforcement panels, if necessary insert the end plugs.

END CAPS FOR DISTANCE TUBE

GREY HD POLYPROPYLENE

PPT 09 / 12




SMOOTH END CAPS - GREY HD POLYPROPYLENE

pack. **1000 Pcs**


Article	Ø mm		
PPT 09	9		
PPT 12	12		

RIBBED DISTANCE TUBE


GREY RIGID PVC




PPD 20



PPD 22



PPD 26



GREY RIGID PVC

bar length 2 lm - pack. 25 Pcs - 50 lm

Article	Ø mm inside		
PPD 20	20		
PPD 22	22		
PPD 26	26		

PPD 20/ PPD 22: 5.000 lm / pallets
PPD 26: 3.000 lm / pallets

COLOURS



G - Grey

WASHERS AND END CAPS FOR DISTANCE TUBE

GREY HD POLYPROPYLENE - PVC / RUBBER

WASHERS - GREY HD POLYPROPYLENE

pack. 1000 Pcs

Article	Ø mm outside		
PPR 20	20		
PPR 22	22		
PPR 26	26		

OUTSIDE WASHERS - GREY HD POLYPROPYLENE

pack. 1000 Pcs

Article	Ø mm		
RETDB 22	26		

INSIDE END CAPS - PVC / RUBBER

pack. 2000 PCS divided into two 1000 Pcs bags

Article	Ø mm		
TIGPC 22	22		

SMOOTH PLUGS - GREY HD POLYPROPYLENE

(PPT 20/ 22/ 26 pack. 2000 Pcs divided into two 1000 Pcs bags)

Article	Ø mm	Pcs/Pack.		
PPT 09	9	1000		
PPT 12	12	1000		
PPT 16	16	1000		
PPT 20	20	2000		
PPT 22	22	2000		
PPT 26	26	2000		

HOLLOW PLUGS - GREY HD POLYPROPYLENE

pack. 2000 Pcs divided into two 1000 Pcs bags


Article	Ø mm	Pcs/Pack.		
PPTC 22	22	2000		

SMOOTH PLUG
for walls without plaster

HOLLOW PLUG
for plaster



PPR 20 / 22 / 26




PPT 09 / 12 / 16 / 20 / 22 / 26



RETDB 22



TIGPC 22




DRIP


GREY RIGID PVC



GCT 20



GCT 30



GREY RIGID PVC

bar length 2 lm - pack. 50 Pcs - 100 lm

Article	L x H mm		
GCT 20	20 x 12		
GCT 30	30 x 15		

GCT 20: 15.000 lm / pallets
GCT 30: 10.000 lm / pallets

COLOURS



G - Grey

LAYING INSTRUCTIONS


Must be fixed below the sheathing/armature to create the drip course.

* = Production on demand with minimum quantity of 10000 pcs. Production delay 4/5 weeks. Price to be agreed.

PROFILE WITH TRIANGULAR CHAMFER

GREY RIGID PVC

The **TRIANGULAR CHAMFER** is made in grey rigid PVC in various widths 10-15-20-30 mm and standard length of 2 lm. It is mainly used to chamfer the corners of the concrete pours when making, for example, walls-columns etc. It is strong and easy to lay.



LAYING INSTRUCTIONS

Put the nails into the central part along the profile before pouring the concrete.

GREY RIGID PVC

bar length 2 lm - pack 50 Pcs - 100 lm

Article	Width mm		
PST 10	10		
PST 15	15		

20.000 lm pallets


GREY RIGID PVC

bar length 2 lm - pack 50 Pcs - 100 lm

Article	Width mm		
PST 20	20/22		
PST 30	30/32		


PST 20: 15.000 lm / pallets

PST 30: 10.000 lm / pallets



ROUNDED TRIANGULAR CHAMFER FILLET

GREY RIGID PVC



LAYING INSTRUCTIONS

Put the nails into the central part along the profile before pouring the concrete.

GREY RIGID PVC

bar length 2 lm - pack 50 Pcs - 100 lm

Article	L mm		
PSD 22	20/22		
PSD 32	30/32		


PSD 22: 15.000 lm / pallets

PSD 32: 10.000 lm / pallets

COLOURS



G - Grey



FISHBONE RIBBED JOINT

GREY RIGID PVC

COLOURS



G - Grey

LAYING INSTRUCTIONS

Laying is very simple: just insert the ribbed joint into the gap deliberately left in the concrete or the screed.


GREY RIGID PVC

bar length 2 lm - pack 50 Pcs - 100 lm

Article	H x L mm		
GRP 25	25 X 5		
GRP 45	45 X 5		

GRP 25: 10.000 lm / pallets

GRP 45: 5.000 lm / pallets



PROFILE WITH DOUBLE CHAMFER - FOR BALCONIES

GREY RIGID PVC

COLOURS



G - Grey

LAYING INSTRUCTIONS

Laying is very simple: just fix it with nails or clamps in the relative formwork prior to pouring the concrete.


GREY RIGID PVC

on demand bar length

Article	H mm		
R 117	80		*

PROFILE SPECIFICATIONS:

- Chamfer angle 45°
- Chamfer length 20 mm
- Bar length on demand
- Weight x metre ≈ 2,3 Kg



* = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed.

WATERSTOP


PLASTICIZED PVC BLUE

The **WATERSTOPS** profiles are made in high-quality polyvinyl chloride (plasticized PVC) and have excellent physical-mechanical properties, strength, flexibility, resistance to ageing and fluid-tightness even under pressure. The "Flat Waterstop" model art. WP is used for adjacent pours of concrete, while the "Waterstop with Bulb" model art. WB is used in concrete casting but as an expansion joint, thanks to the central bulb. They find many applications: floors, underground rooms, trench ducts/ underground passages, face walls, cisterns, silos, swimming pools, tanks, canals, dams, aqueducts, etc. The quality of the materials allows the waterstops to be used on concrete structures exposed to temperatures between -30°C and $+70^{\circ}\text{C}$, also ensuring good resistance to chemicals in alkaline environments, to brackish waters and to acid solutions.

FLAT
WATERSTOPS
WP 100

FLAT
WATERSTOPS
WP 150 / 200 /
220 / 250 / 300

WATERSTOPS
WITH BULB
WB 200 / 220 /
250 / 300



FLAT WATERSTOPS - PLASTICIZED PVC BLUE

pack. rolls 25 lm (WP 150 - pack. rolls 50 lm)

Article	L mm		
WP 100	100		
WP 150 (50 ml)	150		
WP 200	200		
WP 220	220		
WP 250	250		
WP 300	300		



ANCHORING CLIPS for WATERSTOPS on demand.

WATERSTOPS WITH BULB - PLASTICIZED PVC BLUE

pack. rolls 25 lm


Article	L mm		
WB 200	200		
WB 220	220		
WB 250	250		
WB 300	300		

ANCHORING CLIPS for WATERSTOPS on demand.



SEALING OF WATERSTOPS

The Waterstops may be welded together to obtain a single piece of the required length. The two parts must be properly cleaned for perfect fluid-tightness of the joints. The waterstops are usually field welded using a normal hot-air heater on the ends of the sections. The bond is accomplished by melting the material and pressing one end over the other.



COLOURS



SIZE

ART.	A	B	C	D
WP 100	40 mm			
WP 150	13,3 mm	15,5 mm	45,5 mm	
WP 200	22 mm	22 mm	50 mm	
WP 220	23 mm	25 mm	50 mm	
WP 250	19 mm	21 mm	71,5 mm	
WP 300	20,5 mm	22,5 mm	78 mm	
WB 200	16 mm	18 mm	85 mm	32 mm
WB 220	16 mm	18,5 mm	86 mm	33 mm
WB 250	26 mm	20 mm	84 mm	30 mm
WB 300	26 mm	22 mm	88 mm	34 mm

ANCHORING CLIPS FOR WATERSTOPS

GREY UH POLYPROPYLENE

GREY HD POLYPROPYLENE

pack. 1000 Pcs

Article		
CLPS		





* = Production on demand with minimum quantity of 10 rolls. Production delay 4/5 weeks. Price to be agreed.

PRODISTANZ

GREY HD POLYPROPYLENE

PRODISTANZ is a patented new product that simplifies, improves and speeds up the work of securing and preparing shuttering panels used in the casting of concrete; it avoids the cutting and assembling in situ of the tubular water-washer (traditional system). **PRODISTANZ** is recommended for its special, very strong structure, which is resistant to compressive stress and prevents water infiltration thanks to the lateral ribs along the cylindrical part and the horizontal supports and circles. It consists of a single plastic element and is available in a wide range of lengths 15-20-25-30-35-40 cm (in packs of 100 Pcs.). They come with watertight plugs in a choice of two types. Watertight caps at 18 Atm. / Bar.

spacers



GREY HD POLYPROPYLENE

pack. 100 Pcs + 200 end caps

Article	L cm		
PDZ 15	15		
PDZ 20	20		
PDZ 25	25		
PDZ 30	30		
PDZ 35	35		
PDZ 40	40		

SIMPLE FAST ECONOMIC

- Exclusive patented product
- High resistance to compressive stress and to water infiltration
- Fast, assured work, without waste, cutting costs or pipe scraps
- Extremely easy to use
- Vast range available: 15-20-25-30-35-40 cm
- Innovative design - guaranteed
- Quality - Constant colour and quality



END CAPS AND JOINTS FOR PRODISTANZ

GREY HD POLYPROPYLENE - PVC/RUBBER

TIGPC 22




GPDZ 22



PPTC 22



PPTC 22 hollow plug for plaster



Hollow plug: for better anchorage of the plaster. (new) standard.

HOLLOW END CAPS - GREY HD POLYPROPYLENE


pack. 2000 Pcs divided into two 1000 Pcs bags

Article	Ø mm	Pcs/Pack.	
PPTC 22	22	2000	

SMOOTH PLUGS - GREY HD POLYPROPYLENE

pack. 2000 Pcs divided into two 1000 Pcs bags

Article	Ø mm	Pcs/Pack.	
PPT 22	22	2000	



INSIDE END CAPS - PVC/RUBBER


pack. 2000 Pcs divided into two 1000 Pcs bags

Article	Ø mm		
TIGPC 22	22		

JOINT - GREY HD POLYPROPYLENE

pack. 1000 Pcs divided into two 500 Pcs bags




Article	Ø mm		
GPDZ 22	22		



The linear spacer **RAPY 100** is strong and resistant, capable of bearing heavy loads thanks to its shape and size. The lateral and horizontal holes allow perfect penetration of the concrete. Upside down it can be used on insulating panels for floors. Spacers may be joined together longitudinally with a simple slot-in system. Ideal for precasting and civil industry, it ensures stability and invisible finish. On demand available in 50 cm cut.

RAPY 100 FOR HEAVY MESH

GREY HD POLYPROPYLENE



GREY HD POLYPROPYLENE
length 1 lm - pack. 80 lm

Article	H mm		
PLF 20	20		
PLF 25	25		
PLF 30	30		

Maximum weight:
3000 kg a piece (bar length: 1lm) equally distributed.

GREY HD POLYPROPYLENE
length 1 lm - pack. 60 lm

Article	H mm		
PLF 35	35		
PLF 40	40		
PLF 45	45		
PLF 50	50		
PLF 55	55		
PLF 60	60		

Strong and very resistant linear spacer, to be joined lengthwise and have several lengths. The new shape allows to combine high technical performances to a costs optimization.

RAPY 100 ECO

GREY HD POLYPROPYLENE

RAPY 100 ECO
length 1 lm - pack. 64 lm

Article	H mm		
PLFE 20	20		
PLFE 25	25		
PLFE 30	30		
PLFE 35	35		
PLFE 40	40		

ARTICLES NOT FOR SALE SINGLY

RAPY 100 ECO
length 1 lm - pack. 64 lm

Article	H mm		
PLFE 45	45		
PLFE 50	50		
PLFE 55	55		
PLFE 60	60		

ARTICLES NOT FOR SALE SINGLY



The **RAPY 200** spacer is sturdy, resistant and easy to place. Ideal for reinforced horizontal, vertical and sloped structures. The side and horizontal holes allow it to perfectly penetrate into the concrete. When flipped over, it can be used for insulation panels, floors and precast structures. On demand available at 1 metre.


RAPY 200

GREY HD POLYPROPYLENE

GREY HD POLYPROPYLENE
length 2 lm - pack. 96 lm

Article	H mm		
PLF 20R	20		
PLF 25R	25		
PLF 30R	30		
PLF 40R	40		

Maximum weight: 3000 kg a piece (bar length: 2 lm) equally distributed.
The spacer is made up of two 1 lm pieces joined together.



Spacer for horizontal use for heavy reinforcement and meshes; it withstands heavy incidental weights and loads with great stability.


MULTIPIEDE

GREY HD POLYETHYLENE

GREY HD POLYPROPYLENE
bar length 50 cm - Pack. 100 Pcs (DMP 30 - Pack 75 Pcs)

Article	H mm		
DMP 20	20		
DMP 25	25		
DMP 30	30		

Maximum weight:
2.500 kg a piece (bar length: 50 cm) equally distributed.





* = Production on demand with minimum quantity of 10000 pcs. Production delay 4/5 weeks. Price to be agreed.

TYPE "PAV" WHEEL

GREY HD POLYPROPYLENE


spacers for electrically welded mesh



GREY HD POLYPROPYLENE

pack. 2000 Pcs

Article	Formwork spacer mm	Ø rod mm		
PPV 10	10	4/8		
PPV 15	15	4/8		



FORMWORK
DISTANCE



GREY HD POLYPROPYLENE

pack. 1000 Pcs

Article	Formwork spacer mm	Ø rod mm		
PPV 20	20	4/8		
PPV 25	25	4/12		
PPV 30	30	4/12		

GREY HD POLYPROPYLENE

pack. 500 Pcs

Article	Formwork spacer mm	Ø rod mm		
PPV 40	40	8/16		
PPV 50	50	8/16		

NEW PATENTED UNIVERSAL MODEL FOR RODS Ø 4/12 MM.

THE ADVANTAGES OF THE NEW PAV RANGE ARE AS FOLLOWS:

1st The only universal spacer for 4 to 12 mm rods.


2nd Easy to insert.

3rd Innovative and technical design.

TYPE "PAU" TOWER

GREY HD POLYPROPYLENE

spacers for electrically welded mesh



GREY HD POLYPROPYLENE

pack. 4000 Pcs (PPU 10) - pack. 3000 Pcs (PPU 15)

Article	Formwork spacer mm	Ø rod mm		
PPU 10	10	4/12		
PPU 15	15	4/12		

GREY HD POLYPROPYLENE

pack. 1000 Pcs

Article	Formwork spacer mm	Ø rod mm		
PPU 30	30	4/12		
PPU 40	40	4/12		

NEW PATENTED UNIVERSAL MODEL FOR RODS Ø 4/12 MM.

THE ADVANTAGES OF THE NEW PAV RANGE ARE AS FOLLOWS:

1st The only universal spacer for 4 to 12 mm rods.

2nd Easy to insert.

3rd innovative and technical design.



GREY HD POLYPROPYLENE

pack. 2000 Pcs

Article	Formwork spacer mm	Ø rod mm		
PPU 20	20	4/12		
PPU 25	25	4/12		


SPACER for vertical and horizontal meshes. complete with hooks fixing to mesh. dimensions 192 x 90 mm.

SPACER FOR VERTICAL/HORIZONTAL MESH

GREY HD POLYETHYLENE

GREY HD POLYETHYLENE
length 192 mm - width 90 mm

Article		H mm		
DVO 10	400	10		
DVO 15	400	15		
DVO 20	300	20		
DVO 25	120	25		
DVO 30	250	30		
DVO 35	200	35		




spacers

SPACER FOR GLASS BRICK

HD STYROFOAM

WHITE HD STYROFOAM
pack. 600 Pcs

Article	Thick mm		
DSVT	10		*




spacers

With the **DOPPY** type spacer with double slot, two \varnothing 4 to 8 mm mesh reinforcements may be kept simultaneously at the same distance from the formwork.

TYPE "DOPPY" WITH DOUBLE SLOT

GREY HD POLYPROPYLENE




GREY HD POLYPROPYLENE - for mesh up to \varnothing 8 mm
pack. 500 Pcs

Article	mesh dist. L mm		
PPY 15	100		*

GREY HD POLYPROPYLENE - for mesh up to \varnothing 8 mm
pack. 250 Pcs

Article	mesh dist. L mm		
PPY 20	150		*
PPY 25	200		*
PPY 30	250		*



spacers


* = Production on demand with minimum quantity of 10000 pcs. Production delay 4/5 weeks. Price to be agreed.

PROTECTIVE CAPS FOR RODS FOR ADJACENT POURS

HD POLYPROPYLENE

The **PROTECTIVE CAPS** have been created to comply with the safety regulations as per Italian law 81/2008. They protect the end of the protruding rods, thereby preventing injury to operators. Two types for different diameters are available.

laying products



HD POLYPROPYLENE - colour red


pack. 200 Pcs (divided into two 100 Pcs bags)

Article	Ø mm		
PCPF 620	6/20		
PCPF 1630	16/30		

FLAT SPACER FOR MOUNTING PREFABRICATED PANELS

HD POLYPROPYLENE

laying products



HD POLYPROPYLENE

size 170 X 95 mm - pack. 400 Pcs

Article	Thick mm.		
PPN 02	2		

HD POLYPROPYLENE

size 170 X 95 mm - pack. 100 Pcs

Article	Thick mm.		
PPN 10	10		

HD POLYPROPYLENE

size 170 X 95 mm - pack. 200 Pcs

Article	Thick mm.		
PPN 05	5		

The **PAX** spacer is a sturdy spacer used for horizontal mesh; its shape allows the use of Ø 10 / 16 mm mesh.

TYPE "PAX" STURDY

GREY HD POLYETHYLENE

GREY HD POLYETHYLENE - Ø rod 10/16 mm

pack. 2000 Pcs

Article	Formwork spacer mm		
PPX 15	15		

**

GREY HD POLYETHYLENE - Ø rod 10/16 mm

pack. 1000 Pcs

Article	Formwork spacer mm		
PPX 20	20		
PPX 25	25		
PPX 30	30		
PPX 40	40		



spacers for

The **PAL** spacer is a lightweight spacer used to join the iron mesh framework of floor slabs, maintaining the distance from the formwork.

TYPE "PAL" FOR FLOOR SLABS

GREY HD POLYPROPYLENE

GREY HD POLYPROPYLENE - Ø rod 6+5 mm

pack. 2000 Pcs

Article	Formwork spacer mm		
PPO 15	15		
PPO 20	20		

GREY HD POLYPROPYLENE - Ø rod 6+5 mm

pack. 1000 Pcs

Article	Formwork spacer mm		
PPO 25	25		

*



welded mesh

The **PAS** spacer is a sturdy spacer used for heavy reinforcement and large diameter rods.

TYPE "PAS" CHAIR

GREY HD POLYETHYLENE

GREY HD POLYETHYLENE - Ø rod 0/28 mm

pack. 2000 Pcs - divided into two 1000 Pcs bags

Article	Formwork spacer mm		
PPS 15	15		
PPS 20	20		
PPS 25	25		


**

GREY HD POLYETHYLENE - Ø rod 0/28 mm

pack. 1000 Pcs - divided into two 500 Pcs bags

Article	Formwork spacer mm		
PPS 30	30		
PPS 40	40		
PPS 50	50		

**




* = Production on demand with minimum quantity of 10000 pcs. Production delay 4/5 weeks. Price to be agreed.

** = Production on demand with minimum quantity of 50000 pcs. Production delay 4/5 weeks. Price to be agreed.

GASKETS FOR PRECAST FORMS



PVC / RUBBER

gaskets for industrial precast forms




PVC / RUBBER
length rolls 50 lm

Article	
M 232	*






PVC / RUBBER
length rolls 50 lm

Article	
M 233	*




PVC / RUBBER - weight 650 g / lm
length rolls 50 lm

Article	
M 234	*
M 234 A	*
M 234 B	*





PVC / RUBBER - weight 980 g / lm
length rolls 50 lm

Article	
M 235	*




PVC / RUBBER - weight 270 g / lm
length rolls 50 lm

Article	
M 236	*
M 236 A	*
M 236 B	*



PVC / RUBBER - weight 510 g / lm
length rolls 50 lm


Article	
M 237	*



GASKETS FOR PRECAST FORMS


PVC / RUBBER

gaskets for industrial precast forms





PVC / RUBBER - weight 695 g / lm
length rolls 50 lm

Article	
M 238	*





PVC / RUBBER - weight 880 g / lm
length rolls 50 lm

Article	
M 239	*




PVC / RUBBER
length rolls 50 lm

Article	
M 240	*
M 240 A	*
M 240 B	*




PVC / RUBBER
length rolls 50 lm

Article	
M 241	*




PVC / RUBBER - weight 695 g / lm
length rolls 50 lm

Article	
M 242	*



PVC / RUBBER - weight 630 g / lm
length rolls 50 lm

Article	
M 243	*




* = Production on demand with minimum quantity of 50 lm. Production delay 4/5 weeks. Price to be agreed.

GASKETS FOR PRECAST FORMS


PVC / RUBBER

gaskets for industrial precast forms




PVC / RUBBER - weight 180-330 g / lm
length rolls 50 lm

Article	
M 244	*
M 244 A	*





PVC / RUBBER
length rolls 50 lm

Article	
M 245	*




PVC / RUBBER - weight 330 g / lm
length rolls 50 lm

Article	
M 246	*





PVC / RUBBER - weight 335 g / lm
length rolls 50 lm

Article	
M 247	*



PVC / RUBBER - weight 270 g / lm
length rolls 50 lm

Article	
M 248	*
M 248 A	*



PVC / RUBBER - weight 220 g / lm
length rolls 50 lm

Article	
M 249	*



* = Production on demand with minimum quantity of 50 lm. Production delay 4/5 weeks. Price to be agreed.

GASKETS FOR PRECAST FORMS

PVC / RUBBER


gaskets for industrial precast forms



PVC / RUBBER
length rolls 50 lm

Article	
M 250	*


M 250



PVC / RUBBER
length rolls 50 lm

Article	
M 251	*


M 251



PVC / RUBBER
length rolls 50 lm

Article	
M 252	*


M 252



PVC / RUBBER
length rolls 50 lm

Article	
M 253	*



M 253



PVC / RUBBER
length rolls 50 lm

Article	
M 254	*


M 254



PVC / RUBBER
length rolls 50 lm

Article	
M 255	*

M 255




* = Production on demand with minimum quantity of 50 lm. Production delay 4/5 weeks. Price to be agreed.

GASKETS FOR PRECAST FORMS

PVC / RUBBER


gaskets for industrial precast forms

M 256




PVC / RUBBER
length rolls 50 lm

Article	
M 256	*




M 257




PVC / RUBBER
length rolls 50 lm

Article	
M 257	*




M 258




PVC / RUBBER
length rolls 50 lm

Article	
M 258	*




M 259




PVC / RUBBER - weight 750 g / lm
length rolls 50 lm

Article	
M 259	*



M 260



PVC / RUBBER - weight 350 g / lm
length rolls 50 lm



Article	
M 260	*



* = Production on demand with minimum quantity of 50 lm. Production delay 4/5 weeks. Price to be agreed.

GAP-COVERING BALLOON SHEATH

COEXTRUDED FLEXIBLE VINYL RESIN



For industrial floors - FLEXIBLE VINYL RESIN

pack. roll 250 lm

Article	sheath L mm	disk thick mm			
C 550 A..	3,5	2,4			*
C 550 B..	3,8	2,8			*
C 550 C..	5,2	3,2			*
C 550 E..	5,8	3,6/3,8			*
C 550 G..	6	4,2			*

MINIMUM QUANTITY 20 ROLLS = 5000 lm per colour and dimension.
Available for every type of diamond and abrasive disk.

For larger gaps - FLEXIBLE VINYL RESIN

pack. roll 200 lm

Article	sheath L mm	disk thick mm			
C 550 7..	7	5/6			*
C 550 8..	8	6/7			*

For larger gaps - FLEXIBLE VINYL RESIN

pack. roll 150 lm

Article	sheath L mm	disk thick mm			
C 550 9..	9	7/8			*
C 550 10..	10	8/9			*

For larger gaps - FLEXIBLE VINYL RESIN

pack. roll 100 lm

Article	sheath L mm	disk thick mm			
C 550 11..	11	9/10			*
C 550 12..	12	10/11			*


Available in the colours: G - Y - R - N - B. The code of the selected colour must be added to the article code. E.g.: C 550 A.. (chosen colour Grey) C 550 AG.

COLOURS



RESOLVES THE FOLLOWING PROBLEMS:

- Perfectly covers the gap made with any type of disk and remains for a long time at floor level without sinking.
- Thanks to the central semi-rigid shank, the sheath cannot contract in the joint areas.
- When the disk is worn, the sheath need not be changed because it adapts to even the narrowest gaps.
- Also available for larger gaps from 6 mm to 12 mm.
- Very easy to lay.



* = Production on demand with minimum quantity of 5000 lm. Production delay 4/5 weeks. Price to be agreed.


PAVIJOINT

GREY RIGID PVC


PAVIJOINT is a rigid PVC profile with the upper part in elastic PVC/rubber, which absorbs the stress of the floor movements. Two T-irons are inserted inside the profile to strengthen it and to unite two short rods; through holes are also made for the rods 80 cm apart.

The **PAVIJOINT** totally replaces the conventional aluminium beams used for shuttering the concrete cast, thereby avoiding demoulding of the cast and cutting of the joint with diamond-slitting disks in a delicate point such as construction joints.


construction joints for industrial floors



FLOOR TYPE OF LAYING:
example of laying for heights between 15 and 20 mm



FLOOR SLAB TYPE OF LAYING:
example of laying for height of 10 mm



COMPLETE PAVIJOINT - RIGID VINYL RESIN

bar length **3,10 lm**

Article	H mm		
PVJ 10	100		*

PHYSICAL-MECHANICAL CHARACTERISTICS OF RIGID PVC

PROPERTIES	U.M.	RESULTS	METHOD
Specific weight	gr/cm ³	1.45 +/- 0.020	ASTM=D 792
Tensile yield strength	N/mm ²	49	ASTM=D 638
Ultimate tensile stress	N/mm ²	44	ASTM=D 638
Ultimate tensile stress	%	4%	ASTM=D 638
Flexural yield strength	N/mm ²	94	ASTM=D 790
Flexing resistance	N/mm ²	3240	ASTM=D 790
Impact strength	J/m a 23°C	44	ASTM=D 256
Softening temperature	Vicat°C	83 50N	ASTM=D 1525

MECHANICAL CHARACTERISTICS OF SOFT PVC/RUBBER

PROPERTIES	U.M.	RESULTS	METHOD
Specific weight	gr/cm ³	1.25 +/- 0.02	ISO 1183
Hardness	Sh A 15"	67 +/- 2	ISO 868
Ultimate tensile strength	N/mm ²	> 16	ISO 527
Ultimate elongation	%	> 350	ISO 27

* = Production on demand with minimum quantity of 100 lm. Production delay 4/5 weeks. Price to be agreed.

LAYING ACCESSORIES

GREY RIGID PVC



RIBBED DISTANCE TUBE (to neutralise the short rods)
RIGID PVC - bar length 2 lm - pack. 20 Pcs - 50 lm

Article	Ø mm outside		
PPD 20	20		
PPD 22	22		

PLUGS FOR FINNED TUBE - GREY HD POLYETHYLENE
pack. 2000 Pcs divided in two 1000 Pcs bags

Article	Ø mm		
PPT 20	20		
PPT 22	22		

CORNER JOINTS FOR SECURING PAVIJOINT - pack. 20 Pcs

Article			
SQBD			*

* = Production on demand with minimum quantity of 10000 pcs. Production delay 4/5 weeks. Price to be agreed.

The **SHEATH LAYING TROLLEY** was designed to lay different sizes of bubble sheathing easily and correctly. It is supplied with the accessories indicated in the photo (except for the pliers).

SHEATH LAYING TROLLEY

FOR INDUSTRIAL FLOORS

SHEATH LAYING TROLLEY FOR INDUSTRIAL FLOORS
with accessories (extra weight - slurry dragger)

pallet

Article	
CPGC	




START OF LAYING



EASY TO USE



GROUT DRAGGER FOR MORE CONTROLLED LAYING



ROLL-LIFTING FEET




EXTRA WEIGHT



LIGHTWEIGHT FOR MOBILITY

laying products



An interpretation of:
City of Art and Science, Santiago Calatrava, Valencia (Spain), 2009

MARKETING AND SALES STAND SYSTEMS



SQUARE SHOW CASE WITH DRAWERS FOR PROFILES FOR SHOW ROOM

SQUARE SHOW CASE WITH 10 DRAWERS
length 39,5 cm - width 39,5 cm - height 109 cm
(*Brochure and flyers not included)

Article
ESPQCI



1 - Profiles for walls



2 - Profiles for walls



3 - Profiles for floors



4 - Profiles for floors



5 - Profiles for floors



6 - Profiles for floors + joints



7 - Stair nosing profiles



8 - Stair nosing profiles



9 - Terraces



10 - Skirting



11 - Skirting



12 - Profiles for parquet

SET OF SAMPLES AVAILABLE FOR 10 DRAWERS

Set	Samples Description
1	PROFILES FOR WALLS - Projolly Triangle - Prointer - Proterminal Int - Prolistel Channel - Prolistel ACC, P ALL, Led - Profinlist 20 - Proedge AC, OT - Proround - Probord
2	PROFILES FOR WALLS - Proseal 50, 25 - Proshell - Proshell All - Prointer KL - Prokerlam SQ - Prokerlam Line - Prokerlam Jolly - Protop - Protop T - Proshell R, D
3	PROFILES FOR FLOORS - Proterminal Curve - Projolly Curve - Proslider Curve - Prolevigal - Proelegant - Profinal - Prosquare - Proangle - Projoint - Procanal - Proflat
4	PROFILES FOR FLOORS - Proslider - Procarpet - Proslider LR - Proskid - Proskid ALL - Provall 29, 33, 305 - Pronivo - Protrans
5	PROFILES FOR FLOORS - Profloor - Proress - Proslider - Prolinoleoum - Procover - Promoquette Gin - Promoquette Clip - Promoquette - Promoquette Fix
6	PROFILES FOR FLOORS + JOINTS - Proplate - Provall 38 - Proflex - Proflex ALN - Prodilat - Mortar-laid Joints
7	STAIR NOSING PROFILES - Prostair - Prostyle - Prostyle Grip - Prostair - Prostair 50 - Probrastep - Probrastep - Protermstep ACC, ALL - Prostyle
8	STAIR NOSING PROFILES - Prostair Led - Prostep Ins - Prostyle KL - Prostair KL 20 - Prowalk - Proend Ins, Grip - Proend 50 - Proend - Tube 12 - Tube plugs 12 - Eyelet - Hinge support
9	TERRACES - Prot Terrace Drain - Prot Terrace PCG, ALT, pc, PCJ, ECO
10	SKIRTING - Proskirting INS, ISP - Punched support - Proskirting - Proskirting Shell, Led - Cable glands support - Polycarbonate flat - Proskirting Giled - Top Giled
11	SKIRTING - Skirting 40, 60, 100, 7016, 7011 - Support clip - Skirting 60 Flex - Covecap - Skirting
12	PROFILES FOR PARQUET - Proscrow Base - Proscrow 44, 33, 50 - Proinsert Base 45, 40 - Pin Insert - Top Sol 40 P, 30 P - Terminal Pin - Zero Curve - Style Stair - Style Stair L - Terminal - Base LVT 30, 23 - LVT Top, Terminal, Zero Curve

NOTES:

Labels will be delivered with the profiles samples, but in a separated pack.

(*) Write the brochures and flyers codes of the systems to be displayed

EXPOSURE DISPLAY / WALL UNIT FOR SHOWROOM



EXPOSURE DISPLAY / WALL UNIT FOR SHOWROOM

W 208 cm x H 240 cm

Description	Article
<i>Exposure display / wall unit</i>	ESHPAN 250
The exposure display / wall unit is complete with	
19 Sample board PESP	PESP 1 ÷ 19
1 Display PROLEVELING SYSTEM	PNPLSI
1 Bruchure display PROLEVELING SYSTEM	PBPLS
50 Flyer PROLEVELING SYSTEM	FLYPLSI 18
3 Finishes case:	
- PROJOLLY finishes case	COFPJ
- PROJOLLY SQUARE finishes case	COFPJQ
- PROTERMINAL finishes case	COFPT
2 Photo book	BOAM
1 Exposure display PROSHOWER with Design grid	PSHWDL 70 + PSHWD 70
1 Bruchures exposure	ESPB
3 Sample board PROLISTEL	PESPPLT - PESPPLT15 - PESPPLTP
3 Sample board SKIRTING	PESPBT - PESPPK - PESPPKCH
Description	Article
Please order separately 10 brochures	MCAT21/22I

ROTATING DISPLAY EXPOSURE STAND FOR SHOW ROOM

ROTATING DISPLAY EXPOSURE STAND FOR SHOW ROOM
(with 18 sample boards) - diameter 81 cm - height 224 cm

Article

ESPGSM18

The rotating display allows to exposed 18 removable boards with images of different settings. (On the order write the number of the 18 chosen boards PESP) The sample boards are 19. When the display is ordered, specify the desired 18 sample boards according to sales requirements.



SAMPLE BOARD

SAMPLE BOARD
width 30 cm - height 56 cm

Article

PESP 1/ 2/ 3/ 4/ 5/ 6/ 7/ 8/ 9/ 10/ 11/ 12/ 13/ 14/ 15/ 16/ 17/ 18/ 19

For the composition of the display the display ESPGSM and CURAS, choose the boards you wish with the reference number.



Sample board n° 1
Projoly Square, Profilist, Proistel, Procanal



Sample board n° 2
Projoly Square, Proistel, Profilist



Sample board n° 3
Projoly, Projoly Quart, Proimer, Proterminal



Sample board n° 4
Proband, Proetige, Proshell, Prosgusio, Proound, Proabsh, Proseal, Protop, Proteriam



Sample board n° 5
Proterminal, Profrail, Prolegant, Prolegval, Procanal, Propoint, Proangle, Profilat



Sample board n° 6
Proslider, Procarpet, Proshid, Proslider, Procover, Progress, Proplate



Sample board n° 7
Prosal, Prokwall, Protranc, Pronio, Promoquette, Proflor, Prolinoleum, Pronio



Sample board n° 8
Prostar, Prostyle, Prostep, Protermstep, Probrastep



Sample board n° 9
Prostyle, Prowalk, Proend, Prostair, Tube and Accessories



Sample board n° 10
Proflex, Proclac, Adhesive Joint, Mortar-laid Joint




Sample board n° 11
Proexpan, GNS, GDR, Proplate



Sample board n° 12
Profoli, Prodeso, Prodrain 10, Proband, Proband BU, Proband Kall, Proband Fix, Prodrrip, Proterrace



Sample board n° 13
Proterrace



Sample board n° 14
Skirting 40/ 60/ 80/ 100



Sample board n° 15
Proskirting, Gallet, Shell, Led, Flat, INS, ISP, Channel, Line



Sample board n° 16
SOL 40P, Terminal Pin, Zero Cone, Style Stair, Terminal, SOL 30, Profiler Line, SOL 50, Proscrow



Sample board n° 17
Curve Profiles - Proterminal, Projoly, Profrail, Proslider, Procover, Prolegant, Terminal, Do it yourself profiles - Tube, Corner, Canal, Flat, Curve Profile



Sample board n° 18
Triangular Chamfer, Rapp 100/200, Ribbed Distance, Rounded Triangular Chamfer, Prodistanz, Waterstop, Snap-on Strand, PAU/PAV spacers



Sample board n° 19
Projoly Triangle, Proterminal, Proistel channel, Proskirting 40, Skirting 70/11/16, Proseal flex, Protop T, Style stair L, Proside walk

SMALL EXPOSURE STAND



SMALL EXPOSURE STAND (with 4 sample boards)
width 33 cm - depth 50 cm - height 60 cm

Article

CURAS

It allows to expose 4 easily removable boards at your choice. (On the order write the number of the 4 chosen boards PESP) The sample boards are 19. When the stand is ordered, specify the desired 4 sample boards according to sales requirements.

TROLLEY



TROLLEY (with 18 sample boards)
width 50 cm - depth 35 cm - height 63 cm

Article

TRAG18

(On the order write the number of the 18 chosen boards PESP ...)

ROTATING DISPLAY FOR SKIRTING



ROTATING DISPLAY FOR SKIRTING
diameter 81,5 cm - height 170 cm

Article
ESPGSMBT

ESPGSMBT

Note: The revolving tower has a predefined range of samples from PROGRESS PROFILES, that you see on this page, and it is not possible to request customizations or further changes.



PROLISTEL AND SKIRTING DISPLAY

PROLISTEL AND SKIRTING COUNTER DISPLAY


Article
ESPBLSH




PROLISTEL
width 30 cm - height 38 cm

Article
PESPPLT
PESPPLT15
PESPPLTP


PESPPLT



PESPPLT15




PESPPLTP




SKIRTING
width 30 cm - height 38 cm

Article
PESPBT
PESPPK
PESPPKCH

PESPBT



PESPPK



PESPPKCH



SAMPLE CASES

FINISHES CASES

Article	Description
COFPJ	Projolly / Projolly Quart
COFPJQ	Projolly Square
COFPT	Proterminal
COFSTL	Stone Line
COFBT	Skirtings



COLOUR RANGE KEYRINGS

PROFILES COLOUR RANGE

Article	Description
COLBS	Skirtings
COLPJ	Projolly
COLPJM	Projolly marble
COLPJQ	Projolly square
COLPJQT	Projolly quart



COLBS



COLPJ



COLPJM

SAMPLES AND WOODEN

PROFILES FOR LAMINATE, PARQUET AND CARPETED FLOORS

Article
TUBLAM (PROINSERT SYSTEM profiles samples)
CCOLL (standard wood samples)
CCOLLR (on demand wood samples) *



TUBLAM



CCOLLR



CCOLL


PROSKIRTING GILED DISPLAY

PROSKIRTING GILED PANEL
width 70 cm - height 92 cm

Article
ESPGLED



FRONT



BACK

PROSKIRTING LED DISPLAY

PROSKIRTING LED PANEL
width 70 cm - height 92 cm

Article
ESPLED



SWITCHED OFF



SWITCHED ON



BACK OF PROSKIRTING LED BOARD

PRODESO HEAT SYSTEM PRODESO SYSTEM

EXPOSURE PRODESO® HEAT SYSTEM
width 60 cm - depth 60 cm - height 206 cm

Article

ESPPDHI595



EXPOSURE PRODESO® HEAT SYSTEM

Article

SPCPDES...



EXPOSURE PRODESO®

Article

SPCPDES...



MEMBRANES CASE

Article

COFM...



EXPOSURE PRODESO® HEAT / PRODESO® / PROTERRACE
width 60 cm - depth 60 cm - height 206 cm

Article

ESPPDHT...



PROSHOWER SYSTEM DISPLAY

EXPOSURE DISPLAY PROSHOWER SYSTEM FOR SHOWROOM
(with PROSHOWER BASE L + SET OF AVAILABLE GRIDS)
width 100 cm x 36 cm - height 73 cm

Article

ESPSHW 70 + (COLGPSHW 70)



FRONT



BACK



SET OF AVAILABLE GRIDS

PRODUCT BOARD PROLEVELING SYSTEM DISPLAY SPACERS

PROLEVELING SYSTEM DISPLAY

Article

ESPLS 50/70

PROLEVELING SYSTEM DISPLAY

7 COMPARTMENTS



5 COMPARTMENTS



PROLEVELING SYSTEM BOARD - 2 PCS

Article

PNPLS...



PROLEVELING WEDGE SYSTEM BOARD

Article


PNPLWS



PROLEVELING SYSTEM BOARD

Article

PNPLSA3 (29,7 x 42 cm)



SPACERS DISPLAY

SPACERS DISPLAY (ACCESSORIES EXCLUDED)



EXPOSURE DISPLAY DISTANZIATORI PROGRESS PROFILES

Article

ESPD

EXHIBITION BOARD

EXHIBITION BOARD - 80 x 57 cm

Article

PNPSR (80 x 57 cm)



EXPOSURE DISPLAY PROSUPPORT TUBE

EXPOSURE DISPLAY PROSUPPORT TUBE WITH 50 FLYER

Article

ESPPST

FLYPSUP...



EXPOSURE DISPLAY PROTERRACE

EXPOSURE DISPLAY PROTERRACE WITH 50 FLYER

Article

ESPFDP

FLYPTER...



GENERAL CATALOGUE / PRICE LIST

Article

CAT23...



BROCHURE SYSTEMS

Article

BRSYS 22/23



BROCHURE A4 PRODESO DRAIN SYSTEM

Article

BRPDDR...



BROCHURE A4 PRODESO HEAT GRIP SYSTEM

Article

BRDESHG...



MINI CATALOGUE A5 (NO PRICES)

Article

MCAT23...



BROCHURE A4 PRODESO SYSTEM

Article

BRDES...



BROCHURE A4 PROSHOWER SYSTEM

Article

BRPSW...



BROCHURE A4 PROSUPPORT TUBE SYSTEM

Article

BRPSUPT...



COUNTER DISPLAY FOR BROCHURES

Article

ESPB...



COUNTER DISPLAY FOR FLYER

Article

PBPLS

Order the customization sticker separately in line with the exposed flyer



PHOTO BOOK

Article

BOAM




DEPLIANT FLYER 10 X 21 cm - Pack 50 Pcs

Article

Description

FLYPDDR...	Flyer Prodeso Drain system
FLYPDESHG...	Flyer Prodeso Heat Grip system
FLYPDES...	Flyer Prodeso Membrane system
FLYPSHW...	Flyer Proshower system
FLYPFPS...	Flyer Profoil panel system
FLYPTER...	Flyer Proterrace system
FLYPLS...	Flyer Proleveling system
FLYPSUP...	Flyer Prosupport tube system
FLYPLED...	Flyer Proledlight system
FLYPDSD...	Flyer Prodeso sound system
FLYPMITFX...	Flyer Promultifix system

FLYPDDR...




FLYPDESHG...



FLYPDES...



FLYPSHW...



FLYPFPS...



FLYPTER...



FLYPLS...




FLYPSUP...




FLYPLED...



FLYPDSD...



FLYPMITFX...



Available in the following languages: Italian (I), English (E), German (T), French (F), Russian (R), Spanish (ES), American \$ (USA), English £ (UK). The initials of the chosen language must be added to the initials of the article.

Example: CAT22 ... (Desired language Italian) CAT22I;

MODULAR DISPLAY SYSTEM FOR SHOWROOM

The **MODULAR DISPLAY SYSTEM WITH INTECHANGEABLE BOARDS** is composed by a metal base, 225 cm height, 93 width and 44 cm deep. It is possible to fix to this framework boards with pictures, samples and fixing patterns of profiles. A shelf with a fixing example of the most common profiles showed on the boards above is in the middle of the framework. Thanks to the pictures of fixing patterns, profiles samples and fixing examples, the modular display allows the customer to have an overall view of the use of the Progress Profiles products and systems. The modularity and the small size of the display allows its positioning in all showroom and sales point. Thanks to the modularity of the boards, the customer can choose the boards according to the products he wants to show. The system is easy to update with new finishes and products.



MODULAR DISPLAY WITH VIDEO

MODULAR DISPLAY WITH STEPS

MODULAR DISPLAY SYSTEM

Article	Description	
RIV 1	Modular display Profiles for walls 1	*
RIV 2	Modular display Profiles for walls 2	*
RIV 3	Modular display Profiles for walls 3	*
PAV1	Modular display Profiles for floors 1	*
PAV2	Modular display Profiles for floors 2	*
CRV	Modular display Curved profiles	*
GR1	Modular display Stair nosing profiles 1	*
GR2	Modular display Stair nosing profiles 2	*
GIU1	Modular display Joints 1	*
PTR	Modular display Proterrace	*
PSH1	Modular display Proshower 1	*
PSH2	Modular display Proshower 2	*
PFPG	Modular display Profoil panel	*
B1	Modular display Baseboards 1	*
B2	Modular display Baseboards 2	*
LED	Modular display Proedlight	*
LGN	Modular display Profiles for parquet	*
PLV	Modular display Proleveling	*
PSPT	Modular display Prosupport tube	*
PSTS	Modular display Prosupport slim/prorail	*



RIV 1:
Projolly quart,
Projolly angle,
Projolly angle 135,
Prostel p,
Proterminal,
Prostel,
Prostel channel,
Profinlist,
Proterminal int;



RIV 2:
Projolly square;



RIV 3:
Projolly,
Printer,
Printer kl,
Proshell,
Proedge,
Prokerlam square,
Prokerlam jolly,
Prokerlam line,
Prostair kl;



PAV 1:
Proslider,
Procarpet,
Proskid,
Profinal,
Procanal,
Projoint,
Proterminal,
Prolevigal,
Proelegant;



PAV 2:
Procover,
Propress,
Profloor,
Prosol,
Proplate,
Prolevall,
Promoquette;




CRV:
Proterminal curve,
Proelegant curve,
Profinal curve,
Projolly curve,
Proslider curve,
Terminal curve,
Procover;



GR1:
Prostair acc,
Prostair kl,
Prostair wood,
Protermstep,
Prostyle,
Prostyle kl,
Probrastep,
Prostep;



GR2:
Prostyle grip,
Prostyle 2610,
Proend ins,
Proend grip,
Prowalk,
Prostair led,
Proside walk;



GIU:
 Proflex acn
 Proflex acc
 Proflex aln,
 Proflex al,
 Proflex ot,
 Proflex acc pr,
 Proflex 25/5 pr,
 Prodilat;



PTR:
 Prot Terrace drain drip,
 Prot Terrace drain fdp,
 Prot Terrace pcg,
 Prot Terrace pc,
 Prot Terrace pcj,
 Prot Terrace eco drip;



PSH 1:
 Proshower linear system,
 Proshower profile glass,
 Proshower profile,
 Proshower profile wall,
 Proshower profile front;




PSH2:
 Proshower central system;



PFPG:
 PROFOIL PANEL SYSTEM,
 PRO GOBORD SYSTEM,
 PROFOIL PANEL NICHE,



B1:
 Proskirting led,
 Proskirting giled,
 Proskirting list,
 Proskirting isp,
 Proskirting,
 Proskirting shell,
 Proskirting channel,
 Proskirting flat,
 Proskirting ins,
 Proskirting line;




B2:
 Skirtings



LED:
 Proledlight system,
 Proskirting led,
 Proskirting giled,
 Prostair led,
 Prolistel led;



LGN:
 Lvt Profiles,
 Skirting 7016
 Skirting 7011,
 Promultifix,
 Zero Curve,
 Sol 40p,
 Terminal Pin,
 Terminal,
 Style Stair;



PLV:
 Proleveling System,
 Proleveling Wedge
 System;



PSPT:
 Prosupport Tube,
 Prosupport Profile;



PSTS:
 Prosupport Slim,
 Prorail System;



SHOWROOM SET-UP EXAMPLES



PROPOSALS OF SHOWROOM EQUIPMENT - PROPOSAL 1 - Back - panels and desks are not included
DISPLAYS FOR PROFILES ARE AVAILABLE UNDER CUSTOMER REQUEST

Description	Article
Rotating display stand + Sample boards (x18)	ESPGSM18 + PESP...
Counter display for flyer + Proleveling system flyer	PBPLS + FLYPLS 20
Proleveling System Board	PNPLS
Proterrace Display	ESPFDDP
Counter display for mini catalogues	ESPB
Membrane case	COFM
Photo book	BOAM



PROPOSALS OF SHOWROOM EQUIPMENT - PROPOSAL 2 - Back - panels and desks are not included
DISPLAYS FOR PROFILES ARE AVAILABLE UNDER CUSTOMER REQUEST

Description	Article
Exposure Display / Wall unit	ESHPAN 250
Proshower system display + available grids set	ESPSHW 70 + COLGPSHW70
Exhibition Board	PNPSR
Photo Book	BOAM
Proleveling system Sample Board	PNPLS



PROPOSALS OF SHOWROOM EQUIPMENT - PROPOSAL 3 - Back - panels and desks are not included
DISPLAYS FOR PROFILES ARE AVAILABLE UNDER CUSTOMER REQUEST

Description	Article
Exposure Display / Wall unit	ESHPAN 250
Square show case with drawers for profiles custom displays and expositors	ESPQC -



PROPOSALS OF SHOWROOM EQUIPMENT - PROPOSAL 4 - Back - panels and desks are not included
DISPLAYS FOR PROFILES ARE AVAILABLE UNDER CUSTOMER REQUEST

Description	Article
Exposure Display / Wall unit	ESHPAN 250
Square show case with drawers for profiles	ESPQC

EXAMPLE OF CUSTOMIZED SHOWROOM SET-UP - 1



EXAMPLE OF CUSTOMIZED SHOWROOM SET-UP - 3



= News 2023

= Article on demand, Production delay and prices to be agreed.

DISPLAYS FOR PROFILES

ESPF EXPOSURE DISPLAY ESPF (accessories excluded)
width 65 cm - depth 20 cm - height 112 cm


Article	
ESPF	



The displays ESPF and ESPF 2 are supplied with some removable interior dividers that allow you to easily separate the interior space to be able to arrange the profiles according to the sales needs.


ESPF 2 EXPOSURE DISPLAY ESPF 2 (accessories excluded)
width 65 cm - depth 40 cm - height 112 cm

Article	
ESPF 2	



ESPF 2015 EXPOSURE DISPLAY ESPF 2015 (accessories excluded)
width 100 cm - depth 28 cm - height 81 cm

Article	
ESPF 2015	



ESPF 2 2015 EXPOSURE DISPLAY ESPF 2 2015 (accessories excluded)
width 100 cm - depth 56 cm - height 81 cm


Article	
ESPF 2 2015	



DISPLAYS FOR PROFILES

PEPCP EXPOSURE DISPLAY "PEPCP" (accessories excluded)
width 100 cm - depth 50 cm - height 230 cm

Article	
PEPCP (profiles)	*
PEPCPBT (skirtings)	*



PEP EXPOSURE DISPLAY PEP (accessories excluded)
width 100 cm - depth 50 cm - height 230 cm

Article	
PEP (profiles)	
PEPBT (skirtings)	*



PEPCPSP EXPOSURE DISPLAY PEPCPSP (accessories excluded)
width 100 cm - depth 50 cm - height 230 cm

Article	
PEPCPSP (profiles)	*
PEPCPSPBT (skirtings)	*



PEPSP EXPOSURE DISPLAY PEPSP (accessories excluded)
width 100 cm - depth 50 cm - height 230 cm

Article	
PEPSP (profiles)	*
PEPSPBT (skirtings)	*



= News 2023

* = Article on demand, Production delay and prices to be agreed.

DISPLAYS FOR PROFILES

ESPSP EXPOSURE DISPLAY ESPSP (accessories excluded)
width 100 cm - depth 75 cm - height 240 cm

Article	
ESPSP	



PEPINSP EXPOSURE DISPLAY PEPINSP (accessories excluded)
width 100 cm - depth 50 cm - height 230 cm

Article	
PEPINSP	



PEM EXPOSURE DISPLAY PEM (ACCESSORIES EXCLUDED)
width 120 cm - depth 61 cm - height 160 cm

Article	
PEM	



PEPINS EXPOSURE DISPLAY PEPINS (accessories excluded)
width 100 cm - depth 50 cm - height 230 cm

Article	
PEPINS (profiles)	
PEPINSBT (skirtings) *	



= News 2023

= Article on demand, Production delay and prices to be agreed.

GADGETS

GADGETS

Article	Description
PEN	Pen
CUTTER	Cutter
FOGLAPP	Post It
PENCIL	Work pencil
TAPMOUSE	Mousepad
CARTPBPP	Portfolio
USB	USB Pendrive
FLESSOMETRO	Tape
CAP	Baseball cap
MARSUPIO BASIC	Pouch
PRGS10	Profile measurement ruler
OMBRELLOP	Umbrella
PLAN	Planning
PENNA DA BANCO	Counter pen
PENNA TECNICA	Technical Pen



T-SHIRT

Article	Description
TSHIRT S	T-shirt white S
TSHIRT M	T-shirt white M
TSHIRT L	T-shirt white L
TSHIRT XL	T-shirt white XL
TSHIRT XXL	T-shirt white XXL



WHITE POLO

Article	Description
POLOB M	polo stretch wwhite M
POLOB L	polo stretch white L
POLOB XL	polo stretch white XL
POLOB XXL	polo stretch white XXL



BLUE NAVY POLO

Article	Description
POLOBN M	polo stretch wwhite M
POLOBN L	polo stretch blu navy L
POLOBN XL	polo stretch blu navy XL
POLOBN XXL	polo stretch blu navy XXL



GILET PROGRESS PROFILES

Article	Description
GILET	Vest



PILE PROGRESS PROFILES

Article	Description
PILE	Fleece sweatshirt



GENERAL TERMS AND CONDITIONS OF SALES PROGRESS PROFILES S.P.A.

These general terms and conditions (hereafter "General Terms and Conditions of Sales") govern the contractual relationships of the products manufactured or marketed (hereafter "Product/s" or "Good/s") by the company PROGRESS PROFILES S.P.A. (hereafter "Vendor") to its customers (hereafter individually "Buyer" or "Customer") (Buyer and Vendor also referred to jointly as "Parties" and individually as "Party"). These General Terms and Conditions of Sales do not apply to sales to consumers.

1) EFFECTIVENESS OF THE GENERAL TERMS AND CONDITIONS

These General Terms and Conditions of Sales apply even if not explicitly referred to and signed in individual orders. Any provisions in derogation of the requirements herein shall be effective only if expressly accepted in writing by the Parties. Any general terms and conditions of the Customer will not apply, even partially, unless they have been expressly accepted in writing by the Vendor. These General Terms Conditions of Sales are effective until they have been expressly revoked by the Vendor or are replaced by new terms and conditions that will become effective from their signing.

2) ORDER

The Goods object of each sale between the Buyer and the Vendor are described in the purchase order ("Order") that the Buyer sends directly or indirectly through its representatives to the Vendor. The Order is considered irrevocable for the Buyer if confirmed by the Vendor through the Order Confirmation, preform invoice.

3) CONTRACT

The Sales contract of the Goods ("Contract") is governed by the Order, by the Order Confirmation and these General Terms and Conditions. The sending of an Order by the Customer implies his/her full acceptance of these General Terms and Conditions of sales and of any of the specific ones related to the Order itself. The Contract is completed with the acceptance of the Order by Order Confirmation, communicated in writing by the Vendor to the Buyer or, failing that, with the execution of the Order by delivering the Goods to the carrier or forwarder. Any changes to the Contract, proposed by the Buyer, will result in changes to the same only if accepted in writing by the Vendor.

4) DELIVERY TERMS, TRANSPORT OF GOODS

The delivery terms of the Goods will be agreed from time to time in the individual Order and relative Order Confirmation. The delivery terms must always be considered indicative, not essential, and are not binding for the Vendor. Any variations requested in the production phase, nonetheless relieve the Vendor from complying with the agreed terms. In this case the terms and conditions of delivery will be renegotiated. If the Buyer expressly requests an express delivery service in the Order, the Vendor will indicate, in the Order Confirmation the cost for this service which shall be considered accepted, if not contested in writing by the Buyer to the Vendor. Any reference to delivery terms (e.g. EX WORKS, CIF, FOB and others) contained in the Order and in the Order Confirmation refers to the Incoterms® of the International Chamber of Commerce, in the text in force on the date of the Order Confirmation. If a sale has been agreed with transport via carrier, regardless of the Party that appoints the carrier, the risks are transferred to the Customer with the delivery of the Goods to the first carrier: any claims for breakages, deterioration, tampering or deficiencies must be reported by Buyer to the carrier in accordance with the law, providing the Vendor with appropriate information. The Vendor is therefore entitled to reasonably anticipate or postpone the delivery of all or part of the Goods, without this entitling the Buyer to request full or partial termination of the Sales Contract or to claim compensation or indemnity and without the Buyer refusing delivery of the Goods. We shall not be liable for any delays in shipments which will not entitle the Customer to claim damages and/or penalties, to delay payments or reject the Goods. It is understood, however, that maximum effort shall be ensured in the execution of the Order on the agreed dates.

5) FORCE MAJEURE

The occurrence of causes not dependent on the will of the Parties, such as strikes of any kind, earthquakes, fires, floods, lack of motive power or energy, lack or scarcity of raw materials, breakdowns and breakages at the Vendor's production facilities, delays in granting authorizations by the Authorities, embargo or other measures of national or supranational Authorities and other impediments independent of the will of the Parties, which make delivery temporarily impossible or excessively expensive, the delivery time will be extended by a period equal to the duration of the impediment, the Party, upon becoming aware of the impediment, will communicate within a reasonable time to the other Party the existence of the impediment and, where this is not already implicit in the type of impediment, the probable effects it shall have on the delivery obligation. Similarly, the Party will inform the other Party of the removal of the impediment. It is understood that neither the Customer nor the Vendor can demand compensation or indemnity of any kind due to the occurrence of the circumstances provided for in article 5.

6) REFUSAL TO RECEIVE DELIVERY

Where the Buyer refuses to receive the delivery of all or part of the Goods only, the Vendor may, at its own unquestionable choice, demand performance of the Contract, or declare its total or partial termination. In either case, the Vendor retains the right to claim compensation for damages. Any responsibility of the Vendor for risks and costs deriving from or inherent to the stock of the Goods is expressly excluded, which shall be entirely charged to the Buyer.

7) DESCRIPTIVE DRAWINGS AND DOCUMENTS

The dimensions, sections, drawings, colours, finishes, prices and the other data included in the catalogues, prospectuses, circulars, advertisements, illustrations and price lists of the Vendor are approximate indications. These data is not binding except to the extent that they are expressly provided for in the Order Confirmation or in the Contract. Any photographs included in the offer and/or the Vendor's Order Confirmation are not binding and are for illustrative purposes only.

8) PRICES, PAYMENTS AND DEFINITION OF DEFAULT INTERESTS

The prices of the products are those indicated in the price list or on each offer made by the Seller with net prices. Such prices shall be determined on the basis of the price list in force when the order shall be taken in charge and processed by the Seller and shall be clearly indicated on the order confirmation. The prices of the products do not include any taxes or duties whatsoever, and are always Ex Works and do not include any installation or transport. Payments must be made by the Customer as specified and within the times indicated on the order confirmation. Orders for an amount less than € 100.00 shall not be fulfilled, or alternatively their value shall be increased by processing and handling costs. Orders for an amount less than Eur 300.00 shall also be increased by ancillary costs as shown on the "transport cost charges" chart in the Progress Profiles catalogue in the related section. For late payments, default interests shall be charged at the rate established by Italian Legislative Decree no. 231/2002 and subsequent amendments and / or additions, and shall apply from the first day after the expiry of the payment deadline. It is understood however that for any complaints or disputes the Customer is not entitled to suspend or, in all cases, delay payments for the Products subject of the claim, or any other supplies. More generally, no action or exception may be taken or opposed by the Customer unless after the full payment of the Products for which this dispute or exception is referred to. Furthermore, the Customer is not authorized to make any deductions from the agreed price (eg in the case of alleged defects in the Products), unless previously agreed in writing with the Seller.

9) SUSPENSION OF PERFORMANCE AND TERMINATION

The non-payment, even partial, of supplies or any amount due by the Buyer, or the total or partial non-fulfillment of contractual obligations or agreed conditions for the supply, automatically authorizes the Vendor to suspend further shipments or cancel any Orders in progress, or to subordinate the delivery of the Products to the provision of adequate guarantees of payment, and exonerate the Vendor from any ongoing commitment with the same Customer at any time and without prior notice. The Vendor has a similar right whenever changes occur to the Buyer, in its structure or corporate structure, in the composition of its governing or management bodies, in its financial situation, equity or commercial image, as well as in the case of lodging or submission of proof of debt in bankruptcy, pending enforcement or precautionary procedures, suspensions, difficulties or delays in the performance of obligations assumed, including to third parties, of facts referring to the Buyer that may be detrimental to the successful completion of the Contract and/or detrimental to commercial interests of the Vendor.

10) CHANGES - CONFORMITY

The Vendor reserves the right to make non-decisive changes to models, measures, materials always within the tolerances of use and without obligation of communication to the Buyer by sending the Order, the Customer declares to have verified that the Goods described in the Order comply with any legal, regulatory or administrative provisions in force in their country or in another country of destination of the Goods, applicable to the import, sale and use of the Goods. In no case will the Vendor be held responsible for any non-compliance with these legal provisions, regulations or administrative provisions. It is the Buyer's obligation to indicate to the Vendor in the Order any provision of law or regulation and/or any standard applicable to the Goods ordered if different from those applicable in Italy and/or indicated in the Vendor's Offer. In this case, the prices of the Goods will not be those indicated in article 8, but will be agreed between the Parties for each supply. It is understood that, in the absence of such indications, the Vendor will not be in any way responsible for the non-compliance or non-conformity of the Goods supplied to laws, regulations, standards or administrative provisions and the Buyer shall be obliged to keep the Vendor indemnified from any damage or claim that the Vendor, or its staff or administrators, may suffer, even against claims made by third parties, due to such shortcomings.

11) WARRANTY AND LIMITS

In the terms provided for in article 11, the Vendor undertakes to deliver the Products as agreed and exempt from manufacturing defects. The warranty does not cover aesthetic defects, meaning finishes difference or shades in the outward appearance of the products. The Vendor is also not responsible for defects in conformity and defects in the Products due to normal wear. The Vendor likewise is not liable for defects in conformity of the Products and defects caused by non-compliance, even partial, of the rules provided in the instruction manual/product data sheet, maintenance and/or cleaning with unsuitable products and/or materials and from incorrect choice by the Customer of the Product ordered for the purpose and intended use. This warranty does not extend to defects due to tampering or improper use of the Products, negligent preservation thereof, causes of force majeure. The Vendor assumes no responsibility for damages resulting from the installation of the Products supplied. The Vendor declines all responsibility for any damage that may, directly or indirectly, derive from persons or things as a result of failure to comply with all the requirements indicated in the documentation accompanying the Products, and in particular that concern the warnings regarding installation, use and maintenance.

12) REPORTING OF FAULTS AND DEFECTS

The Products purchased must be verified and checked by the Buyer upon receipt. Any apparent defects of the Goods supplied (packaging status, quantity, species, or external characteristics of the Products, etc.) must, under penalty of forfeiture, be contested at the time of delivery directly to the carrier on the transport document and notified not later than 7 (seven) days to the Vendor by registered letter with return receipt or other means of communication that assures the proof and date of receipt (e.g. Certified Electronic Email). After this deadline, the Products will be considered for all purposes accepted; furthermore, the use and/or installation and/or laying of the Products presenting apparent defects, excludes the possibility of disputes or complaints concerning the defects themselves. Any hidden defects (defects not identifiable through diligent control at the time of receipt of the Products) must be notified by the Buyer, under penalty of forfeiture, to the Vendor by registered letter with return receipt or other means of communication that assures the proof and date of receipt (e.g. Certified Electronic Email), within 8 (eight) days of discovery and in any case no later than 12 (twelve) months from delivery to the Buyer. It is understood that the successful use and/or installation and/or laying of the Products that have manifested defects, excludes the possibility of disputes or complaints concerning the defects themselves, implying acceptance of the Products for all purposes. Each complaint must accurately specify the defect found; the Products object of the dispute must always be made available to the Vendor's agents for their verification. Any complaints or disputes will not entitle the Buyer to suspend or delay payments due to the Vendor in any way.

Following a regular complaint by the Customer, within the terms indicated above, the Vendor will only perform the free replacement of the Product recognized as defective by the Vendor, Product that will be accepted in return from the same Vendor only in original packaging, undamaged and complete. Any disputes concerning a single delivery do not exonerate the Customer from the obligation to withdraw the remaining quantity of Products provided for by the specific Order, or by other Orders distinct from the one in question, nor do they entail the termination of the Contract.

13) LIMITATION OF LIABILITY

Any compensation for defective goods to be paid to the Buyer cannot in any case exceed the consideration paid and relative to the quantity of defective Goods. This warranty lasts 12 (twelve) months from the delivery of the Goods, it shall replace and supersede all legal guarantees and/or responsibilities provided by law and excludes any other responsibility of the Vendor, however, originating from the Goods supplied or their resale; in particular, the Buyer cannot make further claims for indemnity or compensation for damages, direct or indirect, of any nature, price reduction or termination of the Contract. Following the term of the warranty, no claim can be made against the Vendor.

14) RETENTION OF TITLE

This sale is carried out with retention of title (art. 1523 Italian Civil Code et seq.): therefore the Products remain the property of the Vendor until full payment of the price by the Buyer. Failure to pay, even partially, entitles the Vendor to reserve the right to undertake any other action, to directly recover the Goods under consideration in the supply, even if held by third parties. The Buyer acquires the property right of the Goods only following full payment of the related price to the Vendor in addition to ancillary charges, but assumes the risks from the time of delivery and will be liable for any damage or loss of the Goods (for example due to poor maintenance or negligence).

15) INDUSTRIAL AND INTELLECTUAL PROPERTY

Any distinguishing mark and/or production and commercial technology of the Vendor, whether registered and/or patented or not, must be treated as confidential by the Customer and must not be used or disclosed without the prior written authorization of the Vendor. All printed matter and other documents (price lists, catalogues or other similar documents, even on IT and digital support) relating to the Products are the exclusive property of the Vendor, covered by copyright. Their reproduction, even if only partial, is prohibited unless previously authorized by the Vendor. The Vendor warns against the unauthorized use of its own brand, and/or other trademarks shown on the Products or connected to the Products supplied, and/or distinguishing names or marks, as well as patents, models and drawings relating to their Products.

16) APPLICABLE LAW AND EXCLUSIVE JURISDICTION


Except when agreed in these General Terms and Conditions of Sales, the Italian law shall apply to these General Terms and Conditions of Sales and to each Sales Contract completed between Vendor and Buyer. The application of the United Nations Convention on contracts for the international sales of movable property, adopted in Vienna on 11.4.1980, is expressly excluded. For any dispute connected or arising from these General Terms and Conditions of Sales and/or Orders and/or Contracts, the Court of Treviso (Italy) shall have exclusive jurisdiction.

17) PRIVACY


In the execution of these General Terms and Conditions and/or of each Contract, personal and contact data (personal data, company e-mails, company telephones, smartphones) may be communicated to each other between Vendor and Buyer, or in any case made available to the respective contacts. For business use, etc.) of administrators, employees and collaborators who, depending on the duties and tasks assigned, manage the Contract and/or execute it. Therefore, both parties will process such personal data to the extent that they are strictly necessary for the execution of all aspects of the Contract (if any); and with their transfer, in consideration of the execution of the Contract, also in extra EU countries. Data shall be retained until the completion of the reciprocal services covered by the Contract and subsequently on the basis of the prescribed terms for the deeds and documents of the entrepreneur. The individual employee or collaborator can exercise all the rights listed in articles 15 to 21 of Regulation EU 2016/679, without prejudice, however, to the limits deriving from the legitimate interest of the employer.

Place and date **Asolo, 01/04/2019**

Signature of Progress Profiles SPA




Signature of the Buyer




Pursuant to and for the purposes of articles 1341 and 1342 of the Italian Civil Code, the Buyer declares to have read all the terms and conditions of this Contract and to expressly approve the following clauses: 4 (DELIVERY TERMS, TRANSPORT OF GOODS), 5 (FORCE MAJEURE), 6. (REFUSAL TO RECEIVE DELIVERY), 8 (PRICES, PAYMENTS AND DEFINITION OF DEFAULT INTERESTS) 9 (SUSPENSION OF PERFORMANCE AND TERMINATION), 10 (CHANGES AND CONFORMITY) 11 (WARRANTY AND LIMITS), 12 (REPORTING OF FAULTS AND DEFECTS) 13 (LIMITATION OF LIABILITY), 16 (APPLICABLE LAW AND EXCLUSIVE JURISDICTION).

Place and date **Asolo, 01/04/2019**

Signature of Progress Profiles SPA



Signature of the Buyer



IN THE CASE OF COMPLAINT, SEND A FAX TO No. +39 0423 950 979
or E-MAIL: cservice2@progressprofiles.com

FORM FOR NON-CONFORMING MATERIAL - PART A

Please fully complete this form

Business name:

Customer Name _____

Street _____

District _____ Zip Code _____

Province _____

e@mail _____

VAT No. _____

Tel. _____ Fax _____

Reason for complaint:

- damaged material
 missing material
 correct documents (confirm/transport documents) but non-conforming material

Material non-conforming in: quality
 quantity

Dispatch references:

Preform Invoice _____ ORD. N° _____

Date _____

Name of carrier _____

Description of material

Cod. / Article	Description	U.M.	Quantity

Required action:

Return of goods

Sending of material

Date and place _____

Signature of agent in confirmation

Signature of customer in acceptance

WATCH OUT FOR DAMAGE

OPERATIONS TO BE CARRIED OUT IN PRESENCE OF THE CARRIER

1

PROGRESS PROFILES SPA (DATI IN CALCE)			
NEL D.D.T. E COMUNICATI ENTRO 48 ORE.			
QTA	PESO LORDO/BRUTO IN KG	PESO NETTO/NET IN KG	NUMERO COLLI
04	9,00	9,00	3,00
FIRMA DEL COMPILATORE			
FIRMA DEL VET.			

1. Verify whether the number of packages corresponds to the number indicated in the transport documents

2

819A 60	RACCORDO INTERNO BATTERICOA 8160mm ANODIZ. 20	22	23
819A 10	PROFILES-ALL-8110mm ANODIZZATO ARGENTO-L	24	24
819A 10	LINEA 2,7 MC-TERMOISOLATO	25	25
819A 10	PROFILES SQUARE-ACC-8110mm ACCIATO INOX AZIET	26	26
819A 10	304 LINO. BARRA 2,7 MC	27	27
819A 10	RES. ORDINE 2424	28	28
819A 10	PROFILES SQUARE-ACC-8110mm ACCIATO INOX AZIET	29	29

MERCE ACCETTATA CON
RISERVA PER
INVOLUCRO DANUSCANTO

2. Verify the state of the outer packaging and on the carrier bulletin write: *"accepted with reserve"* specifying the type of anomaly

3



3. Open the packaging and verify the goods

4

IN CASO DI RECLAMI INVIARE UN FAX AL N° +39 0423 950 979

MODULO RISOLUZIONE N.C. MATERIALE - PARTE A

Si prega di compilare il presente modulo in ogni sua parte

Parte In Cliente	Nome Cliente	Indirizzo	Telefono	Fax
PROGRESS	PROGRESS	Via G. G. 5	0423-950979	0423-950979

Coordinate Bancarie
Banca di appoggio: _____ Agenzia: _____ ABI: _____ N° conto: _____

Motivo reclamo
 Materiale danneggiato
 Materiale marcato
 Materiale non conforme per: qualità quantità

Descrizione materiale
Cod. / Articolo: P13AA H: 40
Descrizione: _____

4. Fill in the *"n.c. resolution form"* (see next page)

5

5. Send the *"n.c. resolution form"* and a copy of the reserve made to the carrier to fax number +39 0423 950979 or by e-mail to: cservice2@progressprofiles.com

In the event of damage or any other anomaly, if no reserve has been specified on the transport document, you will not be entitled to any compensation.

The reserve is a right enshrined in the Civil Code (art. 1688).


SELF PACK and ECO BLISTER

The **SELF PACK** range consists of blister profiles with adhesive labels with all the explanations for the interpretation of technical information regarding our profiles (code, length, finish, etc.). In the perforated version, screws and plugs are included. The **ECO BLISTER** range consists of blister profiles without explanation label but provided only with an EAN barcode. In the perforated version, screws and plugs are not included. Both have 4 colours to identify the 4 types of profiles (blue for window sill covers, red for fitting terminals, yellow for step covers, and beige for the proinsert system).

THRESHOLD-COVER PROFILES	TRANSITION PROFILES	STEP NOSING	PROINSERT SYSTEM
 ↓ THRESHOLD-COVER PROFILES ↓ Prosol Proplate Prolevall	 ↓ TRANSITION PROFILES ↓ Prolevall 29/33/305 Proskid Propress 712 Profloor Promoquette Promoquette Fix	 ↓ STEP NOSING ↓ Proend Grip Proend Ins Proend Prowalk Tube for runners Progrid	 ↓ PROINSERT SYSTEM ↓ Sol 30 self-adhesive Zero Curve self-adhesive Profixer Line System Sol 40P Terminal Pin Zero Curve Terminal
 SERIE PROSOL L. 30mm ARTICOLO PLSOTA 3010 103 cm OTTONE LUCIDO POLISHED BRASS LAITON BRASS MESSING GLANZEND AUTADIESIVO SELF-ADHESIVE AUTOACHESIF SELBSTKLEBEND	 SERIE PROLEVALL L. 30mm ARTICOLO PLVA 339 90 cm OTTONE BRASS LAITON MESSING	 SERIE PROWALK L. 30mm ARTICOLO PWKA 309 90 cm OTTONE BRASS LAITON MESSING	 SERIE SOL 40P L. 30mm ARTICOLO PISPCNC 40795 90 cm NOCE ROSATO RED WALNUT ROYER ROSE NUSS ROSE
			Photos Article Size Code Fixing system Profile length Material Finishes EAN Code

LAYING INSTRUCTION

LAYING INSTRUCTIONS: SELF-ADHESIVE



- 1) Clean the adhesion area. The surface must be dry, dust free, grease free, and non-friable.
- 2) Remove the protective paper.
- 3) Lay the profile and press evenly on the entire length.

LAYING INSTRUCTIONS: WITH SCREWS/PLUGS



- 1) Drill holes in the floor taking care that they match the holes on the profile.
- 2) Insert the plugs in the holes.
- 3) Tighten the profile.

GUIDE TO CONSULTATION

application example

description

finish

name


type of profile

technical drawings

technical information, codes, dimensions and prices



SOL 40P self-adhesive is a joint/threshold cover profile in aluminium covered with film in wooden finishes, which is highly resistant to pedestrian traffic, wear, UV rays and commonly used floor cleaning products. Easy to lay and to match with any wood finish; the surface has an open pore embossed finish. Recommended for covering joints between floors in laminate, wood, ceramic tiles, etc.



SILVER ANODIZED ALUMINIUM with ADHESIVE thermo packed - bar length 90 cm - pack: 20 Pcs

Article	L mm	€/Pc
PNSPAA 409 PAS	40	8,57

ALUMINIUM COVERED 80 wooden finishes (49 on demand) with ADHESIVE - thermo packed - bar length 8,90 lm - 20 Pcs

Article	L mm	€/Pc
PNSP... 409 PAS	40	16,18

SILVER ANODIZED ALUMINIUM with ADHESIVE thermo packed - length 40 mm - bar length 2,7 lm - pack: 40 Pcs - 108 lm

Article	L mm	€/lm	€/Pc
PNSPAA 40 PA	40	8,64	23,33

ALUMINIUM COVERED 80 wooden finishes (49 on demand) with ADHESIVE thermo packed - length 40 mm - bar length 2,7 lm - pack: 40 Pcs - 108 lm

Article	L mm	€/lm	€/Pc
PNSP... 40 PA	40	15,86	42,82

ALUMINIUM COVERED 80 wooden finishes (49 on demand) with ADHESIVE - thermo packed - bar length 1 lm - 20 Pcs

Article	L mm	€/Pc
PNSPAA 4010 PAS	40	9,48


SILVER ANODIZED ALUMINIUM with ADHESIVE - thermo packed - bar length 1 lm - 20 Pcs

Article	L mm	€/Pc
PNSP... 4010 PAS	40	17,73


Available in the colours: 04W - 05W - 07W - 09W - 13W - 18W - 21W - 25W - 29W - 30W - 31W - 32W - 33W - 34W - 35W - 36W - 37W - 38W - 39W - 41W - 42W - 44W - 45W - 46W - 48W - 49W - 53W - 54W - 55W - 65W - 73W - 75W.
The code of the selected colour must be added to the article code. E.g.: PNSP... 40 PA (chosen finish dark beech) PNSP04W 40 PA.

SOL 40P SELF-ADHESIVE

ALUMINIUM COVERED WOODEN FINISHES



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the adhesive "SOL 40" in the required finish. 2. Cut the profile to the required length and clean, degrease and dry the surface, checking that the temperature for application is at least 15°. 3. Remove the protective paper from the adhesive and lay the profile correctly applying a uniform vertical pressure by hand without moving the profile and without using iron/steel hammers.

PROCOVER WOOD is a joint-cover profile in aluminium covered with a very strong film available in wooden finishes. It is applied at the end of laying two adjoining floors with the same height, having left a 6 - 24 mm gap between the two floors set in a thin bed of adhesive. It protects the outside edges of the floor/covering. It is easy to lay and attractive. The design of the profile with lower vertical arrowhead part allows excellent anchorage with the silicone/adhesive.





ALUMINIUM COVERED 80 wooden finishes (76 on demand) thermo packed - bar length 2,7 lm - pack: 40 Pcs - 108 lm

Article	L x H mm	€/lm	€/Pc
PCRA... 149	14 x 9	6,29	16,98
PCRA... 269	26 x 9	11,06	29,86


Available in the wooden finishes: 05W - 11W - 28W - 29W - 30W
The code of the selected colour must be added to the article code.
E.g.: PCRA... 149 (chosen finish light oak) PCRA04W 149.

PROCOVER WOOD

ALUMINIUM COVERED WITH PROTECTIVE FILM IN WOODEN FINISHES



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the "PROCOVER" with the width suitable for the gap between the two floors to be joined, taking into consideration 2/3 mm - 2/32" - 1/8" side lap. 2. Fill the gap with single-pack silicone or with the adhesive used for laying the floor. 3. Bury the profile into the adhesive, making sure that both side laps of the profile rest on the coverings to be joined.

examples and instructions for laying methods

available finishes

COLOURS

05W - Light oak (oak)	11W - Decap bleached	28W - Aspen oak	29W - White oak	30W - Grey oak

On request it is possible to realize other finishes of the color range: minimum order 200 pcs. Production delay 4/5 weeks. Price to be agreed. For sample finishes, contact the sales office for minimum quantities, timing and costs.

PROCOVER INSERT

VINYL RESIN / BLACK RUBBER


Vinyl resin/rubber profile "U-form" for inserting PROCOVER with PINBFT 45 or PINBFT 40 Proinsert System base.

VINYL RESIN / RUBBER
length 2,7 lm and/or in rolls

Article	€/lm	€/Roll
PCPCR	3,81	10,29


PROINSERT BASE 45 and BASE 40 - ALUM. PUNCHED/PERFORED
bar length 2,7 lm - pack: 20 Pcs - 54 lm

Article	H mm	€/lm	€/Pc
PINBFT 45	45	6,07	16,39
PINBFT 40	40	5,99	16,17



Prices are referred to whole packs 0% increase for minimum orders of 10 Pcs 20% increase for orders of less than 10 Pcs.

PCRA... 149/1499/209/269 + INS + BASE 45/40 scale 1:1



accessories

technical drawings

technical information, codes, dimensions and prices

page

CODE COMPOSITION

EXAMPLE REGARDING METAL PROFILE:

PLSOL 308FS

base code | chosen finish | height or width | self pack | perforated

EXAMPLE REGARDING PLASTIC PROFILE:

PEG 25-01A

base code | height or width | adhesive | chosen colour

EXAMPLE REGARDING PAINTED ALUMINIUM:

PEGA 25-01A

base code | height or width | aluminium | chosen colour | adhesive

Progress Profiles SpA
Via Le Marze 7
31011 ASOLO (TV) Italy

Tel. +39 0423 950398
Fax +39 0423 950979
Certified company UNI EN ISO 9001:2015

P.I. IT 03481880262 - R.E.A. TV 275319
C.F. e Iscr. Reg.Impr. TV 03481880262
Cap. soc. € 120.000,00 i.v.
N. Meccanografico TV 44685

IMPORTANT:

Every time a price list will be given to your Client, we ask you to fill in this form and deliver it to the company Progress® Profiles s.p.a. fax: +39 0423 950 979 or mail: cservice2@progressprofiles.com

Kind regards

CEO & A.D.
Dennis Bordin

Place _____

Date _____

Name Agent _____

To the attention of Mr. _____

Name Client _____

Reference person _____

(Stamp)

With the present we give the following material _____

Catalogue / List _____ N° _____ Pcs _____

Discounts _____

Note _____

PROGRESS® PROFILES OFFICIAL CATALOGUE Rev.00_23 - distribution of this catalogue is un controlled - Approval and issue: *Dennis Bordin* (D. Bordin) - Check: *Enrico Torresan* (M. Torresan)

Kind regards

FINISHED PRODUCT AND RAW MATERIALS FEATURES

ALUMINIUM:

Primary alloy suitable for complex extrusions, it is highly resistant and has excellent superficial finish at natural state making it ideal for successive finishing processes: Anodizing, Polishing, Painting. Hot hardened and tempered it reaches a Brinnel Hp hardness degree around 70 kg/mm².

Aluminium ALLOY Mg 0,7 Si 0,4 Conventional Designation: P-Al Mg Si UNI 3569-66 UNI 6060

*Cu%	*Mn%	*Zn%	*Ti%	*Cr%	Si%	Mg%	*Fe%	Al%
0,10	0,10	0,15	0,10	0,10	0,3-0,6	0,35-0,6	0,1-0,3	Remainder

* Maximum admitted values

TILTEX & ANODIZED ALUMINIUM:

Anodic oxidation process against corrosion from atmospheric agents not combined with galvanic processes. The profiles are treated with preventive processes making them evenly matt. They are subsequently coloured by means of electro-chemical oxidation in the standard Silver, Gold, Bronze, Sand, Champagne colours with a thickness of about 15-20 micron.

The Anodized Copper and Titanium finishes are firstly superficially polished and, subsequently, subjected to the above process.

All TILTEX finishes are firstly subjected to a special superficial brushing and, subsequently, to the above process.

BRUSHED & POLISHED ALUMINIUM:

It is made of a special preventive mechanical-chemical polishing treatment and subsequent anodic bath in Chrome and Gold colours. The obtained profiles maintain the same resistance to corrosion features of the anodized profiles, but with a brilliant aesthetical aspect, making them similar to the polished surfaces.

The Polished Copper and Titanium finishes are firstly subjected to superficial polish and, subsequently, to the above process.

All BRUSHED finishes are subjected to a special superficial brushing and, subsequently, to the above process.



PAINTED ALUMINIUM:

The painting process is made of a chromium phosphate-based pre-treatment, of an electrostatic polyester-powder based paint with highly resistant features to U.V. rays and to atmospheric agents. The coating thickness covers the entire profile surface having an average thickness of approx. 50-70 micron. A hot mesh polymerisation process is also carried out for maximum guarantee of the chemical-mechanical resistance.

VARNISHED ALUMINIUM WITH SEASIDE TREATMENT:

special pre-treatment to the epoxy-polyester coating, which increases the resistance to corrosion of the profile when installed at sea front. This treatment is certified after completing 2500 hours (104 days) exposure to saline acetic mist

THERMOPLASTIC VINYL RESIN:



RVA: RIGID THERMOPLASTIC SHOCKPROOF NON TOXIC VINYL RESIN:

Purposely studied material for optimising the performing features of rigid profiles for permanent indoor application with aesthetical and long-lasting requirements. Realised starting from primary pigments and resin, their PVC composition makes it suitable for a high range of applications up to a temperature of +50/60°C. The raw material used guarantees excellent resistance to U.V. rays, to limited chemical impacts and stagnation of fungus and bacteria.

FEATURES	TEST	UNIT OF MEASURE	INDICATIVE VALUE
Specific weight	ASTM D 792	gr/cm ³	1,43 +0,02
Rockwell Hardness	ASTM D 785		108
VICAT Point	ISO 306	°C	83,7
Tensile strength at break	ASTM D 638	Mpa	50
Elongation at Break	ASTM D 638	%	100
IZOD Resistance with Cut	ASTM D 256	J/m	60
Yielding strength point	ASTM D 638	Mpa	48
Flammability	UL 94	CLASS	VO
Reaction to UV Rays	-	-	EXCELLENT RESISTANCE

RVF: FLEXIBLE NON-TOXIC VINYL RESIN (PLASTICISED THERMOPLASTIC):

Same chemical features of RVC with which it is perfectly compatible in the CO-EXTRUSION process used by ourselves in most of the dilatation, fitting joints. Thanks to the nature of the used plasticisers, the material maintains its own essential flexible features in time.

FEATURES	TEST	UNIT OF MEASURE	INDICATIVE VALUE
Specific weight	CEI 20-34	gr/cm ³	1,24 +02
Hardness	ISO 868	Sh-A	70 +2
Breaking load	ISO 527	N/mm ²	> 13
Elongation at Break	ISO 527	%	300
Thermal stability at 200°C	ISO 182	min.	25
Apparent Rigidity Module	ISO R 458	Mpa	310
Cold Flex temperature	ISO R 458	C°	-30

RVC: CO-EXTRUDED THERMOPLASTIC VINYL RESIN FOR CO-EXTRUSION:

Primary resin with chemical composition similar to RVA is characterised by a high resistance and optimised compatibility with regard to long-lasting adherence with plasticised resins used in the co-extrusion process, meaning the permanent joining of two materials with different degrees of Shore hardness.

FEATURES	TEST	UNIT OF MEASURE	INDICATIVE VALUE
Specific weight	ISO 1183	gr/cm ³	1,40 +0,5
Hardness	ISO 868	Sh-A	75+/-2
Breaking load	ISO 527	Mpa	> 18
Elongation at Break	ISO 527	%	> 350
Stiffening temperature	ISO 1183	°C	-40 +/- 2

EPDM AND NEOPRENE VULCANISED RUBBER:

The vulcanised rubber is a modified mix of EPDM and NEOPRENE of Grey or Black colour: below are the particular features:
Excellent mechanical properties in a working temperature interval from -35°C t + 100°C; Resistance to aqueous, oily and hydrocarbon fluids. Low permanent deformation with compression and pulling. Excellent resistance to ageing. Excellent resistance to dynamic fatigue and laceration. The intrinsic features of the material make it particularly suitable in the realisation of profiles where high stresses in time are requested, both indoor and outdoor.

FEATURES	TEST	UNIT OF MEASURE	INDICATIVE VALUE
Specific weight	DIN 53420	gr/cm ³	1,21
Hardness	DIN 53505	Shore A	60 +3

RESISTANCE TO CORROSIVE AGENTS:

Below is the indicative resistance towards the main diluted chemical agents and elements. Normally, the PVC products must never come into contact with Aromatic hydrocarbons, Ketones and Esters.

For further information on the materials write to our technical department.

CORROSIVE AGENT	RIGID VINYL RESIN CONCENTRATION (RVA)
Weak acids reaction	Null
Weak acids reaction	Null
Reaction to alcohol, aliphatic hydrocarbons, oils	Null
Reaction to Ketones, esters, aromatic hydrocarbons	DISSOLUTION
Flammability	CLASS VO UL94
Reaction to UV Rays	excellent resistance

FINISHED PRODUCT AND RAW MATERIALS FEATURES

STAINLESS STEEL:

The steel profiles are realised through cold shaping of constant thickness sheets, therefore, differentiating from the corresponding version in aluminium and brass realised by hot extrusion, despite maintaining the applicative and dimensional features. The stainless steel is efficiently resistant to mechanical stresses, particularly suitable in the chemical, food, hospital sector for responding to hygienic, duration and resistance to chemical agents requisites.

Normally produced with Polished finish, it is possible to realise a brushed finish that is implemented with the partial removal of material using nylon fibre and quartz rotary brushes that confer a brushed/satin matt look to the surface, without altering its features. The ultra-glossy finish happens by means of special brushes to create mirror polished finishes.

Produced in different chemical compositions, below are the main features:

AISI	DIN	*C	Cr	Ni	*Si	*Mn	Mo
430	1,4016	0,10	16,0+18,0	-	1,0	1,0	-
304	1,4301	0,06	18,0+20,0	8,0+10,5	1,0	2,0	-
316L	1,4404	0,03	16,0+18,0	11,0+13,0	1,0	2,0	2,0+2,5

* Maximum admitted values

STAINLESS STEEL AISI 430 – EN X 8 CR 17 – DIN 1.4016:

Chromium stainless steel forming part of the FERRITE category, despite being considered stainless it can easily be stained in presence of particularly aggressive products, and be contaminated by oxidising generated by other materials.

STAINLESS STEEL AISI 304 – EN X 5 CRNI 18 10 – DIN 1.4301:

Nickel/chromium stainless steel forming part of the AUSTENITIC category is the most diffused and used alloy in the manufacturing of products with highly technical and performing features. Highly resistant to most chemical products it can superficially stain or darken; a normal polishing (e.g. sidol/ smac) product is sufficient to give it back its original state.


In presence of oxidising stains in the Brushed/satin version due to the brushes, simply use a wirewool.



STAINLESS STEEL AISI 316 – EN X 2 CRNIMO 17 12 – DIN 1.4404:

Stainless steel AISI 316 is part of the AUSTENITIC category that is characterised by the internal presence of Molybdenum besides Nickel-Chromium. This features confers an excellent resistance of the material in limit conditions, which the presence of Chlorine and Salt.

APPLICATION FIELDS:

Material	Indoor	Outdoor	Floor	Wall	Heavy traffic	High chemical attack (*)	Food Contact	Pools	Thermal environments	Marine environments	 average % of recycling
STAINLESS STEEL - AISI 316	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	70-90%
STAINLESS STEEL - AISI 304	yes	yes	yes	yes	yes	no	yes	no	no	no	70-90%
STAINLESS STEEL - INOX 1.4016	yes	no	yes	yes	no	no	no	no	no	no	70-90%
NATURAL BRASS	yes	yes	yes	yes	yes	no	no	no	no	no	92-98%
CHROME BRASS	yes	no	yes	yes	no	no	no	no	no	no	92-98%
POLISHED VARNISHED BRASS	yes	no	no	yes	no	no	no	no	no	no	92-98%
NATURAL ALLUMINIUM	yes	yes	yes	yes	yes	no	no	no	no	no	20-70%
VARNISHED ALLUMINIUM	yes	yes	no	yes	no	no	no	no	no	no	20-70%
WOOD EFFECT FINISHES ALLUMINIUM	yes	no	yes	yes	no	no	no	no	no	no	20-70%
ANODIZED / POLISHED / BRUSHED ALLUMINIUM	yes	no	yes	yes	no	no	no	no	no	no	20-70%
VINIL RESIN (PVC)	yes	no	no	yes	no	yes	no	yes	yes	yes	10-80%



**PROGRESS
RECYCLE
PROJECT**

Progress Profiles® always at the forefront of the research and development process, uses an important percentage of second-life raw materials for its products. This continuous search for new production technologies together with the use of renewable energy, thanks to the production of its photovoltaic systems, pushes Progress Profiles towards its industrial project with zero environmental impact, "A look into the future", one of the most important values and founders of the company itself.

(*) In the case of applications in environments where they are used special chemicals aggressive, consult the technical department.

BRASS:

The brass profiles are characterised by a high resistance to mechanical stresses making it particularly suitable in heavy traffic applications like, for example, industrial applications with frequent pedestrian crossings. The brass is resistant to the main chemical agents intervening in ceramic coating applications. The surface of the profile, in presence of humidity or particularly aggressive agents, can show superficial oxidising phenomenon that can be removed by using a normal polishing product (e.g. Sidol and Smac). The profiles can be realised by means of hot extrusion and cold shaping of constant thickness sheets.

EXTRUSION ALLOY Cu Zn 43 Pb2 Al EN 12167 CW 624N

**Cu%	*Pb%	*Sn%	*Fe%	*Ni%	**Al%	Other%	Zn%
55-57	1,6-3	0,30	0,30	0,30	0,05-0,5	0,2	Remainder

** Indicative values * Maximum admitted values

LAMINATING ALLOY Cu Zn 37 EN 1652 CW 508L

**Cu%	*Pb%	*Fe%	Zn%	Impurity%
67	0,1	0,1	Remainder	0,30

** Indicative values * Maximum admitted values

POLISHED BRASS:


The polished finish is realised with special machines with springs/brushes that mechanically polish the surface without altering the intrinsic features of the material. A partial darkening of the surface in presence of oxidising materials is a phenomenon that can be contrasted using normal polishing products (e.g. Sidol and Smac).

CHROMIUM BRASS:

The finish is obtained by beams of galvanic process that confers a brilliant look similar to the ultra-glossy stainless steel. The treatment confers an excellent aesthetical look, excellent resistance to chemical aggressions but limited resistance to mechanical superficial impacts and persistent abrasion.



PROGRESS PROFILES IN THE WORLD








1. Saint Vincent and the Grenadines
2. Saint Lucia
3. Saint Kitts and Nevis
4. Antigua and Barbuda
5. Dominica
6. Grenada





11. Democratic Republic of the Congo
12. Equatorial Guinea
13. Sao Tomé and Principe
14. Benin

7. Macedonia 8. Montenegro 9. Serbia 10. Bosnia and Herzegovina

STEEL

Polished stainless steel AISI 304/1.4301-V2A	AC	
Super polished stainless steel AISI 304/1.4301-V2A	ACML	
Satin finish stainless steel AISI 304/1.4301-V2A	ACS	
Sanded stainless steel AISI 304/1.4301-V2A	ACSB	
Polished stainless steel AISI 316L/1.4404-V4A	ACM	

BRASS

ON		Natural brass
OL		Polished brass
OC		Chromed brass
OB		Antique brass
OS		Brushed brass

ALUMINIUM

Natural aluminium	AN		AT		Anodised titanium aluminium
Anodised silver aluminium	AA		BT		Polished titanium aluminium
Polished chrome aluminium	BC		TS		Brushed titanium aluminium
Brushed silver aluminium	BS		TX		Brushed titanium tiltex aluminium
Brushed silver tiltex aluminium	BX		AO		Anodised Gold aluminium
Anodised copper aluminium	AR		BO		Polished Gold aluminium
Polished copper aluminium	BR		BOS		Brushed Gold aluminium
Brushed copper aluminium	RS		AB		Anodised Bronze aluminium
Brushed copper tiltex aluminium	RX		DB		Anodised dark Bronze aluminium
Brushed black aluminium	NS		BRA		Anodised antique bronze aluminium
Anodised black aluminium	NE		BRAS		Brushed antique bronze aluminium
Polished black aluminium	BN		CH		Anodised champagne aluminium
			SB		Anodised sand aluminium

VARNISHED ALUMINIUM

White (9016)	01	
Matt White (9016)	010	
White ivory (9001)	0106	
Light grey (7035)	02	
Stone grey (7030)	03	
Quartz grey (7039)	0211	
Asphalt grey (7043)	0311	
Ivory (1015)	06	
Klinker red (8004)	10	
Black (9005)	11	
Bahama beige	17	
Tuscany grey	03TU	
Tuscany beige	05TU	
Tuscany bronze	20TU	

VARNISHED ALU. (only Proterrace)

	B	White (9010)
	G	Grey (7038)
	T	Dark brown (8019)
	E	Beige (1019)

VARNISHED ALU. (embossed)

	BF	White (9010)
	GF	Grey (7038)
	A	Anthracite grey
	TF	Dark brown (8019)
	C	Corten
	EF	Beige (1019)













VARNISHED ALUMINIUM STONE LINE

Stone white	SL01	
Stone cream	SL02	
Stone greyvory	SL03	
Stone sand	SL04	
Stone gray	SL05	
Stone cristal gray	SL06	
Stone antragray	SL07	

	SL08	Stone antradark
	SL09	Stone bronze
	SL10	Stone corten
	SL11	Stone brown
	SL12	Stone black
	SL13	Stone oyster grey

MARBLED

MARBLED

Carrara white	MC 
Real yellow beige	MB 
Sky blue	MA 
Portugal pink	MR 
Guatemalan green	MV 
Aquamarine green	MVA 
Soft blue	MAS 
Soft pink	MRS 
Soft beige	MBS 
Soft green	MVAS 
Travertino light	MTC 
Travertino dark	MTS 

MARBLED on demand

	MNA	Navona**
	MBC	Polished chrome**
	MBD	Bardiglio**
	MGV	Veined grey**
	MGVC	Light veined grey**
	MBPS	Salt-and-pepper beige**
	MCRI	Ivory cream**
	MCRC	Light cream**
	MBO	Polished gold**
	MAM	Macauba blue**
	MAB	Blue**
	MBDX	Burgundy**
	MVBL	Brazil green**

**Production on demand with a minimum order of 800 pcs. Production delay 4/5 weeks. Price to be agreed

WOOD similar finishes are indicated between brackets

Dark beech	04W	Light oak (strip)	05W	06W	Dark oak (walnut)	07W	Light cherry (strip)
Dark cherry (board)	08W	Red walnut (Merbau-apple-walnut)	09W	10W	Wengé (panga panga-wengé)	11W	Bleached decapè
Indonesian teak	13W	Light zebrano	18W	21W	Powder oak	25W	Bleached fir
Aspen oak	28W	White oak	29W	30W	Grey oak	31W	Victoria oak
Pink oak	32W	Sawed oak	33W	34W	Havana oak	35W	Edimburgo oak
American oak	36W	Carvi oak	37W	38W	Queens oak	39W	Grey elm
Brown oak	40W	Ice oak	41W	42W	Grace oak	43W	Manhattan oak
Honey oak	44W	Morocco oak	45W	46W	Black decapè	47W	Black oak
	48W		49W	50W		51W	
Cork oak	52W	Sand oak	53W	54W		55W	
	56W		57W	58W		59W	
	60W		61W	62W		63W	
	64W		65W	66W		67W	
	68W	Tripoli	69W	70W		71W	
	72W		73W	74W		75W	
	76W	Bangkok	77W	78W		79W	Liotard
	80W		81W	82W		83W	
	84W		85W	86W		87W	
	88W		89W	90W		93W	
	94W		95W	97W			
Mahogany*	M	Natural Oak**					

(for a precise assessment of colours and finishes, request the wood finishes sample range)

*available only with Angle bar AGEM 25 and Skirting BTPRM 70

**available only with Proslider wood, Prostair wood and wood z, Prostep wood, Prostyle wood

WOOD

Rigid PVC

White ice	00		15		Brown
White	01		16		Blue
White ivory	0106		17		Bahama beige
Light grey	02		18		Grey
Cement grey	03		19		Beige**
Light beige	04		20		Dark ivory**
Dark beige	05		21		Light pink**
Ivory	06		22		Dark pink**
Pink	07		23		Dark antique pink**
Sky blue	08		24		Dark sky blue**
Yellow	09		25		Brick red**
Red	10		26		Turquoise green**
Black	11		27		Dark green**
Silver	12		28		Hazel brown**
Gold	13		29		Dark brown**
Green	14				

**Production on demand with a minimum order of 800 pcs.
Production delay 4/5 weeks.
Price to be agreed

PVC

Flexible / Expanded PVC

White	B	
Light grey	GC	
Dark grey	GS	
Brown Only for Flexible PVC	M	
Dark Brown Only for Flexible PVC	T	
Black	N	

INSERTS steps - vinyl rubber

	A	Ivory
	G	Grey
	B	Beige
	N	Black

INSERTS joints - vinyl rubber

	G	Grey
	N	Black

JOINTS rigid part - rigid PVC / flexible part - plastified PVC

Dark grey Dark grey	GS	51	E 86	
Dark grey Transparent	GT	51	E 80	

	GL	50	E 82	Light grey Light grey
--	-----------	----	------	--------------------------

JOINTS rigid part - rigid PVC / flexible part - plastified PVC

Brick red * Transparent	RT	52	E 80	
White * White	BIBI			
Beige * Beige	BB	54	54	

	MT	53	E 80	* Brown Transparent
	N			* Black Black

* Production on demand with a minimum order of 400 pcs.
Production delay 4/5 weeks. Price to be agreed

PRODILAT & JOINTS flexible part - EPDM

Grey	G	
------	----------	--

	N	Black
--	----------	-------